

[Tutorials ▼](#)[References ▼](#)[Exercises ▼](#)[Menu ▼](#)[Log in](#)[Pro NEW](#)[Get Certified](#)[Website](#)[HTML](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)

Python For Loops

[◀ Previous](#)[Next ▶](#)

Python For Loops

A **for** loop is used for iterating over a sequence (that is either a list, a tuple, a dictionary, a set, or a string).

This is less like the **for** keyword in other programming languages, and works more like an iterator method as found in other object-orientated programming languages.

With the **for** loop we can execute a set of statements, once for each item in a list, tuple, set etc.

Example

Print each fruit in a fruit list:

```
fruits = ["apple", "banana", "cherry"]
for x in fruits:
    print(x)
```

Try it Yourself »

The **for** loop does not require an indexing variable to set beforehand.

Looping Through a String

Even strings are iterable objects, they contain a sequence of characters:

Example

Loop through the letters in the word "banana":

```
for x in "banana":  
    print(x)
```

Try it Yourself »

The break Statement

With the **break** statement we can stop the loop before it has looped through all the items:

Example

Exit the loop when **x** is "banana":

```
fruits = ["apple", "banana", "cherry"]  
for x in fruits:  
    print(x)  
    if x == "banana":  
        break
```

[Try it Yourself »](#)

Example

Exit the loop when `x` is "banana", but this time the break comes before the print:

```
fruits = ["apple", "banana", "cherry"]  
for x in fruits:  
    if x == "banana":  
        break  
    print(x)
```

[Try it Yourself »](#)

ADVERTISEMENT

The continue Statement

With the `continue` statement we can stop the current iteration of the loop, and continue with the next:

Example

Do not print banana:

```
fruits = ["apple", "banana", "cherry"]
for x in fruits:
    if x == "banana":
        continue
    print(x)
```

Try it Yourself »

The range() Function

To loop through a set of code a specified number of times, we can use the `range()` function,

The `range()` function returns a sequence of numbers, starting from 0 by default, and increments by 1 (by default), and ends at a specified number.

Example

Using the range() function:

```
for x in range(6):
    print(x)
```

Try it Yourself »

Note that `range(6)` is not the values of 0 to 6, but the values 0 to 5.

The `range()` function defaults to 0 as a starting value, however it is possible to specify the starting value by adding a parameter: `range(2, 6)` , which means values from 2 to 6 (but not including 6):

Example

Using the start parameter:

```
for x in range(2, 6):  
    print(x)
```

Try it Yourself »

The `range()` function defaults to increment the sequence by 1, however it is possible to specify the increment value by adding a third parameter: `range(2, 30, 3)` :

Example

Increment the sequence with 3 (default is 1):

```
for x in range(2, 30, 3):  
    print(x)
```

Try it Yourself »

Else in For Loop

The `else` keyword in a `for` loop specifies a block of code to be executed when the loop is finished:

Example