

NAME

naw – get the atomic weight of nuclides

LIBRARY

ciaaw library (*libciaaw*, *-lciaaw*)

SYNOPSIS

```

Fortran      function naw(s,A,u)result(res)
               character(len=*), intent(in) :: s
               integer(int32), intent(in) :: A
               logical, intent(in), optional :: u
               real(dp) :: res

C             double ciaaw_naw(char *s,int n,int A,bool u);

Python       naw(s:str,A:int,u:bool=False)->float:
```

DESCRIPTION

Get the atomic weight of the nuclide *s* for the mass number *A*. The uncertainty can be retrieved by setting *u*=TRUE.

Arguments:

<i>s</i>	Element symbol.
<i>A</i>	Mass number.
<i>u</i>	Set to True if the uncertainty is desired. Default to FALSE.

RETURN VALUE

NaN	If the provided element or the mass number are incorrect.
-1	If the element does not have a NAW.

SEE ALSO

ciaaw(3), **ciaaw_cli**(1), **ciaaw_version**(3), **ciaaw_saw**(3), **ciaaw_ice**(3), **ciaaw_nice**(3), **ciaaw_naw**(3), **ciaaw_nnaw**(3), **ciaaw_ices**(3), **ciaaw_naws**(3), **ciaaw_s2z**(3)