

**NAME**

naw – function

**LIBRARY**ciaaw library (*libciaaw*, *-lciaaw*)**SYNOPSIS**

```

Fortran      function naw(s,A,u)result(res)
               character(len=*), intent(in) :: s
               integer(int32), intent(in) :: A
               logical, intent(in), optional :: u
               real(dp) :: res

C             double ciaaw_naw(char *s,int n,int A,bool u);

Python       naw(s:str,A:int,u:bool=False)->float:
```

**DESCRIPTION**

Get the atomic weight of the nuclide *s* for the mass number *A*. The uncertainty can be retrieved by setting *u*=TRUE.

Arguments:

|          |                                                              |
|----------|--------------------------------------------------------------|
| <i>s</i> | Element symbol.                                              |
| <i>A</i> | Mass number.                                                 |
| <i>u</i> | Set to True if the uncertainty is desired. Default to FALSE. |

**RETURN VALUE**

|     |                                                           |
|-----|-----------------------------------------------------------|
| NaN | If the provided element or the mass number are incorrect. |
| -1  | If the element does not have a NAW.                       |

**SEE ALSO**

**ciaaw**(3), **ciaaw\_cli**(1), **ciaaw\_version**(3), **ciaaw\_saw**(3), **ciaaw\_ice**(3), **ciaaw\_nice**(3), **ciaaw\_naw**(3), **ciaaw\_nnaw**(3)