

NAME

codata - library for fundamental physical constants

LIBRARY

codata (**-libcodata**, **-lcodata**)

SYNOPSIS

use *codata*

include "codata.h"

import *pycodata*

DESCRIPTION

codata is a Fortran library providing the fundamental physical constants according to CODATA. A C API allows usage from C, or can be used as a basis for other wrappers. A python wrapper allows easy usage from Python.

The latest *codata* constants (2022) were integrated in the Fortran standard library (stdlib) from version 0.7.0. The constants are implemented as derived type which carries the name, the value, the uncertainty and the unit. All the *codata* constants are provided as double precision reals. The names are quite long and can be aliased with shorter names. A module level interface to_real is available for getting the constant value or uncertainty of a constant.

This library is complementary to the constants defined in the stdlib by providing older values for the constants. The latest values (2022) do not have the year as a suffix in their name whereas older values (2010, 2014, 2018) feature the year as a suffix in their name.

The C API exposes a structure *codata_constant_type* that defines the same members as in Fortran.

The Python wrapper encapsulates the members in a dictionary with the keys being name, value, uncertainty and unit.

NOTES

To **use** *codata* within your **fpm**(1) project, add the following lines to your file:

```
[dependencies]
codata = { git="https://github.com/MilanSkocic/codata.git" }
```

EXAMPLE

Example in Fortran ““ program example_in_f **use** *codata* implicit none print '(A)', '##### EXAMPLE IN FORTRAN #####' print '(A)', '# VERSION' print *, "version = ", **version()** print '(A)', '# CONSTANTS'

```
print *, "c = ",
    SPEED_OF_LIGHT_IN_VACUUM%value print '(A)', '# UNCERTAINTY' print *, "u(c) = ",
    SPEED_OF_LIGHT_IN_VACUUM%uncertainty print '(A)', '# OLDER VALUES' print '(A, F23.16)', "Mu_2022(latest) = ", MOLAR_MASS_CONSTANT%value print '(A, F23.16)',
    "Mu_2018 = ", MOLAR_MASS_CONSTANT_2018%value

print '(A, F23.16)', "Mu_2014 = ",
    MOLAR_MASS_CONSTANT_2014%value

print '(A, F23.16)', "Mu_2010 = ",
    MOLAR_MASS_CONSTANT_2010%value end program ““
```

Example in C ““ **#include** <stdio.h> **#include** "codata.h" int main(void){ **printf**("##### EXAMPLE IN C #####0); **printf**("%s0,"# VERSION"); **printf**("version = %s0, **codata_version()**); **printf**("%s0,"# CONSTANTS"); **printf**("c = %f0, SPEED_OF_LIGHT_IN_VACUUM.value); **printf**("%s0,"# UNCERTAINTY"); **printf**("u(c) = %f0, SPEED_OF_LIGHT_IN_VACUUM.uncertainty); **printf**("%s0,"# OLDER VALUES"); **printf**("Mu_2022(latest) = %23.16f0,

```
MOLAR_MASS_CONSTANT.value); printf("Mu_2018 = %23.16f0, MOLAR_MASS_CONSTANT_2018.value); printf("Mu_2014 = %23.16f0, MOLAR_MASS_CONSTANT_2014.value); printf("Mu_2010 = %23.16f0, MOLAR_MASS_CONSTANT_2010.value); return 0; } "
```

```
Example in Python " import sys sys.path.insert(0, "../py/src/") import pycodata print("##### EX-
AMPLE IN PYTHON #####) print("# VERSION") print(f"version = {pycodata.__version__}")
print("# Constants") print("c =", pycodata.SPEED_OF_LIGHT_IN_VACUUM["value"]) print("# UN-
CERTAINTY") print("u(c) = ", pycodata.SPEED_OF_LIGHT_IN_VACUUM["uncertainty"]) print("#
OLDER VALUES") print("Mu_2022 = ", pycodata.MOLAR_MASS_CONSTANT["value"])
print("Mu_2018 = ", pycodata.MOLAR_MASS_CONSTANT_2018["value"]) print("Mu_2014 = ", pyco-
data.MOLAR_MASS_CONSTANT_2014["value"]) print("Mu_2010 = ", pycodata.MO-
LAR_MASS_CONSTANT_2010["value"]) "
```

SEE ALSO

codata(1), codata_2010(3), codata_2014(3), codata_2018(3), codata_2022(3), fpm(1)