

# txt2latex(1)

User Command

16 May 2026

## NAME

**txt2latex** - convert plain ASCII to latex.

## SYNOPSIS

**txt2latex** [*OPTION...*] *ARGS...* | f(a)

## SECTIONS

Section header starts at column 1 and it must be upper case. Subsection are not supported and not left-aligned (upper case) text will not be interpreted as a header.

## PARAGRAPHS

Paragraphs can be either left-aligned or not. They must be separated by a blank line. **txt2latex**

Special characters #, \$, %, &, \_, {, }, ^ \ are protected i.e. escaped.

Symbols such as <, >, <=, >= are transformed to inline math.

## MATH

Inline math such as  $j_{corr}^{25}$ ,  $\alpha_{ox}$ ,  $\alpha_{red}$  is supported even special characters #, \$, %, &, \_, {, }, ^ \ or simple equation environment such as

$$j = j_0 (\exp(X) - \exp(-X))$$

$$\dot{j} = j_a + j_c$$

is also supported.

The equation environment is not used when the display block is detected

\$\$ display block

\$\$ not using equation environment

## LISTS

Three list-like environments are supported: itemize, enumerate and description.

The description environment is triggered when the line contains two consecutive spaces. The left part will be the item and right part will be the description.

**o label** description with inline math  $\Omega^2$  and special characters \_, %

**o label** description

**o label** Multiline descriptions are also supported. They can span over multiple lines either indented after the item or indented to the item beginning. The only requirement is to place 2 spaces after the label.

**o long label** Long labels can be used with the description being written under the label line.

**label** the label can also be a simple word.

The enumerated list is triggered when the line starts with [0-9]. followed by a space.

1. item 1
2. item 2
3. The item can span over multiple lines no matter what is the indentation across the lines.

The itemize environment is triggered when the line starts with [-\*o] followed by a space.

- item
- item
- item
- Another item that can span over multiple lines no matter the indentation. txt2latex will map all those lines as part of the item.

A second list:

- item with spaces

Nested list-like envs:

**o nested 1** Desc

**o nested 2** Description of label nested 2

**o nested 2** Desc

- i1
- i2
  1. e1
  2. e2
- i3

**o nested 2** Desc

Nested list-like envs:

**o nested 1** Desc

**o nested 2** Desc

**o nested 2** Desc

- i1
- i2
  1. e1
  2. e2

New paragraph

## EXAMPLE

Verbatim text can be added by adding indented text preceded by a blank line.

```
program main
implicit none
real ::x  !! Variable declaration
x=1
end program
```

```
type :: test
  real :: x
contains
  procedure :: f => func
end type test
```

```
$ ls -al ./
$ which txt2latex
$ txt2latex -h
```

See man page for information.

## SEE ALSO

codata(3)