

Title

Author

May 8, 2026

1 NAME

txt2latex - convert flat ASCII text to LaTeX.

2 SYNOPSIS

txt2latex [OPTIONS]... FILE

3 DESCRIPTION

txt2latex converts the input text into LaTeX. The conversion procedure is strongly inspired by `txt2man`.

txt2latex is also able to recognize and format sections, paragraphs, lists (standard, numbered, *description*, nested), literal display blocks.

If input file FILE is omitted, standard input is used. Result is displayed on standard output.

Here is how text patterns are recognized and processed:

Sections These headers are defined by a line in upper case, starting column 1.

Optionnally, the Section name can be preceded by a blank line. This is useful for a better visualization of the source text to be used to generate the LaTeX source code.

Paragraphs They must be separated by a blank line, and left aligned. Alternatively two blank spaces can be used to produce the same result. This option will provide a better visualization of the source text to be used to generate the LaTeX source code.

Description list The item definition is separated from the item description by at least 2 blank spaces, even before a new line, if definition is too long.

Bullet list Bullet list items are defined by the first word being "-" or "*" or "o".

Enumerated list The first word must be a number followed by a dot.

Literal display blocks This paragraph type is used to display unmodified text, for example source code. It must be separated by a blank line and be indented by a TAB. It is primarily used to format unmodified source code. It will be printed using fixed font using verbatim environment.

4 OPTIONS

-v, --version Display version.

-h, --help Display help.

-d date Set date. Defaults to current date.

-t mytitle Set the title. If the title is set, txt2latex will automatically add the preamble and tags for the document beginning and end.

-a author Set the author.

-I txt Italicize txt in output. Can be specified more than once.

-B txt Emphasize (bold) txt in output. Can be specified more than once.

-X Compile output with pdflatex.

5 SEE ALSO

txt2man(1)