

R Markdown :: CHEAT SHEET

What is R Markdown?




.Rmd files • An R Markdown (.Rmd) file is a record of your research. It contains the code that a scientist needs to reproduce your work along with the narration that a reader needs to understand your work.


Reproducible Research • At the click of a button, or the type of a command, you can rerun the code in an R Markdown file to reproduce your work and export the results as a finished report.

Dynamic Documents • You can choose to export the finished report in a variety of formats, including html, pdf, MS Word, or RTF documents; html or pdf based slides, Notebooks, and more.

Workflow



- 1 **Open a new .Rmd file** at File ► New File ► R Markdown. Use the wizard that opens to pre-populate the file with a template
- 2 **Write document** by editing template
- 3 **Knit document to create report**; use knit button or `render()` to knit
- 4 **Preview Output** in IDE window
- 5 **Publish** (optional) to web server
- 6 **Examine build log** in R Markdown console
- 7 **Use output file** that is saved along side .Rmd



render

Use `rmarkdown::render()` to render/knit at cmd line. Important args:

input - file to render
output_format

output_options - List of render options (as in YAML)

output_file
output_dir

params - list of params to use

envir - environment to evaluate code chunks in

encoding - of input file

Embed code with knitr syntax

INLINE CODE

Insert with ``r <code>``. Results appear as text without code.

Built with ``r getRversion()`` ➔ Built with 3.2.3

CODE CHUNKS

One or more lines surrounded with ````${r}````. Place chunk options within curly braces, after `r`. Insert with

```
```${r}echo=TRUE`  
getRversion()
```${r}```
```

```
getRversion()  
## [1] '3.2.3'
```

GLOBAL OPTIONS

Set with `knitr::opts_chunk$set()`, e.g.

```
```${r}include=FALSE`  
knitr::opts_chunk$set(echo = TRUE)
```${r}```
```

IMPORTANT CHUNK OPTIONS

cache - cache results for future knits (default = FALSE)

cache.path - directory to save cached results in (default = "cache/")

child - file(s) to knit and then include (default = NULL)

collapse - collapse all output into single block (default = FALSE)

comment - prefix for each line of results (default = '##')

dependson - chunk dependencies for caching (default = NULL)

echo - Display code in output document (default = TRUE)

engine - code language used in chunk (default = 'R')

error - Display error messages in doc (TRUE) or stop render when errors occur (FALSE) (default = FALSE)

eval - Run code in chunk (default = TRUE)

fig.align - 'left', 'right', or 'center' (default = 'default')

fig.cap - figure caption as character string (default = NULL)

fig.height, **fig.width** - Dimensions of plots in inches

highlight - highlight source code (default = TRUE)

include - Include chunk in doc after running (default = TRUE)

message - display code messages in document (default = TRUE)

results (default = 'markup')

'asis' - passthrough results

'hide' - do not display results

'hold' - put all results below all code

tidy - tidy code for display (default = FALSE)

warning - display code warnings in document (default = TRUE)



.rmd Structure

rmarkdown

YAML Header

Optional section of render (e.g. pandoc) options written as key:value pairs (YAML).

At start of file

Between lines of ---

Text

Narration formatted with markdown, mixed with:

Code Chunks

Chunks of embedded code. Each chunk:

Begins with ````${r}````

ends with ````${r}````

R Markdown will run the code and append the results to the doc.

It will use the location of the .Rmd file as the **working directory**

Parameters

Parameterize your documents to reuse with different inputs (e.g., data, values, etc.)

1. **Add parameters** • Create and set parameters in the header as sub-values of params


```
---  
params:  
  n: 100  
  d: !r Sys.Date()  
---
```

2. **Call parameters** • Call parameter values in code as `params$<name>`

Today's date
is `!r params$d`

3. **Set parameters** • Set values with Knit with parameters or the params argument of `render()`:


```
render("doc.Rmd", params = list(n = 1,  
d = as.Date("2015-01-01")))
```



Interactive Documents

Turn your report into an interactive Shiny document in 4 steps

1. Add runtime: shiny to the YAML header.
2. Call Shiny input functions to embed input objects.
3. Call Shiny render functions to embed reactive output.
4. Render with `rmarkdown::run` or click Run Document in RStudio IDE



Embed a complete app into your document with `shiny::shinyAppDir()`

NOTE: Your report will be rendered as a Shiny app, which means you must choose an html output format, like **html_document**, and serve it with an active R Session.



RStudio® is a trademark of RStudio, Inc. • CC BY SA RStudio • info@rstudio.com • 844-448-1212 • rstudio.com • Learn more at **rmarkdown.rstudio.com** • rmarkdown 1.6 • Updated: 2016-02