The gsemthesis class*

Emmanuel Rousseaux emmanuel.rousseaux@gmail.com

February 5, 2015

Abstract

This article introduces the gsemthesis class for LATEX. The gsemthesis class is a PhD thesis template for the Geneva School of Economics and Management (GSEM), University of Geneva, Switzerland. The class provides utilities to easily set up the cover page, the front matter pages, the pages headers, etc. with respect to the official guidelines of the GSEM Faculty for writing PhD dissertations. This class is released under the LaTeX Project Public License version 1.3c.

^{*}This document corresponds to gsemthesis v0.9.3, dated 2015/01/16.

Contents

1	Intr	oduction	3
2	Usa	ge	3
	2.1	Requirements	3
	2.2	Getting started	3
	2.3	Writing the dissertation in French	4
	2.4	Configuring and printing the cover page	4
	2.5	Configuring and printing the front matter pages	4
	2.6	Introduction and conclusion	4
	2.7	Bibliography	5
		2.7.1 Configure TeXstudio to run biber	5
		2.7.2 Configure Texmaker to run biber	5
		2.7.3 Configure Rstudio/knitr to run biber	5
		2.7.4 Basic commands	5
		2.7.5 Using you own bibliography management configuration	5
	2.8	Draft mode	6
	2.9	Miscellaneous	6
3	Min	imal working example	7
4	Implementation		
	4.1	Document properties	8
	4.2	Colors	8
	4.3	Graphics	8
	4.4	Link management	9
	4.5	Maths	9
	4.6	Page headers management	9
	4.7	Bibliography management	10
	4.8	Cover page	11
		4.8.1 System-level functions	11
		4.8.2 User-level functions	12
	4.9	Front matter	15
	4.10	Introduction and conclusion starter	16
	4.11	Miscellaneous	17

1 Introduction

PhD thesis published within the Geneva School of Economics and Management have to follows some guidelines, especially for the cover page. The gsemthesis class is a LATEX template providing utilities to easily set up these guidelines in your thesis. In addition the class loads several usefull packages generally used when writing a thesis. We recommend the user to have a look to the class definition in Section 4.1 to be aware of the list of packages that the class already includes. The Section 2 details how to start with the gsemthesis class and how to configure your thesis. The Section 3 provides a minimal working example you can copy/paste for starting your dissertation. The user interested in customizing the class can read the Section 4 which details the full implementation of the class with usefull comments.

This class was successfully tested with pdfTeX 3.1415926-2.5-1.40.14 (TeX Live 2013/Debian) and with pdfTeX Version 3.14159265-2.6-1.40.15 (TeX Live 2014/Windows).

This class has been written by Emmanuel ROUSSEAUX with contributions from William AEBERHARD and Tuan NGUYEN.

The development version is hosted on GitHub¹. If you are interested in contributing to this class or if you want to beta test latest versions, please visit the repository.

2 Usage

This Section introduces the use of the gsemthesis class. All macros and environments the class provides are described. We assume the user is already familiar with LATEX.

2.1 Requirements

The class requires a recent version of either TeX Live (≥ 2013) or MikTeX ($\geq 2.9.5x$). As the class preload some common packages (see Section 4 for the detailed list), we suggest to use install your LATEX distribution in full mode to make things working out-of-the-box.

The class uses biblatex/biber for managing the bibliography. Please refer to the Section 2.7 for configuring your editor to use it.

2.2 Getting started

To use the class start your document with the command \documentclass{gsemthesis}. A minimal document is:

\documentclass{gsemthesis}
\begin{document}
\printcoverpage
\newpage
Here is it, I started my PhD!
\end{document}

The Section 3 provides a minimal working example you can copy/paste for starting your dissertation. The commands available for configuring you thesis are explained in the following sections.

¹https://github.com/emmanuelrousseaux/gsemthesis

2.3 Writing the dissertation in French

The GSEM accepts English and French for PhD thesis dissertations. Default language is English. If you write your dissertation in French, you have to you the fr class option as follows:

\documentclass[fr]{gsemthesis}

2.4 Configuring and printing the cover page

\printcoverpage

The class provides the GSEM PhD thesis cover page ready to be printed. You can ask to print it by calling \printcoverpage just after the \begin{document}. Before printing the cover page you first need to configure it with your thesis details: title, author, supervisors, committee, etc.

\title
\date
\authorFirstname
\authorLastname
\thesisField

\thesisCommitteeA-F

\thesisNumber

The class uses the classical \title{text} and \date{text} commands of the book class to set the title and the date. Instead of using the \author{text} command we provide the two commands \authorFirstname{text} and \authorLastname{text} to separately handle the firstname and the lastname. You specify the PhD you are enrolled in with the \thesisField{text}, among others: Economics, Management, Statistics, Information Systems. Please contact the scientific committee of your PhD to obtain the applicable title. You can specify information about members of your thesis committee with the six \thesisCommitteeA-F{title}{firstname}{lastname}{role} commands. With the role field you specify the role played by this member in the committee and his/her affiliation. Generally you specify the role "Chair" in \thesisCommitteeA, the role "adviser" for your adviser/co-advisers, and leave the field empty for the other members. When your manuscript has been accepted by your jury, the Faculty attributes a unique thesis number which has to be printed on the cover page. The \thesisNumber{text} allows to supply it.

2.5 Configuring and printing the front matter pages

After the cover page the thesis has to provide in a the following order (1) the acknowledgements, (2,3) an abstract in both English and French (the order depending on the main language of your dissertation: if your dissertation is written in English you will start with the English abstract; if your dissertation is written in Frenchyou will start with the French abstract), (4) the table of contents, and (5) an optional dedication. These elements are usually called the front matter. These pages will be printed by calling the \printfrontmatter command. The best place for this command is just after the \printcoverpage command. To fill these pages use the commands \acknowledgements{text}, \abstractEN{text}, \abstractFR{text}, and \dedication{text}. We suggest you use these commands in the preambule of the document, just after the commands used to set the cover page.

\printfrontmatter

\acknowledgements
\abstractEN
\abstractFR
\dedication

2.6 Introduction and conclusion

\startintroduction \startconclusion

Generally we don't want to number the introduction and the conclusion, but we want they appear in the table of contents. This leads to a specific handling of the creation of these chapter, especially to have correct page headers. Therefore, instead of using \chapter{introduction} (respectively \chapter{conclusion}) to start a such chapter we provide the function \startintroduction (respectively \startconclusion) to easily start the chapter with a correct handling of the table of contents and page headers.

2.7 Bibliography

To produce the bibliography, the gsemthesis class uses the package biblatex with biber in backend instead of the package bibtex. The package biblatex is installed by default with any recent version of TeX Live² (full installation) and MiKTeX, but you must first configure your TeX Editor to use it.

2.7.1 Configure TeXstudio to run biber

In the TeXstudio preferences (click on Options \rightarrow Configure TeXstudio), choose the 'Build' tab and modify the 'Default Bibliography' to 'Biber'.

Run 'Build & View' from the 'Tools' menu (or press the two green arrows icon), which will create a PDF but with the bibliography not completed.

Run 'Bibliography' from the 'Tools' menu.

Run 'Build & View' again to create a PDF with the bibliography.

2.7.2 Configure Texmaker to run biber

In the Texmaker preferences (click on Options \rightarrow Configure Texmaker), choose the 'Commands' tab and replace bibtex % by biber % in the field Bib(la)tex. On Windows, you may also browse to the biber.exe using the folder icon on the side.

Choose the 'Quick Build' tab and select the second option PdfLaTeX + Bib(la)tex + PdfLaTex (x2) + View Pdf

Now your 'Quick Build' button will create a PDF with the bibliography.

2.7.3 Configure Rstudio/knitr to run biber

In Rstudio/knitr you have to include the following chunk in your .Rnw document:

```
<<tex-setup, include=FALSE, cache=FALSE, echo=FALSE>>=
Sys.setenv(
   TEXINPUTS=getwd(),
   BIBINPUTS=getwd(),
   BSTINPUTS=getwd()
)
@
```

2.7.4 Basic commands

To add a bibliography into your document, you have to define your bib file in the preamble of your tex file: \addbibresource{literature-review-topic1.bib} Then, at the end of your document, the command \printbibliography will create the bibliography.

2.7.5 Using you own bibliography management configuration

If you prefer not to use the bibliography management configuration we implemented in this class, you can disabled it and writing you own. Disabling the *gsemthesis* bibliography management configuration is easily done with the custombib class option:

\documentclass[custombib]{gsemthesis}

²On Ubuntu/Debian, you may have to install it manually: sudo apt-get install texlive-bibtex-extra biber

When using this option you will have to provide the package you want to use for managing your bibliography (natbib, chapterbib, etc.). As the option disables all settings you will also need to load the package biblatex if you want to use it.

2.8 Draft mode

When sharing draft versions of your dissertation you may prefer to hide some items of the cover page (thesis committee, thesis number, etc.) and some Sections (acknowledgments, the dedications. etc.) that probably have not been defined yet. For this purpose you can use the draft option:

\documentclass[draft]{gsemthesis}

2.9 Miscellaneous

itemize*

The class also provides some optional functions that can turn out to be usefull when writing your thesis. The default <code>itemize</code> environment set important spaces between each items, the previous paragraph and the next paragraph. The <code>itemize*</code> environment reduces these spaces to allow a more compact (and nicer) presentation of a list item. Forthcoming. To add: section in reduction, todonotes

3 Minimal working example

```
\documentclass{gsemthesis}
\title{An innovative approach to deal with a very important issue}
\date{\today}
\authorFirstname{Firstname}
\authorLastname{Lastname}
\thesisField{Econometrics}
\thesisCommitteeA{Prof.}{Mike}{Moore}{Advisor, University of Geneva}
\thesisCommitteeB{Prof.}{Mike}{Moore}{Chair, University of Honolulu}
\thesisCommitteeC{Prof.}{Mike}{Moore}{University of Omsk}
\thesisCommitteeD{Dr.}{Mike}{Moore}{Eidgenössische Technische Hochschule Zürich}
\thesisNumber{480}
\acknowledgements{Your acknowledgements}
\abstractEN{English version of the abstract}
\abstractFR{French version of the abstract}
\dedication{To my family.}
\addbibresource{literature-review-topic1.bib}
\addbibresource{literature-review-topic2.bib}
\begin{document}
\printcoverpage
\printfrontmatter
% INTRODUCTION
\startintroduction
Write your introduction here.
% CHAPTER
\chapter{A first chapter}
\label{ch:chapterone}
My chapter 1.
% CONCLUSION
\startconclusion
The conclusion.
% BACKMATTER
\listoftables
\listoffigures
% Bibliography (at the end)
\newpage
\printbibliography
\end{document}
```

4 Implementation

In this Section the full code of the gsemthesis is discussed. The reader interested in customizing the class will find useful comments to understand the design of the class.

4.1 Document properties

```
The class is derived from the standard book class as follows:
```

1 \LoadClass[a4paper,12pt,twoside]{book}

We set the document encoding to UTF-8

2 \usepackage[utf8]{inputenc}

We use the lmodern vectorial fonts to render the document.

3 \usepackage{lmodern}

We use the etoolbox package for defining class options (fr, draft)

4 \usepackage{etoolbox}

We add the option fr

- 5 \newtoggle{fr}
- 6 \DeclareOption{fr}{\toggletrue{fr}}

We add the option draft

- 7 \newtoggle{draft}
- 8 \DeclareOption{draft}{\toggletrue{draft}}

We add the option *custombib*

- 9 \newtoggle{custombib}
- 10 \DeclareOption{custombib}{\toggletrue{custombib}}

We process options we just defined

11 \ProcessOptions

We use the geometry package to set margin properties

12 \RequirePackage[top=2.5cm, bottom=2.5cm, left=2.5cm, right=2.5cm]{geometry}

We use the package to handle some specific text spacing (title)

13 \usepackage{setspace}

4.2 Colors

We define some nice colors that will be later used for links (url, email, citations, etc.). The gsemblue color is the official color (to date 2014.02.20) of the GSEM Faculty.

- 14 \usepackage{xcolor}
- 15 \definecolor{erblue}{HTML}{126199}
- 16 \definecolor{erorange}{HTML}{FF7F00}
- 17 \definecolor{gsemblue}{HTML}{465F7F}

4.3 Graphics

We add some practical packages to handle several image files (.png, .pdf), handle placement of graphics, and handle subfigures

- 18 \usepackage{graphicx}
- 19 \usepackage{float}
- 20 \usepackage{subfigure}

4.4 Link management

We use the hyperref package to manage internal links and set colors for each link type.

```
21 \RequirePackage{hyperref}
22 % \hypersetup{%
23 % colorlinks=true,%
24 % linkcolor=black,%
25 % filecolor=gsemblue,%
26 % citecolor=gsemblue,%
27 % urlcolor=gsemblue%
28 % }%
29 \hypersetup{%
30 colorlinks=true,%
31 linkcolor=black,%
32 filecolor=erblue,%
33 citecolor=erblue,%
34 urlcolor=erblue,%
35 }%
```

We use the url package for a complete support of external links and define a nice font style.

```
36 \RequirePackage{url}
37 \urlstyle{sf}
```

4.5 Maths

We add standard packages from the American Mathematical Society to handle mathematical symbols, environment (equations, etc.) and the Computer Modern font use by default to render math.

38 \usepackage{amssymb,amsmath,amsfonts}

4.6 Page headers management

We use the fancyhdr package for a fine tuning of headers and footers of the different page type (cover page, chapters, unumbered chapters, etc.).

```
39 \usepackage{fancyhdr}
```

The capital letters given in option of \fancyhead or \fancyfoot commands respectively stands for:

- E: Even page
- O: Odd page
- \bullet L: Left field
- C: Center field
- R: Right field
- H: Header
- F: Footer

We set the fancy page style (default page style) as follows:

```
40 \pagestyle{fancy}
41 \fancyhf{}
42 \fancyhead[LE]{\thepage}
43 \fancyhead[RE]{\nouppercase{\leftmark}}
44 \fancyhead[LO]{\nouppercase{\rightmark}}
45 \fancyhead[RO]{\thepage}
46 \fancyfoot[LE,RO]{}
We reset the plain style
47 \fancypagestyle{plain}{
48 \fancyhf{}
```

```
\renewcommand{\headrulewidth}{Opt}
50
    \fancyfoot[LE,RO]{}
51 }
We define a style for the cover page (actually not used)
52 \fancypagestyle{cover}{
    \fancyhf{}
    \renewcommand{\headrulewidth}{0.5pt}
    \renewcommand{\footrulewidth}{0.5pt}
55
56 }
We define a style for unumbered chapters (starred chapters)
57 \fancypagestyle{unnumberedchapter}{
    \fancyhf{}
59
    \renewcommand{\headrulewidth}{Opt}
    \renewcommand{\footrulewidth}{Opt}
    \fancyhead[LE]{\thepage}
    \fancyhead[RE]{}
    \fancyhead[L0]{}
63
    \fancyhead[RO]{\thepage}
64
    \fancyfoot[LE,RO]{}
65
66 }
When a new chapter starts on a odd number, we add a blank page to force it to start to
a even number. We define an empty style for this blank page
67 \fancypagestyle{empty}{
    \fancyhf{}
    \renewcommand{\headrulewidth}{0pt}
70
    \fancyfoot[LE,RO]{}
71 }
Then we apply the empty style to odd page before a new chapter
72 \def\cleardoublepage{\clearpage\if@twoside \ifodd\c@page\else
      \hbox{}
      \thispagestyle{empty}
74
      \newpage
75
      \if@twocolumn\hbox{}\newpage\fi\fi\fi}
77 \clearpage{\pagestyle{empty}\cleardoublepage}
We define the default language of the document.
78 \iftoggle{fr}{
    \usepackage[francais]{babel}
    \usepackage[T1]{fontenc}
81 }{
82
    \usepackage[english]{babel}
83 }
This package provides the commands \og and \fg for correctly handling French quotes.
84 \usepackage{csquotes}
We define the date format for the cover page (non-draft mode).
85 \usepackage{datetime}
86 \newdateformat{monthyeardate}{\monthname[\THEMONTH] \THEYEAR}
```

4.7 Bibliography management

We use biblatex/biber to process the bibliography with the following settings: (1) citations with more than two authors will always be writen as "First author et al.", (2) this "et al." rule is applied even if it leads to ambiguities between long list of authors with the same first author.

```
87 \iftoggle{custombib}{}{
```

```
88 \usepackage[backend=biber,natbib=true,style=authoryear-comp,sorting=nymdt,%
89 maxbibnames=99,mincitenames=1,maxcitenames=2,uniquelist=false]{biblatex}
90}
```

We use the style authoryear to print authors and the year when citing a document in the text. We define a customized sorting style to sort the list of references (printed at the end of the document) according to this (ordered) attributes: name, year, month, day, and title. We define the following sorting scheme:

```
91 \iftoggle{custombib}{}{
     \DeclareSortingScheme{nymdt}{
93
        \sort{
94
          \field{presort}
95
        \sort[final]{
96
          \field{sortkey}
97
        }
98
        \sort{
99
          \name{sortname}
100
          \name{author}
101
          \name{editor}
102
          \name{translator}
103
          \field{sorttitle}
104
          \field{title}
105
106
107
        \sort{
          \field{sortyear}
108
          \field{year}
109
110
        \sort{
111
          \field[padside=left,padwidth=2,padchar=0]{month}
112
113
          \literal{00}
114
115
        \sort{
          \field[padside=left,padwidth=2,padchar=0]{day}
116
          \literal{00}
117
118
119
        \sort{
120
          \field{sorttitle}
121
122
123
          \field[padside=left,padwidth=4,padchar=0]{volume}
          \literal{0000}
124
        }
125
126
     }
127 }
```

4.8 Cover page

4.8.1 System-level functions

The following commands define labels for the different parts of the cover page

```
128 \def\theFaculty{Geneva School of Economics and Management}
129
130 \def\thesisLocationLabel{
131 ~ \\[0.4em]%
132 \iftoggle{fr}{
133 Une thèse soumise à la\\[0.2em]
134 \theFaculty\\[0.2em]
135 Université de Genève, Suisse,\\[0.2em]
```

```
pour l'obtention du\\[0.2em]
                   136
                   137
                        }{
                          A thesis submitted to the \\[0.2em]
                   138
                          \theFaculty, \\[0.2em]
                   139
                          University of Geneva, Switzerland, \\[0.2em]
                  140
                          in fulfillment of the requirements for the degree of \[0.2em]
                   141
                   142
                  143 }
                   144
                   145 \iftoggle{fr}{
                       \def\thesisByLabel{par}
                  147 }{
                  148
                       \def\thesisByLabel{by}
                  149 }
                   150 \iftoggle{fr}{
                   151 \def\thesisFieldLabel{Doctorat en}
                   152 }{
                        \def\thesisFieldLabel{PhD in}
                  153
                  154 }
                   155 \left\{ fr \right\}
                       \def\thesisCommitteeLabel{Membres du jury:}
                   157 }{
                   158
                        \def\thesisCommitteeLabel{Members of the thesis committee:}
                  159 }
                   160 \verb| \ftoggle{fr}{f}|
                      \def\thesisNumberLabel{Thèse no.}
                   161
                   162 }{
                   163
                       \def\thesisNumberLabel{Thesis No.}
                  164 }
                   165
                   4.8.2 User-level functions
                   Set up of the cover page and assimilated functions.
 \authorFirstname Set up the \theauthorFirstname variable.
                   166 \def\theauthorFirstname{}
                   167 \newcommand{\authorFirstname}[1]{\def\theauthorFirstname{#1}}
  \authorLastname Set up the \theauthorLastname variable.
                   168 \def\theauthorLastname{}
                   169 \newcommand{\authorLastname}[1]{\def\theauthorLastname{\textsc{#1}}}
     \thesisField Set up the \thethesisField variable.
                   170 \det<caption>
                   171 \mbox{\newcommand{\thesisField}[1]{\def\thethesisField{#1}}}
\thesisCommitteeA Set up the \thethesisCommitteeA variable.
                   172 \def\thethesisCommitteeA{}
                   173 \newcommand{\thesisCommitteeA}[4]{%
                  174 \ifx&#3&%
                  175 \def\thethesisCommitteeA{}%
                  176 \else
                       \def\thethesisCommitteeA{#1~#2~\textsc{#3},~#4}%
                   177
                   178 \fi
                  179 }
\thesisCommitteeB Set up the \thethesisCommitteeB variable.
```

```
180 \def\thethesisCommitteeB{}
                    181 \newcommand{\thesisCommitteeB}[4]{%
                    182 \ifx&#3&%
                    183 \def\thethesisCommitteeB{}%
                    184 \ensuremath{\setminus} else
                    185 \quad \texttt{\def}\thethesisCommitteeB{\#1~\#2~\text{\textsc}{\#3},~\#4}{\%}
                    186 \fi
                    187 }
\thesisCommitteeC Set up the \thethesisCommitteeC variable.
                    188 \def\thethesisCommitteeC{}
                    189 \newcommand{\thesisCommitteeC}[4]{%
                    190 \ifx&#3&%
                    191 \def\thethesisCommitteeC{}%
                    192 \ensuremath{\setminus} else
                    193 \def\thethesisCommitteeC{#1~#2~\textsc{#3},~#4}%
                    194\fi
                    195 }
\thesisCommitteeD Set up the \thethesisCommitteeD variable.
                    196 \def\thethesisCommitteeD{}
                    197 \newcommand{\thesisCommitteeD}[4]{%
                    198 \ifx&#3&%
                    199 \def\thethesisCommitteeD{}%
                    200 \else
                    201 \ \def\thethesisCommitteeD{#1~#2~\textsc{#3},~#4}%
                    202 \fi
                    203 }
\thesisCommitteeE Set up the \thethesisCommitteeE variable.
                    204 \def\thethesisCommitteeE{}
                    205 \newcommand{\thesisCommitteeE}[4]{%
                    206 \ifx&#3&%
                    207 \def\thethesisCommitteeE{}%
                    208 \else
                    \label{lem:committeeE} $$ \def\theta\thethesisCommitteeE{\#1~\#2~\text{textsc}{\#3},~\#4}%$
                    210 \fi
                    211 }
\thesisCommitteeF Set up the \thethesisCommitteeF variable.
                    212 \def\thethesisCommitteeF{}
                    213 \newcommand{\thesisCommitteeF} [4] {\%}
                    214 \ifx&#3&%
                    215 \def\thethesisCommitteeF{}%
                    217 \quad \texttt{\def}\thethesisCommitteeF{\#1^{2}\textsc{\#3},^{\#4}\%}
                    218 \fi
                    219 }
    \thesisNumber Set up the \thethesisNumber variable.
                    220 \def\thethesisNumber{}
                    221 \newcommand{\thesisNumber}[1]{\def\thethesisNumber{#1}}
                     The cover page is created with the following code
  \printcoverpage Print the cover page of the thesis.
                    222 \newcommand{\printcoverpage}{%
                    223 \thispagestyle{empty}
                    224 \begin{center}
```

```
\rule{\linewidth}{0.4pt}
225
226
      \vspace*{1.2cm}
227
228
229
     {\huge
        {\scshape
230
          \begin{spacing}{0.8}
231
            \@title
232
          \end{spacing}
233
234
235
236
      \vspace*{1.2cm}
237
238
239
      \thesisByLabel
240
      \vspace*{0.4cm}
^{241}
242
      {\large \theauthorFirstname~\theauthorLastname}
243
244
      \vspace*{0.8cm}
245
246
      \thesisLocationLabel
247
      \thesisFieldLabel{~}\thethesisField
248
249
250
     \vfill
251
252
      \iftoggle{draft}{
253
        \iftoggle{fr}{
254
          \emph{Ébauche}
        }{
255
          \emph{Draft}
256
257
258
259
      \vspace*{0.8cm}
260
261
262
      \iftoggle{draft}{~}{\thesisCommitteeLabel}
263
      \vspace*{0.2em}
264
265
      \iftoggle{draft}{~}{\thethesisCommitteeA}
266
267
      \vspace*{0.2em}
268
269
      \label{lem:committeeB} $$ \left( \frac{r}{r} \right) = CommitteeB $$
270
271
      \vspace*{0.2em}
272
273
      \iftoggle{draft}{~}{\thethesisCommitteeC}
274
275
276
     \vspace*{0.2em}
277
      \iftoggle{draft}{~}{\thethesisCommitteeD}
278
279
280
      \vspace*{0.2em}
281
282
      \iftoggle{draft}{~}{\thethesisCommitteeE}
283
```

```
\vspace*{0.2em}
                  284
                  285
                   286
                        \iftoggle{draft}{~}{\thethesisCommitteeF}
                  287
                        \vspace*{1.4cm}
                  288
                  289
                        \iftoggle{draft}{~}{\thesisNumberLabel{~}\thethesisNumber}
                  290
                  291
                        \vspace*{0.1cm}
                  292
                  293
                        \iftoggle{draft}{\@date}{\monthyeardate\today}
                  294
                  295
                        \vspace*{0.1cm}
                  296
                  297
                   298
                        \rule{\linewidth}{0.4pt}
                   299
                        \end{center}
                  300 }
                          Front matter
                   4.9
\acknowledgements Set up the \theacknowledgements variable.
                  301 \def\theacknowledgements{}
                  302 \newcommand{\acknowledgements}[1]{\def\theacknowledgements{#1}}
      \abstractEN Set up the \theabstractEN variable.
                  303 \def\theabstractEN{}
                   304 \newcommand{\abstractEN}[1]{\def\theabstractEN{#1}}
      \abstractFR Set up the \theabstractFR variable.
                  305 \def\theabstractFR{}
                  306 \mbox{ } 1]{\mbox{def} \mbox{theabstractFR} $\{1\}$}
      \dedication Set up the \thededication variable.
                  307 \def\thededication{}
                   308 \newcommand{\dedication}[1]{\def\thededication{#1}}
\printfrontmatter The front matter pages are created with the following code
                  309 \newcommand{\printfrontmatter}{%
                  310
                        \iftoggle{draft}{~}{
                  311
                          \frontmatter
                  312
                  313
                          \iftoggle{fr}{
                  314
                  315
                            \chapter*{Remerciements}
                            \addcontentsline{toc}{chapter}{Remerciements}
                  316
                  317
                            \chapter*{Acknowledgements}
                  318
                  319
                            \addcontentsline{toc}{chapter}{Acknowledgements}
                  320
                          \label{ch:acknowledgements}
                  321
                  322
                          \thispagestyle{plain}
                          \theacknowledgements
                  323
                  324
                  325
                          \newpage
                  326
                          \iftoggle{fr}{
                  327
                            \chapter*{Résumé}
                  328
                            \addcontentsline{toc}{chapter}{Résumé}
                  329
```

```
\label{ch:abstractFR}
330
331
         \thispagestyle{plain}
332
         \theabstractFR
333
334
         \newpage
335
         \chapter*{Abstract}
336
         \addcontentsline{toc}{chapter}{Abstract}
337
         \label{ch:abstractEN}
338
         \thispagestyle{plain}
339
         \theabstractEN
340
       }{
341
          \chapter*{Abstract}
342
         \addcontentsline{toc}{chapter}{Abstract}
343
344
         \label{ch:abstractEN}
          \thispagestyle{plain}
         \theabstractEN
346
347
         \newpage
348
349
         \chapter*{Résumé}
350
          \addcontentsline{toc}{chapter}{Résumé}
351
352
         \label{ch:abstractFR}
         \thispagestyle{plain}
353
         \theabstractFR
354
       }
355
     }
356
357
358
     \tableofcontents
359
     \iftoggle{draft}{~}{
360
       \cleardoublepage
361
362
       \thispagestyle{plain}
363
364
       \vspace*{4cm}
365
366
       {\rm m}
367
       \raggedleft\thededication\par
368
369
370
       \newpage
     }
371
372
373
     \mainmatter
374 }%
```

4.10 Introduction and conclusion starter

```
\startintroduction The front matter pages are created with the following code

375 \newcommand{\startintroduction}{%

376 \chapter*{Introduction}

377 \addcontentsline{toc}{chapter}{Introduction}

378 \label{ch:introduction}

379 \markboth{}{Introduction}

380 }

\startconclusion The front matter pages are created with the following code

381 \newcommand{\startconclusion}{%

382 \chapter*{Conclusion}
```

```
383 \addcontentsline{toc}{chapter}{Conclusion}
384 \label{ch:conclusion}
385 \markboth{}{Conclusion}
386 }
```

4.11 Miscellaneous

itemize* A narrowed version of the itemize environment. implementation here.

```
387 \newenvironment{itemize*}%
388 {\vspace{-2mm}\begin{itemize}%
389 \setlength{\itemsep}{0pt}%
390 \setlength{\parskip}{0pt}%
391 }%
392 {\end{itemize}\vspace{-2mm}%
393 }
```