



### Performance

Metrics			_
First Contentful Paint	1.8 s	Time to Interactive	2.3
▲ Speed Index	6.0 s	Total Blocking Time	280 m
Largest Contentful Paint	1.9 s	Cumulative Layout Shift	0.00
-		<u>llated</u> directly from these metrics. <u>See calculated</u>	
View Original Trace			
view Original Trace			

**Opportunities** — These suggestions can help your page load faster. They don't <u>directly affect</u> the Performance score.

Opportunity

Eliminate render-blocking resources

0.14 s ^

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. <u>Learn more</u>.

Show 3rd-party resources (0)

Transfer Size Potential Savings

URL

URL Transfer Potential Size Savings

...swal/sweetalert2.min.js (rakbuku-dicoding.netlify.app) 13.1 KiB 150 ms

**Diagnostics** — More information about the performance of your application. These numbers don't <u>directly affect</u> the Performance score.

▲ Avoid an excessive DOM size — 13,422 elements

A large DOM will increase memory usage, cause longer style calculations, and produce costly layout reflows. Learn more.

3,422
14
275
3

Avoid chaining critical requests — 11 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. Learn more.

Maximum critical path latency: 3,790 ms

Initial Navigation

https://rakbuku-dicoding.netlify.app

```
...css/main.css (rakbuku-dicoding.netlify.app)
```

0 7117

...fonts/fira-sans-v11-latin-700.woff2 (rakbuku-dicoding.netlify.app) - 330 ms, 23.42 KiB

...fonts/fira-sans-v11-latin-regular.woff2 (rakbuku-dicoding.netlify.app) - 190 ms, 22.34 KiB

...modules/module.vars.css (rakbuku-dicoding.netlify.app) - 800 ms, 1.12 KiB

...styles/style.preflight.css (rakbuku-dicoding.netlify.app) - 840 ms, 0.89 KiB

 $...s tyles/style.default.css \ \ (rakbuku-dicoding.net lify.app)$ 

...modules/module.fonts.css (rakbuku-dicoding.netlify.app)

...classes/class.default.css (rakbuku-dicoding.netlify.app) - 170 ms, 1.08 KiB

...styles/style.md.css (rakbuku-dicoding.netlify.app) - 830 ms, 0.34 KiB

...styles/style.lg.css (rakbuku-dicoding.netlify.app) - 840 ms, 0.38 KiB

...swal/swal.css (rakbuku-dicoding.netlify.app)

...swal/\_button.css (rakbuku-dicoding.netlify.app) - 120 ms, 0.82 KiB

...swal/\_form.css (rakbuku-dicoding.netlify.app) - 170 ms, 0.65 KiB

...css/sweetalert2.min.css (rakbuku-dicoding.netlify.app) - 880 ms, 4.19 KiB

...swal/sweetalert2.min.js (rakbuku-dicoding.netlify.app) - 840 ms, 13.06 KiB

Keep request counts low and transfer sizes small — 31 requests • 90 KiB

To set budgets for the quantity and size of page resources, add a budget.json file. Learn more.

Resource Type	Requests	Transfer Size
Total	31	90.4 KiB
Font	2	45.8 KiB
Script	16	31.5 KiB
Stylesheet	12	11.5 KiB
Document	1	1.7 KiB
Image	0	0.0 KiB
Media	0	0.0 KiB
Other	0	0.0 KiB
Third-party	0	0.0 KiB

Largest Contentful Paint element — 1 element found

This is the largest contentful element painted within the viewport. Learn More

#### Element

h1#main-title

Avoid large layout shifts — 5 elements found

These DOM elements contribute most to the CLS of the page.

Element CLS Contribution

footer

0.003

section#contents-wrapper

0.001

Element	CLS	Contribution
h1#main-title		
		0.001
а		
		0.001
nav		
		0
Avoid long main-thread tasks — 2 long tasks found		
Lists the longest tasks on the main thread, useful for identifying wors	et contributore to input delay. Learn more	^
Lists the longest tasks on the main threat, useful for identifying wors		(0)
URL	Show 3rd-party res	Duratior
modules/render.js (rakbuku-dicoding.netlify.app)	1,969 ms	403 ms
https://rakbuku-dicoding.netlify.app	1,519 ms	96 ms
sed audits (30)		^
Properly size images		^
Serve images that are appropriately-sized to save cellular data and i	mprove load time. <u>Learn more</u> .	
Defer offscreen images		^
Consider lazy-loading offscreen and hidden images after all critical re	esources have finished loading to lower time to	)
interactive. <u>Learn more</u> .		
Minify CSS		^
Minifying CSS files can reduce network payload sizes. <u>Learn more</u> .		
Minify JavaScript		^
Minifying JavaScript files can reduce payload sizes and script parse	time. <u>Learn more</u> .	
Remove unused CSS		^

Remove dead rules from stylesheets and defer the loading of CSS not used for above-the-fold content to reduce unnecessary bytes consumed by network activity. Learn more. Remove unused JavaScript Remove unused JavaScript to reduce bytes consumed by network activity. Learn more. Efficiently encode images Optimized images load faster and consume less cellular data. Learn more. Serve images in next-gen formats Image formats like JPEG 2000, JPEG XR, and WebP often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. Learn more Enable text compression Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. Learn more. Preconnect to required origins Consider adding 'preconnect' or 'dns-prefetch' resource hints to establish early connections to important third-party origins. Learn more. Initial server response time was short — Root document took 80 ms Keep the server response time for the main document short because all other requests depend on it. Learn more. Show 3rd-party resources (0) **URL** Time Spent https://rakbuku-dicoding.netlify.app 80 ms Avoid multiple page redirects Redirects introduce additional delays before the page can be loaded. Learn more. Preload key requests Consider using `<link rel=preload>` to prioritize fetching resources that are currently requested later in page load. Learn more. Use HTTP/2 HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. Learn more. Use video formats for animated content Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. Learn more Remove duplicate modules in JavaScript bundles Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity.

Avoid serving legacy JavaScript to modern browsers			^
Polyfills and transforms enable legacy browsers to use new Jav modern browsers. For your bundled JavaScript, adopt a moder detection to reduce the amount of code shipped to modern brow More	n script deployment str	ategy using module/nome	odule feature
Preload Largest Contentful Paint image			^
Preload the image used by the LCP element in order to improve	e your LCP time. <u>Learn</u>	more.	
Avoids enormous network payloads — Total size was 112 KiB			^
Large network payloads cost users real money and are highly o	correlated with long load	d times. <u>Learn more</u> .	
		Show 3rd-part	y resources (0)
URL			Transfer Size
fonts/fira-sans-v11-latin-700.woff2 (rakbuku-dicoding.netlify.ap	p)		23.4 KiB
fonts/fira-sans-v11-latin-regular.woff2 (rakbuku-dicoding.netlify	y.app)		22.3 KiB
/favicon.ico (rakbuku-dicoding.netlify.app)			22.0 KiB
swal/sweetalert2.min.js (rakbuku-dicoding.netlify.app)			13.1 KiB
modules/handle-option-btn.js (rakbuku-dicoding.netlify.app)			4.5 KiB
css/sweetalert2.min.css (rakbuku-dicoding.netlify.app)			4.2 KiB
https://rakbuku-dicoding.netlify.app			1.7 KiB
swal/mixins.js (rakbuku-dicoding.netlify.app)			1.5 KiB
modules/handle-toggle-rak.js (rakbuku-dicoding.netlify.app)			1.4 KiB
modules/handle-search-book.js (rakbuku-dicoding.netlify.app)			1.3 KiB
Uses efficient cache policy on static assets — 0 resources fou	ınd		^
A long cache lifetime can speed up repeat visits to your page. <u>I</u>	<u>_earn more</u> .		
User Timing marks and measures			^
Consider instrumenting your app with the User Timing API to m experiences. <u>Learn more</u> .	easure your app's real-	world performance durin	g key user
JavaScript execution time — 0.2 s			^
Consider reducing the time spent parsing, compiling, and executive with this. <u>Learn more.</u>	uting JS. You may find	delivering smaller JS pay	loads helps
		Show 3rd-part	y resources (0)
URL	Total CPU Time	Script Evaluation	Script Parse
modules/render.js (rakbuku-dicoding.netlify.app)	806 ms	210 ms	0 ms

URL	Total CPU Time	Script Evaluation	Script Parse
Unattributable	636 ms	4 ms	1 ms
https://rakbuku-dicoding.netlify.app	246 ms	6 ms	2 ms
Minimizes main-thread work — 1.9 s			^
Consider reducing the time spent parsing, compiling and executing with this. <u>Learn more</u>	ng JS. You may find de	elivering smaller JS paylo	oads helps
Category			Time Spent
Other			876 ms
Parse HTML & CSS			610 ms
Script Evaluation			238 ms
Style & Layout			76 ms
Garbage Collection			50 ms
Script Parsing & Compilation			17 ms
Rendering			14 ms
All text remains visible during webfont loads			^
Leverage the font-display CSS feature to ensure text is user-visib	le while webfonts are	loading. <u>Learn more</u> .	
Minimize third-party usage			^
Third-party code can significantly impact load performance. Limit load third-party code after your page has primarily finished loading		ant third-party providers	and try to
Lazy load third-party resources with facades			^
Some third-party embeds can be lazy loaded. Consider replacing	them with a facade u	ntil they are required. <u>Le</u>	arn more.
Uses passive listeners to improve scrolling performance			^
Consider marking your touch and wheel event listeners as `passiv	ve` to improve your pa	age's scroll performance.	Learn more.
Avoids document.write()			^
For users on slow connections, external scripts dynamically inject seconds. <u>Learn more</u> .	ted via `document.writ	e()` can delay page load	by tens of
Avoid non-composited animations			^
Animations which are not composited can be janky and increase	CLS. <u>Learn more</u>		
Image elements have explicit width and height			^
Set an explicit width and height on image elements to reduce layo	out shifts and improve	CLS. <u>Learn more</u>	



# Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

**Contrast** — These are opportunities to improve the legibility of your content.

Background and foreground colors do not have a sufficient contrast ratio.	^
Low-contrast text is difficult or impossible for many users to read. <u>Learn more</u> .	
Failing Elements	
span	
ditional items to manually check (10) — These items address areas which an automated testing tool cannot cover. Learn re in our guide on conducting an accessibility review.	^
The page has a logical tab order	^
Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. <u>Learn more</u> .	
Interactive controls are keyboard focusable	^
Custom interactive controls are keyboard focusable and display a focus indicator. <u>Learn more</u> .	
Interactive elements indicate their purpose and state	^
Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. <u>Learn more</u> .	
The user's focus is directed to new content added to the page	^
If new content, such as a dialog, is added to the page, the user's focus is directed to it. <u>Learn more</u> .	
User focus is not accidentally trapped in a region	^
A user can tab into and out of any control or region without accidentally trapping their focus. <u>Learn more</u> .	
Custom controls have associated labels	^
Custom interactive controls have associated labels, provided by aria label or aria labelledby. Learn more	

	Custom controls have ARIA roles	^
	Custom interactive controls have appropriate ARIA roles. <u>Learn more</u> .	
	Visual order on the page follows DOM order	^
	DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more</u> .	
	Offscreen content is hidden from assistive technology	^
	Offscreen content is hidden with display: none or aria-hidden=true. <u>Learn more</u> .	
	HTML5 landmark elements are used to improve navigation	^
	Landmark elements ( <main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology <a href="Learn more">Learn more</a>.</nav></main>	'-
Ра	ssed audits (14)	^
	[aria-*] attributes match their roles	^
	Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. <a href="Learn more"><u>Learn more</u></a> .	<u>l</u>
	[aria-hidden="true"] is not present on the document <body></body>	^
	Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document ` <body>`. <a href="Learn more"><u>Learn more</u></a>.</body>	
	[aria-hidden="true"] elements do not contain focusable descendents	^
	Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. <u>Learn more</u> .	
	[aria-*] attributes have valid values	^
	Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. <u>Learn more</u> .	
	[aria-*] attributes are valid and not misspelled	^
	Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. <u>Learn more</u> .	
	Buttons have an accessible name	^
	When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. <u>Learn more</u> .	ı
	The page contains a heading, skip link, or landmark region	^
	Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more.	
	Document has a <title> element&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;&lt;/td&gt;&lt;td&gt;The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more.&lt;/td&gt;&lt;td&gt;је&lt;/td&gt;&lt;/tr&gt;&lt;/tbody&gt;&lt;/table&gt;</title>	

[id] attributes on active, focusable elements are unique All focusable elements must have a unique 'id' to ensure that they're visible to assistive technologies. Learn more. Heading elements appear in a sequentially-descending order Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. Learn more. <html> element has a [lang] attribute If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more. <html> element has a valid value for its [lang] attribute Specifying a valid BCP 47 language helps screen readers announce text properly. Learn more. Links have a discernible name Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. Learn more. [user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5. Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more. Not applicable (29) [accesskey] values are unique Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more. button, link, and menuitem elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA input fields have accessible names When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more ARIA meter elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA progressbar elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for

users who rely on screen readers. Learn more.

[role]s have all required [aria-*] attributes
Some ARIA roles have required attributes that describe the state of the element to screen readers. <u>Learn more</u> .
Elements with an ARIA [role] that require children to contain a specific [role] have all required children.
Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. <u>Learn more</u> .
[role]s are contained by their required parent element
Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. <u>Learn more.</u>
[role] values are valid
ARIA roles must have valid values in order to perform their intended accessibility functions. <u>Learn more</u> .
ARIA toggle fields have accessible names
When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .
ARIA tooltip elements have accessible names
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .
ARIA treeitem elements have accessible names
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .
<pre><dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements.</pre></td></tr><tr><td>When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. <u>Learn more</u>.</td></tr><tr><td>Definition list items are wrapped in <dl> elements</td></tr><tr><td>Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. <u>Learn more</u>.</td></tr><tr><td>ARIA IDs are unique</td></tr><tr><td>The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. <u>Learn more</u>.</td></tr><tr><td></td></tr><tr><td>No form fields have multiple labels</td></tr><tr><td>No form fields have multiple labels  Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. <a href="Learn more"><u>Learn more</u></a>.</td></tr><tr><td>Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either</td></tr><tr><td>Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. Learn more.</td></tr></tbody></table></script></dd></dt></dl></pre>

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more. <input type="image"> elements have [alt] text When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. Learn more. Form elements have associated labels Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more. Lists contain only elements and script supporting elements (<script> and <template>). Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more. List items () are contained within or parent elements Screen readers require list items ('') to be contained within a parent '' or '' to be announced properly. Learn more. The document does not use <meta http-equiv="refresh"> Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. Learn more <object> elements have [alt] text Screen readers cannot translate non-text content. Adding alt text to '<object>' elements helps screen readers convey meaning to users. Learn more. No element has a [tabindex] value greater than 0 A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more. Cells in a element that use the [headers] attribute refer to table cells within the same table. Screen readers have features to make navigating tables easier. Ensuring `` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more. elements and elements with [role="columnheader"/"rowheader"] have data cells they describe. Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. Learn more. [lang] attributes have a valid value Specifying a valid BCP 47 language on elements helps ensure that text is pronounced correctly by a screen reader. Learn more. <video> elements contain a <track> element with [kind="captions"] When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more.



## **Best Practices**

assed audits (17)	^
Uses HTTPS	_
All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding <u>mixed content</u> where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. <u>Learn more</u> .	,
Links to cross-origin destinations are safe	,
Add `rel="noopener"` or `rel="noreferrer"` to any external links to improve performance and prevent security vulnerabilities. <u>Learn more.</u>	
Avoids requesting the geolocation permission on page load	/
Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. <u>Learn more</u> .	
Avoids requesting the notification permission on page load	,
Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. <u>Learn more</u> .	)
Avoids front-end JavaScript libraries with known security vulnerabilities	,
Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. <u>Learn more</u> .	
Allows users to paste into password fields	,
Preventing password pasting undermines good security policy. <u>Learn more</u> .	
Displays images with correct aspect ratio	,
Image display dimensions should match natural aspect ratio. <u>Learn more</u> .	
Serves images with appropriate resolution	,
Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. <u>Learn</u> <u>more</u> .	
Page has the HTML doctype	/
Specifying a doctype prevents the browser from switching to quirks-mode. <u>Learn more</u> .	

Properly defines charset A character encoding declaration is required. It can be done with a `<meta>` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more. Avoids unload event listeners The 'unload' event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Consider using the 'pagehide' or 'visibilitychange' events instead. Learn more Avoids Application Cache Application Cache is deprecated. Learn more. **Detected JavaScript libraries** All front-end JavaScript libraries detected on the page. Learn more. Avoids deprecated APIs Deprecated APIs will eventually be removed from the browser. Learn more. No browser errors logged to the console Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. Learn more Page has valid source maps Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. Learn more. No issues in the Issues panel in Chrome Devtools Issues logged to the 'Issues' panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue. Not applicable (1) Fonts with font-display: optional are preloaded Preload 'optional' fonts so first-time visitors may use them. Learn more



These checks ensure that your page is optimized for search engine results ranking. There are additional factors Lighthouse does not check that may affect your search ranking. <u>Learn more</u>.

<b>Additional items to manually check (1)</b> — Run these additional validators on your site to check additional SEO best practices.	^
Structured data is valid	^
Run the <u>Structured Data Testing Tool</u> and the <u>Structured Data Linter</u> to validate structured data. <u>Learn more</u> .	
Passed audits (11)	^
Has a <meta name="viewport"/> tag with width or initial-scale	^
Add a ` <meta name="viewport"/> ` tag to optimize your app for mobile screens. Learn more.	
Document has a <title> element&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if is relevant to their search. &lt;u&gt;Learn more&lt;/u&gt;.&lt;/td&gt;&lt;td&gt;f a page&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Document has a meta description&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Meta descriptions may be included in search results to concisely summarize page content. &lt;u&gt;Learn more&lt;/u&gt;.&lt;/td&gt;&lt;td&gt;&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Page has successful HTTP status code&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Pages with unsuccessful HTTP status codes may not be indexed properly. Learn more.&lt;/td&gt;&lt;td&gt;&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Links have descriptive text&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Descriptive link text helps search engines understand your content. &lt;u&gt;Learn more&lt;/u&gt;.&lt;/td&gt;&lt;td&gt;&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Links are crawlable&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor element to an appropriate destination, so more pages of the site can be discovered. Learn More&lt;/td&gt;&lt;td&gt;ts links&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Page isn't blocked from indexing&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Search engines are unable to include your pages in search results if they don't have permission to crawl them. Learn&lt;/td&gt;&lt;td&gt;more.&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Document has a valid hreflang&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;hreflang links tell search engines what version of a page they should list in search results for a given language or regi&lt;br&gt;Learn more.&lt;/td&gt;&lt;td&gt;ion.&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Document uses legible font sizes — 100% legible text&lt;/td&gt;&lt;td&gt;^&lt;/td&gt;&lt;/tr&gt;&lt;tr&gt;&lt;td&gt;Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. St have &gt;60% of page text ≥12px. &lt;u&gt;Learn more&lt;/u&gt;.&lt;/td&gt;&lt;td&gt;trive to&lt;/td&gt;&lt;/tr&gt;&lt;/tbody&gt;&lt;/table&gt;</title>	

Show 3rd-party resources (0)

Source	Selector	% of Page Text	Font Size
Legible text		100.00%	≥ 12px
Document avoids p	ugins		^
Search engines car	't index plugin content, and m	nany devices restrict plugins or don't supp	ort them. <u>Learn more</u> .
Tap targets are size	d appropriately — 100% app	propriately sized tap targets	^
	s like buttons and links should without overlapping onto othe	be large enough (48x48px), and have ener elements. <u>Learn more</u> .	nough space around them, to be
Not applicable (3)			^
robots.txt is valid			^
If your robots.txt file indexed. <u>Learn mor</u>	•	not be able to understand how you want y	our website to be crawled or
Image elements ha	ve [alt] attributes		^
Informative element attribute. <u>Learn mor</u>	•	ptive alternate text. Decorative elements o	can be ignored with an empty alt
Document has a va	lid rel=canonical		^
Canonical links sug	gest which URL to show in se	earch results. <u>Learn more</u> .	



### Progressive Web App

These checks validate the aspects of a Progressive Web App. Learn more.

#### Installable

▲ Web app manifest or service worker do not meet the installability requirements — 1 reason

Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. <u>Learn more</u>.

Failure reason

No manifest was fetched

### **PWA Optimized**

_	Does not register a service worker that controls page and start_url	
	Boos hot register a service worker that controls page and start_ur1	^
	The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. <u>Learn more</u> .	ł
	Redirects HTTP traffic to HTTPS	^
	If you've already set up HTTPS, make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. <u>Learn more</u> .	
<b>A</b>	Is not configured for a custom splash screen Failures: No manifest was fetched.	^
	A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. <u>Learn more</u> .	
<b>A</b>	Does not set a theme color for the address bar. Failures: No manifest was fetched.	^
	The browser address bar can be themed to match your site. <u>Learn more</u> .	
<b>A</b>	Content is not sized correctly for the viewport The viewport size of 360px does not match the window size of 1366px.	^
	If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. <u>Learn more</u> .	
	Has a <meta name="viewport"/> tag with width or initial-scale	^
	Add a ` <meta name="viewport"/> ` tag to optimize your app for mobile screens. <u>Learn more</u> .	
<b>A</b>	Does not provide a valid apple-touch-icon	^
	For ideal appearance on iOS when users add a progressive web app to the home screen, define an `apple-touch-icon`. It must point to a non-transparent 192px (or 180px) square PNG. <u>Learn More</u> .	
<b>A</b>	Manifest doesn't have a maskable icon No manifest was fetched	^
	A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. <u>Learn more</u> .	
	litional items to manually check (3) — These checks are required by the baseline PWA Checklist but are not omatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.	^
	Site works cross-browser	^
	To reach the most number of users, sites should work across every major browser. <u>Learn more</u> .	
	Page transitions don't feel like they block on the network	^
	Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. <u>Learn more</u> .	
	Each page has a URL	^

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. Learn more.

#### Runtime Settings

URL https://rakbuku-dicoding.netlify.app/

**Fetch Time** Jul 26, 2021, 12:15 AM GMT+7

**Device** Emulated Moto G4

Network throttling 150 ms TCP RTT, 1,638.4 Kbps throughput (Simulated)

**CPU throttling** 4x slowdown (Simulated)

Channel devtools

User agent (host) Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like

Gecko) Chrome/91.0.4472.164 Safari/537.36

User agent (network) Mozilla/5.0 (Linux; Android 7.0; Moto G (4)) AppleWebKit/537.36 (KHTML, like

Gecko) Chrome/90.0.4420.0 Mobile Safari/537.36 Chrome-Lighthouse

CPU/Memory Power 1102

Axe version 4.1.2

Generated by Lighthouse 7.2.0 | File an issue