

Universidade Federal de Alagoas
Instituto de Computação
Bacharelado em Ciência da Computação

Especificação da Gramática - Isengard++

Márcio Henrique Vieira de Oliveira
Michael Miller Rodrigues Cardoso

Maceió - AL, 2021

Sumário

Sumário	2
1. Gramática livre de contexto	3
2. Gramática LL(1)	5

1. Gramática livre de contexto

S = DcMain | DcFun S | Dcld S | ϵ

DcMain = 'Funct' 'Int' 'Main' '(' ' ' BlockDc

DcFun = 'Funct' FunType 'id' '(' Param ')' BlockDc

FunType = 'Void' | VarType

VarType = 'Int' | 'Float' | 'Char' | 'Str' | 'Bool'

Param = ParamDc | ϵ

ParamDc = VarType 'id' Vet ',' ParamDc | VarType 'id' Vet

BlockDc = 'Begin' Instructions 'End'

Vet = '[' ']' | ϵ

Instructions = Dcld Instructions | Command Instructions | CommandIO Instructions | FunCall Instructions | AtrDir Instructions | Size Instructions | Return Instructions | ϵ

Dcld = VarType DcldAtr ','

DcldAtr = Id | Id ',' DcldAtr | Atr | Atr ',' DcldAtr

Id = 'id' '[' Ea ']' | 'id'

Atr = 'id' '[' Ea ']' '=' '[' AtrVet ']' | 'id' '=' Ec

AtrVet = Ec ',' AtrVet | Ec

AtrDir = 'id' '[' Ea ']' '=' Ec ';' | 'id' = Ec ','

Command = IfElse | While | For

CommandIO = Input | Output

FunCall = 'id' '(' ParamFun ')' ';'

ParamFun = ParamFun ',' Ec | Ec | ϵ

Size = DcInt '=' 'OP_SIZE' 'id' ';'

Return = 'Return' Ec ';'

IfElse = 'If' '(' Eb ')' BlockDc | 'If' '(' Eb ')' BlockDc 'Else' BlockDc

While = 'While' '(' Eb ')' BlockDc

For = 'For' '(' 'DcInt' ',' 'IntValue' ',' 'IntValue' ')' BlockDc | 'For' '(' 'DcInt' ',' 'IntValue' ')' BlockDc

DcInt = 'Int' 'id' | 'id'

IntValue = 'id' | 'CT_INT'

Input = 'Input' '(' 'InputParam' ')' ';'

InputParam = 'id' | 'id' ',' InputParam

Output = 'Output' '(' 'OutputParam' ')' ';' | 'Outputln' '(' 'OutputParam' ')' ';'

OutputParam = Ec | Ec ',' OutputParam

Ec = Ec 'OP_CONCAT' Eb | Eb

Eb = Eb 'PR_OR' Tb | Eb 'PR_AND' Tb | Tb

Tb = Tb 'PR_NOT' Ra | Ra

Ra = Ra Rel Rb | Rb

Rb = Rb Ops Ea | Ea

Ea = Ea 'OP_AD' Ta | Ea 'OP_SUB' Ta | Ta

Ta = Ta 'OP_MULT' Fa | Ta 'OP_DIV' Fa | Ta 'OP_RES' Fa | Fa

Fa = '(' Ec ')' | Id | FunCall | 'CT_INT' | 'CT_FLOAT' | 'CT_BOOL' | 'CT_CHAR' | 'CT_STR' | 'OP_NOTUNI'

Rel = 'OP_RELEQUAL' | 'OP_RELDIF'

Ops = 'OP_GREATER' | 'OP_LESS' | 'OP_GREATERT' | 'OP_LESST'

2. Gramática LL(1)

S = DcMain | DcFun S | DcId S | ϵ

DcMain = 'Funct' 'Int' 'Main' '(' ')' BlockDc

DcFun = 'Funct' FunType 'id' '(' Param ')' BlockDc

FunType = 'Void' | VarType

VarType = 'Int' | 'Float' | 'Char' | 'Str' | 'Bool'

Param = ParamDc | ϵ

ParamDc = VarType 'id' Vet ',' ParamDc | VarType 'id' Vet

BlockDc = 'Begin' Instructions 'End'

Vet = '[' ']' | ϵ

Instructions = DcId Instructions | Command Instructions | CommandIO Instructions | FunCall Instructions | AtrDir Instructions | Size Instructions | Return Instructions | ϵ

DcId = VarType DcIdAtr ','

DcIdAtr = Id | Id ',' DcIdAtr | Atr | Atr ',' DcIdAtr

Id = 'id' '[' Ea ']' | 'id'

Atr = 'id' '[' Ea ']' '=' '[' AtrVet ']' | 'id' '=' Ec

AtrVet = Ec ',' AtrVet | Ec

AtrDir = 'id' '[' Ea ']' '=' Ec ';' | 'id' = Ec ';'

Command = IfElse | While | For

CommandIO = Input | Output

FunCall = 'id' '(' ParamFun ')' ';'

ParamFun = Ec ParamFunLL | ϵ

ParamFunLL = ‘,’ Ec ParamFunLL | ϵ

Size = DcInt ‘=’ ‘OP_SIZE’ ‘id’ ‘;’

Return = ‘Return’ Ec ‘;’

IfElse = ‘If’ ‘(’ Eb ‘)’ BlockDc | ‘If’ ‘(’ Eb ‘)’ BlockDc ‘Else’ BlockDc

While = ‘While’ ‘(’ Eb ‘)’ BlockDc

For = ‘For’ ‘(’ ‘DcInt’ ‘,’ ‘IntValue’ ‘,’ ‘IntValue’ ‘)’ BlockDc | ‘For’ ‘(’ ‘DcInt’ ‘,’ ‘IntValue’ ‘)’ BlockDc

DcInt = ‘Int’ ‘id’ | ‘id’

IntValue = ‘id’ | ‘CT_INT’

Input = ‘Input’ ‘(’ ‘InputParam’ ‘)’ ‘;’

InputParam = ‘id’ | ‘id’ ‘,’ InputParam

Output = ‘Output’ ‘(’ ‘OutputParam’ ‘)’ ‘;’ | ‘Outputln’ ‘(’ ‘OutputParam’ ‘)’ ‘;’

OutputParam = Ec | Ec ‘,’ OutputParam

Ec = Eb EcLL

EcLL = ‘OP_CONCAT’ Eb EcLL | ϵ

Eb = Tb EbLL

EbLL = ‘PR_OR’ Tb EbLL | ‘PR_AND’ Tb EbLL | ϵ

Tb = Ra TbLL

TbLL = ‘PR_NOT’ Ra TbLL | ϵ

Ra = Rb RaLL

RaLL = Rel Rb RaLL | ϵ

Rb = Ea RbLL

RbLL = Ops Ea RbLL | ϵ

Ea = Ta EaLL

EaLL = 'OP_AD' Ta EaLL | 'OP_SUB' Ta EaLL | ϵ

Ta = Fa TaLL

TaLL = 'OP_MULT' Fa TaLL | 'OP_DIV' Fa TaLL | 'OP_RES' Fa TaLL | ϵ

Fa = '(' Ec ')' | Id | FunCall | 'CT_INT' | 'CT_FLOAT' | 'CT_BOOL' | 'CT_CHAR' | 'CT_STR' | 'OP_NOTUNI'

Rel = 'OP_RELEQUAL' | 'OP_RELDIF'

Ops = 'OP_GREATER' | 'OP_LESS' | 'OP_GREATERT' | 'OP_LESST'