

Im trying to build an interactive map for my project, how can i make the functions work? (functions = clickable "Dots" that change the "location description" when clicked on (part of the actual map), "filter" buttons on the side to only display the relevent "Dots", etc...): return (

```
<>
  <main>
    <div className={styles.contentLayer}>

      <Navbar />

      <Background />

      <QuickLinks />

      <section className={styles.mapPageLayout}>
        <aside className={styles.mapHero}>
          <div className={styles.mapHeroContent}>
            <div>

              <div className={styles.eyebrow}>Campus
Companion</div>

              <h1>Campus Map</h1>

              <p>Find study spaces, food spots, support
services, and key buildings across campus.</p>
            </div>
          </div>
        </aside>

        <div className={styles.mapContentColumn}>
          <section className={styles.mapPanel}>
            <h2 className={styles.mapHeading}>Campus
Overview</h2>

            <div className={styles.mapTopSearch}>

              <input id="map-search" type="text"
placeholder="Search by building, service, or category"
value={query}
              onChange={(e)
```

I'll show the pattern you need: keep the map data in an array, store the selected dot/filter/search in React state, then render only the matching dots.

Thought for a couple of seconds

You need **state + filtered data + click handlers**.

Example pattern:

```
const locations = [
  {
    id: 1,
    name: "Library",
    category: "Study",
    description: "Quiet study spaces, books, printing, and computers.",
    x: 42,
    y: 35,
  },
  {
    id: 2,
    name: "Cafeteria",
    category: "Food",
    description: "Main food hall with hot meals, snacks, and drinks.",
    x: 68,
    y: 52,
  },
  {
    id: 3,
    name: "Student Support",
    category: "Support",
    description: "Help desk, wellbeing services, and student advice.",
    x: 25,
    y: 62,
  },
];

const categories = ["All", "Study", "Food", "Support"];

const [query, setQuery] = useState("");
const [activeCategory, setActiveCategory] = useState("All");
const [selectedLocation, setSelectedLocation] = useState(locations[0]);

const filteredLocations = locations.filter((location) => {
  const matchesCategory =
    activeCategory === "All" || location.category === activeCategory;

  const matchesSearch =
    location.name.toLowerCase().includes(query.toLowerCase()) ||
    location.category.toLowerCase().includes(query.toLowerCase()) ||
    location.description.toLowerCase().includes(query.toLowerCase());
```

```

    return matchesCategory && matchesSearch;
  });

```

Then your search input:

```

<input
  id="map-search"
  type="text"
  placeholder="Search by building, service, or category"
  value={query}
  onChange={(e) => setQuery(e.target.value)}
/>

```

Filter buttons:

```

<div className={styles.filterButtons}>
  {categories.map((category) => (
    <button
      key={category}
      onClick={() => setActiveCategory(category)}
      className={activeCategory === category ? styles.activeFilter : ""}
    >
      {category}
    </button>
  ))}
</div>

```

Map dots:

```

<div className={styles.mapImageWrapper}>
  

  {filteredLocations.map((location) => (
    <button
      key={location.id}
      className={styles.mapDot}
      style={{
        left: `${location.x}%`,
        top: `${location.y}%`,
      }}
      onClick={() => setSelectedLocation(location)}
      aria-label={location.name}
    />
  ))}
</div>

```

Location description:

```

<div className={styles.locationDescription}>
  {selectedLocation ? (
    <>
      <h3>{selectedLocation.name}</h3>
      <p>{selectedLocation.description}</p>
      <span>{selectedLocation.category}</span>
    </>
  ) : (
    <p>Select a location on the map.</p>
  )}
</div>

```

CSS idea:

```

.mapImageWrapper {
  position: relative;
  width: 100%;

  CSS

.mapImage {
  width: 100%;
  display: block;
}

.mapDot {
  position: absolute;
  transform: translate(-50%, -50%);
  width: 18px;
  height: 18px;
  border-radius: 50%;
  border: 2px solid white;
  background: #ff4d4d;
  cursor: pointer;
}

.mapDot:hover {
  transform: translate(-50%, -50%) scale(1.2);
}

.activeFilter {
  background: #222;
  color: white;
}

```

Make sure you import `useState` :

JavaScript

```
import { useState } from "react";
```

The important idea is: **don't manually show/hide dots**. Store the data once, filter it with React, and render the dots from the filtered array.

