NHD-C0216CiZ-FSW-FBW-3V3

Chip-on-Glass (COG) Liquid Crystal Display

NHD-	Newhaven Display
C0216-	COG, 2 Line x 16 Characters
CiZ-	Model
F-	Transflective
SW-	Side white LED Backlight
F-	FSTN (+)
B-	6:00 Optimal View
W-	Wide Temperature
3V3-	3.0V LCD, 3.0V Backlight

REACH
Compliant

RoHS
Compliant

Table of Contents

Additional Resources

- **Support Forum:** https://support.newhavendisplay.com/hc/en-us/community/topics

- **GitHub:** https://github.com/newhavendisplay

- **Example Code:** https://support.newhavendisplay.com/hc/en-us/categories/4409527834135-Example-Code/

- **Knowledge Center:** https://www.newhavendisplay.com/knowledge_center.html

- **Quality Center:** https://www.newhavendisplay.com/quality_center.html

- **Precautions for using LCDs/LCMs:** https://www.newhavendisplay.com/specs/precautions.pdf

- **Warranty / Terms & Conditions:** https://www.newhavendisplay.com/terms.html

Document Revision History

Revision	Date	Description	Changed By
0	03/10/2000	Initial Release	-
1	05/14/2009	User Guide Reformat	BE
2	10/09/2009	Updated Electrical Characteristic Information	MC
3	11/05/2009	Block Diagram Update	BE
4	11/19/2009	Updated backlight current	MC
5	02/12/2010	Updated Font table	MC
6	04/18/2011	Mechanical Drawing Updated	AK
7	08/26/2011	Mechanical Drawing Updated	TJ
8	11/29/2011	Mechanical Drawing Updated	AK
9	03/30/2012	Example Initialization Program Updated	AK
10	07/22/2014	User Guide Reformat	ML
11	04/28/2016	Mechanical drawing, Electrical Characteristics, Optical Characteristics Updated	SB
12	06/07/2016	Added Pin Numbers to Mechanical Drawing	SB
13	12/01/2016	Wiring Diagram & Electrical Characteristics Updated	SB
14	05/18/2017	Backlight Characteristics Updated	SB
15	04/03/2019	Backlight Voltage &V_{LCD} Updated	SB
16	06/24/2019	Added PCB Footprint Drawing	AS
17	10/23/2020	Updated Symbol for LCD Supply Voltage	AS
18	12/14/2020	Change in Backlight Mold & Optical Characteristics Part Revision Upgraded to Rev1A	AS
19	04/30/2021	IC, Mechanical Drawing, Optical, Electrical & Font Table Updated	ZP
20	05/28/2021	Updated Mechanical Drawing & Font Table	ZP
21	07/05/2023	Updated Date Code/ Paper Label Format	KL

Mechanical Drawing

56.80±0.5
49.70(LCD)
45.70(V.A)
42.86(A.A)
0.80
0.80(MAX)
0.90
26.20±0.5
25.30(LCD)
18.30(LCD)
14.30(V.A)
11.32(A.A)
7.00
2.00
1.49
10.00(MAX)

K
A

8   1
P1.5*7=10.50
19.60

5.50±0.5
2.0LCD
2.50
15.34±0.5
0.30
8.0±0.5

K
A

Silicon
Black Tape

NEWHAVEN DISPLAY
NHD-C0216CiZ-FSW-FBW-3V3_Rev1B
PO-YYWW

3.5±0.3
3.5BKL
±5°
0.5
25.90±0.3
0.5
0.75±1.0
±5°

LED Backlight Circuit

2.71
2.21
4.68
0.55
0.59
1.96
0.41
0.45

| PIN | |
NO	SYMBOL
1	REST
2	SCL
3	SDA
4	VSS
5	VDD
6	VOUT
7	C1+
8	C1-

Product Description: 2x16 Character COG LCD

1. Driver IC: AiP31032

2. Driving Mode: 1/16 Duty, 1/5 Bias

3. Interface: I²C

4. Power Requirement: 3.0V LCD, 2.96V/20mA Backlight

5. Optical Features: FSTN (+), Transflective, 6:00 View, White Backlight

Recommended PCB Footprint

56.80

0.75

Ø1.80 Diameter

Ø1.20 Diameter

Ø0.80 Hole Size

Ø1.00 Hole Size

K

A

2.50

18.90

7.45

15.34

8

1

19.60

P1.5*7=10.50

Applicable Displays:
1) NHD-C0216CiZ-FSW-FBW-3V3

Pin Description

Pin No.	Symbol	External Connection	Function Description
1	RST	MPU	Active LOW Reset signal
2	SCL	MPU	Serial Clock input
3	SDA	MPU	Serial Data input
4	V_{SS}	Power Supply	Ground
5	V_{DD}	Power Supply	Supply Voltage for LCD and Logic (3.0V)
6	VOUT	Power Supply	Connect to 0.47~2.2 µF capacitor to V_{DD}
7	C1+	CAP	Connect to 0.1~1 µF cap to PIN8
8	C1-	CAP	Connect to 0.1~1 µF cap to PIN7
A	LED+	Power Supply	Backlight Anode (20 mA @ 3V)
K	LED-	Power Supply	Backlight Cathode (Ground)

Recommended LCD connector: 1.5mm Pitch LCD pins should be soldered directly onto thru-hole connection on PCB

Backlight connector: Backlight pins should be soldered directly onto thru-hole connection on PCB

Recommended Breakout Board: NHD-PCB40

Wiring Diagram

C = 1 µF
R = 4.7kΩ – 10kΩ

Electrical Characteristics

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Operating Temperature Range	T_{OP}	Absolute Max	-20	-	+70	°C
Storage Temperature Range	T_{ST}	Absolute Max	-30	-	+80	°C
Supply Voltage	V_{DD}	-	2.7	3.0	3.3	V
Supply Current	I_{DD}	V_{DD} = 3.0V	0.1	0.3	0.5	mA
Supply for LCD (Contrast)	V_{LCD}	T_{OP} = 25°C	4.8	5.0	5.2	V
"H" Level input	V_{IH}	-	2.2	-	V_{DD}	V
"L" Level input	V_{IL}	-	0	-	0.6	V
"H" Level output	V_{OH}	-	2.4	-	V_{DD}	V
"L" Level output	V_{OL}	-	GND	-	0.4	V
Backlight Supply Current	I_{LED}	-	10	20	30	mA
Backlight Supply Voltage	V_{LED}	I_{LED} = 20mA	2.88	2.96	3.12	V

*The LED of the backlight is driven by current drain; drive voltage is for reference only. Drive voltage must be selected to ensure backlight current drain
 is below MAX level stated.

Optical Characteristics

Item		Symbol	Condition	Min.	Typ.	Max.	Unit
Optimal Viewing Angles	Top	φY+	CR ≥ 2	30	40	-	°
	Bottom	φY-		50	60	-	°
	Left	θX-		50	60	-	°
	Right	θX+		50	60	-	°
Contrast Ratio		CR	-	2	5	-	-
Response Time (Rise)		T_R	T_{OP} = 25°C	-	150	250	ms
Response Time (Fall)		T_F		-	200	300	ms

Controller Information

Built-in AiP31032 Controller: https://support.newhavendisplay.com/hc/en-us/articles/4414489955351-AiP31032

## Slave Address = 0x7C

Write mode

Figure 5. 2-line Interface protocol

Co	0	Last control byte to be sent. Only a stream of data bytes is allowed to follow. This stream may only be terminated by a STOP condition.
	1	Another control byte will follow the data byte unless a STOP condition is received.

Table of Commands

➢ **instruction table at "Extension mode"**
(when "EXT" option pin connect to Vss, the instruction set follow below table)

Instruction	RS	R/W	DB7	DB6	DB5	DB4	DB3	DB2	DB1	DB0	Description	OSC= 380KHz	OSC= 540kHz	OSC= 700KHz
Clear Display	0	0	0	0	0	0	0	0	0	1	Write "20H" to DDRAM. and set DDRAM address to "00H" from AC	1.08 ms	0.76 ms	0.59 ms
Return Home	0	0	0	0	0	0	0	0	1	x	Set DDRAM address to "00H" from AC and return cursor to its original position if shifted. The contents of DDRAM are not changed.	1.08 ms	0.76 ms	0.59 ms
Entry Mode Set	0	0	0	0	0	0	0	1	I/D	S	Sets cursor move direction and specifies display shift. These operations are performed during data write and read.	26.3 us	18.5 us	14.3 us
Display ON/OFF	0	0	0	0	0	0	1	D	C	B	D=1:entire display on C=1:cursor on B=1:cursor position on	26.3 us	18.5 us	14.3 us
Function Set	0	0	0	0	1	DL	N	DH	*0	IS	DL: interface data is 8/4 bits N: number of line is 2/1 DH: double height font IS: instruction table select	26.3 us	18.5 us	14.3 us
Set DDRAM address	0	0	1	AC6	AC5	AC4	AC3	AC2	AC1	AC0	Set DDRAM address in address counter	26.3 us	18.5 us	14.3 us

Instruction table 0(IS=0)														
Cursor or Display Shift	0	0	0	0	0	1	S/C	R/L	x	x	S/C and R/L: Set cursor moving and display shift control bit, and the direction, without changing DDRAM data.	26.3 us	18.5 us	14.3 us
Set CGRAM	0	0	0	1	AC5	AC4	AC3	AC2	AC1	AC0	Set CGRAM address in address counter	26.3 us	18.5 us	14.3 us

Instruction table 1(IS=1)														
Internal OSC frequency	0	0	0	0	0	1	BS	F2	F1	F0	BS=1:1/4 bias BS=0:1/5 bias F2~0: adjust internal OSC frequency for FR frequency.	26.3 us	18.5 us	14.3 us
Set ICON address	0	0	0	1	0	0	AC3	AC2	AC1	AC0	Set ICON address in address counter.	26.3 us	18.5 us	14.3 us
Power/ICON control/Contrast set	0	0	0	1	0	1	Ion	Bon	C5	C4	Ion: ICON display on/off Bon: set booster circuit on/off C5,C4: Contrast set for internal follower mode.	26.3 us	18.5 us	14.3 us
Follower control	0	0	0	1	1	0	Fon	Rab2	Rab1	Rab0	Fon: set follower circuit on/off Rab2~0: select follower amplified ratio.	26.3 us	18.5 us	14.3 us
Contrast set	0	0	0	1	1	1	C3	C2	C1	C0	Contrast set for internal follower mode.	26.3 us	18.5 us	14.3 us

Timing Characteristics

Item	Signal	Symbol	Condition	VDD=2.7 to 4.5V Rating		VDD=4.5 to 5.5V Rating		Units
				Min.	Max.	Min.	Max.	
SCL clock frequency	SCL	f_{SCLK}		DC	400	DC	400	KHz
SCL clock low period		t_{LOW}	—	1.3	—	1.3	—	us
SCL clock high period		t_{HIGH}		0.6	—	0.6	—	
Data set-up time	SI	$t_{SU;DAT}$	—	**180**	—	100	—	ns
Data hold time		$t_{HD:DAT}$		0	0.9	0	0.9	us
SCL,SDA rise time	SCL, SDA	t_r	—	$20+0.1C_b$	300	$20+0.1C_b$	300	ns
SCL,SDA fall time		t_f		$20+0.1C_b$	300	$20+0.1C_b$	300	
Capacitive load represent by each bus line		C_b	—	–	400	–	400	pf
Setup time for a repeated START condition	SI	$t_{SU;STA}$	—	0.6	–	0.6	–	us
Start condition hold time		$t_{HD;STA}$	—	0.6	–	0.6	–	us
Setup time for STOP condition		$t_{SU;STO}$	—	0.6	–	0.6	–	us
Bus free time between a Stop and START condition	SCL	t_{BUF}	—	1.3	–	1.3	–	us

- **I2C interface**

Built-In Font Table

OPR1, OPR2 = (0,0)

Replaced By CCRAM Pattern

b7-b4 b3-b0	0000	0001	0010	0011	0100	0101	0110	0111	1000	1001	1010	1011	1100	1101	1110	1111
0000																
0001																
0010																
0011																
0100																
0101																
0110																
0111																
1000																
1001																
1010																
1011																
1100																
1101																
1110																
1111																

Example Initialization Program

```
/**************************************************/
void I2C_out(unsigned char j)                    //I2C Output
{
        int n;
        unsigned char d;
        d=j;
        for(n=0;n<8;n++){
                if((d&0x80)==0x80)
                SDA=1;
                else
                SDA=0;
                d=(d<<1);
                SCL = 0;
                SCL = 1;
                SCL = 0;
                }
        SCL = 1;
        while(SDA==1){
                SCL=0;
                SCL=1;
                }
        SCL=0;
}
/**************************************************/
void I2C_Start(void)
{
        SCL=1;
        SDA=1;
        SDA=0;
        SCL=0;
}
/**************************************************/
void I2C_Stop(void)
{
        SDA=0;
        SCL=0;
        SCL=1;
        SDA=1;
}
/**************************************************/
void Show(unsigned char *text)
{
        int n;
        I2C_Start();
        I2C_out(Slave);
        I2C_out(Datasend);
        for(n=0;n<16;n++){
                I2C_out(*text);
                ++text;
                }
        I2C_Stop();
}
/**************************************************
```

```
*************************************************/
void init_LCD()
{
I2C_Start();
I2C_out(0x7C);
I2C_out(0x00);
I2C_out(0x38);
delay(10);
I2C_out(0x39);
delay(10);
I2C_out(0x14);
I2C_out(0x78);
I2C_out(0x5E);
I2C_out(0x6D);
I2C_out(0x0C);
I2C_out(0x01);
I2C_out(0x06);
delay(10);
I2C_stop();
}
/*************************************************/
```

Quality Information

Test Item	Content of Test	Test Condition	Note
High Temperature storage	Endurance test applying the high storage temperature for a long time.	+80^{o}C , 48hrs	2
Low Temperature storage	Endurance test applying the low storage temperature for a long time.	-30^{o}C , 48hrs	1,2
High Temperature Operation	Endurance test applying the electric stress (voltage & current) and the high thermal stress for a long time.	+70^{o}C , 48hrs	2
Low Temperature Operation	Endurance test applying the electric stress (voltage & current) and the low thermal stress for a long time.	-20^{o}C , 48hrs	1,2
High Temperature / Humidity Storage	Endurance test applying the electric stress (voltage & current) and the high thermal with high humidity stress for a long time.	+40^{o}C , 90% RH , 48hrs	1,2
Thermal Shock resistance	Endurance test applying the electric stress (voltage & current) during a cycle of low and high thermal stress.	0^{o}C,30min -> 25^{o}C,5min -> 50^{o}C,30min = 1 cycle 10 cycles	
Vibration test	Endurance test applying vibration to simulate transportation and use.	10-55Hz , 15mm amplitude. 60 sec in each of 3 directions X,Y,Z For 15 minutes	3
Static electricity test	Endurance test applying electric static discharge.	VS=800V, RS=1.5kΩ, CS=100pF One time	

Note 1: No condensation to be observed.

Note 2: Conducted after 4 hours of storage at 25^{o}C, 0%RH.

Note 3: Test performed on product itself, not inside a container.