Right but Unsure: How Focal Loss and Label Smoothing Miscalibrate Multi-Class Voice Activity Detection

Minahil Rauf
School of Electrical Engineering and Computer Science (SEECS)
National University of Sciences and Technology (NUST)
Islamabad, Pakistan
mrauf.bese23seecs@seecs.edu.pk

Muhammad Ijaz
School of Electrical Engineering and Computer Science (SEECS)
National University of Sciences and Technology (NUST)
Islamabad, Pakistan
muhammad.bese23seecs@seecs.edu.pk

***Abstract*—Voice activity detectors (VADs) output confidence scores that deployed systems act on through fixed thresholds, so the scores must be calibrated. Multi-class detectors, which separate speech, music and overlapping speech and music, face strong class imbalance, and class weighting, focal loss and label smoothing are common remedies. These losses are known to reduce the over-confidence of large image classifiers; we measure what they do to a compact audio detector and to the thresholds that act on its scores. A compact convolutional recurrent network is trained on labelled mixtures of public corpora with four losses, three seeds each, and evaluated on in-domain audio and on audio from unseen source corpora. Plain cross-entropy is well calibrated, with an expected calibration error (ECE) of 0.010. Focal loss and label smoothing raise it to 0.105 and 0.059 and make the detector under-confident, without improving macro-F1 or the F1 score of the rare overlapping class. As a result, fixed thresholds change meaning: at a confidence threshold of 0.9 the cross-entropy model accepts 81% of frames, the label-smoothing model 59% and the focal-loss model 35%. A single temperature fitted on validation data restores calibration for focal loss on both test sets (ECE 0.112 to 0.006 on unseen sources) and largely for label smoothing. We conclude that for compact VADs these losses cost calibration without buying accuracy, and that any change of training loss should be followed by recalibration or by re-tuning every threshold that depends on the scores.**

Keywords—voice activity detection, confidence calibration, focal loss, label smoothing, temperature scaling, class imbalance

I. Introduction

Voice activity detection (VAD) decides, frame by frame, whether speech is present, and gates more expensive processing such as speech recognition, speaker diarization and dialogue enhancement. Recent work pushes VADs towards very small, low-latency models for always-on devices [1]–[3]. In deployment, the detector's output is rarely used as a hard label: a system wakes up, transmits or enhances audio when a score exceeds a threshold. Such thresholds are only meaningful if the scores are *calibrated*, that is, if frames scored 0.9 are correct about 90% of the time [4].

Many applications need more than speech versus non-speech. Broadcast monitoring, music-aware speech recognition and dialogue enhancement must tell speech from music and must detect speech that overlaps with music [5], [6]. A multi-class VAD with the classes *background*, *speech*, *music* and *speech+music* faces a strong imbalance: overlapping speech and music is rare in natural audio. The usual remedies are class-weighted cross-entropy, focal loss [7] and label smoothing [8]. The latter two are also promoted as ways to *improve* calibration, because they counteract the over-confidence of large networks [8], [9].

The general behaviour of these losses is not new: in image classification they lower confidence, and a fixed focal parameter can over-correct and leave samples under-confident [10]. What is unknown is how they behave in a different regime, which this paper addresses. Recent VAD studies report AUC, F1 or latency but do not examine whether their scores are calibrated (Section II). Calibration studies in speech and audio target recognition, captioning and bioacoustics [11]–[13], not frame-level multi-class VAD. Compact detectors, unlike large image networks, need not be over-confident in the first place, so a remedy for over-confidence may simply over-correct. Finally, no study has quantified what such a shift in confidence does to the fixed thresholds through which a VAD is actually deployed.

This paper answers these questions in a controlled study. Its contributions are:

1) To our knowledge, the first calibration study of a four-class VAD, using synthetic mixtures with exact frame labels and clip-level bootstrap intervals.
2) Evidence that in a compact detector whose cross-entropy baseline is already calibrated, focal loss and label smoothing over-correct into strong *under*-confidence, with no accuracy benefit even for the rare class; the effect is significant in every seed.
3) A quantification of the operational consequence, i.e. how much the meaning of a fixed confidence threshold changes with the loss, together with an analysis of when re-tuning thresholds suffices and when one fitted temperature is needed instead.

II. Related Work

Voice activity detection. Recent VAD research concentrates on accuracy, robustness and efficiency. kiloVAD [1] reaches 0.850 AUC on AVA-Speech with about 2 k parameters; S4VAD [2] uses state-space models and a latency-aware evaluation; SincQDR-VAD [14] trains with a

XXX-X-XXXX-XXXX-X/XX/$XX.00 ©20XX IEEE

ranking loss that optimises AUROC; FusionVAD [15] fuses MFCCs with pretrained speech features; and further work targets noise robustness [3], [16]. Beyond binary detection, foreground VAD [17] and personal VAD [18], [19] separate target from background speakers, overlapped-speech detection [20] separates one from several talkers, and SR-SAD [5] rejects singing. As Table I shows, none of these studies measures whether the output scores are calibrated, and the only one that compares losses for imbalance [19] evaluates them by accuracy alone.

Calibration in speech and audio. Over-confidence of modern networks and its correction by temperature scaling were established by Guo et al. [4]; classwise calibration error was introduced by Kull et al. [21]. Recent work analyses the theory of temperature scaling [22], benchmarks post-hoc calibrators on tabular and vision data [23], and studies calibration under label noise and domain shift [24]. In audio, Whisper is over-confident in noise [11], captioning models are over-confident regardless of semantic accuracy [12], and multi-label bird-sound classifiers can be under-confident [13]. None of these covers VAD.

Losses and calibration. Focal loss [7] and label smoothing [8] reduce over-confidence in image classification [9]. AdaFocal [10] showed that a fixed focal parameter can leave samples under-confident, and recent work notes that label smoothing only addresses over-confidence [25] and that focal-type weighting does not align with sample uncertainty [26]. Confidence-aware reweighting for long-tailed data [27] targets accuracy and does not evaluate calibration. These studies mostly concern large vision networks, whose cross-entropy baselines are typically over-confident [4].

Research gap. The prior work establishes *that* focal loss and label smoothing can push confidence too far, but only for large vision models and measured by calibration error alone. No prior work measures the calibration of a multi-class VAD. The effect of imbalance-oriented losses on a compact audio detector, whose baseline need not be over-confident, has not been studied, and neither has its consequence for the fixed thresholds at which detectors operate. Our contribution is therefore not the existence of loss-induced under-confidence, but its size and practical cost in a setting where it has not been examined.

TABLE I. RECENT RELATED WORK (2025–2026) AND THE GAP EACH LEAVES FOR THIS STUDY.

Work	Task and classes	Calib.	Gap relative to this work
kiloVAD [1]	Ultra-tiny causal VAD, speech vs. non-speech	no	Binary; reports AUC, never checks whether scores are calibrated
S4VAD [2]	State-space VAD, onset-latency evaluation	no	Binary; latency metric, frame-score calibration unexamined
Foreground VAD [17]	Dominant speaker vs. background talkers	no	No music classes; no confidence analysis
SR-SAD [5]	Speech activity robust to singing voice	no	Speech vs. singing only; AUC only, no loss comparison
FusionVAD [15]	Binary VAD, MFCC + pretrained features	no	Accuracy and efficiency only; no calibration or loss study
SincQDR-VAD [14]	Binary VAD, ranking loss for AUROC	no	Optimises ranking, explicitly not probabilities
TS-VAD [16]	Target-speaker VAD in noise, SSL pre-training	no	Robustness only; confidence not assessed
Tiny VAD [3]	Binary VAD for voice assistants in noise	no	Accuracy in noise only
WavLM OSD [20]	Overlapping-speech detection	no	Speaker overlap, not speech/music; F1 only
PVAD study [19]	Personal VAD, losses for imbalance	no	Imbalance losses judged by accuracy, not calibration
Noisy ASR [11]	Token confidence of Whisper in noise	yes	ASR over-confidence; not frame-level detection
Captioning [12]	Confidence of audio captioning models	yes	Sequence generation; no loss-induced under-confidence
Bird sound [13]	Multi-label bioacoustic classification	yes	Notes under-confidence but does not link it to the loss
CalArena [23]	Post-hoc calibrator benchmark	yes	Tabular and vision only; no training losses
Well-tempered [22]	Theory of temperature scaling	yes	Theoretical; no audio, no training-loss effects
CCAR [27]	Confidence-aware reweighting, long-tailed images	partly	Targets accuracy; calibration not evaluated
FedLAS [25]	Bidirectional label smoothing, images	yes	Vision only; no detection or audio
UWG [26]	Focal-loss family analysis, images	yes	Vision only; no fixed-threshold consequence

III. METHOD

A. Task and data

Each 10-ms frame is assigned one of four classes: background (silence or noise), speech (with or without noise), music (singing counts as music) and speech+music. Fig. 1 summarises the design. Exact labels are essential for measuring calibration, so the data are synthetic mixtures with known ground truth. MUSAN [28] speech, music and noise files are split by file into training (70%), validation (10%) and in-domain test (20%) pools. An *unseen-source* test set uses LibriSpeech test-clean [29] speech, GTZAN [30] music without the hip-hop genre (rap is speech-like) and ESC-50 [31] noise without its human-vocal classes.

Each 10-s clip at 16 kHz consists of a quiet noise bed and a sequence of 1–4 s events whose class is drawn with probabilities 0.25/0.50/0.20/0.05 (background/speech/music/speech+music). Speech-over-music events use a speech-to-music ratio of −5, 0, 5, 10 or 15 dB. Speech labels come from an energy detector on the clean speech (frames within 35 dB of the segment peak, pauses under 150 ms bridged), music labels from the placed music above −60 dBFS. The splits contain 7,200 training clips (20 h), 700 validation clips and 1,000 clips in each test set. The resulting frame shares are about 30% background, 45% speech, 21% music and 4% speech+music.

B. Model and training

The detector is a CRNN with 64-band log-mel input (25-ms window, 10-ms hop), three convolutional blocks (16, 32 and 64

channels, pooling over frequency only), one GRU layer with 64 units and a linear output of four logits per frame (85.6 k parameters). It is trained with Adam (learning rate 10^{-3}, batch 32, random 4-s crops) for up to 20 epochs, with early stopping on validation macro-F1. Four losses are compared: cross-entropy (CE); weighted CE with inverse-frequency class weights normalised to mean one; focal loss [7] with $\gamma = 2$; and label smoothing [8] with $\varepsilon = 0.1$. Each loss is trained with three seeds, giving 12 models.




Fig. 1. Study design. Labelled mixtures are generated from public corpora, a compact CRNN is trained with four losses (three seeds each), calibrators are fitted on validation data, and calibration, accuracy and threshold behaviour are evaluated on an in-domain test set and on a test set built from unseen source corpora. The colour strip illustrates the frame labels of one clip.

C. Calibration measures and post-hoc calibration

For N test frames with predicted class $\hat{y}_i$ and confidence $\hat{p}_i = \max_k p_{ik}$, frames are grouped into $B = 15$ equal-width confidence bins S_b and

$$ECE = \sum_{b=1}^{B} \frac{|S_b|}{N} \left| acc(S_b) - conf(S_b) \right| \qquad (1)$$

Classwise-ECE [21] applies the same measure to each class probability and averages over classes. Frames within a clip are strongly correlated, so 95% confidence intervals and paired comparisons use 1,000 bootstrap resamples of *clips*, not frames.

Two calibrators are fitted on the validation set by minimising the negative log-likelihood: temperature scaling [4], $\mathbf{p} = \mathrm{softmax}(\mathbf{z}/T)$, which never changes the predicted class; and vector scaling, $\mathbf{p} = \mathrm{softmax}(\mathbf{w} \odot \mathbf{z} + \mathbf{b})$ with one weight and bias per class. $T < 1$ sharpens the scores and therefore indicates an under-confident model.

D. Threshold behaviour

To quantify what calibration means for a deployed system, we compute the *coverage* $C(\tau)$, the share of frames whose confidence is at least a fixed threshold $\tau \in \{0.5, \ldots, 0.95\}$, together with the accuracy of those frames. For a calibrated model, the frames accepted at τ have an accuracy of at least τ, and coverage is as high as accuracy allows.

TABLE II. ACCURACY AND CALIBRATION OF THE UNCALIBRATED MODELS (MEAN ± STD OVER THREE SEEDS). BEST VALUE PER COLUMN IN BOLD. SP+MU: SPEECH+MUSIC CLASS.

	In-domain test				Unseen-source test			
Loss	Macro-F1 ↑	F1 sp+mu ↑	ECE ↓	cw-ECE ↓	Macro-F1 ↑	F1 sp+mu ↑	ECE ↓	cw-ECE ↓
Cross-entropy	**0.875** ± .003	**0.710** ± .018	**0.010** ± .003	**0.009** ± .003	**0.878** ± .011	**0.740** ± .022	0.010 ± .005	**0.011** ± .006
Weighted CE	0.862 ± .008	0.680 ± .023	0.011 ± .004	0.015 ± .001	0.863 ± .005	0.701 ± .013	**0.009** ± .005	0.022 ± .002
Focal loss	0.865 ± .003	0.686 ± .007	0.105 ± .008	0.054 ± .005	0.873 ± .004	0.730 ± .009	0.112 ± .009	0.058 ± .005
Label smoothing	0.866 ± .003	0.688 ± .011	0.059 ± .007	0.035 ± .001	0.874 ± .008	0.736 ± .005	0.060 ± .012	0.037 ± .000

IV. RESULTS

A. Accuracy is similar, calibration is not

Table II shows that all four losses reach a similar accuracy, with plain CE the most accurate: macro-F1 0.875 in-domain against 0.862–0.866 for the alternatives. None of the imbalance-oriented losses improves the rare speech+music class, whose F1 is 0.710 with CE and 0.680–0.688 otherwise. Calibration, in contrast, differs by an order of magnitude. CE has an ECE of 0.010 and weighted CE of 0.011, whereas focal loss reaches 0.105 and label smoothing 0.059. The paired clip bootstrap confirms that the ECE increase of focal loss and label smoothing over CE is significant in all three seeds on both test sets. Weighted CE leaves the top-label ECE unchanged but nearly doubles the classwise-ECE (0.015 against 0.009 in-domain).

B. The miscalibration is under-confidence

The reliability diagrams in Fig. 2 show the direction. CE and weighted CE lie close to the diagonal, with a mild over-confidence of 3–4 points in the 0.7–0.9 confidence range, which contains about 18% of the frames. Focal loss and label smoothing lie clearly *above* the diagonal: in the bin around 0.7 confidence, focal-loss frames are correct about 87% of the time. The fitted temperatures agree. They are 1.06 ± 0.04 for CE and 1.07 ± 0.06 for weighted CE, so these models are very slightly over-confident, but 0.53 ± 0.02 for focal loss and 0.68 ± 0.02 for

label smoothing, which means their scores must be sharpened, not softened.




Fig. 2. Reliability diagrams of the uncalibrated models (bins pooled over three seeds; bins with fewer than 0.1% of frames omitted). Points above the diagonal are under-confident: the model is right more often than it claims.




Fig. 3. Share of in-domain frames accepted at a fixed confidence threshold τ (mean ± std over seeds), before and after temperature scaling. The dotted line marks $\tau = 0.9$.

C. *Fixed thresholds change meaning*

Fig. 3 shows the practical consequence. At $\tau = 0.9$, the CE model accepts 80.6% of in-domain frames, weighted CE 78.3%, label smoothing 59.1% and focal loss only 34.9%, although all four models are about equally accurate. The accepted frames of the focal-loss model are correct 99.7% of the time while their mean confidence is 93.5%, so the threshold rejects many frames that the model in fact classifies correctly. The same pattern holds on the unseen-source test set (79.3%, 76.4%, 55.5% and 30.4%). After temperature scaling the curves nearly coincide: at $\tau = 0.9$ the spread between losses shrinks from 46 to 9 percentage points (CE 79.0%, weighted CE 76.5%, focal 74.9%, label smoothing 83.7%). At the default threshold of 0.5, by contrast, all losses behave alike: false alarms of a speech-versus-rest decision are 4.6–4.9% and misses 5.8–6.9% in-domain, and calibration hardly changes them. The effect therefore matters exactly where high thresholds are used to suppress false triggers.

Is re-tuning the threshold enough? A threshold re-tuned on labelled validation data for each model would reach a comparable operating point: at $\tau = 0.7$ the focal-loss model accepts 79.7% of in-domain frames at 97.7% accuracy, almost exactly what the CE model achieves at $\tau = 0.9$ (80.6%, 97.8%). Re-tuning therefore fixes one decision rule for one model. It does not fix the scores. A threshold keeps its meaning only if it is re-tuned for every model, every loss change and every rule that reads the scores, and many deployed rules are not re-tuned: thresholds are inherited from a previous model, written into product requirements as probabilities ("act when at least 90% sure"), or shared by several components. After temperature scaling, the frames accepted at $\tau = 0.9$ are correct 97.0–98.1% of the time for all four losses, so the same threshold means the same thing whichever loss was used. Before it, coverage at the same threshold ranges from 35% to 81%. Both remedies need the same validation data, but recalibration fixes the scores once, for every threshold.

TABLE III. FITTED TEMPERATURE AND ECE BEFORE (RAW) AND AFTER TEMPERATURE (TS) AND VECTOR SCALING (VS), MEANS OVER THREE SEEDS.

		In-domain			Unseen sources		
Loss	T	raw	TS	VS	raw	TS	VS
Cross-entropy	1.06	0.010	0.005	0.006	0.010	0.005	0.004
Weighted CE	1.07	0.011	0.006	0.007	0.009	0.003	0.003
Focal loss	0.53	0.105	0.007	0.005	0.112	0.006	0.006
Label smoothing	0.68	0.059	0.016	0.015	0.060	0.016	0.015




Fig. 4. ECE before and after post-hoc calibration fitted on in-domain validation data (mean ± std over seeds). W-CE: weighted CE; LS: label smoothing.

D. *One temperature repairs the damage*

Table III and Fig. 4 show that a single temperature, fitted on in-domain validation data, removes most of the miscalibration. Focal-loss ECE falls from 0.105 to 0.007 in-domain and from 0.112 to 0.006 on unseen sources; label smoothing falls from about 0.060 to 0.016 on both sets; CE halves from 0.010 to 0.005. Temperature scaling reduced ECE significantly in 11 of 12 models in-domain and 10 of 12 on unseen sources, without changing any prediction. Vector scaling gives similar ECE and additionally recovers part of the accuracy lost by weighted CE on unseen sources: macro-F1 rises from 0.863 to 0.879 and speech+music F1 from 0.701 to 0.740.

E. *Robustness checks*

Two further analyses support these findings. First, the calibrators transfer to the unseen-source test set: accuracy and ECE there match the in-domain values (macro-F1 0.878 against 0.875 and ECE 0.010 for CE), so the calibration differences are

not specific to the MUSAN recordings. Second, deployed VADs smooth their posteriors over time. A median filter of 5–21 frames raises CE macro-F1 by up to 0.004 (0.875 to 0.878 in-domain) and changes ECE by less than 0.001, both before and after temperature scaling. Smoothing therefore neither hides nor causes the miscalibration.

V. Discussion

Why the losses backfire. Focal loss and label smoothing were designed to counter the over-confidence of large networks [8], [9]. A compact VAD trained with CE is already nearly calibrated ($T \approx 1.06$), so the same corrections overshoot into under-confidence. This agrees with the finding that a fixed focal parameter can leave samples under-confident [10]. Our results extend that finding from image classifiers to a compact audio detector, where the over-correction affects the whole model and not just some samples: the fitted temperature is 0.53. They also show that the over-correction comes with no gain in accuracy. Label smoothing has a further, structural effect: with $\varepsilon = 0.1$ and $K = 4$ classes the training target for the correct class is $1 - \varepsilon + \varepsilon/K = 0.925$, so confidence rarely exceeds 0.95. This explains why the label-smoothing model accepts only 0.9% of frames at $\tau = 0.95$, and why we use $\tau = 0.9$ for the main comparison.

The rare class. None of the imbalance-oriented losses improved speech+music detection. For weighted CE, the vector-scaling bias fitted for the speech+music class is strongly negative (about −1.1, against −0.4 for CE), which suggests that class weighting mainly shifts the decision towards the rare class rather than learning it better; correcting this shift after training recovered part of the lost accuracy.

Practical recommendations. For compact multi-class VADs we recommend (i) starting from plain cross-entropy, (ii) refitting a temperature on validation data whenever the training loss or its hyper-parameters change, or else re-tuning every threshold that depends on the scores, and (iii) reporting calibration and coverage at the operating threshold alongside F1 or AUC.

Scope. The study uses one compact architecture and one setting per loss ($\gamma = 2$, $\varepsilon = 0.1$). The mixtures are synthetic, which gives exact frame labels but cleaner conditions than broadcast audio, and the unseen-source test changes the recordings while keeping the mixing recipe. As is standard practice [4], the validation set serves both early stopping and calibrator fitting. Larger self-supervised models, sweeps over γ and ε, and real recordings with co-occurrence labels [6] are natural next steps.

VI. Conclusion

We measured the calibration of a compact four-class voice activity detector trained with four losses. Plain cross-entropy produced the most accurate and best-calibrated detector. Focal loss and label smoothing, often used against class imbalance and over-confidence, made the detector strongly under-confident without improving the rare speech+music class, so that a threshold of 0.9 accepted between 35% and 81% of frames depending only on the loss. Re-tuning a threshold can hide this for one decision rule, but a single temperature fitted after training restored calibrated scores, and thus the meaning of every threshold, on in-domain audio and on audio from unseen corpora. Calibration should therefore be reported, and re-established, whenever a VAD's training loss changes. Code and result tables will be released with the final version of the paper.

References

[1] S. Bauer, S. Seidel, S. Iftikhar, S. Veidenheimer, and G. Ulkar, "VAD to the bone: Ultra-tiny speech activity detection for edge deployment," in *Proc. Interspeech*, 2026, arXiv:2607.25870.

[2] E. Cohen, A. Netzer, and H. V. Habi, "Low-latency state space voice activity detection with robust onset time evaluation," arXiv:2609.11110, 2026.

[3] H. Jafarzadeh Asl, M. Ghazvini Nejad, A. Edraki, M. Asgharian, and V. Partovi Nia, "Tiny noise-robust voice activity detector for voice assistants," in *Proc. IEEE International Workshop on Machine Learning for Signal Processing (MLSP)*, 2025, pp. 1–6.

[4] C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger, "On calibration of modern neural networks," in *Proc. International Conference on Machine Learning (ICML)*, ser. Proceedings of Machine Learning Research, vol. 70, 2017, pp. 1321–1330.

[5] P. Grundhuber, M. M. Halimeh, M. Strauß, and E. A. P. Habets, "Robust speech activity detection in the presence of singing voice," in *Proc. IEEE Workshop on Applications of Signal Processing to Audio and Acoustics (WASPAA)*, 2025, pp. 1–5.

[6] Y.-N. Hung, K. N. Watcharasupat, C.-W. Wu, I. Orife, K. Li, P. Seshadri, and J. Lee, "AVASpeech-SMAD: A strongly labelled speech and music activity detection dataset with label co-occurrence," arXiv:2111.01320, 2021.

[7] T.-Y. Lin, P. Goyal, R. Girshick, K. He, and P. Dollár, "Focal loss for dense object detection," in *Proc. IEEE International Conference on Computer Vision (ICCV)*, 2017, pp. 2999–3007.

[8] R. Müller, S. Kornblith, and G. Hinton, "When does label smoothing help?" in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019, arXiv:1906.02629.

[9] J. Mukhoti, V. Kulharia, A. Sanyal, S. Golodetz, P. H. S. Torr, and P. K. Dokania, "Calibrating deep neural networks using focal loss," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2020, arXiv:2002.09437.

[10] A. Ghosh, T. Schaaf, and M. R. Gormley, "AdaFocal: Calibration-aware adaptive focal loss," in *Advances in Neural Information Processing Systems (NeurIPS)*, vol. 35, 2022, pp. 1583–1595.

[11] M. Huo, Y. Zhang, and Y. Tang, "Identifying and calibrating overconfidence in noisy speech recognition," in *Proc. IEEE Automatic Speech Recognition and Understanding Workshop (ASRU)*, 2025, pp. 1–7.

[12] L. Dunker, S. A. Menta, S. M. Addepalli, and V. K. R. Garapati, "Semantic-aware confidence calibration for automated audio captioning," arXiv:2512.10170, 2025.

[13] R. Schwinger, B. McEwen, V. S. Kather, R. Heinrich, L. Rauch, and S. Tomforde, "Uncertainty calibration of multi-label bird sound classifiers," in *Proc. International Conference on Agents and Artificial Intelligence (ICAART)*, 2026.

[14] C.-C. Wang, E.-L. Yu, J.-W. Hung, S.-C. Huang, and B. Chen, "SincQDR-VAD: A noise-robust voice activity detection framework leveraging learnable filters and ranking-aware optimization," in *Proc. IEEE Automatic Speech Recognition and Understanding Workshop (ASRU)*, 2025, pp. 1–8.

[15] K. Tripathi, C. V. Kumar, and P. Wasnik, "Attention is not always the answer: Optimizing voice activity detection with simple feature fusion," in *Proc. Interspeech*, 2025, pp. 509–513.

[16] H. S. Bovbjerg, J. Østergaard, J. Jensen, and Z.-H. Tan, "Noise-robust target-speaker voice activity detection through self-supervised pretraining," arXiv:2501.03184, 2025.

[17] G. Yang, M. Huzaifah, Y. Pan, J. Sakurai, and N. Bai, "Foreground voice activity detection: Learning speaker selectivity from supervision," arXiv:2609.19856, 2026.

[18] S. Ding, Q. Wang, S. yiin Chang, L. Wan, and I. Lopez Moreno, "Personal VAD: Speaker-conditioned voice activity detection," in *Proc. The Speaker and Language Recognition Workshop (Odyssey)*, 2020, pp. 433–439.

[19] Y.-T. Yeh, C.-C. Chang, and J.-W. Hung, "Empirical analysis of learning improvements in personal voice activity detection frameworks," *Electronics*, vol. 14, no. 12, p. 2372, 2025.

[20] Z. Sun, L. Zhang, Q. Wang, P. Zhou, and L. Xie, "Towards robust overlapping speech detection: A speaker-aware progressive approach using WavLM," in *Proc. Interspeech*, 2025, pp. 1653–1657.

[21] M. Kull, M. Perello-Nieto, M. Kängsepp, T. Silva Filho, H. Song, and P. Flach, "Beyond temperature scaling: Obtaining well-calibrated multiclass probabilities with Dirichlet calibration," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2019, arXiv:1910.12656.

[22] P.-A. Mattei and B. Loureiro, "The well-tempered classifier: Some elementary properties of temperature scaling," arXiv:2602.14862, 2026.

[23] E. Berta, D. Holzmüller, F. Bach, and M. I. Jordan, "CalArena: A large-scale post-hoc calibration benchmark," arXiv:2605.30188, 2026.

[24] C. Penso, "Confidence calibration of deep learning systems," arXiv:2608.12100, 2026, thesis.

[25] T. T. N. Bahavan, S. Seneviratne, and S. Halgamuge, "FedLAS: Feature-modulated bidirectional label smoothing for neural network calibration," arXiv:2606.28654, 2026, provisionally accepted at ECCV 2026.

[26] J. Lin, L. Tao, M. Dong, and C. Xu, "Uncertainty weighted gradients for model calibration," in *Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2025, pp. 15 497–15 507.

[27] B. P. Jagati, J. Tembhurne, H. Goud, R. P. Singh, and C. Meshram, "Class confidence aware reweighting for long tailed learning," arXiv:2601.15924, 2026.

[28] D. Snyder, G. Chen, and D. Povey, "MUSAN: A music, speech, and noise corpus," arXiv:1510.08484, 2015.

[29] V. Panayotov, G. Chen, D. Povey, and S. Khudanpur, "Librispeech: An ASR corpus based on public domain audio books," in *Proc. IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2015, pp. 5206–5210.

[30] G. Tzanetakis and P. Cook, "Musical genre classification of audio signals," *IEEE Transactions on Speech and Audio Processing*, vol. 10, no. 5, pp. 293–302, 2002.

[31] K. J. Piczak, "ESC: Dataset for environmental sound classification," in *Proc. 23rd ACM International Conference on Multimedia*, 2015, pp. 1015 –1018.