

Thời gian còn lại 0:20:14

Câu hỏi 3

Không hoàn thành

Chấm điểm của 2,00

Class `BSTNode` is used to store a node in binary search tree, described on the following:

```
class BSTNode {
public:
    int val;
    BSTNode *left;
    BSTNode *right;
    BSTNode() {
        this->left = this->right = nullptr;
    }
    BSTNode(int val) {
        this->val = val;
        this->left = this->right = nullptr;
    }
    BSTNode(int val, BSTNode*& left, BSTNode*& right) {
        this->val = val;
        this->left = left;
        this->right = right;
    }
};
```

Where `val` is the value of node, `left` and `right` are the pointers to the left node and right node of it, respectively. If a repeated value is inserted to the tree, it will be inserted to the left subtree.

Also, a static method named `createBSTree` is used to create the binary search tree, by iterating the argument array left-to-right and repeatedly calling `addNode` method on the root node to insert the value into the correct position. For example:

```
int arr[] = {0, 10, 20, 30};
auto root = BSTNode::createBSTree(arr, arr + 4);
```

is equivalent to

```
auto root = new BSTNode(0);
root->addNode(10);
root->addNode(20);
root->addNode(30);
```

Request: Implement function:

```
int singleChild(BSTNode* root);
```


Where `root` is the root node of given binary search tree (this tree has between 0 and 100000 elements). This function returns the number of single children in the tree.

More information:

- A node is called a **single child** if its parent has only one child.

Example:

Given a binary search tree in the following:



There are 2 single children: node 2 and node 3.

Note: In this exercise, the libraries `iostream` and `using namespace std` are used. You can write helper functions; however, you are not allowed to use other libraries.

For example:

Test	Result
<pre>int arr[] = {0, 3, 5, 1, 2, 4}; BSTNode* root = BSTNode::createBSTree(arr, arr + sizeof(arr)/sizeof(int)); cout << singleChild(root); BSTNode::deleteTree(root);</pre>	3

Answer: (penalty regime: 0, 0, 0, 5, 10, ... %)

Reset answer

```
1 int singleChild(BSTNode* root) {
2     // STUDENT ANSWER
3 }
```

Precheck

Kiểm tra

BÁCH KHOA E-LEARNING



WEBSITE

HCMUT

MyBK

BKSI

LIÊN HỆ

📍 268 Lý Thường Kiệt, P.14, Q.10, TP.HCM

☎ (028) 38 651 670 - (028) 38 647 256 (Ext: 5258, 5234)

