Interview Questions: Quicksort (ungraded)

3/3 points (100%)

Practice Quiz, 3 questions

✔ Congratulations! You passed!

Next Item

✔ 1 / 1 points

1.

Nuts and bolts. A disorganized carpenter has a mixed pile of n nuts and n bolts. The goal is to find the corresponding pairs of nuts and bolts. Each nut fits exactly one bolt and each bolt fits exactly one nut. By fitting a nut and a bolt together, the carpenter can see which one is bigger (but the carpenter cannot compare two nuts or two bolts directly). Design an algorithm for the problem that uses $n \log n$ compares (probabilistically).

Note: these interview questions are ungraded and purely for your own enrichment. To get a hint, submit a solution.

quick sort

Your answer cannot be more than 10000 characters.

Thank you for your response.

Hint: modify the quicksort partitioning part of quicksort.

R*emark*: This research paper gives an algorithm that runs in $n \log^4 n$ time in the worst case.

Interview Questions: Quicksort (ungraded)

3/3 points (100%)

Practice Quiz, 3 questions

1 / 1 points

2.

Selection in two sorted arrays. Given two sorted arrays $a[\,]$ and $b[\,]$, of sizes n_1 and n_2, respectively, design an algorithm to find the k^{th} largest key. The order of growth of the worst case running time of your algorithm should be $\log n$, where $n = n_1 + n_2$.

- Version 1: $n_1 = n_2$ and $k = n/2$
- Version 2: $k = n/2$
- Version 3: no restrictions

version 1

Your answer cannot be more than 10000 characters.

Thank you for your response.

Hint: there are two basic approaches.

- Approach A: Compute the median in $a[\,]$ and the median in $b[\,]$. Recur in a subproblem of roughly half the size.
- Approach B: Design a constant-time algorithm to determine whether $a[i]$ is the k^{th} largest key. Use this subroutine and binary search.

Dealing with corner cases can be tricky.

---

1 / 1 points

3.

Interview Questions: Quicksort (ungraded)

Practice Quiz, 3 questions

Decimal dominants. Given an array with n keys, design an algorithm to find all values that occur more than $n/10$ times. The expected running time of your algorithm should be linear.

3/3 points (100%)

quick sort 3-way

Your answer cannot be more than 10000 characters.

Thank you for your response.

Hint: determine the $(n/10)^{th}$ largest key using quickselect and check if it occurs more than $n/10$ times.

Alternate solution hint: use 9 counters.