

USB4 1.0 ENGINEERING CHANGE NOTICE FORM

Title: Disconnect Behavior During Lane Disable
Applied to: USB4 Specification Version 1.0

Brief description of the functional changes:

Requiring the Disconnect behavior only when Lane 0 of the Port is enabled.
--

Benefits as a result of the changes:

A full description of expected behavior

An assessment of the impact to the existing revision and systems that currently conform to the USB specification:
--

None

An analysis of the hardware implications:
--

None

An analysis of the software implications:
--

None

An analysis of the compliance testing implications:
--

No checks for Disconnect behavior when Lane 0 of the Port is disabled.
--

USB4 1.0 ENGINEERING CHANGE NOTICE FORM

Actual Change

(a). 4.4.5 – Disconnect

To Text:

This section defines how a disconnect on a USB4 Port is handled when Lane Disable bit in the Lane 0 Adapter Configuration Capability is set to 0b. When a disconnect is required, it takes precedence over all other pending requirements.

(b). 4.4.5.2.1 – SBRX Goes Low

To Text:

When a Downstream Facing Port detects SBRX at logical low for tDisconnectRx ~~and its Lane Disable bit in the Lane 0 Adapter Configuration Capability is set to 0b~~, the USB4 Port is disconnected and shall: