

USB4 2.0 ENGINEERING CHANGE NOTICE FORM

Title: LTTPR Revision (DPCD F0000h)
Applied to: USB4 Specification Version 2.0

Brief description of the functional changes:

LTTPR revision condition was fixed:

1. It had a typo 21h instead of 20h
2. It needs to consider the position of the Adapters in respect to the chain of LTTPRs

Benefits as a result of the changes:

USB4 spec is coherent and aligned to the DisplayPort spec

An assessment of the impact to the existing revision and systems that currently conform to the USB specification:
--

None

An analysis of the hardware implications:
--

None

An analysis of the software implications:
--

None

An analysis of the compliance testing implications:
--

None

USB4 2.0 ENGINEERING CHANGE NOTICE FORM

Actual Change

(a). Table 10-13. Aggregated DisplayPort Capabilities

Table 10-13. Aggregated DisplayPort Capabilities

DPCD Register (Address)	DPCD Field Name	DisplayPort Capability
LT_TUNABLE_PHY_REPEATER_FIELD_DATA_STRUCTURE_REV (F0000h)	Revision Number	If DP_COMMON_CAP.Protocol Adapter Version equals 5h: -, If DP Adapters are the nearest LTTPR to the DPRX then set to 20h else set to Min{24h20h, Downstream response}. Else set to 14h.

(b). Table 10-1. DisplayPort Feature Requirements

Table 10-1. DisplayPort Feature Requirements

Feature/Attribute	Requirement
LTTPR Revision	24h 20h