

## Video 22 : Functions as Objects

In this video I'll explore how we can treat functions as objects which opens up a world of possibilities. We'll also explore function annotations. Then we'll present you with another problem for you to solve.

### CODE

```
# Function multiplies a parameter by 2
def mult_by_2(num):
    return num * 2

# A function can be
# 1. Assigned to another name

times_two = mult_by_2

print("4 * 2 =", times_two(4))

# 2. Passed into other functions

def do_math(func, num):

    return func(num)

print("8 * 2 =", do_math(mult_by_2, 8))

# 3. Returned from a function

def get_func_mult_by_num(num):

    # Create a dynamic function that will receive a value
    # and then return that value times the value passed
    # into get_func_mult_by_num()
    def mult_by(value):
        return num * value

    return mult_by

generated_func = get_func_mult_by_num(5)

print("5 * 10 =", generated_func(10))

# 4. Embedded in a data structure

list_of_funcs = [times_two, generated_func]

print("5 * 9 =", list_of_funcs[1](9))
```

Python Problem for you to Solve

Now that we have explored new ways we can use functions let's try another problem. I want you to create a function that receives a list and a function. The function passed will return True

or False if a list value is odd. And then the surrounding function will return a list of odd numbers.

### **Solution**

```
def is_it_odd(num):
    if num % 2 == 0:
        return False
    else:
        return True

def change_list(list, func):

    odd_list = []

    for i in list:
        if func(i):
            odd_list.append(i)

    return odd_list

a_list = range(1, 21)

print(change_list(a_list, is_it_odd))
```

### **Function Annotations**

It is possible to define the data types of attributes and the returned value with annotations, but they have no impact on how the function operates, but instead are for documentation.

```
def random_func(name: str, age: int, weight: float) -> str:
    print("Name :", name)
    print("Age :", age)
    print("Weight :", weight)

    return "{} is {} years old and weighs {}".format(name, age, weight)

print(random_func("Derek", 41, 165.5))

# You don't get an error if you pass bad data
print(random_func(89, "Derek", "Turtle"))

# You can print the annotations
print(random_func.__annotations__)
```

That's it for this video. In the next video we'll cover Anonymous functions, lambda, map, filter, reduce and 2 new problems.