

Scheme

Announcements

Scheme

Scheme is a Dialect of Lisp

What are people saying about Lisp?

- "If you don't know Lisp, you don't know what it means for a programming language to be powerful and elegant."
 - Richard Stallman, created Emacs & the first free variant of UNIX
- "The only computer language that is beautiful."
 - Neal Stephenson, DeNero's favorite sci-fi author
- "The greatest single programming language ever designed."
 - Alan Kay, co-inventor of Smalltalk and OOP (from the user interface video)

Scheme Expressions

Scheme programs consist of expressions, which can be:

- Primitive expressions: 2 3.3 true + quotient
- Combinations: (quotient 10 2) (not true)

Numbers are self-evaluating; symbols are bound to values

Call expressions include an operator and 0 or more operands in parentheses

```
> (quotient 10 2)
5
> (quotient (+ 8 7) 5)
3
> (+ (* 3
      (+ (* 2 4)
          (+ 3 5)))
      (+ (- 10 7)
          6))
```

“quotient” names Scheme’s
built-in integer division
procedure (i.e., function)

Combinations can span
multiple lines
(spacing doesn’t matter)

(Demo)

Special Forms

Special Forms

A combination that is not a call expression is a special form:

- **if** expression: `(if <predicate> <consequent> <alternative>)`
- **and** and **or**: `(and <e1> ... <en>)`, `(or <e1> ... <en>)`
- **Binding symbols**: `(define <symbol> <expression>)`
- **New procedures**: `(define (<symbol> <formal parameters>) <body>)`

Evaluation:
(1) Evaluate the predicate expression
(2) Evaluate either the consequent or alternative

```
> (define pi 3.14)
> (* pi 2)
6.28
```

The symbol "pi" is bound to 3.14 in the global frame

```
> (define (abs x)
  (if (< x 0)
      (- x)
      x))
> (abs -3)
3
```

A procedure is created and bound to the symbol "abs"

(Demo)

Scheme Interpreters

(Demo)

Lambda Expressions

Lambda Expressions

Lambda expressions evaluate to anonymous procedures

```
(lambda (<formal-parameters>) <body>)
```

Two equivalent expressions:

```
(define (plus4 x) (+ x 4))
```

```
(define plus4 (lambda (x) (+ x 4)))
```



An operator can be a call expression too:

```
((lambda (x y z) (+ x y (square z))) 1 2 3) ► 12
```

Evaluates to the
 $x+y+z^2$ procedure

Sierpinski's Triangle

(Demo)

More Special Forms

Cond & Begin

The cond special form that behaves like if-elif-else statements in Python

if x > 10: print('big')		(print
elif x > 5: print('medium')	(cond ((> x 10) (print 'big'))	(cond ((> x 10) 'big)
else: print('small')	((> x 5) (print 'medium'))	((> x 5) 'medium)
	(else (print 'small'))	(else 'small'))

The begin special form combines multiple expressions into one expression

if x > 10: print('big')	(cond ((> x 10) (begin (print 'big)	(print 'guy'))
print('guy')	(else (begin (print 'small)	(print 'fry'))))
else: print('small')	(if (> x 10) (begin	
print('fry')	(print 'big)	
	(print 'guy'))	
	(begin	
	(print 'small')	
	(print 'fry'))	

Let Expressions

The `let` special form binds symbols to values temporarily; just for one expression

```
a = 3
b = 2 + 2
c = math.sqrt(a * a + b * b)
a and b are still bound down here
```


```
(define c (let ((a 3)
                 (b (+ 2 2)))
  (sqrt (+ (* a a) (* b b)))))
a and b are not bound down here
```

Lists

Scheme Lists


In the late 1950s, computer scientists used confusing names

- **cons:** Two-argument procedure that creates a linked list
- **car:** Procedure that returns the first element of a list
- **cdr:** Procedure that returns the rest of a list
- **nil:** The empty list



Important! Scheme lists are written in parentheses with elements separated by spaces

```
> (cons 1 (cons 2 nil))  
(1 2)  
> (define x (cons 1 (cons 2 nil)))  
> x  
(1 2)  
> (car x)  
1  
> (cdr x)  
(2)  
> (cons 1 (cons 2 (cons 3 (cons 4 nil))))  
(1 2 3 4)
```



(Demo)

Symbolic Programming

Symbolic Programming

Symbols normally refer to values; how do we refer to symbols?

```
> (define a 1)
> (define b 2)
> (list a b)
(1 2)
```

No sign of “a” and “b” in the resulting value

Quotation is used to refer to symbols directly in Lisp.

```
> (list 'a 'b)
(a b)
> (list 'a b)
(a 2)
```

Short for **(quote a)**, (quote b):
Special form to indicate that the expression itself is the value.

Quotation can also be applied to **combinations** to form lists.

```
> '(a b c)
(a b c)
> (car '(a b c))
a
> (cdr '(a b c))
(b c)
```

(Demo)

Programs as Data

A Scheme Expression is a Scheme List

Scheme programs consist of expressions, which can be:

- Primitive expressions: 2 3.3 true + quotient
- Combinations: (quotient 10 2) (not true)

The built-in Scheme list data structure (which is a linked list) can represent combinations

```
scm> (list 'quotient 10 2)
(quotient 10 2)
```

```
scm> (eval (list 'quotient 10 2))
5
```

In such a language, it is straightforward to write a program that writes a program

(Demo)

Generating Code

Quasiquote

There are two ways to quote an expression

Quote: '(a b) => (a b)

Quasiquote: `(a b) => (a b)

They are different because parts of a quasiquoted expression can be **unquoted with ,**

```
(define b 4)
```

Quote: '(a ,(+ b 1)) => (a (unquote (+ b 1)))

Quasiquote: `(a ,(+ b 1)) => (a 5)

Quasiquote is particularly convenient for generating Scheme expressions:

```
(define (make-add-procedure n) `(lambda (d) (+ d ,n)))
```

```
(make-add-procedure 2) => (lambda (d) (+ d 2))
```

Example: While Statements

What's the sum of the squares of even numbers less than 10, starting with 2?

```
x = 2
total = 0
while x < 10:
    total = total + x * x
    x = x + 2
```

```
(begin
  (define (f x total)
    (if (< x 10)
        (f (+ x 2) (+ total (* x x)))
        total))
  (f 2 0)))
```

What's the sum of the numbers whose squares are less than 50, starting with 1?

```
x = 1
total = 0
while x * x < 50:
    total = total + x
    x = x + 1
```

```
(begin
  (define (f x total)
    (if (< (* x x) 50)
        (f (+ x 1) (+ total x))
        total))
  (f 1 0)))
```

(Demo)