





```
select airport.airport_code,count(flight_id)as number
from airports_data airport
join flights f on airport.airport_code = f.arrival_airport or airp
where airport_code IN('KZN','DME','OVB','IKT','LED','SVO')
g⊫oup by airport.airport_code
order by airport_code DESC
  □ number ÷
    1 SVO
                             5963
  2 OVB
                             2110
  3 LED
                             3802
  4 KZN
                             941
  5 IKT
                             731
  6 DME
                             6434
```

```
select airport.airport_code,count(flight_id)as number
 from airports_data airport
 join flights f on airport.airport_code = f.arrival_airport or airp
 where airport_code IN('KZN','DME','OVB','IKT','LED','SVO')
 g⊫oup by airport.airport_code
 order by airport_code DESC
      Output
                  m Result 6 ×
                      < 6 rows ~
        ☐ airport_code
                                       □ number ÷
     1 SV0
                                               5963
     2 OVB
                                               2110
     3 LED
                                               3802
                                                941
     4 KZN
     5 IKT
                                                731
                                               6434
     6 DME
select concat('Код:',airport_code,',Имя:',airport_name,'Город:',city,',Координаты:',coordinates,',Временная зона:',timezone)as info
from airports_data
order by info
                  Код:AER,Имя:{"en": "Sochi International Airport", "ru":...
                    Код:ASF,Имя:{"en": "Astrakhan Airport", "ru": "Астрахан...
```