





UNIVERSITY OF COLOMBO SCHOOL OF COMPUTING

DEGREE OF BACHELOR OF INFORMATION TECHNOLOGY (EXTERNAL)

Academic Year 2005/2006 – 2nd Year Examination – Semester 3

IT3102: Object Oriented Systems Development PART 2 – Structured Question Paper

18th March, 2006 (ONE AND HALF HOURS)

To be completed by th	e candid	late	
BIT Examination	Index	No:	

Important Instructions:

- The duration of the paper is 1 ½ (one and half) hours.
- The medium of instruction and questions is English.
- This paper has 4 questions and 12 pages.
- Answer question 1 and any 2 of the other questions only.
- All questions will carry equal marks.
- Write your answers in English using the space provided in this question paper.
- Do not tear off any part of this answer book.
- Under no circumstances may this book, used or unused, be removed from the Examination Hall by a candidate.
- Note that questions appear on both sides of the paper.

 If a page is not printed, please inform the supervisor immediately.
- Non-programmable Calculators may be used.

Questions Answered	Q	ues	tions	: Ans	we	ered	
--------------------	---	-----	-------	-------	----	------	--

Indicate by a cross (x), (e.g. X) the numbers of the questions answered.

	(Question	number	·s	
To be completed by the candidate by marking a cross (x).	1	2	3	4	
To be completed by the examiners:					

Based on the following case study answer question 1.

1)

ABC Bank

Case Study

The following text describes the operations of the ABC Bank.

The ABC Bank wishes to develop an information system for handling accounts. The following is a summary of interviews with employees and customers of the Bank in connection with the matter.

The Bank has three different types of account, namely Savings Account (SA), Checking Account (ChA) and Current Account (CuA). CuAs are meant for Corporate Customers and are opened in the name of the Corporation/Company/Organization. SAs or ChAs can be in the name of one person as an individual account or in the name of more than one person as a joint account. In the case of a joint account, one of the account holders is identified as the nominated customer. In the case of a CuA, the nominated customer is the Corporation/Company/Organization.

SA Customers do not get Monthly Account Statements(MS). Instead, each SA Customer has a passbook which gets updated on request after presentation. The Bank has printers and printing software in place for updating passbooks.

A Checking Account (ChA) is just like a SA, except that customers can also write cheques. Books of cheques are sold at Rs. 500/- per book of 100 cheques. When cheque #90 comes in, a notice is sent to the address of the nominated customer via mail asking whether he needs to purchase more cheques. ChAs do not have passbooks, and SAs do not have MSs.

A Current Account (CuA) works like a ChA, with a few extra features. For example, a Quarterly Account Statement (QS) (which is exactly the same as a Monthly Account Statement (MS), except that it is done for an entire quarter) is sent out, in addition to the regular MS. The QS is sent in the same envelope as the statement for that month. CuA are not joint accounts and they cannot be accessed through an ATM (Automatic Teller Machine). Furthermore, because of the different service needs of the corporate customers, they are dealt with at special branches called "Corporate Branches" which serve only corporate customers. Although corporate customers can be served at 'retail branches', they rarely do because the tellers in a retail branch do not have the necessary background to meet their special needs.

Customers are able to open and close accounts. They can withdraw money and deposit money or cheques, or get the current balance. The current balance is displayed on an account update screen, which will be part of the teller's information system. This screen displays the account number, the nominated customer's name, and the current balance of the account. An account is associated with a specific branch. Although the Bank now supports multi-branch Banking, every account is still assumed to have a 'home' branch.

More than one account can be accessible from a ATM (Automatic Teller Machine) Card issued by the Bank. Any customer except corporate customers can request for an ATM card. Customers can access their accounts using two different methods: at an ATM or at a Bank branch. ATMs enable customers to deposit to, withdraw from, and get balance statements of their accounts. They can also pay bills (this is basically a withdrawal) and transfer money between accounts (this is basically withdrawing from one account and depositing into another).

Everything that can be done at the Bank can also be done by a real live teller in a branch. The teller will have an information system that provides the screens to perform all of these functions. Additionally, tellers can also help customers to open and close their accounts, as well as print out account statements for the customer. Such account statements are just like the MS or QSs, except that they can be for any time period. For example the customer could request a statement from the 15th August to 23rd of September, and the system should print the statement immediately.

MS and QSs are normally printed out on the first Saturday of the following month. This is done as an automated batch job.

The Bank has started setting up ATMs into variety stores and restaurants. Every ATM, including those in the branches, are considered as branches of the Bank. This means that ATMs will have branch Ids and addresses, just like a normal branch.

To manage the Bank effectively, it is split up into collections of branches called 'areas'. An area is a group of between 10 and 30 branches. Each ATM belongs to one and only one area. Each area has a unique name and is managed by an 'Area Manager' who receives weekly transaction summary reports every Monday before 9 in the morning. This report summarizes separately the number and total amounts of all withdrawals, deposits, and bill payments performed at each branch (including ATMs) for the previous week. For branches where accounts can be opened, there is also an indication of how many accounts were opened during the week, how many accounts in total were there at the end of the week, and how many accounts were closed during the week. Finally all these figures are summarized, and will be sent to the Area Manager.

(a) Identify the Actors and the Use Cases one should identify for this system.

(30% Marks)

ANSWER	R IN THIS BOX	
Act	tors: Customer, ATM	
Use	e Cases : Open Account, Close Account, Withdraw Money, Deposit	
Мо	ney, Get Account Balance , Transfer Money, Pay Bills, Get Reports	

(b) Identify the potential Classes for the above system.

(30 Marks)

ANSWER IN THIS BOX	·
Area	Customer
Branch	Account
Retail Branch	Savings Account
Corporate Branch	Current Account
ATM	Checking Account

(c) Identify the static relationships between the above classes identified in (b). Indicate the cardinality of the appropriate relationships.

(25% Marks)

ANSWER IN THIS BOX					
Class name1	Class name2	Relationship and UML notation			
Area	Branch	Composition 1 1*			
Branch	Account	Composition 1 1*			
Retail Branch	Branch	Inherintance			
Corporate Branch	Branch	Inherintance			
Customer					
Account	Customer	*1 Association			
Savings Account	Account	Generalization			
Current Account	Account	Generalization			
Checking Account	Account	Generalization			

(d) Identify the object(s) responsible for the Use Case *Close Account*(a).

(15% Marks)

	(13/0 Marks)
ANSWER IN THIS BOX	
Customer, Account, Savings Account, Current Account, Checking Account	

2) (a) Consider the following scenario related to buying a drink from a drink dispenser machine.

When a customer wants to buy a drink from the drink dispenser he/she first makes a selection and inserts the money. The register checks for the availability of the selected drink in the dispenser. If it is not in the stock returns the money and display message "Sold Out". If the selected drink is in the stock the register checks for the money input. If it is insufficient returns the money and display message "Insufficient cash" otherwise the dispenser releases the drink.

(i) Identify the classes in the above scenario.

(10% Marks)


ANSWER IN THIS I	BOX
Register Dispenser	Interface class

(ii) Draw a sequence diagrams that models the scenario where selected drink is not available.


(15% Marks) **ANSWER IN THIS BOX** <u>Customer</u> <u>Interface</u> <u>Register</u> <u>Dispenser</u> accept(cah,selection) getCustomerInput(cash,selection) checkAvailability() returnCash() DisplayPrompt("Sold out")

(iii) Draw a sequence diagrams that models the scenario where selected drink is available and the input money is sufficient.

(15% Marks)



(b) Consider the following class Diagram:



The Volume of a Cylinder can be found with the following formula:

Volume = PI * Radius*Radius*Height where PI=3.14159

It is required to map the above class diagram to C++ code.

(i) W	Vrite down the C++ definition of class container	(200/ Mayles)
	ANSWER IN THIS BOX	(20% Marks)
	class Container	
	{	
	public.	
	virtual double Volume()=0; };	
(ii)	Write the C++ Definition of class CylindricalContainer. (Method implementation is not	needed.) (20% Marks)
	ANSWER IN THIS BOX	(20 /0 Walks)
	class CylindricalContainer : public Container	
	{ double Radius, Height;	
	public: CylindricalContainer(double R, double H);	
	double volume(),	
•	} ;	
(iii)	Implement the Volume function	(20% Marks)
	ANSWER IN THIS BOX	(20 /0 Walks)
	double Volume()	
	return Radius*Radius*Height*3.14159;	
	}	

3) (a) A Use Case narrative for receiving a product into a ware house is given below.

Use Case Name Receive Product

Number 3.0 Author J.Y. Perera

Assumptions The use has authority to use this transaction Pre Conditions Shipment is from a valid shipping company

Use Case Initiation This Use Case starts on demand

Use Case dialog The user enters the shipper identification number (ShipperID)

If not found, display the "Shipper not found" error message

Prompt to re-enter or cancel

Else (found) proceed Display the Shipper Details

Enter the Shipment details (date, sender, number of pieces)

For each product in the Shipment

Find the Purchase Order using the PO_nbr

If not found, display "invalid P.O." error message

and set the item aside Else (P.O. found)

Match the product to an item on the Purchase Order.

If not matched, display "invalid item" error message and set the item

aside

Else check off the item and qty on the Purchase Order Notify Accounts payable of the updated Purchase Order Display the "Accounts Payable Notified" message

And

Update inventory for the items Products received Display "inventory updated successfully" message

Print the receiving confirmation

Use Case termination This Use Case ends when:

The System displays the message that it could not find the Shipping

company and the user cancels

Accounts Payable has been notified and the inventory has been updated.

The User cancels the transaction

Post-conditions Upon successfully completion of the transaction:

Update inventory

Notify Accounts Payable


Print a confirmation to go with the receiving documents

Upon receiving the cancel option:

Return to its initial state prior to this Use Case

Draw an Activity Diagram for the given Use Case narrative for Receive Product.

(100 % Marks)



The twattribut area of Class Cattribut there in	of attributes are of type double. The two argument constructor sets values to the two es. A public pure virtual function, <i>calcArea</i> with return type double, which will return the figure is defined in this class as well. Chicago recommendation of the control o
The twattribut area of Class (attribut there in Area of	of attributes are of type double. The two argument constructor sets values to the two sets. A public pure virtual function, <i>calcArea</i> with return type double, which will return to the figure is defined in this class as well. Coircle needs to be created based on Cfigure. This class should utilize only dimentioned defined in Cfigure, to hold the radius of the Circle. A constructor with a single argument of class Coircle and calcalated by using the formula 3.14*radius*radius. at type of a class is Cfigure in terms of C++? Give reasons for your answer
The twattribut area of Class (attribut there in Area of	or attributes are of type double. The two argument constructor sets values to the two sets. A public pure virtual function, <i>calcArea</i> with return type double, which will return to the figure is defined in this class as well. Ceircle needs to be created based on Cfigure. This class should utilize only dimention to defined in Cfigure, to hold the radius of the Circle. A constructor with a single argument of class Ceircle and calcarea function in Cfigure is overridden in this class. If a circle is calculated by using the formula 3.14*radius*radius. at type of a class is Cfigure in terms of C++? Give reasons for your answer
The tw attribut area of Class C attribut there in Area of	Coircle needs to be created based on Cfigure. This class should utilize only dimention e defined in Cfigure, to hold the radius of the Circle. A constructor with a single argument a class Coircle a calcArea function in Cfigure is overridden in this class. If a circle is calculated by using the formula 3.14*radius*radius.

answer in this box class Cfigure { protected: double dimention1; double dimention2; public: Cfigure(double d1, double d2); virtual double calcArea() = 0; }; at is the type of relationship that exists between Cfigure and Ccircle in terms of UML ANSWER IN THIS BOX INHERITANCE fine the class Ccircle in C++ (15% Man ANSWER IN THIS BOX class Ccircle: public Cfigure { public: Ccircle(int r): Cfigure(r) double calcArea(); };	ANS	
class Cfigure { protected:		
at is the type of relationship that exists between Cfigure and Ccircle in terms of UML ANSWER IN THIS BOX INHERITANCE ANSWER IN THIS BOX Class Ccircle: public Cfigure { public:		
double dimention1; double dimention2; public: Cfigure(double d1, double d2); virtual double calcArea() = 0; }; at is the type of relationship that exists between Cfigure and Ccircle in terms of UML (10% Mai ANSWER IN THIS BOX INHERITANCE fine the class Ccircle in C++ (15% Mai ANSWER IN THIS BOX class Ccircle : public Cfigure { public:		class Cfigure {
double dimention2; public: Cfigure(double d1, double d2); virtual double calcArea() = 0; }; at is the type of relationship that exists between Cfigure and Ccircle in terms of UML (10% Man ANSWER IN THIS BOX INHERITANCE fine the class Ccircle in C++ (15% Man ANSWER IN THIS BOX class Ccircle : public Cfigure { public:		
public: Cfigure(double d1, double d2); virtual double calcArea() = 0; }; at is the type of relationship that exists between Cfigure and Ccircle in terms of UML (10% Man ANSWER IN THIS BOX INHERITANCE ine the class Ccircle in C++ (15% Man ANSWER IN THIS BOX class Ccircle : public Cfigure { public:		
virtual double calcArea() = 0; }; at is the type of relationship that exists between Cfigure and Ccircle in terms of UML (10% Mai ANSWER IN THIS BOX INHERITANCE ine the class Ccircle in C++ (15% Mai ANSWER IN THIS BOX class Ccircle : public Cfigure		public:
at is the type of relationship that exists between Cfigure and Ccircle in terms of UML (10% Man ANSWER IN THIS BOX INHERITANCE INHERITANCE (15% Man ANSWER IN THIS BOX class Ccircle : public Cfigure		
at is the type of relationship that exists between Cfigure and Ccircle in terms of UML (10% Man ANSWER IN THIS BOX INHERITANCE (15% Man ANSWER IN THIS BOX class Ccircle : public Cfigure { public: Ccircle(int r) : Cfigure(r) double calcArea();		· · · · · · · · · · · · · · · · · · ·
ine the class Ccircle in C++ (15% Mail ANSWER IN THIS BOX class Ccircle: public Cfigure { public:		} ;
INHERITANCE Ine the class Ccircle in C++ (15% Mail ANSWER IN THIS BOX class Ccircle : public Cfigure { public:		
INHERITANCE Intervention of the class Coircle in C++ (15% Mail Answer in this box class Coircle : public Cfigure { public:		
INHERITANCE fine the class Ccircle in C++ (15% Mail ANSWER IN THIS BOX class Ccircle : public Cfigure { public:		
INHERITANCE Interest in C++ (15% Main and a second and		
INHERITANCE fine the class Ccircle in C++ (15% Mail ANSWER IN THIS BOX class Ccircle : public Cfigure { public:		
INHERITANCE fine the class Ccircle in C++ (15% Mail ANSWER IN THIS BOX class Ccircle : public Cfigure { public:		
INHERITANCE Interpretation of the class Coircle in C++ (15% Mail Answer in this box class Coircle : public Cfigure	at is the	e type of relationship that exists between Cfigure and Ccircle in terms of UML
INHERITANCE fine the class Ccircle in C++ (15% Man ANSWER IN THIS BOX class Ccircle : public Cfigure public: Ccircle(int r) : Cfigure(r) double calcArea();	-	(10% M
fine the class Ccircle in C++ (15% Man ANSWER IN THIS BOX class Ccircle : public Cfigure	ANS	SWER IN THIS BOX
class Ccircle : public Cfigure public: Ccircle(int r) : Cfigure(r) double calcArea();		INHERITANCE
class Ccircle : public Cfigure public: Ccircle(int r) : Cfigure(r) double calcArea();		
class Ccircle : public Cfigure public: Ccircle(int r) : Cfigure(r) double calcArea();		
class Ccircle : public Cfigure		
class Ccircle : public Cfigure		
class Ccircle : public Cfigure { public:	See	
class Ccircle : public Cfigure { public:	ine the	
public: Ccircle(int r) : Cfigure(r) double calcArea();	ine the	
public: Ccircle(int r) : Cfigure(r) double calcArea();		(15% Ma
Ccircle(int r) : Cfigure(r) double calcArea();		SWER IN THIS BOX
double calcArea();		Class Ccircle : public Cfigure
} ;		class Ccircle : public Cfigure
		class Ccircle : public Cfigure
		class Ccircle : public Cfigure public: Ccircle(int r) : Cfigure(r) double calcArea();
		class Ccircle : public Cfigure public: Ccircle(int r) : Cfigure(r) double calcArea();
		class Ccircle : public Cfigure public: Ccircle(int r) : Cfigure(r) double calcArea();

(e) Single argument Constructor in Ccircle needs to pass values to constructor in Cfigure. However only one dimention is available within the Ccircle constructor. Re write the definition of the Cfigure constructor to accommodate this situation (only definition is required)

(10% Marks)

AN	WER IN THIS BOX	
	Cfigure(double d1, double d2=1);	

(f) Write the implementation of the overridden function calcArea() in Ccircle class

(10% Marks)

```
double calcArea()

return 3.14*dimention1*dimention1;
```

(g) Assuming there is C++ definition for a class based on Cfigure called Crectangle (dimention1 and dimention2 is utilized to hold length and breadth of Rectangle) Demonstrate run time polymorphism by using above classes within a main() method in c++.

```
void main()
{
Cfigure *F;

Ccircle C(7);
Crectangle R(2,3);

F=&C;
cout << "Area of the Circle is " << F->calcArea();

F=&R;
cout << "Area of the Rectangle is " << F->calcArea();
}
```
