

The following materials have been collected from the numerous sources such as Stanford CS106 and Harvard CS50 including my own and my students over the years of teaching and experiences of programming. Please help me to keep this tutorial up-to-date by reporting any issues or questions. Please send any comments or criticisms to [idebtor@gmail.com](mailto:idebtor@gmail.com). Your assistances and comments will be appreciated..

## PSet 03 (Part 1) – Recursion

### Table of Contents

Getting Started - Recursion.....	1
Implementing Recursion Functions .....	1
Example 1: Factorial.....	2
Example 2: GCD (Great Common Divisor).....	2
Example 3: Fibonacci .....	3
Example 4: Bunny Ears .....	4
Example 5: Funny Ears .....	4
Example 6: Triangle .....	4
Example 7: Sum of digits.....	5
Example 8: Count 8.....	5
Example 9: Power N .....	5
A command line to build .....	6
Submitting your solution .....	6
Files to submit and Grade.....	6
Due .....	6

## Getting Started - Recursion

**Recursion** in computer science is a method where the solution to a problem depends on solutions to **smaller instances** of the same problem (as opposed to iteration). The approach can be applied to many types of problems, and recursion is one of the central ideas of computer science. An infinite number of computations can be described by a finite recursive program, even if this program contains no explicit repetitions. Most computer programming languages support recursion by allowing a [function](#) to call itself within the program text.

(Resources: <https://en.wikipedia.org/wiki/Recursion> & [www.codingBat.com](http://www.codingBat.com))

**Recursive algorithm** is expressed in terms of

1. **base case(s)** for which the solution can be stated **non-recursively**,
2. **recursive case(s)** for which the solution can be expressed in terms of a smaller version of itself.

## Implementing Recursion Functions

1. Take a look at the sample solution of Example 1 ~ 4 in **recursion.cpp** and **recursionDriver.cpp**.

2. Implement the rest of examples while following the patterns of the program including comment sections in **recursion.cpp**. Well written comments are required such that that we can clearly see both how the algorithms work and what the testing results are.

## Example 1: Factorial

$$\text{fact}(n) = \begin{cases} 1 & \text{if } n = 0 \\ n \cdot \text{fact}(n-1) & \text{if } n > 0 \end{cases}$$

factorial(n)

**input:** integer  $n$  such that  $n \geq 0$

**output:**  $[n \times (n-1) \times (n-2) \times \dots \times 1]$

1. if  $n$  is 0, **return** 1

2. otherwise, **return**  $[n \times \text{factorial}(n-1)]$

**end** factorial

factorial(1)  $\rightarrow$  1

factorial(2)  $\rightarrow$  2

factorial(3)  $\rightarrow$  6

factorial(8)  $\rightarrow$  40320

factorial(12)  $\rightarrow$  479001600

factorial(20)  $\rightarrow$  2432902008176640000

### Hint:

First, detect the "base case", a case so simple that the answer can be returned immediately (here when  $n=1$ ). Otherwise make a recursive call of **factorial**( $n-1$ ) (towards the base case). Assume the recursive call returns a correct value and fix that value up to make our result.

### Code:

```
long long factorial(int n) {
    if (n == 1) return n;
    return n * factorial(n-1);
}
```

or

```
long long factorial(int n) {
    return n == 0 ? 1 : n * factorial(n - 1);
}
```

## Example 2: GCD (Great Common Divisor)

$$\text{gcd}(x, y) = \begin{cases} x & \text{if } y = 0 \\ \text{gcd}(y, \text{remainder}(x, y)) & \text{if } y > 0 \end{cases}$$

Recurrence relation for greatest common divisor, where  $x\%y$  expresses the remainder of  $x/y$ :

$$\begin{aligned} \text{gcd}(x, y) &= \text{gcd}(y, x\%y) & \text{if } y \neq 0 \\ &= \text{gcd}(x, 0) = x & \text{if } y = 0 \end{aligned}$$

gcd(x, y)

```

input: integer x, y such that  $x \geq y$ ,  $y > 0$ 
output: gcd of x and y
  1. if y is 0, return x
  2. otherwise, return [ gcd (y, x%y) ]
end gcd

```

**Ex:** Computing the recurrence relation for  $x = 27$  and  $y = 9$

```

gcd(27, 9)  = gcd(9, 27 % 9)
            = gcd(9, 0)

```

**Ex:** Computing the recurrence relation for  $x = 111$  and  $y = 259$

```

gcd(111, 259) = gcd(259, 111% 259)
              = gcd(259, 111)
              = gcd(111, 259% 111)
              = gcd(111, 37)
              = gcd(37, 111% 37)
              = gcd(37, 0)
              = 37

```

**Code:**

```

int gcd(int x, int y) {
  if (y == 0) return x;
  return gcd(y, x % y);
}

```

or

```

int gcd(int x, int y) {
  return y == 0 ? x : gcd(y, x % y);
}

```

## Example 3: Fibonacci

The fibonacci sequence is a famous bit of mathematics, and it happens to have a recursive definition. The first two values in the sequence are 0 and 1 (essentially 2 base cases). Each subsequent value is the sum of the previous two values, so the whole sequence is: 0, 1, 1, 2, 3, 5, 8, 13, 21 and so on.

Define a recursive **fibonacci(n)** method that returns the nth fibonacci number, with  $n=0$  representing the start of the sequence.

```

fibonacci(0) → 0
fibonacci(1) → 1
fibonacci(2) → 1
fibonacci(3) → 2
fibonacci(4) → 3
fibonacci(5) → 5
fibonacci(11) → 89
fibonacci(33) → 3524578
fibonacci(44) → 701408733 (It takes some time to compute.)

```

**Code:**

```

long long fibonacci(int n) {
  if (n == 0 || n == 1) return n;

```

```
    return fibonacci(n-1) + fibonacci(n-2);  
}
```

or

```
long long fibonacci(int n) {  
    return n <= 1 ? n : fibonacci(n - 1) + fibonacci(n - 2);  
}
```

## Example 4: Bunny Ears

We have a number of bunnies and each bunny has two big floppy ears. We want to compute the total number of ears across all the bunnies recursively (without loops or multiplication).

bunnyEars(0) → 0  
bunnyEars(1) → 2  
bunnyEars(2) → 4  
bunnyEars(3) → 6  
bunnyEars(234) → 468

Hint:

First detect the base case (`bunnies == 0`), and in that case just return 0. Otherwise, make a recursive call to `bunnyEars(bunnies-1)`. Trust that the recursive call returns the correct value, and fix it up by adding 2.

**Code:**

```
int bunnyEars(int bunnies) {  
    if (bunnies == 0) return 0;  
  
    // Recursive case: otherwise, make a recursive call with bunnies-1  
    // (towards the base case), and fix up what it returns.  
    return 2 + bunnyEars(bunnies-1);  
}
```

## Example 5: Funny Ears

We have bunnies and funnies standing in a line, numbered 1, 2, ... The odd bunnies (1, 3, ...) have the normal 2 ears. The even funnies (2, 4, ...) we'll say have 3 ears, because they each have a raised foot. Recursively return the number of "ears" in the bunny and funny line 1, 2, ... n (without loops or multiplication).

funnyEars(0) → 0  
funnyEars(1) → 2  
funnyEars(2) → 5  
funnyEars(3) → 7  
funnyEars(4) → 10  
funnyEars(9) → 22  
funnyEars(10) → 25

**Code:**

```
int funnyEars(int funnies) {  
    // your code here  
}
```

## Example 6: Triangle

We have triangle made of blocks. The topmost row has 1 block, the next row down has 2 blocks, the next row has 3 blocks, and so on. Compute recursively (no loops or multiplication) the total number of blocks in such a triangle with the given number of rows.

triangle(0) → 0  
triangle(1) → 1  
triangle(2) → 3  
triangle(3) → 6  
triangle(4) → 10  
triangle(7) → 28

**Code:**

```
int triangle(int rows) {  
    // your code here  
}
```

## Example 7: Sum of digits

Given a non-negative int n, return the sum of its digits recursively (no loops). Note that mod (%) by 10 yields the rightmost digit (126 % 10 is 6), while divide (/) by 10 removes the rightmost digit (126 / 10 is 12).

sumDigits(126) → 9  
sumDigits(12) → 3  
sumDigits(1) → 1  
sumDigits(10110) → 3  
sumDigits(235) → 10

**Code:**

```
int sumDigits(int n) {  
    // your code here  
}
```

## Example 8: Count 8

Given a non-negative int n, return the count of the occurrences of 8 as a digit, so for example 818 yields 2. (no loops). Note that mod (%) by 10 yields the rightmost digit (126 % 10 is 6), while divide (/) by 10 removes the rightmost digit (126 / 10 is 12).

count8(818) → 2  
count8(8) → 1  
count8(123) → 0  
count8(881238) → 3  
count8(48581) → 2  
count8(888586198) → 5  
count8(99899) → 1

**Code:**

```
int count8(int n) {  
    // your code here  
}
```

## Example 9: Power N

Given base and n that are both 1 or more, compute recursively (no loops) the value of base to the n power, so powerN(3, 2) is 9 (3 squared).

powerN(2, 5) → 32  
powerN(3, 1) → 3

powerN(3, 2) → 9  
powerN(3, 3) → 27  
powerN(10, 2) → 100  
powerN(10, 3) → 1000

**Code:**

```
long long powerN(int base, int n) {  
    // your code here  
}
```

## A command line to build

To build this program:

```
g++ recursionDriver.cpp recursion.cpp -I../include -L../lib -lnowic -o recursion
```

This command line works in the following folder structures and two source files exist at pset03.

```
nowicx/lib  
nowicx/include  
nowicx/psets/pset03
```

## Submitting your solution

- Include the following line at the top of your every source file with your name signed.  
On my honour, I pledge that I have neither received nor provided improper assistance in the completion of this assignment.  
Signed: \_\_\_\_\_ Section: \_\_\_\_\_ Student Number: \_\_\_\_\_
- Make sure your code **compiles** and **runs** right before you submit it. Every semester, we get dozens of submissions that don't even compile. Don't make "a tiny last-minute change" and assume your code still compiles. You will not get sympathy for code that "almost" works.
- If you only manage to work out the problem sets partially before the deadline, you still need to turn it in. However, don't turn it in if it does not compile and run.
- Place your source files in the folder you and I are sharing.
- After submitting, if you realize one of your programs is flawed, you may fix it and submit again if it is **before the deadline**. You will have to resubmit any related files together, even if you only change one. You may submit as often as you like. **Only the last version** you submit before the deadline will be graded.

## Files to submit and Grade

Submit the following file.

- **recursion.cpp**
- **1.0 point**

Upload your file **pset3** folder in Piazza.

## Due

- Due: 11:55 pm