

Research Proposal: Comparative Analysis of Kernel-Level Zero Trust vs. Traditional VPNs

Researcher: Minsoo Ahn (114743792)

Proposed Duration: Feb 19, 2025 – June 18, 2025 (17 Weeks)

1. Project Outline

This research aims to transition from traditional perimeter-based security models to a **Zero Trust Architecture (ZTA)**. The primary objective is to design and implement a high-performance ZTA gateway utilizing **Kernel-level networking technologies** and **Policy-as-Code** principles.

In this study, Zero Trust is defined as a **network-layer access control architecture** that minimizes implicit trust by evaluating access requests at the smallest feasible granularity.

The project will provide a rigorous comparative analysis against traditional VPN solutions to validate the engineering feasibility of ZTA in terms of both security and system performance, distinguishing architectural effects from implementation-level optimizations.

2. Research Hypotheses

This study seeks to verify the following engineering hypotheses:

- **H1 (Security Hypothesis):** "Traditional VPNs inherently expose a broad attack surface due to their static perimeter model. A micro-segmented ZTA implementation will significantly reduce this surface by restricting access to explicitly authorized resources, rather than granting broad network-level connectivity."
- **H2 (Performance Hypothesis):** "Implementing continuous verification often raises concerns about latency. However, by leveraging **Kernel-space tunneling protocols**, this research hypothesizes that ZTA can achieve security granularities superior to traditional VPNs while maintaining comparable or superior network throughput."

3. Technology Strategy

To achieve the research objectives, specific technologies have been selected as

representative implementations of architectural concepts:

- **Enforcement Point (PEP): Kernel-Level Tunneling Mechanism** A **kernel-level tunneling mechanism** is used as the policy enforcement point to minimize user-space context switching overhead. A representative modern implementation (e.g., **WireGuard**) is selected to instantiate this role, utilizing its in-kernel execution model.
- **Decision Point (PDP): Decoupled Policy Engine** A **decoupled policy decision component** is employed to represent dynamic and context-aware access control. This structure enables policy evaluation independent of enforcement logic. A standard cloud-native policy engine (e.g., **Open Policy Agent**) will be used to demonstrate this architectural separation.
- **Comparison Target: User-Space VPN Architecture** A traditional **user-space VPN architecture** (e.g., **OpenVPN**) is used as a control group to represent perimeter-based access models commonly deployed in practice.
- **Infrastructure & Automation: Containerization & IaC Infrastructure as Code (IaC)** tools are utilized to ensure the experimental environment is reproducible and consistent, prioritizing architectural comparison over manual configuration.

4. Methodology: Experimental Design

Two distinct environments will be established to facilitate direct comparison under equivalent conditions.

Environment A: Control Group (Traditional Model)

- **Configuration:** Represents a perimeter-based security model.
- **Characteristics:** Authenticated clients receive broad network access via static routing.

Environment B: Experimental Group (Proposed ZTA Model)

- **Configuration:** Represents a Zero Trust access model.
- **Characteristics:** Access is granted per request based on real-time policy evaluation via dynamic routing.

Comparative Analysis Metrics

The environments will be evaluated using the following dimensions:

1. **Network Performance:**
 - **Throughput:** Measurement of maximum sustainable bandwidth.
 - **Latency:** Analysis of delay introduced by verification logic.
2. **System Efficiency:**

- **Resource Overhead:** CPU and Memory utilization on the gateway.
- 3. **Security Posture:**
 - **Attack Surface Visibility:** Assessment of reachable resources from a compromised client.

5. Implementation Roadmap (17 Weeks)

The project timeline is structured into four phases, aligned with the academic semester.

Phase 1: Foundation & Design (Weeks 1-3)

- **Objective:** Establish the theoretical background and automated infrastructure.
- **Activities:**
 - Literature review of NIST ZTA standards and Kernel networking protocols.
 - Design of the system architecture and network topology.
 - Development of IaC scripts to automate the deployment of the base testbed.

Phase 2: Core Implementation (Weeks 4-9)

- **Objective:** Develop the functional ZTA system.
- **Activities:**
 - Implementation of the **Kernel-based VPN** interface.
 - Development of the **Policy Engine** logic for context-aware access.
 - Creation of the **Middleware** to orchestrate dynamic routing based on policy decisions.

Phase 3: Validation & Data Collection (Weeks 10-13)

- **Objective:** Execute comparative experiments.
- **Activities:**
 - **Mid-term Review:** Code refactoring and system optimization.
 - Deployment of the **Control Group** environment.
 - Execution of **Security Scans** and **Performance Benchmarks** on both environments.
 - Collection of raw data for analysis.

Phase 4: Analysis & Reporting (Weeks 14-17)

- **Objective:** Interpret results and finalize deliverables.
- **Activities:**
 - Statistical analysis of performance data (Latency/Throughput trade-offs).
 - Drafting of the final technical report and engineering documentation.

- Creation of the final demonstration video and presentation materials.

6. Expected Outcomes

1. **Quantitative Comparison:** A comprehensive analysis of performance and security characteristics between ZTA and traditional VPN models.
2. **Reproducible Prototype:** A functional prototype demonstrating network-layer Zero Trust enforcement.
3. **Engineering Evidence:** Empirical evidence that Zero Trust principles can be practically applied without assuming inherent performance degradation.

Appendix: Selected Bibliography & Key Technologies

- NIST SP 800-207: Zero Trust Architecture Defines the standard architectural model used in this research to establish the baseline for logical components and trust evaluation. [NIST Special Publication 800-207](#)
- Forrester: The Zero Trust Model Provides the framework for analyzing the engineering trade-offs between attack surface reduction and implementation complexity. [Forrester Zero Trust DNA](#)
- WireGuard: Next Generation Kernel Network Tunnel Selected as the Policy Enforcement Point (PEP) to validate the hypothesis that kernel-level execution minimizes ZTA latency. [WireGuard Paper](#)
- Open Policy Agent (OPA) Utilized to implement the Policy Decision Point (PDP), demonstrating the decoupling of access control logic from network routing. [OPA Documentation](#)
- OpenVPN Community Resources Serves as the Control Group (traditional perimeter model) to provide baseline metrics for throughput and security comparison. [OpenVPN Resources](#)
- Infrastructure as Code (IaC) Applied to the experimental methodology to ensure reproducibility and consistency across both test environments. [What is IaC](#)