Silver Point Gateway - Peecho API Technical Specification

Webhook Endpoint, Dual-Key HMAC-SHA256 Authentication, Inbound Payloads & Outbound Callbacks

1. Unified Webhook Endpoint & Environment Routing

Both Production and Staging Sandbox webhooks use the **same HTTPS endpoint** and are automatically differentiated by the secret key used in the **X-Peecho-Signature** header:

Environment	Webhook Endpoint URL	Key Variable (.env) & Flag
Production (Live)	`https://orderflow.silverpointprint.com/api/v1/peecho/webhook/`	**PEECHO_PRODUCTION_SECRET_KEY** is_sandbox = False (Status: RECEIVED)
Staging (Sandbox)	`https://orderflow.silverpointprint.com/api/v1/peecho/webhook/`	**PEECHO_STAGING_SECRET_KEY** is_sandbox = True (Status: TEST_ORDER)

2. Secret Key & HMAC-SHA256 Authentication

- **Strict .env Storage:** Both **PEECHO_PRODUCTION_SECRET_KEY** and **PEECHO_STAGING_SECRET_KEY** are stored strictly in the server **.env** file (not created or editable via Admin UI).
- **Header Validation:** Inbound requests pass **X-Peecho-Signature: sha256=<HEX_DIGEST>** computed via HMAC-SHA256 over the raw UTF-8 JSON body using constant-time digest comparison (**hmac.compare_digest**). Invalid signatures return **401 Unauthorized**.

```
# Server .env Configuration
PEECHO_PRODUCTION_WEBHOOK_URL=https://orderflow.silverpointprint.com/api/v1/peecho/webhook/
PEECHO_STAGING_WEBHOOK_URL=https://orderflow.silverpointprint.com/api/v1/peecho/webhook/
PEECHO_PRODUCTION_SECRET_KEY=sp_live_0ec35c74077b7829c266dcaad98e3bc7184028b85b5ab9750cddcdd3c18bd7b1
PEECHO_STAGING_SECRET_KEY=sp_stg_2ff0c322e540420a1d6aab4ec8de93d72ea63941d37a8529272d814d60ec2403
```

3. Inbound API (Peecho → Silver Point)

Endpoint: `POST /api/v1/peecho/webhook/` | **Headers:** `Content-Type: application/json`, `X-Peecho-Signature: sha256=<digest>`

```
{
  "event": "order.created",
  "order_id": "PEECHO-904120",
  "priority": "EXPRESS_24H",
  "currency": "EUR",
  "total_amount": "48.50",
  "customer": {"name": "Jan de Vries", "email": "jan@example.nl"},
  "shipping_address": {"street": "Keizersgracht 241", "city": "Amsterdam", "postal_code": "1016 EA", "country"
: "NL"},
  "items": [{
    "item_id": "ITEM-01", "product_type": "Hardcover Photo Book A4", "quantity": 1, "page_count": 64,
    "spine_width_mm": 9.5, "paper_stock": "200gsm Silk", "pdf_artwork_url": "https://cdn.peecho.com/904120/int
erior.pdf"
  }]
}
```

4. Outbound APIs (Silver Point → Peecho)

Callback Type	Endpoint	Trigger & Retry Policy
Shipment Callback	`POST /v2/orders/{id}/shipment`	Sent on AWB dispatch scan with tracking_code, carrier, shipment_date, and tracking_url.
Status Callback	`POST /v2/orders/{id}/status`	Sent on status changes (IN_PRODUCTION, QC_REJECTED, PRINT_FAILED, CANCELLED). Retries with exponential backoff (5 retries: 60s–960s).