



## DC City Charger 50/60KW

### Key Features:

- Simultaneous charging of two vehicles.
- Easy to install, operate and service.
- More than 94% nominal efficiency.
- Wired/wireless connectivity for integration with CMS.
- User-friendly LCD display for customer interface.
- IP55 outdoor charging station.

### Applications:



Highway  
Service



Parking



Service  
Station



Commercial



Fleet



Smarter. Greener. Together.

# Product Specification

Input Power		
Input Voltage (AC)	3 Phase, 400 Vac (360 ~ 440 Vac), 50Hz	
Power Factor	≥0.99	
Nominal Efficiency	≥94%	
Wires	5 Wire, L1, L2, L3, N, PE	
Outputs		
Number of Outputs	2 Nos.	
Output Power	50/60kW Max. @ 50°C	
Connectors	CCS Type 2	CCS Type 2
Output Voltage	200-1000VDC	200-1000VDC
Output Current	125A Max.	125A Max.
Environment		
Ambient Temperature	Full Power: 0°C to 50°C De-rated: 50°C to 55°C	
Storage Temperature	0°C to 70°C	
Altitude	<2000 Mtr.	
Humidity	<95%, non-condensing	
User Interface & Control		
Display	7” TFT LCD with Touch Control	
Language	English	
Key/Switch	Start/Stop, Emergency Stop (Mushroom Headed Red Color)	
User Authentication	OTP/RFID based/Mobile App	
Visual Indication	Mains, Charging Status, System error	
Communication		
Charger & CMS	Protocol: OCPP 1.6J (Open Charge Point Protocol) Interface : Ethernet, GSM - 3G/4G	
Protection		
Protection	Over Voltage, Under Voltage, Over Current, Short Circuit, Surge Protection, Over Temperature, Ground Fault, Residual Current.	
Mechanical		
Ingress protection	IP55	
Enclosure protection	IK10	
Cooling	Air cooled	
Wire length	5mtr. Standard	
Dimensions (HxWxD)	1730mm x 750mm x 450mm	
Weight	~300Kg	

\*Product outlook subject to change without notice.

## India office:

Delta Electronics India Pvt. Ltd.  
Plot No. 43, Sector- 35, HSIIDC, Gurgaon 122001, India.  
Website: [www.deltaelectronicsindia.com](http://www.deltaelectronicsindia.com)  
Doc. No: Leaflet/City-V1.0

