Cat Electronic Technician 2018A v1.0

Product Status Report

20-Jul-2019 5:01 PM

Product Status Report

Parameter	Value
Product ID	JAD02274
Equipment ID	NOT PROGRAMMED
Comments	

C7 950H (KHX46832)

Parameter	Value
Engine Serial Number	KHX46832
ECM Part Number	3722906-00
ECM Serial Number	10926145JM
Software Group Part Number	4349487-00
Software Group Release Date	MAR13
Software Group Description	C7-950H
Active Diagnostic Codes Present	Yes

Logged Diagnostic Codes [Diagnostic Clock = 12294.7551 hours] - C7 950H (KHX46832)

Code	Description	Occ.	First	Last
91- 8	Throttle Position Sensor : Abnormal Frequency, Pulse Width, or Period	1	12294	12294
100- 3	Engine Oil Pressure Sensor : Voltage Above Normal	1	12294	12294
110- 3	Engine Coolant Temperature Sensor : Voltage Above Normal	1	12294	12294
164- 3	Injector Actuation Pressure : Voltage Above Normal	1	12294	12294
172- 3	Intake Manifold Air Temperature Sensor : Voltage Above Normal	1	12294	12294
267- 2	Remote Shutdown Input : Erratic, Intermittent, or Incorrect	1	12294	12294
274- 3	Atmospheric Pressure Sensor : Voltage Above Normal	1	12294	12294
275- 3	Right Turbocharger Inlet Pressure Sensor : Voltage Above Normal	1	12294	12294
291- 5	Engine Cooling Fan Solenoid : Current Below Normal	1	12294	12294
296- 9	Transmission Control : Abnormal Update Rate	1	12294	12294
596- 9	Implement Control : Abnormal Update Rate	1	12294	12294
1785- 3	Intake Manifold Pressure Sensor : Voltage Above Normal	1	12294	12294
617- 5	Inlet Air Heater Relay : Current Below Normal	2	12294	12294

Logged Event Codes [Diagnostic Clock = 12294.7551 hours] - C7 950H (KHX46832)

Code	Description	Occ.	First	Last
No Logged Event Codes				

Active Diagnostic Codes - C7 950H (KHX46832)

Code	Description
91- 8	Throttle Position Sensor : Abnormal Frequency, Pulse Width, or Period
100- 3	Engine Oil Pressure Sensor : Voltage Above Normal
110- 3	Engine Coolant Temperature Sensor : Voltage Above Normal
164- 3	Injector Actuation Pressure : Voltage Above Normal
172- 3	Intake Manifold Air Temperature Sensor : Voltage Above Normal
267- 2	Remote Shutdown Input : Erratic, Intermittent, or Incorrect
274- 3	Atmospheric Pressure Sensor : Voltage Above Normal
275- 3	Right Turbocharger Inlet Pressure Sensor : Voltage Above Normal
291- 5	Engine Cooling Fan Solenoid : Current Below Normal
296- 9	Transmission Control : Abnormal Update Rate
596- 9	Implement Control : Abnormal Update Rate
1785- 3	Intake Manifold Pressure Sensor : Voltage Above Normal

Active Event Codes - C7 950H (KHX46832)

Code	Description
No Active Event Codes	

Current Totals - C7 950H (KHX46832)

Description	Value	Unit
Total Idle Time	5660:09	hours
Total Fuel	45518	gal
Total Idle Fuel	5871	gal
Total Max Fuel	141779	gal
Total Operating Hours	12295	hours
Engine Starts	15701	
Lifetime Total Engine Revolutions	874591260	rev
Total Engine Idle Shutdown Count	0	
Total Engine Idle Shutdown Overrides Count	0	
Average RPM	1185.66	rpm
Percentage Idle Time	46.04	%
Average Fuel Rate	3.70	gal/h
Overall Load Factor	32	%

Configuration - C7 950H (KHX46832)

Description	Value	Unit
Engine Serial Number	KHX46832	
ECM Part Number	3722906-00	
ECM Serial Number	10926145JM	

Software Group Part Number	4349487-00	
Software Group Release Date	MAR13	
Software Group Description	C7-950H	
Engine Fan Control	On	
Low System Battery Voltage Elevated Idle	Enabled	
Ether Solenoid Configuration	Not Installed	
Engine Fan Reversing Feature	Disabled	
Engine Fan Purge Cycle Interval	Unavailable	sec
Security System Immobilizer Installation Status	Disabled or Not Installed	
Engine Warm Up Elevated Idle Feature Enable Status	Disabled	
Machine Working Engine Low Idle Speed Configuration	825.0	rpm
Machine Hibernating Engine Low Idle Speed Configuration	700.0	rpm
Engine Idle Shutdown Enable Status	Disabled	
Engine Idle Shutdown Delay Time	5.0	min
FLS	-7	
FTS	0	
Total Tattletale	12	

Lifetime: Time vs Engine Coolant Temperature - C7 950H (KHX46832)

Engine Coolant Temperature(Deg F)	hours	%
<122.0	56.55	0.46
122.0-130.0	22.15	0.18
131.0-139.0	26.80	0.22
140.0-148.0	35.55	0.29
149.0-157.0	50.30	0.41
158.0-166.0	93.40	0.75
167.0-175.0	549.90	4.44
176.0-184.0	8929.60	72.14
185.0-193.0	2540.90	20.53
194.0-202.0	72.70	0.59
203.0-211.0	0.00	0.00
212.0-220.0	0.00	0.00
221.0-229.0	0.00	0.00
230.0-238.0	0.00	0.00
239.0-247.0	0.00	0.00
>248.0	0.00	0.00

Lifetime: Time vs Inlet Air Temperature - C7 950H (KHX46832)

Inlet Air Temperature(Deg F)	hours	%
<104.0	466.15	49.22
104.0-112.0	250.05	26.40
113.0-121.0	209.65	22.14
122.0-130.0	20.95	2.21
131.0-139.0	0.15	0.02

140.0-148.0	0.05	0.01
149.0-157.0	0.00	0.00
158.0-166.0	0.00	0.00
167.0-175.0	0.00	0.00
176.0-184.0	0.00	0.00
185.0-193.0	0.00	0.00
194.0-202.0	0.00	0.00
203.0-211.0	0.00	0.00
>212.0	0.00	0.00

Lifetime: Time vs Boost Pressure - C7 950H (KHX46832)

Boost Pressure(psi)	hours	%
<11.6	55.00	5.81
11.6-12.1	34.75	3.67
13.1-13.5	42.30	4.47
14.5-15.0	57.60	6.08
16.0-16.4	219.50	23.18
17.4-17.9	264.05	27.89
18.9-19.3	91.10	9.62
20.3-20.8	29.75	3.14
21.8-22.2	80.45	8.50
23.2-23.7	71.45	7.55
24.7-25.1	0.90	0.10
26.1-26.6	0.00	0.00
27.6-28.0	0.00	0.00
>29.0	0.00	0.00

Lifetime: Time vs Engine Speed And Engine Load Factor - C7 950H (KHX46832)

rpm	<1100	1100-1299	1300-1499	1500-1699	1700-1899	1900-2099	2100-2299	>2300	Total
%									
<50.0	6539.65	744.80	667.65	407.15	178.45	69.10	19.90	0.35	8627.05
50.0-59.9	124.70	89.80	123.80	130.35	102.45	27.25	7.95	0.45	606.75
60.0-69.9	77.45	77.95	120.20	125.30	137.70	48.95	10.95	0.75	599.25
70.0-79.9	59.65	70.05	102.90	117.60	130.60	87.65	17.25	0.60	586.30
80.0-89.9	24.55	28.05	45.60	80.70	116.40	158.70	28.55	0.80	483.35
>90.0	12.95	23.65	64.35	200.15	376.45	515.30	40.05	1.00	1233.90
Total	6838.95	1034.30	1124.50	1061.25	1042.05	906.95	124.65	3.95	12136.60

Lifetime: Total Occurrences vs Engine Speed - C7 950H (KHX46832)

Engine Speed(rpm)		%
<2500.0	0.00	0.00
2500.0-2599.0	1.00	2.63
2600.0-2699.0	1.00	2.63
2700.0-2799.0	2.00	5.26

2800.0-2899.0	0.00	0.00
2900.0-2999.0	2.00	5.26
3000.0-3099.0	4.00	10.53
3100.0-3199.0	1.00	2.63
3200.0-3299.0	1.00	2.63
>3300.0	26.00	68.42

Injector Trim Calibration - C7 950H (KHX46832)

Injector	Serial Number	File Version	Tattletale
Injector1	000000003B1313263597	0	0
Injector2	000000003B13132664D1	0	0
Injector3	000000003B13132718F5	0	0
Injector4	000000003B13132643EE	0	0
Injector5	000000003B13132661CA	0	0
Injector6	000000003B13132612A8	0	0

Monitoring System - C7 950H (KHX46832)

Description	State	Trip Point	Delay Time
Engine Overspeed			
Least Severe (1)	Always On	2600 rpm	0 sec
Moderate Severity (2)	Always On	2800 rpm	0 sec
High Air Filter Restriction Pressure			
Least Severe (1)	Always On	30.1 " H2O	10 sec
Moderate Severity (2)	Always On	36.1 " H2O	10 sec
High Engine Coolant Temperature			
Least Severe (1)	Always On	226 Deg F	10 sec
Moderate Severity (2)	Always On	232 Deg F	10 sec
High Engine Inlet Air Temperature			
Least Severe (1)	Always On	194.0 Deg F	8 sec
Moderate Severity (2)	Always On	230.0 Deg F	8 sec
High Fuel Pressure			
Least Severe (1)	Always On	109.9 psi	8 sec
Low Engine Oil Pressure			
Least Severe (1)	Always On	None	8 sec
Moderate Severity (2)	Always On	None	4 sec