Dual-ligand fluorination

01 / Experiment

Use the two-page bench sheet at the robot. Keep the protocol and its generated CSVs together; `dosing.csv` gives well identities and `deck_loads.csv` gives stage-specific source fills.

Reaction and design

Pyridine-2-sulfonyl fluoride (PyFluor) to 2-fluoropyridine. Per vial: 25 µmol SM, 1.5 µmol each ligand, 3 µmol Pd(COD)(DQ), 2.5 µmol mesitylene; 250 µL toluene, 95 °C, 500 rpm, 4 h under air. No base or external fluoride.

Round one: **48 distinct pairs, all 30 available ligands**; L07 is unavailable. Round two: **22 new pairs + L17 tBuBrettPhos at 12 mol% total ligand**. No repeats. A better pair yield establishes improvement against this reference; it does not establish reproducibility or ligand synergy.

Before the clock starts

- Fit **p300 single GEN2 left; p300 eight-channel GEN2 right**. Reaction vials have 13 mm pitch: use the single only. The multi serves the standard 96-well LC preparation plate.
- Check the supplied block on the flat adapter: secure mounting, latch closure, cap clearance within **45 mm**, offsets and thermal transfer. Pipette **1.5 mm above the bottom** by default; check actual immersion. Caps are manual; no stir bars or gripper.
- Confirm the existing **1.7-min full LC cycle**, method ID, injection volume, UV channel/wavelength and authentic-standard RT/LOQ settings. Requested 210 nm is provisional; the old example wavelengths are not our method. Record local evidence before release.
- Prepare stocks, caps, tips, 71 fresh reaction vials, two final autosampler-compatible 96-well deep-well LC plates with pierceable seals, plus standards. The supplied VWR definition is 2.2 mL/well; confirm the physical plate fits BOTH the flat adapter and autosampler, including seal, carrier and needle depth. The derived `_hs.json` adds movement geometry only; it does not establish physical compatibility. App-simulate the released Python. Open setup details.

Slot	Load
1 / 4	Ligand source racks; exact CSV addresses, L07 absent
2	A1 SM/DCM; A2 Pd; A3 toluene; A8 mesitylene. Quench A4/A6/A9; diluent A5/A7/A10/A11/A12
3 / 10	Reaction block: staff move it by hand at App prompts; pipetting / heater-shaker
6	VWR 96-well 2.2 mL deep-well preparation plate, or matching configured replacement; fill here, shake on 10, then directly to HPLC
5 / 8 / 9	Single tips / multi tips / multi tips. Keep slots 7 and 11 empty

Dose and react

1. Robot doses **50 µL 500 mM SM/DCM** per vial. At the pause, move the block off deck and evaporate completely by HTEL's ventilated procedure. Cool; return to slot 3.
2. Add **25 µL mesitylene +37.5 µL ligand A +37.5 µL ligand B +75 µL Pd +75 µL toluene =250 µL**. Stocks: mesitylene 100 mM; ligands/Pd 40 mM. Reference: use 75 µL L17 instead of the two ligand portions.
3. Hand-tighten all caps. Move/latch at the local pauses; run **95 °C, 500 rpm, 4 h**. Every block move, cap change and tip-rack replacement is manual.
4. During hold one, run the **14 calibration injections**. Hand-dose **23 labelled fresh vials with SM/DCM only** in an ordinary off-deck rack; evaporate fully and cap the dry SM. Add mesitylene/catalysts only after round two is selected. Reuse the same reaction block.

Timing: one LC plate per round minimizes handling: four LC-plate moves total, excluding initial loading. Retained allowances give **752.7 /720 min**, with no within-round LC overlap. Measure automated preparation/caps/cooling: total handling must fall by **32.7 min**. Alternatively use a timed split-plate plan; live release rejects an overrun.

Workup and LC sampling

1. **Cool sealed vials off the heater.** Open for addition; add **500 µL 9:1 ACN/water +0.15% formic acid**. Nominal extract: 750 µL, 0.1% acid, 1.25 mL headspace. Quench and diluent contain no IS.
2. **Hand-recap every vial.** Shake **1500 rpm, 2 min**, heater off; return to slot 3. The block must have cooled for workup.
3. **One LC plate per round.** Let bubbles settle after the automated extract shake; open the indicated reaction vials for sampling. Other vials stay capped.
4. **Robot dilution:** fresh tip per sample; two slow same-well prewet cycles, without blowing air into the extract. Aspirate 21 µL at 1.5 mm, retain 1 µL reverse surplus, add 2 µL air gap and dispense nominal **20 µL into 980 µL LC diluent**, noncontact. Discard the tip; never revisit the source after destination contact.
5. **Recap sampled reaction vials.** The reaction block stays in slot 3. At the App move prompt, take the completed LC plate **slot 6 → cooled heater-shaker slot 10**. Keep A1 orientation. Robot latches and shakes the plate **UNCOVERED, heater OFF, 1000 rpm for 2 min**; use the locally confirmed splash-free speed. It waits for module temperature ≤30 °C before loading. No manual sample mixing/pipetting.
6. **Move directly 10 → HPLC** at the prompt; apply the confirmed pierceable autosampler seal. Load the correct carrier, plate definition and needle depth. R1 plate **R1-LC01: A1-H6, 48 samples**; R2 **R2-LC01: A1-H2 plus A3-G3, 23 samples**, column-wise. **H3 contains diluent only: do not inject.** Use `lc_plates.csv` and `lc_sequence.csv`; the 48-vial reaction map differs from the LC map. Inject directly from the plate; no individual sample-vial transfers.

Optional timing route: set `robot.lc_batch_size=24`, then regenerate protocols/maps. R1 uses two fresh LC plates (A1-H3 and A4-H6); R2 uses one. **Six LC-plate moves total.** Keep these actual well coordinates; do not renumber the second plate. Start each completed plate before resuming robot preparation. Set overlap only from a timed rehearsal, exclusively R1; R2 has no preparation overlap. A claimed 35-min R1 overlap fits its 40.8-min injection window but is not demonstrated.

Final sample: 1.00 mL; maximum SM/product **666.7 µM**; mesitylene **66.7 µM**; formic acid **0.1%**; toluene **0.667%**. Set injection volume from the actual calibrated method. Final LC plates and their headspace remain unchanged during injection; seal after shaking to limit evaporation.

Pipetting and transfer faults

Condition fresh dosing tips twice in their own stock. Use slow aspiration, short settling delays, a small air gap and reverse surplus for the organic stocks. Keep active sources covered between stages and bulk reserves capped. Follow CSV fills and dead volumes; never return working liquid to bulk stock.

Reuse a tip only for consecutive **same-stock, noncontact** dosing above the destination top. Different ligands and all analytical samples use fresh tips. Avoid deep immersion, walls and bottoms. Repeated aspiration does not dissolve an insoluble stock and may introduce bubbles.

Pause for persistent layers, solids at the aspiration point, bubbles, air uptake, dripping or tip contact. Do not sample an arbitrary layer. Do not filter, centrifuge or decant without recording its effect on analyte/IS recovery. High rpm alone does not establish quench completeness or extraction recovery; no separate homogeneity study is planned.

For an uncertain LC dilution, remix the original extract and prepare a fresh documented dilution. Do not guess a top-up. Retain rejected measurements with a reason and accept one result per sample; do not select the highest yield.

Changeover and finish

After all **48 R1 results** pass analytical QC, the local pipeline selects **22 new pairs + L17 reference**. Archive R1 vials; fit the 23 dry predosed vials into the same block and verify orientation. Refill sources using R2 deck loads. **No SM redosing; mesitylene is added once after dry-down.** Repeat reaction and workup.

Stop the clock after all 23 final injections and quantitative analysis. Archive source exports, maps, assay/stock records, method/channel, calibration, QC, times, scoring/cache records, final CSVs, matching protocols and robot JSON logs. Keep experimental data private pending team agreement.

02 / Stocks and calibration

Use `stock_preparation.csv` for masses/reserves; load only the stage's `deck_loads.csv` quantities. **Bulk volume is not deck fill.** Correct masses for COA assay. Prepare ligands in the glovebox.

Reaction stocks

Stock	Bulk preparation at 100% assay	Per reaction
SM, MW 161.16	**10.00 mL, 500 mM in DCM:** 805.8 mg; make to volume in a capped 20 mL glass vial	50 µL; evaporate fully
Each ligand	**40 mM in toluene**; masses and reserves in CSV	37.5 µL each
Pd(COD)(DQ), MW 378.8	**40 mM in toluene**; current plan 9.53 mL, 144.399 mg	75 µL
Mesitylene, MW 120.19	**5.00 mL, 100 mM in toluene:** 60.095 mg	25 µL, after dry-down
Toluene	Current reserve plan 15.57 mL	75 µL

Capped glass bulk reserves; ordinary plastic working racks, maximum 1.4 mL/tube; common liquids in the 12-channel reservoir. CSVs include 50% working margin, dead volume and conservative R2 reserves. Refill stage sources; never return working liquid to bulk.

Workup solvents - no internal standard

Solution	Prepare	Use
Quench	**100 mL, 9:1 ACN/water +0.15% v/v formic acid:** 150 µL acid, make to volume with premixed solvent	500 µL; recap, 1500 rpm, 2 min
LC diluent	**125 mL, 1:1 water/ACN +0.1% v/v formic acid:** 125 µL acid, make to volume with premixed solvent	980 µL +20 µL extract

Analytical stocks - matched matrix

Matrix, 100 mL: 0.6667 mL toluene +50.1492 mL ACN +0.1000 mL formic acid; water to volume. Approximate diluted-extract matrix; ignores volume contraction. Prepare all analytical stocks in it.

Separate 10 mM analyte masters, 10.00 mL: SM 16.116 mg; product 9.709 mg. No IS. For 1 mM working stocks, dilute 100 µL master to 1.00 mL. Make check masters by **independent weighing**.

Analytical mesitylene, 5 mM, 20.00 mL: 12.019 mg in matched matrix. Do not use the reaction mesitylene/toluene stock.

Calibration during hold one - 14 injections

Prepare seven **1.00 mL standards per analyte**, in a separate compatible calibration plate or confirmed vials. Every standard, including blank/check, receives **13.333 µL of 5 mM mesitylene** (66.667 µM final IS). Add the quantities below; mix, seal and use `calibration_template.csv` IDs.

Analyte, µM	Role	Stock, mM	Analyte, µL	Matrix, µL
0	Fit blank	None	0	986.667
10	Fit	1	10	976.667
50	Fit	1	50	936.667
150	Fit	10	15	971.667
350	Fit	10	35	951.667
800	Fit	10	80	906.667
666.667	Independent check	10, independent	66.667	920.000

Fit blank +five levels; exclude the check. Require **R^2 >=0.995**, **check error <=15%**, separation and measured LOQs on the actual method. The lowest standard is not automatically the LOQ. Record method, wavelength and injection volume.

Maximum sample: 666.667 µM analyte; 64.7 µg/mL product or 107.4 µg/mL SM. Calibration must establish the detector range. LC import and pilot replay covers reviewed blank absences and optional mixed-standard practice. Retain failed checks/rejected measurements.

03 / Local pipeline

The **initial 48 pairs are ready** in `campaigns/hackathon2026/round1_design.csv`. Local Python converts integrated UV areas to calibrated yields; Claude selects the next conditions. Staff use the bench sheet.

Set up before the clock

Use Python 3.12: `uv sync --python 3.12 --extra sources`, then prefix commands with `uv run`. Alternatively activate a venv and install `python -m pip install -e '.[sources]'`.

```
mkdir -p local_data
cp -n hte_inputs/campaign.json local_data/campaign.json
cp -n hte_inputs/calibration_template.csv local_data/calibration-plan.csv
cp -n anthropic.key.example anthropic.key
chmod 600 anthropic.key
```

Put the raw Claude key in `anthropic.key`; preserve any existing key. Never send it to the robot, Git or email.

In `local_data/campaign.json`, set actual method/channel, full LC cycle, measured reference RTs/LOQs and applicable release evidence. Confirm final-plate shaker/autosampler compatibility and uncovered shake speed; revise the 752.7-min timing before release. HTEL setup facts.

```
python -m hte.cli --config local_data/campaign.json check
python -m hte.cli --config local_data/campaign.json export \
  --design campaigns/hackathon2026/round1_design.csv \
  --output output/r1-dose --live --stage dose_and_react
```

App-simulate the exported Python; use matching CSVs and start locally. For previews omit `--live`; physical execution stays blocked. R1 dosing can precede calibration once other checks pass.

During hold one

Run/import **14 calibration injections** using the LC instructions. Staff prepare 23 dry SM-only vials. After calibration passes, set `lc_calibration_validated=true`; export workup:

```
python -m hte.cli --config local_data/campaign.json export \
  --design campaigns/hackathon2026/round1_design.csv \
  --output output/r1-workup --live --stage workup
```

After all 48 R1 results

Default: **one final LC plate/export per round, four moves total**. Robot dilutes and shakes. Use `lc_plates.csv` and complete `lc_batchNN_injections.csv` with actual method/sequence identities. Each export needs its own map; match glob order and exclude unrelated files.

```
python scripts/hte-lc-results.py next \
  --dosing output/r1-dose/dosing.csv \
  --exports local_data/r1-batch*.csv \
  --injections local_data/r1-map*.csv \
  --output output/r1-decision
```

Calibration defaults to `local_data/calibration.csv` (`--calibration` overrides). After all 48 results pass QC, Claude scores **387 untested pairs** and selects **22 new pairs +L17 reference**. Both prompts include the 17 individual SI yields; no embedding selector runs in R2.

The printed decision folder holds `next_design.csv`, `next_dosing.csv`, analysis, scores and `protocols/`. Use released Python and R2 deck loads. If checks remain open, export `next_design.csv` with `--history output/r1-dose/dosing.csv`, a fresh folder and `--live`. Fit the 23 dry predosed vials; **no SM redosing**.

After all 23 R2 injections, run the helper with `final`, R2 `dosing.csv`, the matching plate export/map and a new output folder. This calculates final results without Claude. Compare pair yields with the measured L17 reference and retain run times.

Practice and recovery

Practice: `python -m hte.cli practice-analytics --output output/pilot`; real pilot replay. `rehearse-loop` also mocks feedback; no paid calls. Use fresh import folders and review interrupted scoring before retrying.

169 tests passed; protocols simulated; initial design reproducible. Bench results/calibration and feedback latency remain unmeasured. Validation, ML strategy, PDF updates.