



ANDROID STATIC ANALYSIS REPORT

app_icon



Biblia Dourada (1.0)

File Name:

app-debug.apk

Package Name:

com.example.bibliadourada


Scan Date:

Sept. 26, 2026, 4:56 p.m.

App Security Score:

42/100 (MEDIUM RISK)

Grade:



 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
3	6	1	1	0

FILE INFORMATION

File Name: app-debug.apk
Size: 18.25MB
MD5: 460bbb6ce1e3b6c962ffe0c733965797
SHA1: ed96b73f6127ffb94a90bbaf0336a38b3863defb
SHA256: c0d421285567d62f7e91e0fd4597c814eccbedbd0bdccf554ea6b8bc40428ee3

APP INFORMATION

App Name: Biblia Dourada
Package Name: com.example.bibliadourada
Main Activity: com.example.bibliadourada.MainActivity
Target SDK: 36
Min SDK: 24
Max SDK:
Android Version Name: 1.0
Android Version Code: 1

APP COMPONENTS

Activities: 3
Services: 0
Receivers: 1
Providers: 1
Exported Activities: 2
Exported Services: 0

Exported Receivers: 1
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: CN=Android Debug, O=Android, C=US
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2026-09-26 16:55:00+00:00
Valid To: 2056-09-18 16:55:00+00:00
Issuer: CN=Android Debug, O=Android, C=US
Serial Number: 0x1
Hash Algorithm: sha256
md5: 2dca3be0da0b34d879dbe55005626f6e
sha1: aaf2f78b5a13836b9d401b7ddfd81f2d089283da
sha256: 90bfd1c52d745c87f5d3502dc6c47215f26d854e4a5ffef04d0d510592c0416a
sha512: 18c34e7c5b3c5c05931581f3da6e735fadcb61ad2763f00d7a60ba52375a9d7dc6cb73ea95d10ad3eaabf65c3a04d0a8f54dd425c4d570cee061413740670a0f
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 81f59254f819ddaf39c0daf6be1a9f4977d215811ae83857eacaf3bb4e190a61
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
com.example.bibliadourada.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

APKID ANALYSIS

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	Compiler	r8
classes10.dex	FINDINGS	DETAILS
	Compiler	unknown (please file detection issue!)
classes11.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check
	Compiler	r8 without marker (suspicious)
classes12.dex	FINDINGS	DETAILS
	Compiler	r8 without marker (suspicious)
classes2.dex	FINDINGS	DETAILS
	Compiler	unknown (please file detection issue!)

FILE	DETAILS	
classes3.dex	FINDINGS	DETAILS
	Compiler	r8
classes4.dex	FINDINGS	DETAILS
	Compiler	r8
classes5.dex	FINDINGS	DETAILS
	Compiler	r8
classes6.dex	FINDINGS	DETAILS
	Compiler	r8
classes7.dex	FINDINGS	DETAILS
	Compiler	r8

FILE	DETAILS	
classes8.dex	FINDINGS	DETAILS
	Compiler	r8
classes9.dex	FINDINGS	DETAILS
	Compiler	r8

 NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

 CERTIFICATE ANALYSIS

HIGH: 1 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate
Application signed with debug certificate	high	Application signed with a debug certificate. Production application must not be shipped with a debug certificate.

 MANIFEST ANALYSIS

HIGH: 2 | WARNING: 4 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version 7.0, [minSdk=24]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Debug Enabled For App [android:debuggable=true]	high	Debugging was enabled on the app which makes it easier for reverse engineers to hook a debugger to it. This allows dumping a stack trace and accessing debugging helper classes.
3	Application Data can be Backed up [android:allowBackup=true]	warning	This flag allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
4	Activity (androidx.compose.ui.tooling.PreviewActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Activity (androidx.activity.ComponentActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

</> CODE ANALYSIS

HIGH: 0 | WARNING: 2 | INFO: 1 | SECURE: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
----	-------	----------	-----------	-------

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	com/example/bibliadourada/data/AnnotationImporter.java com/example/bibliadourada/data/BibleDatabaseHelper.java com/example/bibliadourada/data/BibleRepositoryImpl\$getBooks\$2.java com/example/bibliadourada/data/BibleRepositoryImpl\$getChapter\$2.java com/example/bibliadourada/data/BibleRepositoryImpl\$getChapterByBookAndNumber\$2.java com/example/bibliadourada/data/BibleRepositoryImpl\$getChaptersForBook\$2.java com/example/bibliadourada/data/BibleRepositoryImpl\$getCommentsForVerse\$2.java com/example/bibliadourada/data/BibleRepositoryImpl\$getDailyReadings\$2.java com/example/bibliadourada/data/BibleRepositoryImpl\$getVersesForChapter\$2.java com/example/bibliadourada/data/BibleRepositoryImpl\$search\$2.java
2	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/example/bibliadourada/data/BibleDatabaseHelper.java
3	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/example/bibliadourada/ui/components/TourStep.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
----	---------------	----	-----	--------------	-------	-------	---------	---------	------------------

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	x86_64/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	armeabi-v7a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	x86/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00063	Implicit intent(view a web page, make a phone call, etc.)	control	com/example/bibliadourada/ui/components/AboutAppSheetKt.java
00036	Get resource file from res/raw directory	reflection	com/example/bibliadourada/ui/components/AboutAppSheetKt.java
00022	Open a file from given absolute path of the file	file	com/example/bibliadourada/data/BibleDatabaseHelper.java
00013	Read file and put it into a stream	file	com/example/bibliadourada/data/BibleDatabaseHelper.java
00009	Put data in cursor to JSON object	file	com/example/bibliadourada/data/AnnotationImporter.java

🔗 ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	0/25	
Other Common Permissions	0/44	

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
--------	----------------

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
jeielfmiranda.com.br	ok	IP: 216.198.79.65 Country: United States of America Region: Ohio City: Cleveland Latitude: 41.508816 Longitude: -81.673981 View: Google Map
www.universal.org	ok	IP: 179.191.177.9 Country: Brazil Region: Rio Grande do Sul City: Porto Alegre Latitude: -30.033060 Longitude: -51.230000 View: Google Map
is.gd	ok	IP: 104.25.234.53 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

EMAILS

EMAIL	FILE
jeielfmirand@gmail.com	com/example/bibliadourada/ui/components/AboutAppSheetKt.java

POSSIBLE SECRETS

9aaf5f34c4c84da429ef7f8f6217a1817876f2618cfcf539aba3d7d5a0c703e0

 SCAN LOGS

Timestamp	Event	Error
2026-09-26 16:56:30	Generating Hashes	OK
2026-09-26 16:56:30	Extracting APK	OK
2026-09-26 16:56:30	Unzipping	OK
2026-09-26 16:56:30	Parsing APK with androguard	OK
2026-09-26 16:56:30	Extracting APK features using aapt/aapt2	OK
2026-09-26 16:56:30	Getting Hardcoded Certificates/Keystores	OK
2026-09-26 16:56:32	Parsing AndroidManifest.xml	OK

2026-09-26 16:56:32	Extracting Manifest Data	OK
2026-09-26 16:56:32	Manifest Analysis Started	OK
2026-09-26 16:56:32	Performing Static Analysis on: Biblia Dourada (com.example.bibliadourada)	OK
2026-09-26 16:56:32	Fetching Details from Play Store: com.example.bibliadourada	OK
2026-09-26 16:56:32	Checking for Malware Permissions	OK
2026-09-26 16:56:32	Fetching icon path	OK
2026-09-26 16:56:32	Library Binary Analysis Started	OK
2026-09-26 16:56:32	Analyzing apktool_out/lib/x86_64/libandroidx.graphics.path.so	OK
2026-09-26 16:56:32	Analyzing apktool_out/lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2026-09-26 16:56:32	Analyzing apktool_out/lib/x86/libandroidx.graphics.path.so	OK
2026-09-26 16:56:32	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-09-26 16:56:32	Analyzing lib/x86_64/libandroidx.graphics.path.so	OK

2026-09-26 16:56:32	Analyzing lib/armeabi-v7a/libandroidx.graphics.path.so	OK
2026-09-26 16:56:32	Analyzing lib/x86/libandroidx.graphics.path.so	OK
2026-09-26 16:56:32	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2026-09-26 16:56:32	Reading Code Signing Certificate	OK
2026-09-26 16:56:33	Running APKiD 3.0.0	OK
2026-09-26 16:56:37	Updating Trackers Database....	OK
2026-09-26 16:56:37	Detecting Trackers	OK
2026-09-26 16:56:43	Decompiling APK to Java with JADX	OK
2026-09-26 16:57:39	Converting DEX to Smali	OK
2026-09-26 16:57:39	Code Analysis Started on - java_source	OK
2026-09-26 16:57:47	Android SBOM Analysis Completed	OK
2026-09-26 16:57:48	Android SAST Completed	OK

2026-09-26 16:57:48	Android API Analysis Started	OK
2026-09-26 16:57:53	Android API Analysis Completed	OK
2026-09-26 16:57:54	Android Permission Mapping Started	OK
2026-09-26 16:57:56	Android Permission Mapping Completed	OK
2026-09-26 16:57:57	Android Behaviour Analysis Started	OK
2026-09-26 16:57:57	Android Behaviour Analysis Completed	OK
2026-09-26 16:57:57	Extracting Emails and URLs from Source Code	OK
2026-09-26 16:57:58	Email and URL Extraction Completed	OK
2026-09-26 16:57:58	Extracting String data from APK	OK
2026-09-26 16:57:59	Extracting String data from SO	OK
2026-09-26 16:57:59	Extracting String data from Code	OK
2026-09-26 16:57:59	Extracting String values and entropies from Code	OK

2026-09-26 16:58:07	Performing Malware check on extracted domains	OK
2026-09-26 16:58:08	Saving to Database	OK

Report Generated by - MobSF v4.4.6

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).