

# Contents

1	Toggle switch stability . . . . .	3
1.1	Introduction . . . . .	3
1.2	Stability Finder algorithm . . . . .	3
1.2.1	Algorithm overview . . . . .	4
1.2.2	Initial condition sampling . . . . .	6
1.2.3	Distance function . . . . .	7
1.2.3.1	Clustering methods . . . . .	7
1.2.4	Particle rejection . . . . .	8
1.2.5	Model checking . . . . .	8
1.3	Calculating robustness . . . . .	8
1.3.1	Case study 1: Infectious diseases . . . . .	11
1.3.2	Case study 2: Population growth . . . . .	14
1.4	Applications of Stability Finder . . . . .	16
1.4.1	Testing StabilityFinder . . . . .	16
1.4.2	Lu toggle switch models . . . . .	20
1.4.2.1	Extending the Lu models . . . . .	22
1.4.2.2	Multistability in the Lu models . . . . .	26
1.4.2.3	Extending the Lu switch to three nodes . . . . .	30
1.4.3	Mass Action switches . . . . .	32
1.4.3.1	Multistability in the MA switces . . . . .	37
1.4.3.2	Robustness prior dependence . . . . .	39
1.5	Discussion . . . . .	43
1.6	Summary . . . . .	44
	Bibliography . . . . .	45



# 1 Toggle switch stability

## 1.1 Introduction

In this chapter, I aim to uncover the underlying principles that govern the stability of a given switch. To do this, I developed an algorithm, called Stability Finder, that can find the parameter value ranges that can produce the desired stability in a given model. I use this algorithm to examine a variety of switch architectures using different modelling abstractions.

Structurally, this chapter is organised as follows: In the first section I examine the current understanding of the stability landscape of the genetic toggle switch. Then, I discuss the development of Stability Finder, justify the choices made and the drawbacks of this method. In the sections following I apply Stability Finder to a variety of models and finally I discuss the implications our findings have to the overall understanding of the toggle switch stability.

## 1.2 Stability Finder algorithm

To investigate the multistable behaviour of systems, I had to make a number of extensions to existing approaches. Firstly, a wide range of initial condition samples are required in order to determine the stability of a system. For a given set of parameter values, sample points are taken across initial conditions using latin hypercube sampling (McKay, Beckman, & Conover 2000), and the ensemble system simulated in time until steady state. As a distance function I use the desired stability of the simulated model. An overview of the algorithm is given in section 1.2.1. Then each module in the algorithm is described in Sections ??-1.2.5.

## 4 TOGGLE SWITCH STABILITY

### 1.2.1 Algorithm overview

The Stability Finder algorithm is summarised below. Stability Finder is available as a Python package, and can be downloaded from <https://github.com/ucl-cssb/StabilityFinder.git>.


---

#### **Algorithm 1** StabilityFinder algorithm

---

- 1: Initialise  $\epsilon$
  - 2: population  $p \leftarrow 1$
  - 3: **if**  $p = 1$  **then**
  - 4:     Sample particles ( $\theta$ ) from priors
  - 5: **else**
  - 6:     Sample particles from previous population
  - 7:     Perturb each particle by  $\pm$  half the range of the previous population (j) to obtain new perturbed population (i).
  - 8: **end if**
  - 9: Sample initial conditions via latin hypercube sampling.
  - 10: Simulate each particle to obtain steady state values.
  - 11: Cluster steady state
  - 12: Reject particles if  $d > \epsilon$ .
  - 13: Calculate weight for each accepted  $\theta$
  - 14:  $w_t^{(i)} = \begin{cases} 1, & \text{if } p = 1 \\ \frac{\pi(\theta_t^{(i)})}{\sum_{j=1}^N w_{t-1}^{(j)} K_t(\theta_{t-1}^{(j)}, \theta_t^{(i)})}, & \text{and if } p \geq 1. \end{cases}$
  - 15: Normalise weights
  - 16: Repeat steps 3 - 15 until  $\epsilon \leq \epsilon_T$
-


The user provides an SBML model file and an input file that contains all the necessary information to run the algorithm, including the desired stability and the final tolerance  $\epsilon$ , for the distance from the desired behaviour necessary for the algorithm to terminate. The flow of execution is illustrated in Figure 1.1E. Since the algorithm is computationally intensive, all deterministic and stochastic simulations are parallelised and performed using algorithms implemented on Graphical Processing Units (GPUs).



**Figure 1.1** : Using sequential Monte Carlo to examine system stability. The algorithm takes as input a model (A) and evolves it to the stability of choice (C) via intermediate populations. In this example model shown in A, There are two species and two parameters. For the model to be bistable, the phase plot of the two species of interest must have two distinct densities, as shown in (C). The parameter space of the model is searched through our algorithm until the resulting simulations give rise to bistability. The parameter values for the model that demonstrated the desired behaviour are given as an output (D). The output consists of the accepted values for each parameter, as well as each density plotted against the other. This allows us to uncover correlations between parameter values. We made this algorithm into a python package, called Stability Finder. The overview of the algorithm is shown in (E).

### 1.2.2 Initial condition sampling

In Stability Finder, latin hypercube sampling is used to sample initial conditions (McKay, Beckman, & Conover 2000). This is used to ensure that the whole space is sampled uniformly. Latin hypercube sampling is done in two dimensions in Stability Finder. The uniform priors of the two species in consideration represent a rectangle space, which is subdivided into equal parts. Then a random sample is drawn from each sub-part. This ensures the whole space is evenly sampled.



**Figure 1.2** Latin hypercube sampling ensures that the whole space is sampled evenly. For the two species concerned, A and B, we assume uniform distributions, shown in grey. The joint space of the two distributions is divided into smaller equal parts and a random sample is drawn from within each subspace.

Stability Finder can only be used for stability analysis concerning two species. By that I refer to models where the phase plot is always and only two-dimensional. Stability landscapes involving more than two species are beyond the scope of this thesis.

### 1.2.3 Distance function

The distance function is the function the algorithm uses to compare the desired behaviour to the behaviour observed in each particle (Toni et al. 2009). In Stability Finder the distance function consists of three distances. The first one is the difference between the number of desired clusters and the number of clusters observed in the phase plot. For this distance metric the number of clusters in the phase plot must be calculated. The clustering methods used are outlined in section 1.2.3.1.

The other two distance metrics used in Stability Finder are the variance within each cluster and the overall, between cluster, variance. The within cluster variance ensures that the clusters are tight, and the between cluster variance is used to ensure the clusters are far apart from each other. In the context of this thesis, the ideal behaviour of a system is tight, widely separated clusters. This means that the genetic system has distinct steady states, and the difference in the protein levels between each steady state is observable.

#### 1.2.3.1 Clustering methods

Whether the model was simulated using ODEs or the Gillespie algorithm (Gillespie 1977) dictated the method of clustering that we used. For the deterministic models I used an algorithm I developed, that will be referred to as the delta clustering algorithm in this thesis. This algorithm consists of defining the number of clusters by counting a new cluster every time a data point is more than a distance  $\delta$  away from any existing clusters. The benefits of the delta clustering algorithm are that it is fast and can be used on deterministic solutions, where steady state values tend to be identical if all the particles have reached steady state.

Steady states of stochastic models are clustered using the K-means clustering (Lloyd 1982) and the number of clusters determined using the Gap statistic (Tibshirani, Walther, & Hastie 2001). This method is more suited to stochastic solutions, where the delta clustering method would fail as the steady state solutions tend to be more widely dispersed than in the deterministic case. The detailed algorithms used are shown in Appendix (XXX).

The method used for clustering can be altered by the user if he/she wants to add their own preferred clustering algorithm that might be more appropriate for their specific purposes. For the models I used here, the above methods were successful in clustering the steady state solutions.

## 8 TOGGLE SWITCH STABILITY

### 1.2.4 Particle rejection

Once the distance from the desired behaviour has been calculated, the algorithm rejects any particles whose distance is farther than the current  $\varepsilon$ . The distances taken into account are the number of clusters ( $C$ ), the between cluster variance ( $V_{bc}$ ) and the within cluster variance ( $V_{wc}$ ) as outlined in section 1.2.3. In addition to these distances I have included another two checks for the particles. Firstly, Stability Finder checks if the simulation of a particle has reached steady state. If the standard deviation of the last ten time points in the simulation is larger than a user-specified value, then the particle is rejected. This is to ensure that only particles that have reached steady state are considered. Secondly, there is a check for the minimum level of the steady states. This is to allow the user to select for steady states whose protein levels are above a certain threshold. This has to be added as an additional check as the steady state levels must be experimentally observable if they are to be used to design new systems. Two steady state levels of very low levels would be biologically indistinguishable and thus meaningless in an experimental setup. This check is optional to the user, and can be set to zero if not desirable.

### 1.2.5 Model checking

A problem that can arise by using this method with stochastic simulations is that the behaviour observed may not be the true behaviour but it might be a result of noise. We need to ensure that the resulting behaviour is reproducible. Therefore, I added model checking to the algorithm. Model checking consists of resampling from the posterior distribution and simulating each sample. If the resulting behaviour is the same as what we expected we can be confident that it is the true behaviour of the system and not a result of noise.

## 1.3 Calculating robustness

Unlike other ABC SMC methods, Stability Finder does not have model selection integrated into the method. This is because the purpose of Stability Finder is not necessarily to compare models for robustness but to elucidate the stability a given model is capable of. Nevertheless, robustness analysis is an outcome that Bayesian methods are well suited for. Therefore, here I discuss another algorithm I developed in order to extract robustness information from the results of Stability Finder and apply model selection.

As discussed in Section ??, two models can be compared for their robustness using Equation ?? . This represents the ratio of the robustness measure of each model which in turn is defined as the ratio between the volume of functional region  $F$  and the volume of the prior  $P$ . In order to calculate the Bayes' factor we must first be able to approximate the volume of the viable parameter space. The viable parameter space is the space that approximates the posterior distribution that can give rise to the desired behaviour. I tested two methods of approximating the volume of the viable space, which are outlined in Algorithm 2. The first method is based on the method used by (Hafner et al. 2009), where the volume of the cuboid containing all the viable space is calculated. I modified this part of their method by only including the area of the viable space where the majority of the last population lies. Therefore only the 1<sup>st</sup> and 99<sup>th</sup> percentile of the viable space are taken into account. This is necessary in order to exclude outliers in the distribution that would skew the volume calculation significantly. Each parameter represents a side in the cuboid and since the volume of a cuboid is equal to the product of its sides, the volume of the viable space is equal to the product of the ranges of all the parameters. This cuboid method will be prone to overestimating robustness especially in cases of correlation between parameters. This caveat could be alleviated if a Principal component analysis (PCA) (Fukunaga 2013) is done on the data before the cuboid is calculated (Hafner et al. 2009). This would align the axes of the cuboid to the major axes of the distribution. This would still be a crude estimation of the volume, since if the posterior distribution is assumed to be normally distributed the volume would still be overestimated.

Thus we used a second method, where the volume of the viable space was represented by a hyper-ellipsoid, an ellipse in higher dimensions. This method should not be as prone to overestimation of robustness as the cuboid method as an ellipsoid can take correlation into account. For this method the distribution of the viable space is assumed to be normal. The method calculates the covariance matrix of the distribution, whose volume is given by Equation 1.1. Just as in the cuboid method, the 1<sup>st</sup> and 99<sup>th</sup> percentile of the data is ignored.

$$V = \frac{2\pi^{\frac{k}{2}}}{k\Gamma(\frac{k}{2})} [\chi_k^2(\alpha)]^{\frac{k}{2}} |\Sigma|^{\frac{1}{2}}, \quad (1.1)$$

where  $k$  is the number of dimensions,  $\Gamma$  is the Gamma function,  $\alpha$  is the confidence interval required and  $|\Sigma|$  is the determinant of the covariance matrix.

## 10 TOGGLE SWITCH STABILITY

To validate these methods I compare them to ABC-SysBio model selection (Liepe et al. 2014). ABC-SysBio has been used extensively for model selection (Toni et al. 2009; Toni et al. 2011; Barnes et al. 2011) There is good agreement between the three methods as can be seen in Figures 1.3 and 1.4.

---

### Algorithm 2 Approximating robustness

---

```

1: for each model  $m$  of  $M$  do
2:   Prior  $\sim U(a, b)$ 
3:    $V_{prior}^m = \prod_{i=1}^k (i_b - i_a)$ 

4:   Get  $1^{st} < data < 99^{th}$  percentiles
5:   if Cuboid calculation then
6:      $V_{post}^m = \prod_{i=1}^k (i_{max} - i_{min})$ 
7:   end if
8:   if Ellipsoid calculation then
9:     Calculate data covariance matrix
10:     $V_{post}^m = \frac{2\pi^{\frac{k}{2}}}{p\Gamma(\frac{k}{2})} [\chi_k^2(\alpha)]^{\frac{k}{2}} |\Sigma|^{\frac{1}{2}}$ 
11:   end if

12:    $R^m = \frac{V_{post}^m}{V_{prior}^m}$ 
13:    $R_{norm}^m = \frac{R_i^m}{\sum_{i=1}^M R_i^m}$ 
14: end for

```

---

We use the following two examples used in ABC-SysBio (Toni et al. 2009):

### 1.3.1 Case study 1: Infectious diseases

For the first case study utilizes the models used in autociteToni:2009tr. As described in Toni et al. (2009), the models describe the spread of an infectious disease through a population over time. The population is made up of susceptible, infected or recovered individuals, denoted as  $S$ ,  $I$  and  $R$  respectively. Three models are compared for the robustness of their posterior distributions. The first model (Model 1), is the simplest model of the three. Each individual  $S$  or  $R$  can be infected once and then it can immediately infect other individuals (Toni et al. 2009).

$$\dot{S} = \alpha - \gamma SI - dS \quad (1.2)$$

$$\dot{I} = \gamma SI - vI - dI \quad (1.3)$$

$$\dot{R} = vI - dR, \quad (1.4)$$

where  $\alpha$  denotes the birth rate,  $d$  the death rate,  $\gamma$  the infection rate, and  $v$  the recovery rate.

The second model, Model 2, includes a time delay between an individual getting infected and being infectious.  $\delta$  denotes the rate of transition of a non-infectious infected individual to an infectious one.

$$\dot{S} = \alpha - \gamma SI - dS \quad (1.5)$$

$$\dot{L} = \gamma SI - \delta L - dL \quad (1.6)$$

$$\dot{I} = \delta L - vI - dI \quad (1.7)$$

$$\dot{R} = vI - dR, \quad (1.8)$$

Finally the third model, Model 3, extends Model 1 and includes the recovered individuals being able to become susceptible again. This is denoted by rate  $e$ .

$$\dot{S} = \alpha - \gamma SI - dS + eR \quad (1.9)$$


$$\dot{I} = \gamma SI - vI - dI \quad (1.10)$$

$$\dot{R} = vI - dR - eR, \quad (1.11)$$

The three models are simulated using ODEs. In ABC-SysBio model selection is used. Parameter inference is also used for each model separately without the use

## 12 TOGGLE SWITCH STABILITY

of model selection. I used the two methods outlined in Algorithm 2 to calculate the robustness of the posterior distributions of all three models. This robustness measure was then compared to the result of ABC-SysBio model selection. As shown in Figure 1.3, there is good agreement between the three measures of robustness. The posterior distributions of all three models are also shown in Figure 1.3.



**Figure 1.3** : Robustness analysis of the three models for the spread of infectious diseases. (A-C) The posterior distributions of the three models compared. (D) I use three methods to calculate robustness, ABC-SysBio model selection, the volume of the hyper-cuboid approximation of the posterior distribution and the volume of the hyper-ellipsoid approximation of the posterior distribution. Each analysis was repeated three times. The height of the bars indicate the mean robustness from the three repeats and the error bars represent the standard deviation. There is good agreement between all three methods. All three methods show that Model 1, the simplest model, is the most robust model.

### 1.3.2 Case study 2: Population growth

The second example I will use to demonstrate the effectiveness of the methods used here for robustness calculation is a population growth model. This is another example used in ABC-SysBio (Toni et al. 2009).


The data was obtained by simulating an immigration-death model shown in Equation 1.12. This model (referred to as Model 1) and a model of logistic growth are compared for robustness of their posterior distributions. Model 1:

$$\frac{dI}{dt} = \alpha - \beta I \quad (1.12)$$

Logistic growth, model 2:

$$\frac{dI}{dt} = \gamma - I(\delta - \epsilon I) \quad (1.13)$$

As in Section 1.3.1, two analyses were carried out on these two models. First, ABC-SysBio model selection was used to find the most robust model. Then parameter inference was done on each model. The resulting posterior distributions (shown in Figure 1.4), were compared for robustness using the cuboid and the ellipsoid approximation methods. All three robustness measures find that Model 1 is the most robust model. The analysis was repeated for ODE, MJP and SDE simulations, all arriving to the same result of Model 1 being the most robust. The results are shown in Figure 1.4.



**Figure 1.4** : Robustness comparison of two population growth models. (A) The posterior distributions of the two models. (B-D) The models were simulated using ODE, MJP and SDE. Both the cuboid and the ellipsoid approximations agree with ABC-SysBio model selection results. Each analysis was repeated three times. The height of the bars indicate the mean robustness from the three repeats and the error bars represent the standard deviation.

## 16 TOGGLE SWITCH STABILITY

The two case studies used above show that the cuboid and the ellipsoid approximation of model robustness agree with the results obtained from ABC-SysBio model selection. A point I must draw attention to is that for ABC-SysBio model selection where model selection is incorporated in the process, each model is also considered a particle with an associated weight (Toni et al. 2009). If a model is performing poorly it does not proceed in the algorithm and is dropped when the weight falls low enough so that the model is not sampled (Toni et al. 2009). This can save time in the analysis as computational resources are not wasted on 'dead' models, models that perform the required behaviour poorly. Using Stability Finder for model selection, each model must reach the given final  $\epsilon$  in order for the cuboid and ellipsoid methods to be valid. This means that time and computational power will be spent on models that are potentially a bad fit, or that have posterior distributions so small compared to the prior that it will take a long time for Stability Finder to find it. Despite this, the results agree between the all three methods of model selection. This shows that the requirement for all models to reach the final  $\epsilon$  does not affect the results for the models used in the above case studies. The potentially wasted computational resources on 'dead' models is a compromise we make in order to be able to run the models separately, as model selection is not the primary purpose of Stability Finder.

## 1.4 Applications of Stability Finder

In this section I apply Stability Finder to switch models in order to find the design principles underlying their stabilities. First I apply it to a simple model with known results, the Gardner, Cantor, & Collins (2000) toggle switch. This model can serve as a test for Stability Finder, as the conditions for bistability are derived in Gardner, Cantor, & Collins (2000).

### 1.4.1 Testing StabilityFinder

Gardner, Cantor, & Collins (2000) constructed the first synthetic genetic toggle switch (Gardner, Cantor, & Collins 2000). Their model consisted of two mutually repressing transcription factors, as shown in Figure 1.5A, and in the deterministic case is defined by the following ODEs:

$$\frac{du}{dt} = \frac{a_1}{1 + v^\beta} - u \quad (1.14)$$

$$\frac{dv}{dt} = \frac{a_2}{1 + u^\gamma} - v, \quad (1.15)$$


where  $u$  is the concentration of repressor 1,  $v$  the concentration of repressor 2,  $a_1$  and  $a_2$  denote the effective rates of synthesis of repressors 1 and 2 respectively,  $\beta$  is the cooperativity of repression of promoter 1 and  $\gamma$  of repressor 2. Gardner, Cantor, & Collins (2000) studied the deterministic case and concluded that there are two conditions for bistability for this model; that  $a_1$  and  $a_2$  are balanced and that  $\beta, \gamma > 1$  (Gardner, Cantor, & Collins 2000). I test Stability Finder by using it to find the posterior distribution for which this model exhibits bistable behaviour. Therefore, the desired behaviour is set to two steady states, and using a wide range of values as priors as shown in Table 1.1, I used Stability Finder to find the parameter values necessary for bistability to occur. The posterior distribution calculated by Stability Finder for the Gardner deterministic case is shown in Figure 1.6A.

Table 1.1 Gardner switch priors in the deterministic and stochastic cases


Parameters				Species	
$a_1$	$\beta$	$a_2$	$\gamma$	$s_1$	$s_2$
0-60	0-5	0-60	0-5	0-100	0-100

These results agree with the results reported by Gardner, Cantor, & Collins (2000). For this switch to be bistable  $a_1$  and  $a_2$  must be balanced while  $\beta$  and  $\gamma$  must both be  $> 1$ , as can be seen in the marginal distributions of  $\beta$  and  $\gamma$  in Figure 1.6A.

I next applied Stability Finder to the case of the Gardner switch under stochastic dynamics using the same priors as the deterministic case, and again searched the parameter space for bistable behaviour. The posterior distribution is shown in Figure 1.6B. We can see that the conditions on the parameters required for bistability in the deterministic case generally still stand in the stochastic case. There appears to be slightly looser requirements on the parameters of the stochastic model (wider marginal distributions). Some difference between the deterministic and stochastic posteriors is expected as different clustering algorithms are used for the stochastic and the deterministic cases. The Gap statistic is used in the case of the stochastic case, as it is capable of dealing with noisier data whereas a simpler and faster algorithm is used for clustering the deterministic solutions. These results demonstrate that Stability Finder can be used to find the parameter values that can produce a desired stability and can be confidently applied to more complex models.



**Figure 1.5** The Gardner switch model used to test Stability Finder. The Gardner model (A) consists of two mutually repressing transcription factors. It can be reduced to a two-equation system (B), where  $u$  and  $v$  are the two transcription factors,  $\alpha_1, \alpha_2$  are their effective rates of synthesis,  $u, v$  are their concentrations and  $\beta, \gamma$  represent the cooperativity of each promoter. (C) Two samples of deterministic simulated timecourses of the Gardner switch and (D) The resulting phase plot. (E) Two samples of timecourses of the stochastic simulations and (F) the resulting phase plot.



**Figure 1.6** Elucidating the stability of the Gardner switch. The Gardner model has four parameters, for which I want to find the values for which this system is bistable. I use Stability Finder to find the posterior distribution of the bistable Gardner switch, deterministically (A) and stochastically (B). The posterior distributions are shown as the density plots of each parameter as well as each one plotted against the other.

### 1.4.2 Lu toggle switch models

Next I analyzed an extension of the Gardner switch model developed by Lu, Onuchic, & Ben-Jacob (2014). I use these models as they are of increased complexity from the Gardner model. Lu, Onuchic, & Ben-Jacob (2014) considered two types of switches, the classic switch consisting of two mutually repressing transcription factors (model CS-LU), as well as a Lu double positive switch (DP-LU). The CS-LU switch was found to be bistable given the set of parameters used, while the DP-LU switch was found to be tristable (Lu, Onuchic, & Ben-Jacob 2014). The CS-LU model used in their study is given by the following system of ODEs.

$$\dot{x} = g_x H_{xy}^S(y) - k_x x \quad (1.16)$$

$$\dot{y} = g_y H_{yx}^S(x) - k_y y, \quad (1.17)$$

where:

$$H_I^S(x) = H_I^-(x) + \lambda_I H_I^+(x) \quad (1.18)$$

$$H_I^-(x) = 1 / [1 + (x/x_I)^{n_I}] \quad (1.19)$$

$$H_I^+(x) = 1 - H_I^-(x), \quad (1.20)$$


and the DP-LU model is given by

$$\dot{x} = f_x(x, y) = g_x H_{xy}^S(y) H_{xx}^S(x) - k_x x \quad (1.21)$$

$$\dot{y} = f_y(x, y) = g_y H_{yx}^S(x) H_{yy}^S(y) - k_y y, \quad (1.22)$$

$g_I$  represents the production rate,  $k_I$  the degradation rate,  $n_I$  the Hill coefficient,  $x_I$  the Hill threshold concentration and  $\lambda_I$  the fold change of the transcription rates, and  $I \in \{xy, yx, xx, yy\}$ .

For the parameter values used in the Lu study, the CS-LU switch exhibits three steady states, two of which are stable and one is unstable. The CS-LU switch exhibits five steady states, of which three are stable and two are unstable. This analysis of the stability of the switch steady states was carried out by Mae Woods, PhD. Bifurcation diagrams of the two Lu models are shown in Figure 1.7.




**Figure 1.7** Stream plot of the vector plot of the (A) CS-LU and DP-LU switches.

The colours indicate the magnitude of the vectors, with yellow indicating high and red low values. The blue points represent stable steady states and the grey points represent unstable steady states.

### 1.4.2.1 Extending the Lu models

I start the analysis of the Lu models by extending their analytical approach to solving the system. I use Stability Finder to explore a larger parameter space which allows us to distinguish between rare events and robust behaviours. The advantage of using Stability Finder over solving the system analytically is that the full parameter space is explored rather than solving the system for a single set of parameters. This allows us to deduce model properties that could not otherwise be identified. Robustness to parameter fluctuations can be explored, as well as parameter correlations and restrictions on the values they can take while still producing the desired behaviour.

It is known that the addition of positive autoregulation to the classical toggle switch can induce tristability (Lu, Onuchic, & Ben-Jacob 2014). Here I investigate the interplay of positive autoregulation on the values of the other parameters in the model. I extended the analysis presented in Lu, Onuchic, & Ben-Jacob (2014) by including the switch with single positive autoregulation (model SP-LU), where an asymmetry of positive feedbacks is present between the two genes. The three switches considered in this analysis are shown in Figure 1.8.



**Figure 1.8** The three LU toggle switch models. (A) CS-LU, (B) SP-LU and (C) DP-LU.

The SP-LU switch is modelled using the following ODE system


$$\dot{x} = g_x H_{xy}^S(y) H_{xx}^S(x) - k_x x \quad (1.23)$$

$$\dot{y} = g_y H_{yx}^S(x) - k_y y. \quad (1.24)$$


Using Stability Finder with priors centred around the parameter values used in the original paper (see Table 1.2), we can identify the most important parameters for achieving the models' stability. The phase plots of the final populations of the models are shown in Figure 1.9 and the posterior distribution of these models are shown in Figure 1.10A. We find that the parameters representing the rates of degradation of the transcription factors in the system ( $k_x, k_y$ ) must both be large in relation to the prior ranges for bistability to occur. Protein degradation rates have been shown to be important for many system behaviours including oscillations (Woods et al. 2015).

**Table 1.2** Priors of the classical(CS-LU), single positive (SP-LU) and double positive (DP-LU) models.

Parameter	Symbol	CS-LU	SP-LU	DP-LU
Production rate	gx	30-50	1-2	1-100
	gy	30-50	20-25	1-100
Degradation rate	kx	0-0.5	50-55	0-1
	ky	0-0.5	48-52	0-1
Hill coefficient	nxy	1-5	30-35	0-10
	nyx	1-5	0.1-0.2	0-10
Hill thresholds concentration	xxY	100-300	2-3	100-1000
	xyx	100-300	0.4-0.6	100-1000
Transcription rate fold change	lxy	0-0.5	0.02-0.04	0-1
	lyx	0-0.5	0.02-0.04	0-0.2
Hill coefficient	nXX	-	25-30	0-10
	nYY	-	0.01-0.02	0-10
Hill thresholds concentration	xxx	-	0.4-0.5	50-500
	xYY	-	1-3	50-500
Transcription rate fold change	lXX	-	65-72	1-20
	lYY	-	0.02-0.04	1-20



**Figure 1.9** : The phase plots of 100 particles from the last population of the three Lu switches. (A) The bistable CS-LU (B) The bistable SP-LU and (C) The tristable DP-LU. We find two types of tristable behaviour, one where the third steady state is zero-zero and one where the third state is high (non-dead).



**Figure 1.10** : The three variants of the Lu models. (A) The CS-LU switch is bistable. The most restricted parameters for this behaviour are  $k_x$  and  $k_y$  which both have to be high relative to the prior while the net protein production for  $X$  and  $Y$  must be balanced. (B) The extended Lu model with a single positive autoregulation on  $X$ . This model is bistable when  $g_X$  is small, but the net production of protein is equal for the two nodes.(C) The Lu model with double positive autoregulation is tristable, and its posterior distribution shown here.

## 26 TOGGLE SWITCH STABILITY

We find that the switch with single positive autoregulation is capable of bistable behaviour as seen in Figure ??B, but this is only possible when the strength of the promoter under positive autoregulation,  $gx$ , is small (Figure 1.10). There appear to be no such constraints on the strength of the original, unmodified, promoter,  $gy$ .


Upon examination of the DP-LU model, we also find that tristability in the switch is relatively robust, as tristability is found across a large range of parameter values, with no parameters strongly constrained. Two types of tristable behaviour are identified, one where the third steady state is at  $(0,0)$  and one where the third steady state has non-zero values, as seen in Figure 1.9. This result agrees with previous work by Guantes & Poyatos (2008), who found that a switch can exhibit two kinds of tristability, one in which the third steady state is high ( $\text{III}_H$ ) and one in which it is low ( $\text{III}_L$ ) (Guantes & Poyatos 2008).

### 1.4.2.2 Multistability in the Lu models

The DP switch is capable of both bistable and tristable behaviour as well as 4 coexisting states under deterministic dynamics (Guantes & Poyatos 2008). It is of great interest to understand the conditions under which these three behaviours occur. Doing a bifurcation analysis of the DP switch can give us an indication of the stabilities this model is capable of, and at which parameter ranges these are found.

Since the Lu models can be solved analytically, we can obtain the bifurcation diagram of the DP-LU by keeping all parameters constant apart from gene expression ( $gx$ ). The result shown in Figure 1.11B, the system can exhibit 2, 3 or 4 steady states depending on the value of the gene expression rate. We observe that if  $100 \leq gx \leq 120$  the system exhibits four steady states, if  $9 \leq gx \leq 10$  the system is tristable and if  $10 \leq gx \leq 100$  the system is bistable. I use the whole range tested above ( $0 \leq gx \leq 140$ ) as prior distributions in Stability Finder and searched parameter space for 2, 3 and 4 steady states.

Using Stability Finder we obtain a more complex picture of the parameter space that can produce each behaviour. This is because, unlike the bifurcation analysis, Stability Finder does not require any of parameters to be fixed. Since there are no such restraints on the value each parameter can take we obtain a bigger range of parameters that can produce each behaviour than the ranges found during the bifurcation analysis. The priors used for each analysis are identical and include the whole range of values found in the bifurcation diagram, varying only the required number of steady states. In addition, unlike the bifurcation analysis the values for  $gx$  and  $gy$  are not forced to be equal in the analysis done on Stability Finder.



**Figure 1.11** : Design principles of multistable switches. (A) Using the Lu model with added positive autoregulation we uncover the design principles dictating if a switch will be bistable, tristable, or will have 4 steady states. (B-D) By considering the bivariate distributions of the parameters we can uncover the differences in the parameters of a bistable switch compared to a tristable switch, compared to a quadrastable switch . The posterior distribution of the bistable switch is shown in purple, of the tristable switch in pink and of a quadrastable in green. The bivariate distributions for which a difference is observed between teh stabilities are in black boxes. An example of a phase plot from each behaviour is shown next to the corresponding posterior distribution.


## 28 TOGGLE SWITCH STABILITY

Using StabilityFinder, we obtained posterior distributions for bistable, tristable and quadrable behaviours in the DP-LU model and then compared the posterior parameter distributions (Figure 1.11). Upon examination of the posterior distributions for all three switches we observe that a subset of the posterior parameter values is different under the three behaviours. We find differences in the univariate distribution of the parameters for gene expression,  $gx$ , as highlighted in Figure 1.11, box 1. This parameter must be small for a quadrable switch to occur but there are no such restraints for a bistable or a tristable switch. Furthermore, parameter  $xx$  must be small for three and four steady states to be achieved but there are no such restraints for a bistable switch, as can be seen in Figure 1.11, box 2.

We also find a difference in the bivariate distributions in the posterior. Most notably, we find that parameters  $xx$  and  $gX$  are tightly constrained in the tristable and the four steady state cases, where both parameters are required to be small, but less so in the bistable case (Figure 1.11, box 3). Another notable difference is between parameters  $xx$  and  $nXX$  shown in Figure 1.11, box 5, where they are constrained and in the tristable and four steady state cases but not the bistable case. Interestingly, we also find parameter correlations conserved between the three behaviours, as seen in Figure 1.11, box 4, where parameters  $lXX$  and  $gx$ , positive autoregulation and gene expression are negatively correlated in both cases. This highlights the importance of treating unknown parameters as distributions rather than fixed values when studying the parameter values of a model, as they are capable of uncovering not only the ranges and values needed but also the correlations between parameters that would not have otherwise been detected.

I further analyse these models by studying the phase plots resulting from simulating the particles from the posterior distribution to steady state. The phase plots from 100 particles from each posterior are shown in Figure 1.12. We find that there is a strong conservation on the locations of the steady states between each particle. This indicates that the steady states in a two-node toggle switch tend to be symmetrical. This gives rise to the patterns seen in Figure 1.12. This is especially evident in the quadrable switch. For every steady state at  $(0,0)$  there is another steady state on its diagonal, at  $XX = YY$ . All the combinations of these two steady states form the straight line seen in Figure 1.12C. This indicates that two of the four steady states exist where  $XX=YY$ . The other two exist where one of the two proteins dominates the other.

This same principle can be seen in the bistable and the tristable switches. In the bistable switch the two steady states are also symmetrical and one never completely



**Figure 1.12** : The phase plots from 100 particles from each posterior. Each particle is represented by a different shade of blue. We find a strong conservation on the location of the steady states between particles.


dominates the other. For the tristable case we observe that two of the steady states exist where the levels of one protein is much larger than the other, and a third steady state exists where  $XX = YY$ . We also observe that the third steady state is not necessarily a 'dead' state, but they can exist over a range of values for  $XX$  and  $YY$ .

### 1.4.2.3 Extending the Lu switch to three nodes

To further demonstrate the flexibility of Stability Finder I investigated a system capable of higher stabilities. Multistability is found in differentiating pathways, like the myeloid differentiation pathway (Ghaffarizadeh, Flann, & Podgorski 2014; Cinquin & Demongeot 2005). I allow for these more complex dynamics by extending the DP-LU model by adding another gene, making it a three gene switch. This new system is depicted in Figure 1.13A. This model has symmetric parameters, which means that the parameters for equivalent reactions (e.g. gene expression) are the same. In Stability Finder I look for six steady states, the output being in nodes X and Y and using the priors shown in Table 1.3. We successfully find that the system is capable of six steady states, as shown in Figure 1.13C.

**Table 1.3** Priors used in the three-node switch

Parameter	Symbol	Range
Production rate	gx	3-5
Degradation rate	kx	0-0.2
Hill coefficient	nxy	0-2
Hill thresholds concentration	xxy	140-160
Transcription rate fold change	lxy	0-0.2
Hill coefficient	nxx	2-4
Hill thresholds concentration	xxx	90-110
Transcription rate fold change	lxz	8-12




**Figure 1.13** : The three-node mutual repression model, with added positive auto-regulation on each node. (A) The model. The model is studied in two dimensions using Stability Finder, for nodes X and Y. (B) The phase plot of 100 particles from the posterior found by Stability Finder. There are 6 steady states. (C) The posterior distribution of the 6-steady state three-node system. Parameters  $k_x$  and  $n_{xy}$  are the most constrained.

We find that the most constrained parameters for this behaviour are again the degradation rate of the proteins,  $k_x$ . If they are too large or too small the system will not exhibit hexa-stability. Additionally we find that the Hill coefficients for the repressors,  $n_{xy}$ , are constrained to be smaller than 1.5 as seen in Figure 1.13D. This example demonstrates that Stability Finder can be used to elucidate the dynamics of more complex network architectures, which will be key to the successful design and construction of novel gene networks as synthetic biology advances.


Consistently with the results found in section 1.4.2.2, we find that the steady states are symmetric (Figure 1.13B). Each of six steady states exists in symmetry with another one, in tightly constrained regions.

### 1.4.3 Mass Action switches


In order to study the switch system in a more realistic way, I developed an extension to the switches used in Sections 1.4.1 and 1.4.2. This new set of switches does not use the quasi-steady state approximation (QSSA) that is often used in modelling the toggle switch. Using mass action, this changes the two-equation system used in Gardner, Cantor, & Collins (2000) and Lu, Onuchic, & Ben-Jacob (2014) into a system of 8 ODEs and 10 parameters in the classical switch case with no autoregulation (model CS-MA). The equations describing the system are shown below.




For the model with added double positive autoregulation (model DP-MA) the following equations are added to the system:



The ODEs describing the above switches are shown in Appendix (XXX). These models are too complex to be solved analytically and ideal for use in Stability Finder. Thus, I use Stability Finder and fit the models to a bistable behaviour. The two models used and the resulting phase plots are shown in Figure 1.14 and the posterior distributions obtained are shown in Figure 1.15.



**Figure 1.14** : The two mass action switches I developed. (A) The simple switch CS-MA (B) The switch with double positive autoregulation DP-MA. (C, D) The phase plots of 100 particles simulated from the posterior distributions of the bistable mass action switches.



**Figure 1.15** : The posterior distributions of the symmetric deterministic (A) CS-MA and (B) DP-MA switches. (C) Robustness comparison of the two models.

By examining the posterior distributions shown in Figure 1.15 we see that the CS-MA is much more constrained than the DP-MA switch. We find that gene expression must be low for bistability to occur in the CS-MA model but there is no such constraint in the DP-MA model. We also find that the monomerization rate  $dim\_r$  and the monomer degradation rate  $deg$  must both be larger than 2. This is not found in the DP-MA model.


Next I compare the two models for robustness using the ellipsoid method described in Section 1.3. We find that the addition of positive feedback loops greatly increases the system's robustness to parameter fluctuations as seen in Figure 1.15C. Adding positive feedback loops to the model allows it to be bistable over a greater range of parameter values. This indicates that small fluctuations in parameters in the cellular environment will not flip the switch and thus makes it more suitable for use in synthetic biological applications where spontaneous and undesired switching might be detrimental. This makes it a better candidate for building new synthetic devices based on the toggle switch design. We identified the parameter region within which these models are bistable, information that is important when building such a device in the lab.

The models used in the above analysis assume the parameters for equivalent reactions are equal. This is a constraint that simplifies the model. When building this model into a synthetic system in the lab, this assumption is not necessarily justified. When choosing promoters to build this synthetic system two promoters can be chosen to have similar strength but their strength will not necessarily be identical. In order to study how this might affect the results, I further eliminate modelling assumptions made in the toggle switch by making the parameters representing gene expression ( $ge$ ) and repression ( $rep$ ), as well as the protein degradation parameters asymmetric (independent parameters for each protein, versus fixed to be equal). We find that the features of the posterior distributions of the symmetric and the asymmetric models remain the same. The posterior distribution of the asymmetric CS-MA model was more constrained than the posterior distribution of the asymmetric DP-MA model.

We further study the asymmetric mass action models by examining the QSSA approximation. As stated above, the QSSA is a common analytical tool for model simplification. By examining the posterior distributions of the asymmetric CS-MA and DP-MA models we find that the QSSA does not necessarily hold for these models (Figure 1.16). That is, the systems function as switches even when the QSSA does not hold. These assumptions, necessary for the reduction of the model, are

### 36 TOGGLE SWITCH STABILITY

therefore not always justified in this case.



**Figure 1.16** : The QSSA that the dimerization reaction ( $\text{dim}$ ) is much faster than its reverse ( $\text{dim\_r}$ ) cannot be justified here. The median of the data (red) lies below the  $x=1$  line (black dashed line) which indicates that in the majority of the particles in the posterior  $\frac{\text{dim}}{\text{dim\_r}} < 1$

### 1.4.3.1 Multistability in the MA switches


To investigate how the level of abstraction affects switch design principles, I expand the analysis under the assumption of mass action kinetics and stochastic dynamics. The asymmetric CS-MA and DP-MA models are simulated using the Gillespie algorithm (Gillespie 1977).

Ma et al. (2012) found that the stochastic fluctuations in a system involving such a small number of molecules, like the toggle switch, uncovers effects that can not be predicted by the fully deterministic case (Ma et al. 2012). We find that in the stochastic case, both the simple switch, CS-MA, and positive autoregulation switch, DP-MA, are capable of both bistable and tristable behaviour. The fact that tristability can occur in the classical model is consistent with the effect of small molecule numbers; if gene expression remains low, it provides the opportunity for small number effects to be observed, and the third steady state to stabilise (Ma et al. 2012). In order to ensure that the tristable switches found in the stochastic case are truly tristable, I re-sample the posterior distributions and simulate to steady state. If the resulting phase plots are tristable then we know that the posterior truly represents tristability.

As can be seen in Figure 1.17, differences in the parameter values are observed between the bistable and tristable switches, in both CS-MA and DP-MA models. We find that the simple switch is tristable when dimerisation rate is low and bistable when it is high. The degradation of the dimer proteins must have a low rate for bistability but there are no restraints in the case of the tristable switch. For the case of the DP switch, we find that the rates for dimerisation, degradation and dimer degradation are different for the bistable and tristable behaviours (Figure 1.17). The rate of dimerisation must be low for tristability to occur and large for bistability, as observed for the simple switch. The parameter for protein degradation must be low for tristability whereas there are no constraints for the bistable case. Finally, the parameter for dimer degradation must be low for bistability whereas it has no constraints for tristability, as observed in the simple switch. The design principles for both the CS-MA model and the DP-MA model are summarised in Table 1.4

Table 1.4 Design principles of bistable and tristable switches

	CS-MA		DP-MA	
	Bistable	Tristable	Bistable	Tristable
dimerisation	High	Low	High	Low
protein degradation	-	-	-	Low
dimer degradation	Low	-	Low	-



**Figure 1.17** : Tristability is possible in the mass action toggle switch models only when simulated stochastically. (A) The simple toggle switch with no autoregulation can be both bistable and tristable. The two posteriors are shown, where the posterior distribution of the bistable switch is shown in red and of the tristable switch in blue. From the posterior distribution we can deduce the the dimerization parameter must be small for tristability to occur but large for bistability. The switch with double positive autoregulation and its posterior distributions for the bistable and tristable case are shown in (B). (C) A sample phase plot of a stochastic tristable and bistable mass action switch.

### 1.4.3.2 Robustness prior dependence

An important aspect of robustness that I must address is its dependence on the prior distributions. From Equation ?? we can expect that the measure for robustness will depend on the size of the prior.

I use the symmetric CS-MA model and Stability Finder to find the posterior distribution that makes this model bistable. This is repeated using the same model, but with larger prior ranges. The priors used are shown in Table 1.5. The posterior distributions are shown in Figure 1.18A and B. We find that for this model, if the prior ranges are very large, the robustness of the model will be much larger. If one of the parameters is able to have a larger value, then the constraints on the rest of the parameters are not necessary any more.

In order to test this observation, I test each parameter separately. All the priors are kept the same as the priors in the very narrow case (Figure 1.18A), except for one. Each run, one of the parameters has priors equal to the priors used in the wide case, Figure 1.18B. The priors are summarised in Table 1.5. Every time the robustness is calculated using the ellipsoid method. Since robustness is only meaningful when used in relation to another model, the robustness of the CS-MA model is compared to the robustness of the DP-MA model used in Figure 1.15. The same posterior distribution of the DP-MA model as used in Figure 1.15 are used every time. For the parameters this model shares with the CS-MA model I used the priors used in the narrow case in Table 1.5, for their shared parameters.


**Table 1.5** Priors used for studying the effect of priors to robustness

	Very narrow	Narrow	Wide
ge	5 - 10	1 - 10	1 - 100
rep	2 - 10	1 - 10	1 - 100
rep_r	0 - 5	1 - 10	0 - 10
dim	5 - 10	1 - 10	0 - 10
dim_r	0 - 5	0 - 5	0 - 10
deg	1 - 5	0 - 10	0 - 100
deg_dim	0 - 0.1	0 - 0.5	0 - 1

We can see from Figure 1.18C that when the priors for  $ge$  are much larger, the Bayes' factor increases significantly. This is due to the fact that when the rest of the parameters are constrained to being within a very narrow range, gene expression must be small for bistability to occur. This has the effect of lower robustness since the prior volume added to the system is much larger than the volume of the

functional region, thus greatly decreasing the robustness.


Robustness of the CS-MA model is increased when the priors for degradation and dimerisation have wider priors (Figure 1.18C). Therefore, if degradation and dimerisation can take larger values, the system becomes more robust.



**Figure 1.18 :** The volume of the priors has an effect on the posterior distribution obtained. (A) The CS-MA model with narrow priors and (B) the CS-MA with wide priors. (C) The increase in robustness seen is due to the gene expression parameter being able to be large.

In Section 1.4.3 we found that the DP-MA is more robust than the CS-MA model. Here I want to test whether this result still remains when the priors of the models are made wider. I change the prior ranges of both models and measure their robustness each time. The results are shown in Figure 1.19A. We find that the robustness measure changed significantly as the priors of the models changed. When both models have very narrow or when both models have wide priors then their robustness measures are very similar. When both models have vary narrow priors the Bayes' factor is equal to 1.32 and when the priors are wide the Bayes' factor is equal to 1.06. In both these cases there is no significant difference in robustness between the two models. When the priors for both models are narrow the Bayes' factor is equal to 2.25. Most notably, when the priors for the CS-MA model are very narrow and the priors of the DP-MA model are narrow, the Bayes' factor is at 9.14.

It is evident that the robustness measure depends on the prior volume. It is therefore useful to think of the Bayes' factor in terms of the difference in the volume of the priors of the models that are being compared. I carry out this analysis for the above priors and the results are shown in Figure 1.19B. Here we see that even though the prior difference is within the same order of magnitude, the Bayes' factor increases significantly. This point corresponds to the case where the priors of CS-MA are very narrow and the priors of DP-MA are narrow, and there is where we see the Bayes' factor between the two models maximise. We can take advantage of this observation to design a switch with double positive autoregulation that is significantly more robust than the Gardner toggle switch. By choosing the parameter values carefully we can maximise the gain of robustness that adding two positive feedback loops gives.



**Figure 1.19** : Changing the priors in both models affects the robustness measure. (A) Using different prior ranges for the CS-MA and the DP-MA models yields different robustness for each. (B) The Bayes' factor as a function of the prior volume difference.

## 1.5 Discussion

Here I developed a novel framework, Stability Finder, that can be used to infer parameter values that can produce a desired behaviour. The novelty in the framework I developed over existing methodology is that complex models can be analyzed assuming both deterministic and stochastic dynamics. I have used Stability Finder to uncover the design principles of a bistable, a tristable and a quadrable switch. I found key parameters that are important in determining the number of steady states a model is capable of. This is critical to the design of novel synthetic switches, where the stability of a system has to be well defined and predictable. A bistable, a tristable or a quadrable switch could each be used for different functions within a synthetic system. Being able to predetermine the stability a system is capable of is vital for the design of new systems. This is especially true when multiple such systems are used together, and the success of the whole system depends on all the parts working as expected.

Tools that can identify parameter regions that give rise to specific behaviours will be key for the success of synthetic biology. In the future, by selecting the system components accordingly, the parameter values can be adjusted *in vivo*. For example, the desired level of gene expression can be accomplished by selecting the appropriate RBS sequence (Salis, Mirsky, & Voigt 2009). Another method to modify the parameter values *in vivo* is to select the promoter to have the strength corresponding to the levels of gene expression and repression desired. Activity of each promoter can be measured and standardised (Kelly et al. 2009) making this process possible. For a system requiring more than one promoter, these can be efficiently selected from a promoter library using a genetic algorithm (Wu, Lee, & Chen 2011). These standardised interchangeable components with known sequence and activity (Kelly et al. 2009; Canton, Labno, & Endy 2008) can be selected and used to construct a desired system and replicate the parameter values found using Stability Finder.

The methodology used here can only be used to study the presence of a given stability and not its absence. If the algorithm is not converging it cannot be concluded that the given model is not capable of the desired stability under these priors. For example, the mass action switches were found to be both bistable and tristable when stochastic effects were taken into account. Using deterministic dynamics the algorithm did not converge using priors within the ranges used in this work. Nevertheless this does not permit the conclusion of absence of tristability in the deterministic classic or double positive mass action switches. The methodology

presented here only permits the interpretation of models that have converged to a given stability.s

The methodology presented here can also be used to study the topology of more complex multistable switches that exist in natural biological systems such as developmental pathways. I also limited this framework to the objective behaviour of a given number of stable steady states. This could be extended to examine systems with a given switching rate or systems robust to a particular set of perturbations, both of which could be of great importance for building more complex genetic circuits.

Importantly I find that the prior distributions used during such an analysis greatly affect the robustness observed. More generally, the assumptions made when building a model can have a significant effect on the predictions made. This is consistent with current understanding (Babtie, Kirk, & Stumpf 2014) and highlight the importance of a programme of experimental work, combined with systems modelling, in order to understand the rules of thumb for abstraction in model based design of synthetic biological systems.

## 1.6 Summary

In this chapter I discussed the algorithm I developed and demonstrated how it can identify the parameter regions necessary for a model to achieve a given number of stable steady states. I used it to uncover the underlying principles that govern the stability of a given switch.

I first tested Stability Finder on a known switch and then proceeded to apply it to more complex models. I uncovered the design principles that make the Lu switch bistable, tristable or quadrable. I extended the Lu models to a three-node switch and showed how it can achieve 6 steady states.

Furthermore, I built two novel models of the toggle switch which do not use the QSSA and showed that the QSSA cannot be justified in these models. Using these models I studied the effect positive autoregulation has on the robustness of a model. I also studied the effect the priors have on the posteriors and on the robustness of a model. Finally, using stochastic modelling I showed that these switch models are capable of both bistable and tristable behaviour.

In the next chapter I study the genetic toggle switch in the lab and fit the toggle switch models used here to experimental data.

# Bibliography

- Babtie, A. C., Kirk, P., & Stumpf, M. P. H. (2014). ‘Topological sensitivity analysis for systems biology.’ *Proceedings of the National Academy of Sciences of the United States of America* **111**(52), 18507–18512.
- Barnes, C. P., Silk, D., Sheng, X., & Stumpf, M. P. H. (2011). ‘Bayesian design of synthetic biological systems.’ *Proceedings of the National Academy of Sciences of the United States of America* **108**(37), 15190–15195.
- Canton, B., Labno, A., & Endy, D. (2008). ‘Refinement and standardization of synthetic biological parts and devices.’ *Nature Biotechnology* **26**(7), 787–793.
- Cinquin, O. & Demongeot, J. (2005). ‘High-dimensional switches and the modelling of cellular differentiation’. *Journal of Theoretical Biology* **233**(3), 391–411.
- Fukunaga, K. (2013). *Introduction to Statistical Pattern Recognition*. Academic Press.
- Gardner, T. S., Cantor, C. R., & Collins, J. J. (2000). ‘Construction of a genetic toggle switch in *Escherichia coli*’. *Nature* **403**(6767), 339–342.
- Ghaffarizadeh, A., Flann, N. S., & Podgorski, G. J. (2014). ‘Multistable switches and their role in cellular differentiation networks.’ *BMC Bioinformatics* **15 Suppl 7**, S7.
- Gillespie, D. T. (1977). ‘Exact Stochastic Simulation of Coupled Chemical-Reactions’. *Journal of Physical Chemistry* **81**(25), 2340–2361.
- Guantes, R. & Poyatos, J. F. (2008). ‘Multistable decision switches for flexible control of epigenetic differentiation.’ *PLoS Computational Biology* **4**(11), e1000235.
- Hafner, M., Koepll, H., Hasler, M., & Wagner, A. (2009). ‘‘Glocal’ Robustness Analysis and Model Discrimination for Circadian Oscillators’. *PLoS Computational Biology* **5**(10), e1000534.
- Kelly, J. R., Rubin, A. J., Davis, J. H., Ajo-Franklin, C. M., Cumbers, J., Czar, M. J., de Mora, K., Glieberman, A. L., Monie, D. D., & Endy, D. (2009). ‘Measuring the activity of BioBrick promoters using an in vivo reference standard.’ *Journal of Biological Engineering* **3**(1), 4–4.

- Liepe, J., Kirk, P., Filippi, S., Toni, T., Barnes, C. P., & Stumpf, M. P. H. (2014). ‘A framework for parameter estimation and model selection from experimental data in systems biology using approximate Bayesian computation.’ *Nature Protocols* 9(2), 439–456.
- Lloyd, S. P. (1982). ‘Least squares quantization in PCM’. *Information Theory*.
- Lu, M., Onuchic, J., & Ben-Jacob, E. (2014). ‘Construction of an Effective Landscape for Multistate Genetic Switches’. *Physical review letters* 113(7), 078102.
- Ma, R., Wang, J., Hou, Z., & Liu, H. (2012). ‘Small-number effects: a third stable state in a genetic bistable toggle switch’. *Physical review letters* 109(24), 248107.
- McKay, M. D., Beckman, R. J., & Conover, W. J. (2000). ‘A comparison of three methods for selecting values of input variables in the analysis of output from a computer code’. *Technometrics* 42(1), 55–61.
- Salis, H. M., Mirsky, E. A., & Voigt, C. A. (2009). ‘Automated design of synthetic ribosome binding sites to control protein expression’ *Nature Biotechnology* 27(10), 946–950.
- Tibshirani, R., Walther, G., & Hastie, T. (2001). ‘Estimating the number of clusters in a data set via the gap statistic’. *Journal of the Royal Statistical Society, Series B* 69(2), 465–475.
- Toni, T., Jovanovic, G., Huvet, M., Buck, M., & Stumpf, M. P. H. (2011). ‘From qualitative data to quantitative models: analysis of the phage shock protein stress response in Escherichia coli’ *BMC systems biology* 5, 69–69.
- Toni, T., Welch, D., Strelkowa, N., Ipsen, A., & Stumpf, M. P. H. (2009). ‘Approximate Bayesian computation scheme for parameter inference and model selection in dynamical systems’ *Journal of the Royal Society, Interface / the Royal Society* 6(31), 187–202.
- Woods, M., Leon, M., Perez-Carrasco, R., & Barnes, C. P. (2015). ‘A statistical approach reveals designs for the most robust stochastic gene oscillators’ *bioRxiv*, 025056.
- Wu, C.-H., Lee, H.-C., & Chen, B.-S. (2011). ‘Robust synthetic gene network design via library-based search method’. *Bioinformatics (Oxford, England)* 27(19), 2700–2706.