

VIM QUICK REFERENCE CARD

:viusageShow a summary of all commands

Movements

h l k jcharacter left, right; line up, down
b w word/token left, right
ge eend of word/token left, right
{ }beginning of previous, next paragraph
() beginning of previous, next sentence
O ^ \$ beginning, first, last character of line
nG ngg line *n*, default the last, first
n|column *n* of current line
% ... match of next brace, bracket, comment, **#define**
- +line up, down on first non-blank character
B W space-separated word left, right
gE E end of space-separated word left, right
gO gmbeginning, middle of *screen* line
g^ g\$ first, last character of *screen* line
fC Fcnext, previous occurrence of character *c*
tC Tc before next, previous occurrence of *c*

Insertion & Replace → insert mode

i ainsert before, after cursor
I Ainsert at beginning, end of line
gIinsert text in first column
o O open a new line below, above the current line
rcreplace character under cursor with *c*
grclike **r**, but without affecting layout
Rreplace characters starting at the cursor
gRlike **R**, but without affecting layout
cmchange text of movement command *m*
cc or S change current line
C change to the end of line

Deletion

x Xdelete character under, before cursor
dmdelete text of movement command *m*
dd Ddelete current line, to the end of line
J gJjoin current line with next, without space
:rd delete range *r* lines
:rdxdelete range *r* lines into register *x*

Insert Mode

^Vc ^Vninsert char *c* literally, decimal value *n*
^Vn insert decimal value of character
^Ainsert previously inserted text
^@ same as ^A and stop insert → command mode
^Rx ^R^Rxinsert content of register *x*, literally
^N ^P text completion before, after cursor
^Wdelete word before cursor
^Udelete all inserted character in current line
^D ^T shift left, right one shift width
^Kc₁c₂ or c₁←c₂ enter digraph {*c*₁, *c*₂}
^Ocexecute *c* in temporary command mode
^X^E ^X^Y scroll up, down
<esc> or ^[..... abandon edition → command mode

Search & Substitution

/s← ?s←search forward, backward for *s*
/s/o← ?s?o←search fwd, bwd for *s* with offset *o*
n or /←repeat forward last search
N or ?←repeat backward last search
* ..search backward, forward for word under cursor
g# g* same, but also find partial matches
gd gD ..local, global definition of symbol under cursor
:rs/f/t/x substitute *f* by *t* in range *r*
[*x* : g—all occurrences, c—confirm changes
:rs *x*repeat substitution with new *r* & *x*

Formatting/Filtering

m is movement; leave out for visual mode commands
gqmformat *m* (*formatprg*)
gqgq or gqipformat current paragraph
= *m*reindent movement *m* (*equalprg*)
:rce *w*center lines in range *r* to width *w*
:rle *i*left align lines in range *r* with indent *i*
:rri *w*right align lines in range *r* to width *w*
!mc← .filter lines of movement *m* through command *c*
n!lc← filter *n* lines through command *c*
:r!cfilter range *r* lines through command *c*
~switch case and advance cursor
g~m gum gUm ... switch case, lc, uc on movement *m*
<*m* >*m* shift left, right text of movement *m*
n<< n>>shift *n* lines left, right
^A ^X increment/decrement number under cursor

Visual Mode & Text Objects

v V ^V highlight characters, lines, block
o exchange cursor pos with start of highlighting
gvstart highlighting on previous visual area
aw as apselect a word, a sentence, a paragraph
ab aB a] a>select a block (), { }, [] < >
atselect an html tag
a" a' a'select a quoted string
iw is ip ib iB i] i> it i" i' i' ..select “inner”
n> n< =indent/unindent *n* levels, reindent

Undoing, Repeating & Registers

u Uundo last command, restore last changed line
. ^R repeat last changes, redo last undo
n.repeat last changes with count replaced by *n*
qc qC .. record, append typed characters in register *c*
qstop recording
@cexecute the content of register *c*
@@repeat previous @ command
:@cexecute register *c* as an *Ex* command

Copying (Yanking)

"*x* use register *x* for next delete, yank, put
:reg [*x*] show content registers/*x* reg
ymyank the text of movement command *m*
yy or Yyank current line into register
p Pput register after, before cursor position
]p [plike p, P with indent adjusted
gp gPlike p, P leaving cursor after new text

Patterns (differences to Perl) :help pattern

\< \> start, end of word
\i \k \I \K an identifier, keyword; excl. digits
\f \p \F \P . a file name, printable char.; excl. digits
\e \t \r \b<esc>, <tab>, <←>, <←>
\= * \+ ... match 0..1, 0..∞, 1..∞ of preceding atoms
\{*n*,*m*> match *n* to *m* occurrences
\{-> non-greedy match
\|separate two branches (≡ or)
\(\)group patterns into an atom
\& \1the whole matched pattern, 1st () group
\u \lupper, lowercase character
\c \C ignore, match case on next pattern
\%x match hex character

```

\@= \@! ..... (?=pattern) (!pattern)
\@<= \@<! ..... (?<=pattern) (?<!pattern)
\@> ..... (?>pattern)
\_^ \_$. start-of-line/end-of-line, anywhere in pattern
\_. ..... any single char, including end-of-line
\zs \ze ..... set start/end of pattern
\%^ \%$ ..... match start/end of file
\%V ..... match inside visual area
\'m ..... match with position of mark m
%\(\) ..... unnamed grouping
\[ ] ..... collection with end-of-line included
\[ ] ..... sequence of optionally matched atoms
\v ..... very magic: patterns almost like perl

```

Spell Checking

```

:set spell spellang=de_20 .... activate spellcheck
]s ..... next misspelled word
zg zG ..... add good word (to internal word list)
zw zW ..... mark bad word (to internal word list)
z= ..... suggest corrections

```

Marks, Motions, and Tags

```

mc ..... mark current position with mark  $c \in [a..Z]$ 
'c 'C ..... go to mark  $c$  in current,  $C$  in any file
'' '" ..... go to position before jump, at last edit
'[ ] ..... go to start, end of previously operated text
:marks ..... print the active marks list
:jumps ..... print the jump list
n^0 ..... go to  $n^{th}$  older position in jump list
n^I ..... go to  $n^{th}$  newer position in jump list
^T .. jump to the tag under cursor, return from tag
:ts t ..... list matching tags and select one for jump
:tj t ... jump to tag or select one if multiple matches
gf ..... open file which filename is under cursor
:tags ..... print tag list

```

Multiple Files / Buffers (\leftrightarrow)

```

:tab ball ..... show buffer tablist
:buffers ..... show list of buffers
:buffer n ..... switch to buffer n
:badd f.txt ..... load file into new buffer
:bdelete n ..... delete buffer n (also with filename)
:bnext :bprev :bfirst :blast ... buffer movement

```

Scrolling & Multi-Windowing

```

^D ^U ^F ^B ..... scroll half / full page page down, up
zt zz zb ... current line to top, center, bottom of win
:[v]split ^Ws ^Wv ..... split window (horiz., vert.)
:vert help ..... open help vertically
^Wf ^W] ..... open file, tag in split
:[v]new ^Wn ..... new empty window (horiz., vert.)
:on ^Wo ..... make current win the only one
^Wj ^Wk ^Wh ^Wl ... move down, up, left, right to win
^WJ ^WK ^WH ^WL ..... move win down, up, left, right
^Wn+ ^Wn- ..... increase/decrease win size by  $n$  lines
^Wn > ^Wn < ..... increase/decrease window width
^Wn_ ^Wn| ..... set height/width (max if no  $n$ )
^W= ..... Make win size equal
^Wr ^Wx ..... Rotate, exchange windows
^Wc ..... close window

```

Misc Ex Commands (\leftrightarrow) :help holy-grail

```

:e f ..... edit file  $f$ , reload current file if no  $f$ 
:r w f ..... write range  $r$  to file  $f$  (current file if no  $f$ )
:r w>>f ..... append range  $r$  to file  $f$ 
:r g[!]/p/cmd .. ex  $cmd$  on range  $r$  [not] matching  $p$ 
:q :q! .. quit and confirm, quit and discard changes
:wq or :x or ZZ ..... write to current file and exit
:r f ..... insert content of file  $f$  below cursor
:r! c ..... insert output of command  $c$  below cursor
:rc a :rm a ..... copy, move range  $r$  below line  $a$ 

```

Ex Ranges

```

, ; ..... separates two lines numbers, set to first line
n ..... an absolute line number  $n$ 
. $ ..... the current line, the last line in file
% * ..... entire file, visual area
't ..... position of mark  $t$ 
/p/ ?p? ..... the next, previous line where  $p$  matches
+n -n ..... + $n$ ,  $-n$  to the preceding line number

```

Completion

```

^X^L ..... whole lines
^X^N ^X^I .. keywords in current file, plus included files
^X^K ^X^N ..... keywords in dictionary, thesaurus
^X^] ^X^F ^X^D ..... tags, filenames, defs/macros
^X^V ..... vim command line
^X^U ^X^O ..... user defined, omni- completion

```

Folding

```

:set fdm=indent ..... indent-foldmethod
zfm ..... create fold of movement  $m$ 
:rfo ..... create fold for range  $r$ 
zd zE ..... delete fold at cursor, all in window
zo zc zO zC ..... open, close one fold; recursively
[z ]z ..... move to start, end of current open fold
zj zk ..... move down, up to start, end of next fold
zm zM ..... fold more, close all folds
zr zR ..... fold less, open all folds
zn zN zi ..... fold non, fold normal, invert folding
:set foldcolumn=4 ..... show foldcolumn

```

Compiling

```

:compiler c ..... set/show compiler plugins
:make ..... run makeprg, jump to first error
:cope ..... navigate errors from make
:cn :cp ..... display the next, previous error
:cl :cf ..... list all errors, read errors from file

```

Miscellaneous

```

:sh :!c ..... start shell, execute command  $c$  in shell
K ..... run keywordprg (man) on word under cursor
^L ..... redraw screen
^G ... show cursor column, line, and character position
:set cuc ..... show cursor column visually
ga ..... show ASCII value of character under cursor
:mkview [f] :loadview [f] .. save/load configuration
:set ff=dos ..... convert file to dos eol format
:e ++ff=unix ..... reopen file in unix eol format
:write ++enc=utf-8 ..... Write file in utf-8
:set hlsearch ..... highlight searches
:rhardcopy > file.ps ..... print range to ps file
:set list ..... show listchar characters (tabs etc.)

```