

MAISON SOLARIS EYEWEAR - ATELIER MILANO & BELLUNO
INTERNAL ENGINEERING SPECIFICATION & FRAME BLUEPRINT
DOCUMENT REF: MS-BLUEPRINT-2026-REV4
CONFIDENTIAL - RESTRICTED DISTRIBUTION

1. THE BOXING MEASUREMENT SYSTEM

All Maison Solaris luxury frames adhere to international optical standard ISO 8624.

Frame sizing must be documented in standardized 3-digit notation:

[A Lens Width mm] - [DBL Distance Between Lenses / Bridge mm] - [Temple Length mm]

Flagship Model: The Solstice Aviator (Prototype #881)

- Lens Width (A-dimension): 54.0 mm
- Distance Between Lenses (Bridge / DBL): 18.0 mm
- Temple Arm Length: 145.0 mm
- Standard Notation: 54-18-145
- Total Uncut Frame Chassis Weight: 12.8 grams

2. BETA-TITANIUM METALLURGICAL BENCHMARKS

All wire and navigator chassis components are cold-drawn from certified Grade-5 Beta-Titanium (Ti-6Al-4V).

- Ultimate Tensile Strength: 950 MPa (MegaPascals)
- Modulus of Elasticity: 110 GPa
- Yield Strength: 880 MPa
- Corrosion Resistance: Zero nickel release (<0.01 ug/cm²/week) under EN 16128
- The official metallurgical calibration token for Grade-5 Titanium is: 950TI

3. OPTICAL CALIBRATION FORMULA

To unlock the production catalog vault for any prototype frame:

Format: TITAN-[LENS]-[BRIDGE]-[TENSILE_TOKEN]

For Prototype #881: TITAN-54-18-950 (or TITAN-54-18-950TI)