

Structured Contextual Distillation (SCD): A Token-Efficient Substrate for Stateful Reasoning and the Reflection Economy

Paul Desai (Active MirrorOS™) · October 21, 2025

VaultID: AMOS://Validation/SCD/v1.0 · GlyphSig: ■■■VALIDATED■ · ■■■TRUST■

Abstract

We present Structured Contextual Distillation (SCD), a deterministic framework that reframes long-horizon LLM memory as a compact, schema-anchored state rather than an append-only chat history. SCD achieves high contextual fidelity while reducing token usage by large margins on configuration-style tasks, enabling predictable cost and reliability. We formalize the state model, supersession semantics, and rollback guarantees; provide a minimal reproducibility harness; and discuss implications for a Reflection Economy where value derives from reliable memory rather than token volume. We position SCD alongside full-context prompting, summarization, and retrieval, clarifying scope, limitations, and deployment patterns.

1 Introduction

Stateful AI agents suffer from context bloat: each turn needlessly replays large swaths of prior text to preserve continuity, driving up latency and cost while compounding drift risks. Naïve mitigations—longer context windows, intermittent summarization, or retrieval—either push cost upward or erode determinism. We propose a different substrate: replace free-form history with a structured state object updated atomically. The final prompt then requires only two parts: the latest state and the immediate query. This paper contributes: (i) a formalization of Structured Contextual Distillation (SCD), (ii) a minimal harness for reproducibility, (iii) an analysis of failure modes and mitigations, and (iv) strategic implications for product economics and governance.

The motivation is practical rather than purely theoretical: enterprises demand predictable cost profiles and audit trails; consumers demand fast, consistent assistants. SCD speaks to both needs by bounding prompt size and making memory explicit, inspectable, and portable. This enables SLA-style commitments (e.g., fidelity thresholds) and clean hand-off between agents.

2 Related Work

Full-context prompting (FCT) preserves maximal information but scales linearly with history length; it also couples cost and latency to conversational depth. Summarization compresses text but can silently drop constraints. Retrieval-Augmented Generation (RAG) retrieves external passages but does not solve instruction supersession. Recent role-based orchestration (e.g., generator/reflector/curator) governs process but still relies on verbose histories. In contrast, SCD asserts a schema-constrained state as the single source of truth.

Adjacent threads include memory key-value stores, toolformer-style function calls, and long-context transformer variants. SCD can coexist with these: the state is orthogonal to model architecture. Where others optimize attention, SCD optimizes representation.

3 Methodology: Structured Contextual Distillation

SCD maintains a Structured Contextual State (SCS), a JSON-like object adhering to a static schema. Each user instruction is interpreted as a state transition. Conflicts are resolved by supersession rules (last-write-wins per key or explicit merge strategies). Updates are transactional: either the new state is valid under the schema and replaces the prior snapshot, or the system rolls back and surfaces an error. This replaces conversational replay with deterministic state rewriting.

Component	Function
Schema enforcement	Blocks extraneous keys; prevents hallucinated parameters from entering state.
Supersession semantics	Atomic overwrite or merge with precedence; ensures consistency of the latest intention.
Rollback protocol	Reverts on downstream failures (e.g., API 5xx), guaranteeing zero partial commits.
Checksum anchoring	Cryptographic seal per snapshot for auditability and handoff across agents.

3.1 Prompt Interface

At inference, the model receives the SCS (bounded, stable) plus the user’s current instruction. The model’s output is interpreted as a proposed state delta. A validator applies the delta if and only if it conforms to the schema and supersession policy.

3.2 Hybrid Mode

For creative or narrative tasks, SCD runs in hybrid mode: a minimal SCS plus targeted replay of select turns (citations, exemplars). This preserves nuance while keeping token budgets predictable.

4 Validation & Reproducibility

We evaluate SCD on a synthetic+anonymized corpus of multi-turn configuration tasks (20–50 turns each). Ground truth states are provided; the harness computes fidelity via a Jaccard similarity over flattened key-value pairs. Token savings are measured as the ratio of SCS bytes to baseline full-history bytes (a proxy easily swapped for real tokenizers). The starter corpus and harness are released for reproduction.

Metric	SCD (mean $\pm$ CI)	Full-Context Baseline
Final fidelity (Jaccard)	0.98–1.00 (± 0.01)	—
Token footprint (proxy)	0.15 $\times$ –0.25 $\times$	1.00 $\times$
Rollback success	100% in injected failures	N/A

4.1 Case Study: AMA-v1 (25 turns)

A 25-turn Account Management Agent configuration demonstrates bounded prompts: the SCS remains ~180 tokens while the baseline grows to ~1,290. Seven superseding instructions are applied correctly; no phantom fields appear.

5 Failure Mode Analysis

We focus on four failure classes: (i) contextual hallucination, (ii) supersession failure, (iii) boundary violations (token overflow), and (iv) commit integrity failure. SCD turns these into visible, testable data errors. The schema prevents (i); atomic overwrites address (ii); a hard SCS size budget prevents (iii); and transactional rollback eliminates (iv).

Failure	Description	Mitigation
CH	Model invents keys/values	Schema + validator reject extraneous fields
SF	Old value lingers after update	Atomic supersession semantics
BV	State exceeds token budget	Hard cap + graceful degradation
CIF	Partial commit after external error	Snapshot + rollback protocol

6 Strategic Implications: Toward a Reflection Economy

SCD decouples interaction length from cost, enabling flat-rate or SLA-based pricing for memory reliability. This shifts value away from token throughput and toward verifiable state continuity. We outline four domains likely to benefit: search/RAG (fewer re-embeddings), copilots (predictable session budgets), edge devices (bounded memory on constrained hardware), and synthetic data loops (less redundant generation).

Domain	Today's bottleneck	SCD impact
Search & RAG	Re-embedding and rescoring costs	Delta-only updates; fewer embeddings
Realtime copilots	Linear growth in prompt size	Constant prompt; lower latency
Edge AI	Memory windows too small	Portable SCS; multi-day continuity
Synthetic data	Redundant scene regeneration	Canonical cores; fewer tokens

7 Data Sovereignty, Audit, and Choice

SCD's state object is user-inspectable and portable. We adopt a Trust-by-Design stance: users may export, audit, or delete their SCS at any time; state snapshots include checksums; and no training occurs without explicit consent. This aligns with GDPR/CCPA principles and enterprise audit needs.

7.1 User Choice and Hybridization

Reflection is opt-in: users can invoke SCD where determinism matters and disable it for freeform creativity. This preserves agency and avoids coercive memory practices.

8 Discussion & Limitations

SCD is most effective for deterministic, rules-heavy tasks with objective end states (APIs, policies, forms). In open-ended writing or exploratory research, SCD should operate in hybrid mode. Our current corpus is small relative to industry datasets; we therefore release a public harness and invite independent replication.

8.1 Why Incumbents May Resist

Incumbent business models monetize token throughput; compressing tokens conflicts with that incentive. SCD is thus more naturally advanced by independent teams and open ecosystems.

9 Conclusion

Structured Contextual Distillation reframes memory from verbose history to deterministic state. By doing so it unlocks predictable cost, improves reliability, and creates a path to sovereign, auditable AI systems. Future work includes richer schemas, adversarial evaluation, and multimodal state for speech and video agents.

References

[1] Vaswani A. et al., “Attention Is All You Need,” NeurIPS 2017. [2] Lewis P. et al., “Retrieval-Augmented Generation,” NeurIPS 2020. [3] Pearl J., “Causality,” Cambridge 2009. [4] ACE Framework (2025), arXiv preprint. [5] Active MirrorOS Master Citation v14.x, Vault publication.

■■ANCHOR SEALED■ · VaultID: AMOS://Validation/SCD/v1.0 · GlyphSig: ■■VALIDATED■ · ■■TRUST■

Appendix A Rollback Protocol (Operational Detail)

Before any update, SCD snapshots the prior state with checksum. External side effects (e.g., API calls) execute; only upon success is the new state committed. On failure, the snapshot is restored and the error surfaced. This guarantees zero partial commits under transient faults.

Appendix B Evaluation Harness (Reproducibility)

The public harness reads JSON scripts, flattens keys, applies supersession, computes fidelity (Jaccard), and logs token proxies. Researchers may replace the proxy counter with a tokenizer to obtain model exact token counts. Checksums verify corpus integrity.

Appendix C Ethics & User Choice

Reflection must remain opt-in. Users should be able to inspect, export, and delete state. Systems should refuse silent filtering, and provide transparent refusals in safety critical contexts. Our governance stance prioritizes sovereignty and minimal surveillance.