

Sp25-bcs-062

Mirza Awais Raza

SQL*Plus: Release 21.0.0.0.0 - Production on Wed Feb 25 13:10:14 2026

Version 21.3.0.0.0

Copyright (c) 1982, 2021, Oracle. All rights reserved.

Enter user-name: system

Enter password:

Last Successful login time: Sun Feb 22 2026 00:03:53 +05:00

Connected to:

Oracle Database 21c Express Edition Release 21.0.0.0.0 - Production

Version 21.3.0.0.0

```
SQL> connect hr/hr @localhost:1521/xepdb1;
```

Connected.

```
SQL> select table_name from user_tables;
```

TABLE_NAME

REGIONS

COUNTRIES

LOCATIONS

DEPARTMENTS

JOBS

EMPLOYEES

JOB_HISTORY

7 rows selected.

Describe Employees:

SQL> desc employees;

Name	Null?	Type

EMPLOYEE_ID	NOT NULL	NUMBER(6)
FIRST_NAME		VARCHAR2(20)
LAST_NAME	NOT NULL	VARCHAR2(25)
EMAIL	NOT NULL	VARCHAR2(25)
PHONE_NUMBER		VARCHAR2(20)
HIRE_DATE	NOT NULL	DATE
JOB_ID	NOT NULL	VARCHAR2(10)
SALARY		NUMBER(8,2)
COMMISSION_PCT		NUMBER(2,2)
MANAGER_ID		NUMBER(6)
DEPARTMENT_ID		NUMBER(4)

Employee2 table Creation:

SQL> create table Employees2(Id Number(2) primary key,Firstname varchar(20),Lastname varchar(20),salary INT,Deptid Number(2));

Table created.

Describe Employees2:

SQL> desc Employees2

Name	Null?	Type

ID	NOT NULL	NUMBER(2)
FIRSTNAME		VARCHAR2(20)
LASTNAME		VARCHAR2(20)
SALARY		NUMBER(38)
DEPTID		NUMBER(2)

Insert Values Into Employees2:

SQL> Insert into Employees2 Values(1,'Ali','Raza',200000,20);

1 row created.

Display all the data of employees2:

SQL> select * from employees2;

ID	FIRSTNAME	LASTNAME	SALARY	DEPTID

1	Ali	Raza	200000	20

Modify the domain of the FirstName column:

SQL> alter table employees2 modify(Firstname varchar(50));

Table altered.

Drop Employee2:

SQL> drop table employees2;

Table dropped.

Describe Department:

SQL> desc departments;

Name	Null?	Type

DEPARTMENT_ID		NOT NULL NUMBER(4)
DEPARTMENT_NAME		NOT NULL VARCHAR2(30)
MANAGER_ID		NUMBER(6)
LOCATION_ID		NUMBER(4)

Create Dept2:

SQL> create table DEPT2(departmentid varchar(10) PRIMARY KEY,departmentname
varchar(10) NOT NULL);

Table created.

Describe Dept2:

SQL> desc DEPT2;

Name	Null?	Type

DEPARTMENTID		NOT NULL VARCHAR2(10)
DEPARTMENTNAME		NOT NULL VARCHAR2(10)

*

Create Employee2 With foreign Key:

```
SQL> create table Employees2(Id Number(2) primary key,Firstname varchar(20),Lastname
varchar(20),salary INT,departmentid varchar(10) references DEPT2(departmentid));
```

Table created.

Describe Dept2:

```
SQL> desc DEPT2;
```

Name	Null?	Type

DEPARTMENTID	NOT NULL	VARCHAR2(10)
DEPARTMENTNAME	NOT NULL	VARCHAR2(10)

Describe Employees2:

```
SQL> DESC EMPLOYEES2;
```

Name	Null?	Type

ID	NOT NULL	NUMBER(2)
FIRSTNAME		VARCHAR2(20)
LASTNAME		VARCHAR2(20)
SALARY		NUMBER(38)
DEPARTMENTID		VARCHAR2(10)

Insert Values in Dept2:

```
SQL> INSERT INTO DEPT2 VALUES ('ABC123','CS');
```

1 row created.

Insert Values into Employees:

```
SQL> INSERT INTO EMPLOYEES2 VALUES(1,'ALI','RAZA',20000,'ABC123');
```

1 row created.

Display all the from Dept2:

SQL> SELECT * FROM DEPT2;

DEPARTMENT DEPARTMENT

ABC123 CS

Display all the data from employees2:

SQL> SELECT * FROM EMPLOYEES2;

ID FIRSTNAME LASTNAME SALARY DEPARTMENT

1 ALI RAZA 20000 ABC123

Modify Domain of FirstName :

SQL> alter table employees2 modify(Firstname varchar(50));

Table altered.

Describe employees2 again to check domain updated or not:

SQL> desc Employees2

Name Null? Type

ID NOT NULL NUMBER(2)

FIRSTNAME VARCHAR2(50)

LASTNAME	VARCHAR2(20)
SALARY	NUMBER(38)
DEPARTMENTID	VARCHAR2(10)

Drop Employees2:

```
SQL> DROP TABLE EMPLOYEES2;
```

Table dropped.

```
SQL> DROP TABLE DEPT2;
```

Table dropped.