


Bypassing Security Filters

The other and more common type of HTTP Verb Tampering vulnerability is caused by **Insecure Coding** errors made during the development of the web application, which lead to web application not covering all HTTP methods in certain functionalities. This is commonly found in security filters that detect malicious requests. For example, if a security filter was being used to detect injection vulnerabilities and only checked for injections in **POST** parameters (e.g. `$_POST['parameter']`), it may be possible to bypass it by simply changing the request method to **GET**.

Identify


In the **File Manager** web application, if we try to create a new file name with special characters in its name (e.g. `test;`), we get the following message:




This message shows that the web application uses certain filters on the back-end to identify injection attempts and then blocks any malicious requests. No matter what we try, the web application properly blocks our requests and is secured against injection attempts. However, we may try an HTTP Verb Tampering attack to see if we can bypass the security filter altogether.

Exploit

To try and exploit this vulnerability, let's intercept the request in Burp Suite (Burp) and then use **Change Request Method** to change it to another method:



This time, we did not get the **Malicious Request Denied!** message, and our file was successfully created:



To confirm whether we bypassed the security filter, we need to attempt exploiting the vulnerability the filter is protecting: a Command Injection vulnerability, in this case. So, we can inject a command that creates two files and then check whether both files were created. To do so, we will use the following file name in our attack (`file1; touch file2;`):

[📄 Cheat Sheet](#)[? Go to Questions](#)

Table of Contents

[Introduction to Web Attacks](#) ✓

HTTP Verb Tampering

[Intro to HTTP Verb Tampering](#) ✓[🛡️ Bypassing Basic Authentication](#) ✓[🛡️ Bypassing Security Filters](#) ✓[Verb Tampering Prevention](#) ✓

Insecure Direct Object References (IDOR)

[Intro to IDOR](#) ✓[Identifying IDORs](#) ✓[🛡️ Mass IDOR Enumeration](#) ✓[🛡️ Bypassing Encoded References](#) ✓[🛡️ IDOR in Insecure APIs](#) ✓[🛡️ Chaining IDOR Vulnerabilities](#) ✓[IDOR Prevention](#) ✓

XML External Entity (XXE) Injection

[Intro to XXE](#) ✓[🛡️ Local File Disclosure](#) ✓[🛡️ Advanced File Disclosure](#) ✓[🛡️ Blind Data Exfiltration](#) ✓[XXE Prevention](#) ✓

Skills Assessment

[🛡️ Web Attacks - Skills Assessment](#) ✓

My Workstation


OFFLINE

[🔌 Start Instance](#)


🟢 / 1 spawns left





Then, we can once again change the request method to a **GET** request:




Once we send our request, we see that this time both **file1** and **file2** were created:



This shows that we successfully bypassed the filter through an HTTP Verb Tampering vulnerability and achieved command injection. Without the HTTP Verb Tampering vulnerability, the web application may have been secure against Command Injection attacks, and this vulnerability allowed us to bypass the filters in place altogether.



Waiting to start...



Questions

[Cheat Sheet](#)

Answer the question(s) below to complete this Section and earn cubes!

Target(s): [Click here to spawn the target system!](#)

+ 1 🟩 To get the flag, try to bypass the command injection filter through HTTP Verb Tampering, while using the following filename: file; cp /flag.txt ./

HTB{b3_v3rb_c0n51573n7}

[Submit](#)[Hint](#)[← Previous](#)[Next →](#)[Mark Complete & Next](#)

Powered by HACKTHEBOX

