

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 04/21/2013

Reviewed on 04/21/2013

www.greenchemindustries.com

1 Product and Company Identification

- · Product identifier
- · Trade name: N-Butanol (N-Butyl Alcohol)
- · Article number: GrnChm NButylA
- · CAS Number:

71-36-3

· EC number:

200-751-6

· Index number:

603-004-00-6

- · Relevant identified uses of the substance or mixture and uses advised against
- · Product description Synonyms: n-butyl alcohol, butyl alcohol, propyl carbinol
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GreenChem

222 Clematis St, Suite 207 West Palm Beach, FL 33401

Office: (561) 659-2236 Fax: (561) 659-2237

· Emergency telephone number: Chemtrec 800-424-9300

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

H226 Flammable liquid and vapour.



GHS05 Corrosion

H318 Causes serious eye damage.



GHS07

H302 Harmful if swallowed.H315 Causes skin irritation.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS05 GHS07

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 04/21/2013 Reviewed on 04/21/2013

Trade name: N-Butanol (N-Butyl Alcohol)

(Contd. of page 1)

- · Signal word Danger
- · Hazard-determining components of labeling:

butanol

· Hazard statements

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.H315 Causes skin irritation.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.


· Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

· NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 3

REACTIVITY | Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

71-36-3 butanol

- · Identification number(s)
- · EC number: 200-751-6
- · Index number: 603-004-00-6

(Contd. on page 3)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 04/21/2013 Reviewed on 04/21/2013

Trade name: N-Butanol (N-Butyl Alcohol)

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

(Contd. on page 4)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 04/21/2013 Reviewed on 04/21/2013

Trade name: N-Butanol (N-Butyl Alcohol)

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

71-36-3 butanol

PEL 300 mg/m³, 100 ppm

REL Short-term value: C 150 mg/m³, C 50 ppm

Skin

TLV 61 mg/m³, 20 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eves and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 04/21/2013 Reviewed on 04/21/2013

Trade name: N-Butanol (N-Butyl Alcohol)

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid Colorless

Odor: Alcohol-like

Odour threshold: Not determined.

• pH-value at 20 °C (68 °F): 7

· Change in condition

Melting point/Melting range:
Boiling point/Boiling range:-89 °C (-128 °F)⋅ Flash point:116 °C (241 °F)⋅ Flammability (solid, gaseous):Not applicable.

Ignition temperature: 340 °C (644 °F)
 Decomposition temperature: Not determined.
 Auto igniting: Not determined.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

· Explosion limits:

Lower: 1.5 Vol % **Upper:** 9.4 Vol %

· Vapor pressure at 20 °C (68 °F): 6.7 hPa (5 mm Hg)

• **Density at 20 °C (68 °F):** 0.81 g/cm³ (6.759 lbs/gal)

Relative density
Vapour density
Evaporation rate
Not determined.
Not determined.
Not determined.

· Solubility in / Miscibility with

Water at 20 °C (68 °F): 77 g/l

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:Not determined.Kinematic:Not determined.Organic solvents:100.0 %

VOC content: 100.0 %

• Other information No further relevant information available.

(Contd. on page 6)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 04/21/2013 Reviewed on 04/21/2013

Trade name: N-Butanol (N-Butyl Alcohol)

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
71-36-3 butanol			
Oral	LD50	790 mg/kg (rat)	
Dermal	LD50	3400 mg/kg (rabbit)	
Inhalative	LC50/4 h	8000 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 7)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 04/21/2013 Reviewed on 04/21/2013

Trade name: N-Butanol (N-Butyl Alcohol)

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number

DOT, ADR, IMDG, IATA
UN proper shipping name
DOT, IMDG, IATA
ADR
UN1120
None
BUTANOLS
1120 BUTANOLS

· Transport hazard class(es)

· DOT



Class
 3 Flammable liquids.

· Label 3

· ADR, IMDG, IATA



Class
 3 Flammable liquids

· Label 3

· Packing group

· DOT, ADR, IMDG, IATA

· Environmental hazards:

· Marine pollutant: No

Special precautions for user
 Warning: Flammable liquids

Danger code (Kemler): 30EMS Number: F-E,S-D

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": UN1120, BUTANOLS, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

Substance is not listed.

(Contd. on page 8)

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 04/21/2013 Reviewed on 04/21/2013

Trade name: N-Butanol (N-Butyl Alcohol)

(Contd. of page 7)

Section 313 (Specific toxic chemical listings):
Substance is listed.

TSCA (Toxic Substances Control Act):
Substance is listed.

Proposition 65
Chemicals known to cause cancer:
Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

· Carcinogenic categories

• EPA (Environmental Protection Agency)
71-36-3 | butanol

D

· TLV (Threshold Limit Value established by ACGIH)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

· GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

butanol

· Hazard statements

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.H315 Causes skin irritation.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

OSHA Hazard Communication Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 04/21/2013 Reviewed on 04/21/2013

Trade name: N-Butanol (N-Butyl Alcohol)

(Contd. of page 8)

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent