

Safety Data Sheet

LOCTITE 542

Page 1 of **11**

SDS No.: 168433

V002.6

Revision: 25.09.2018 printing date: 28.09.2019

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE 542

Other means of identification: LOCTITE 542 BO 50ML EGFD

Product code: IDH234422

Recommended use of the chemical and restrictions on use

Intended use: Anaerobic Sealant

Identification of manufacturer, importer or distributor

Importer: Henkel Adhesive Technologies Vietnam Co., Ltd, No. 7, Road 9A Bien Hoa II Industrial Zone, Bien Hoa City,

Dong Nai Province, Vietnam Phone: +84 251 3835 461 Fax: +84 251 3835 463

E-mail address of person responsible for Safety Data

Sheet:

ap-ua-psra.sea@henkel.com

Emergency information: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call

CHEMTREC: +1 703-741-5970

Section 2. Hazards identification

GHS Classification:

Hazard Class Hazard Category Target organ

Serious eye damage/eye irritation Specific target organ toxicity -

single exposure

Category 2 Category 3

respiratory tract irritation

Chronic hazards to the aquatic

environment

ne aquatic Category 3

GHS label elements:

Hazard pictogram:



Signal word:

Warning

SDS No.: 168433 Page 2 of 11

V002.6 LOCTITE 542

Hazard statement: H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precaution:

Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P273 Avoid release to the environment. P280 Wear eye protection/face protection.

Response: P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product characteristics at time of

disposal.

SDS No.: 168433 Page 3 of 11

LOCTITE 542 V002.6

Section 3. Composition / information on ingredients

Substance or Mixture: Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Cumene hydroperoxide	1- 10 %	Flammable liquids 4
80-15-9		H227
		Organic peroxides E H242
		Acute toxicity 4; Ingestion H302
		Acute toxicity 3; Inhalation - dust and mist H331
		Acute toxicity 4; Dermal
		Skin corrosion/irritation 1B H314
		Specific target organ toxicity - repeated exposure 2 H373
		Acute hazards to the aquatic environment 2 H401
		Chronic hazards to the aquatic environment 2 H411
N,N-Diethyl-p-toluidine 613-48-9	0.1- 1 %	Acute toxicity 3; Ingestion H301
		Acute toxicity 3; Inhalation - dust and mist H331
		Acute toxicity 3; Dermal H311
		Specific target organ toxicity - repeated exposure 2 H373
		Acute hazards to the aquatic environment 3 H402
		Chronic hazards to the aquatic environment 3 H412
N,N-dimethyl-o-toluidine 609-72-3	0.1- 1 %	Acute toxicity 3; Ingestion H301
		Acute toxicity 3; Inhalation - dust and mist H331
		Acute toxicity 3; Dermal H311
		Specific target organ toxicity - repeated exposure 2 H373
		Acute hazards to the aquatic environment 3 H402
		Chronic hazards to the aquatic environment 3 H412
Methyl methacrylate 80-62-6	0.1- 1 %	Flammable liquids 2 H225
		Acute toxicity 5; Inhalation H333
		Skin corrosion/irritation 2 H315
		Skin Sensitization 1 H317
		Target Organ Systemic Toxicant - Single exposure 3 H335
		Acute hazards to the aquatic environment 3 H402
1,4-Naphthalenedione	< 0.1 %	Acute toxicity 3; Ingestion
130-15-4		H301 Acute toxicity 1; Inhalation - dust and mist H330
		Skin corrosion/irritation 2; Dermal H315
		Serious eye damage/eye irritation 2A H319
		Skin Sensitization 1; Dermal H317

SDS No.: 168433 Page 4 of 11

V002.6 LOCTITE 542

Target Organ Systemic Toxicant - Single exposure 3;
Inhalation - dust and mist
H335
Acute hazards to the aquatic environment 1
H400
Chronic hazards to the aquatic environment 1
H410

Section 4. First aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if

necessary.

Ingestion: Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Indication of immediate medical attention and special treatment

needed:

See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

Specific hazards arising from the

chemical:

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

Special protection equipment and precautions for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Section 6. Accidental release measures

Personal precautions: Avoid skin and eye contact.

Ensure adequate ventilation. See advice in section 8

Environmental precautions: Do not let product enter drains.

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Page 5 of 11 SDS No.: 168433 LOCTITE 542

V002.6

Handling: Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Storage: Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to

containers as contamination may reduce the shelf life of the bulk product.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

METHYL METHACRYLATE 80-62-6	Value type	Time Weighted Average (TWA):
00 02 0	ppm	50
İ	Remarks	ACGIH
METHYL METHACRYLATE 80-62-6	Value type	Time weighted average (TWA):
j	mg/m ³	50
	Remarks	VN OEL
METHYL METHACRYLATE 80-62-6	Value type	Short Term Exposure Limit (STEL):
İ	ppm	100
	Remarks	ACGIH
METHYL METHACRYLATE 80-62-6	Value type	Short-term exposure limit (STEL):
İ	mg/m ³	150
	Remarks	VN OEL

Respiratory protection: Use only in well-ventilated areas.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if

the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection: Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection

index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; \geq 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6,

corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the

gloves should be replaced.

Eye protection: Wear protective glasses.

Protective eye equipment should conform to EN166.

Body protection: Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for

dusts.

Ensure good ventilation/extraction. **Engineering controls:**

Hygienic measures: Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while

working. Good industrial hygiene practices should be observed.

SDS No.: 168433 Page 6 of 11

V002.6 LOCTITE 542

Section 9. Physical and chemical properties

Appearance: brown liquid

Odor: characteristic
Odor threshold (CA): No data available.

pH: 3 - 6

Melting point / freezing point: No data available.

Specific gravity: 1.08

Boiling point: > 149 °C (> 300.2 °F) **Flash point:** > 100 °C (> 212 °F) **Evaporation rate:** Not available.

Flammability (solid, gas):

Lower explosive limit:

Upper explosive limit:

Vapor pressure:

No data available.

No data available.

Va data available.

(no method; 50 °C (122 °F))

Vapor density:Not available.Density:1.08 g/cm3Solubility:No data available.Partition coefficient: n-No data available.

octanol/water:

Auto ignition:No data available.Decomposition temperature:No data available.Viscosity:No data available.

VOC content: < 5 %

(2010/75/EC)

Section 10. Stability and reactivity

Reactivity/Incompatible Reaction with strong acids. **materials:** Reacts with strong oxidants.

Conditions to avoid: Stable under recommended storage conditions.

Hazardous decomposition Irritating organic vapours. **products:** Oxides of carbon.

Sulphur oxides nitrogen oxides

Section 11. Toxicological information

Oral toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg

Method: Calculation method

Inhalative toxicity: Acute toxicity estimate (ATE) : > 20 mg/l

Exposure time: 4 h Test atmosphere: Vapor. Method: Calculation method

Dermal toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg

Method: Calculation method

SDS No.: 168433 Page 7 of 11 LOCTITE 542

V002.6

Health Effects:

Ingestion:

May cause gastrointestinal tract irritation if swallowed.

Skin: Prolonged contact with skin, particularly damaged skin, may cause sensitization or dermatitis in

sensitive individuals.

Eyes: Causes serious eye irritation. Inhalation: May cause respiratory irritation.

Prolonged or repeated contact may cause skin irritation. Symptoms of Overexposure:

Acute oral toxicity:

Cumene hydroperoxide	Value type	LD50
80-15-9	Value	550 mg/kg
	Species	rat
	Method	not specified
Methyl methacrylate	Value type	LD50
80-62-6	Value	9,400 mg/kg
	Species	rat
	Method	not specified
1,4-Naphthalenedione	Value type	LD50
130-15-4	Value	190 mg/kg
	Species	rat
	Method	not specified

Acute inhalative toxicity:

Methyl methacrylate	Value type	LC50
80-62-6	Value	29.8 mg/l
	Exposure time	4 h
	Species	rat
	Method	not specified

Acute dermal toxicity:

Cumene hydroperoxide	Value type	LD50
80-15-9	Value	1,200 - 1,520 mg/kg
	Species	
	Method	not specified
Methyl methacrylate	Value type	LD50
80-62-6	Value	> 5,000 mg/kg
	Species	rabbit
	Method	not specified

Skin corrosion/irritation:

Cumene hydroperoxide	Result	corrosive
80-15-9	Exposure time	
	Species	rabbit
	Method	Draize Test

Respiratory or skin sensitization:

Methyl methacrylate	Result	sensitising
80-62-6	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Page 8 of 11 SDS No.: 168433 **LOCTITE 542**

V002.6

Germ cell mutagenicity:

Cumene hydroperoxide	Result	positive
80-15-9	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide	Result	negative
80-15-9	Type of study / Route of administration	dermal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified
Methyl methacrylate	Result	negative
80-62-6	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	not specified

Repeated dose toxicity:

Cumene hydroperoxide	Result	
80-15-9	Route of application	inhalation: aerosol
	Exposure time / Frequency of treatment	6 h/d5 d/w
	Species	rat
	Method	not specified
Methyl methacrylate	Result	LOAEL=2000 ppm
80-62-6	Route of application	inhalation
	Exposure time / Frequency of treatment	14 weeks6 hrs/day, 5 days/wk
	Species	mouse
	Method	Dose Range Finding Study
Methyl methacrylate	Result	NOAEL=1000 ppm
80-62-6	Route of application	inhalation
	Exposure time / Frequency of treatment	14 weeks6 hrs/day, 5 days/wk
	Species	mouse
	Method	Dose Range Finding Study

Section 12. Ecological information

General ecological information: Cured Loctite products are typical polymers and do not pose any immediate

environmental hazards.

Ecotoxicity: Harmful to aquatic life with long lasting effects., Do not empty into drains / surface

water / ground water.

Toxicity:

Cumene hydroperoxide	Value type	LC50
80-15-9	Value	3.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide	Value type	EC50
80-15-9	Value	18 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide	Value type	ErC50
80-15-9	Value	3.1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide	Value type	EC10
80-15-9	Value	70 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min

SDS No.: 168433 V002.6 LOCTITE 542

	Species	
	Method	not specified
N,N-dimethyl-o-toluidine	Value type	LC 50
609-72-3	Value	46 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Fathead minnow (Pimephales promelas)
	Method	
Methyl methacrylate	Value type	LC50
80-62-6	Value	350 mg/l
	Acute Toxicity Study	Fish
	Exposure time	
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methyl methacrylate	Value type	EC50
80-62-6	Value	69 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methyl methacrylate	Value type	EC50
80-62-6	Value	170 mg/l
	Acute Toxicity Study	Algae
	Exposure time	4 d
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	4 d
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methyl methacrylate	Value type	EC0
80-62-6	Value	100 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	
	Method	not specified
1,4-Naphthalenedione	Value type	EC50
130-15-4	Value	0.011 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Dunaliella bioculata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)

Persistence and degradability:

Cumene hydroperoxide	Result	
80-15-9	Route of application	no data
	Degradability	0 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Methyl methacrylate	Result	readily biodegradable
80-62-6	Route of application	aerobic
	Degradability	95 %
	Method	EU Method C.4-B (Determination of the "Ready" BiodegradabilityModified
		OECD Screening Test)
1,4-Naphthalenedione	Result	
130-15-4	Route of application	no data
	Degradability	0 - 60 %
	Method	OECD 301 A - F

${\bf Bioaccumulative\ potential\ /\ Mobility\ in\ soil:}$

Cumene hydroperoxide	Bioconcentration factor (BCF)	9.1
80-15-9	Exposure time	
	Species	calculation
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)

SDS No.: 168433 Page 10 of 11

V002.6 LOCTITE 542

Cumene hydroperoxide	LogPow	2.16
80-15-9	Temperature	
	Method	not specified
Methyl methacrylate	LogPow	1.38
80-62-6	Temperature	
	Method	not specified
1,4-Naphthalenedione 130-15-4	LogPow	1.71
	Temperature	
	Method	not specified

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in

which it is used

Packaging

Disposal of uncleaned packages: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Section 14. Transport information

Road transport ADR:

Not dangerous goods

Railroad transport RID:

Not dangerous goods

Inland water transport ADN:

Not dangerous goods

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

Regulatory Information: This Safety Data Sheet has been generated based on Circular No 32/2017/TT-BCT, December 28,

2017 (Regulations On The Classification And Labeling Of Chemicals) only.

Global inventory status:

Regulatory list	Notification
TSCA	yes
NDSL	yes
ENCS (JP)	yes
KECI (KR)	yes
IECSC	yes
ISHL (JP)	yes

SDS No.: 168433 Page 11 of 11

V002.6 LOCTITE 542

Section 16. Other information

Disclaimer:

This Safety Data Sheet has been generated based on Circular No 32/2017/TT-BCT, December 28, 2017 (Regulations On The Classification And Labeling Of Chemicals) only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance. This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.