


Where to See Poecile: Understanding Swiss Willow Tit Occupancy

Misha Tseitlin

24 March 2024

Project 3: Occupancy Modelling



University of
St Andrews

School of Mathematics and Statistics

in partial fulfilment of the requirements for
MT5751: Estimating Animal Abundance and Biodiversity

Executive Summary

Willow tits (*Poecile montanus*) etc etc.

Introduction

Willow tits are a well-studied resident Eurasian breeding bird species seeing substantial population declines in some areas like Britain and Finland.^{1,2} Divided into several subspecies, Swiss alpine (*montanus*) and willow (*rhenanus* and *salicarius*) tits have experienced fewer pressures and maintained their population better than their international compatriots. Even so, alpine tits have proven especially resilient in contrast to more vulnerable willow tits, possibly caused by interspecific and intraspecific competition, changing vegetation onset, and rising temperatures.^{3,4} Some environmental drivers are particularly clear: whether via its species name *montanus* or its French common name (la mésange boréale), we have long known about the bird’s dependence on mountainous, forested habitats. Averse to competition, the species shows strong density-dependence and preference for forest edge habitats and thus particularly responds to land use changes.⁵ Using occupancy modelling, we unpack specific drivers of willow tit occupancy and detectability, provide habitat management recommendations, and predict national-level as well as some quadrant-specific occurrence.

Methods

The Swiss programme MHB (Monitoring Häufige Brutvögel) annually surveys 267 squares nationwide to understand bird populations: we use a pre-processed subset of 237 quadrants with detected willow tits across three survey occasions (two for high-altitude quadrants) and various possible factors including elevation, forest cover, survey duration, survey route length, and survey day.⁶ Data quality may be imperfect—MHB documentation lists surveys as running from mid-April to mid-July, but our “day” measure allegedly starts at the start of the year which suggests surveying outside the breeding season from January to April.³ (Table 1) For analysis, we z-score elevation, convert forest cover to a proportion, and assume that survey day measures the date from 1 April rather than 1 January. As we lack spatial quadrant locations, we forgo initial exploration of detected willow tit distribution and skip directly to occupancy.

Hierarchical occupancy modelling provides the best method of separating out tit detectability p from occupancy ψ ; we need to determine which of our observations stemmed from observer patterns versus the true underlying state process. The resulting two-tier model looks across i quadrants and j survey occasions to estimate p and ψ using a logistic relationship $\ln(\frac{x}{1-x})$ for probabilities:

$$\begin{aligned} \text{logit}(\psi_i) = & \beta_0 + \beta_1 \text{Elevation}_i + \beta_2 \text{Elevation}_i^2 + \beta_3 \text{Forest}_i + \beta_4 \text{Forest}_i^2 \\ & + \beta_5 \text{Forest}_i \text{Elevation}_i^2 + \beta_6 \text{Forest}_i^2 \text{Elevation}_i^2 \end{aligned}$$

$$\text{logit}(p_{ij}) = \alpha_0 + \alpha_1 \text{Day}_{ij} + \alpha_2 \text{Duration}_{ij} + \alpha_3 \text{Forest}_{ij} + \alpha_4 \text{Forest}_{ij} \text{Day}_{ij}$$

Though detection and state functions look complex at first glance, they more-so demonstrate the difficult of fitting highly non-linear relationships using a linear (GLM) framework. As exploratory analysis showed clear non-linearities in forest cover and elevation, and we manually explored model fits followed by `dredge` in R to evaluate all models containing relevant covariates using various information criteria.^{7,8,aikake_new_1974?} Showing all possibilities would be excessive, but adding non-linear terms substantially improves model fit as evaluated by AIC. (Table 2)

Table 1: Data Summary Statistics Split by First Occasion Detection

Variable	Overall, N = 237	Undetected, N = 170	Detected, N = 67
Occasion 2 Detected, # (%)	61 (26%)	9 (5.4%)	52 (78%)
Occasion 3 Detected, # (%)	54 (28%)	7 (5.2%)	47 (80%)
Occasion 1 Duration (min)			
Mean (SD)	229 (62)	214 (57)	266 (58)
[Min, Max]	[95, 390]	[95, 390]	[120, 390]
Occasion 2 Duration (min)			
Mean (SD)	232 (63)	217 (59)	270 (57)
[Min, Max]	[90, 391]	[90, 391]	[120, 375]
Occasion 3 Duration (min)			
Mean (SD)	232 (66)	217 (64)	265 (56)
[Min, Max]	[85, 406]	[85, 406]	[110, 360]
Length (km)			
Mean (SD)	5.10 (1.35)	5.15 (1.46)	4.99 (1.04)
[Min, Max]	[1.20, 9.40]	[1.20, 9.40]	[2.90, 8.50]
Day of Occasion 1			
Mean (SD)	38 (21)	35 (21)	45 (19)
[Min, Max]	[13, 91]	[13, 91]	[13, 87]
Day of Occasion 2			
Mean (SD)	57 (19)	55 (19)	63 (17)
[Min, Max]	[29, 102]	[29, 102]	[37, 97]
Day of Occasion 3			
Mean (SD)	69 (13)	66 (11)	75 (14)
[Min, Max]	[42, 107]	[42, 101]	[47, 107]
Forest Cover (%)			
Mean (SD)	35 (28)	30 (28)	47 (23)
[Min, Max]	[0, 98]	[0, 98]	[2, 95]
Elevation (m)			
Mean (SD)	1,183 (646)	1,047 (665)	1,526 (442)
[Min, Max]	[250, 2,750]	[250, 2,750]	[380, 2,310]

Results

Binning data results spawned near-identical outcomes to original analysis with less data and thus precluded robust goodness-of-fit testing (Figure 1).

Discussion

Despite multiple adjustments, we remain concerned about perfect detectability and other DS assumptions. Alternatives like passive monitoring (e.g., using cameras or hydrophones) could improve future surveys. As whales also continually move—behaviourally demonstrating observer avoidance—animals are certainly undetected at their initial locations.

Table 2: Fitted Model Comparisons

Detection	Occupancy	AIC
p(day + dur + forest + forest*day + elev)	psi(elev + elev ² *(forest + forest ²))	382.4294
p(day + dur + forest + forest*day)	psi(elev + elev ² *(forest + forest ²))	391.1644
p(day + dur + forest + forest ²)	psi(elev + elev ² + forest + forest ²)	392.1461
p(day + dur + forest + forest*day)	psi(elev)	392.6263
p(day + dur + forest + forest*day)	psi((elev + elev ²)*(forest + forest ²))	394.7457
p(day + dur + forest)	psi(elev + elev ² + forest + forest ²)	400.9895
p(day + dur + forest)	psi(elev + forest)	405.8298
p(.)	psi(.)	528.9870

Note. Models include survey day, survey duration, forest cover, and elevation as well as their squared and interaction terms. Interaction terms imply including base terms (e.g., elev*forest includes elev and forest).




Figure 1: Spatial trends of elevation, forest cover, and estimated occupancy across Switzerland.

Code Appendix

```
library(statsecol)
library(unmarked)
library(tidyverse)
library(MuMIn)
library(AICcmodavg)
library(viridisLite)
library(latex2exp)
# read in data
data(willow)
# prepare the data how I need it
willowNum <- willow %>% mutate(forestsq = forest^2,
                             iLength = 1/length) %>%
  mutate_all(as.numeric) %>%
  rownames_to_column("id")

willowSum <- willowNum %>% mutate(forestP = forest*100,
                                elevR = 1182.574 + elev*646.333,
                                y.1 = as.factor(y.1),
                                y.2 = as.factor(y.2),
                                y.3 = as.factor(y.3)) %>%
  select(-c("id", "elev", "elevsq", "forest", "forestsq", "iLength"))

# brief data visualisation
hist(willowNum$forest)
hist(willowNum$elev)
hist(willowNum$length)
# no clear relationship here, except that there's no forest at very high-elevation areas
ggplot(willowNum, aes(x = forest, y = elev)) + geom_point()
# no occurrence at lower elevations, higher occurrence at higher elevations
# no real shifts between time periods
ggplot(willowNum, aes(x = elev, fill = y.1)) + geom_histogram() + facet_wrap(~y.1) + theme(
ggplot(willowNum, aes(x = elev, fill = y.2)) + geom_histogram() + facet_wrap(~y.2) + theme(
ggplot(willowNum, aes(x = elev, fill = y.3)) + geom_histogram() + facet_wrap(~y.3) + theme(
# complex forest relationship w/ no occurrence at predominantly low forest cover and an inv
# no shifts between time periods again
ggplot(willowNum, aes(x = forest, fill = y.1)) + geom_histogram() + facet_wrap(~y.1) + theme(
ggplot(willowNum, aes(x = forest, fill = y.2)) + geom_histogram() + facet_wrap(~y.2) + theme(
ggplot(willowNum, aes(x = forest, fill = y.3)) + geom_histogram() + facet_wrap(~y.3) + theme(

willowUnm <- unmarkedFrameOccu(
  y = willowNum[,c("y.1", "y.2", "y.3")],
  # we are interested in breeding bird occupancy for the WHOLE breeding season, so days (wh
  siteCovs = data.frame(elev = willowNum$elev,
                        elev2 = willowNum$elevsq,
                        forest = willowNum$forest,
                        forest2 = willowNum$forestsq,
                        iLength = willowNum$iLength),
```

```

obsCovs = list(day = willowNum[,c("day1", "day2", "day3")],
              dur = willowNum[,c("dur1", "dur2", "dur3")],
              intensity = willowNum[,c("intensity1", "intensity2", "intensity3")],
              length = willowNum[,c("length", "length", "length")],
              iLength = willowNum[,c("iLength", "iLength", "iLength")],
              forest = willowNum[,c("forest", "forest", "forest")],
              forest2 = willowNum[,c("forestsq", "forestsq", "forestsq")],
              elev = willowNum[,c("elev", "elev", "elev")],
              elev2 = willowNum[,c("elevsq", "elevsq", "elevsq")])
)
summary(willowUnm)

# some more plotting
hist(willowUnm@obsCovs$day)
hist(willowUnm@obsCovs$dur)
hist(willowUnm@obsCovs$intensity)

# null model
m0 <- occu(~1 ~1, data = willowUnm)

# full model
# intensity:length interaction is just dur and thus not included
mfull <- occu(formula = ~day + dur + intensity + length + day*dur + dur*intensity + day*length +
              ~elev + elev2 + forest + forest2 + elev*forest + elev2*forest2 + elev*forest2
              data = willowUnm) #the data object

summary(mfull)

# all three agree on a few things
# elev2 and elev:forest are mutually exclusive
# p(day) is not worth including
# all p interaction terms are useless
mDredgeB <- dredge(mfull, rank = "BIC")
mDredgeA <- dredge(mfull, rank = "AIC")
mDredgeAc <- dredge(mfull, rank = "AICc")

mBIC <- occu(formula = ~dur # p formula
              ~elev + forest + forest^2 + elev*forest, #psi formula
              data = willowUnm) #the data object
summary(mBIC)

# we missed a few variables, mainly forests which could affect visibility by surveyors (even
mfullAct <- occu(formula = ~day + dur + intensity + length + day*dur + dur*intensity + day*length +
              ~elev + elev2 + forest + forest2 + elev*forest + elev2*forest2 + elev*forest2
              data = willowUnm) #the data object

summary(mfullAct)

# all three agree on a few things
# elev2 and elev:forest are mutually exclusive

```

```

# p(day) is not worth including
# all p interaction terms are useless
mDredgeB2 <- dredge(mfullAct, rank = "BIC")
mDredgeA2 <- dredge(mfullAct, rank = "AIC")
mDredgeAc2 <- dredge(mfullAct, rank = "AICc")

# create some representative models to display
mAlt <- occu(formula = ~day + dur + forest # p formula
             ~elev + forest, #psi formula
             data = willowUnm) #the data object

mAlt1 <- occu(formula = ~day + dur + forest # p formula
             ~elev + elev2 + forest + forest2, #psi formula
             data = willowUnm) #the data object

mAlt2 <- occu(formula = ~day + dur + forest + forest2 # p formula
             ~elev + elev2 + forest + forest2, #psi formula
             data = willowUnm) #the data object

mOptm_Alt <- occu(formula = ~day + dur + forest + forest*day # p formula
                 ~elev, #psi formula
                 data = willowUnm) #the data object

# recording visibility/leafing may be a good way to increase separability and avoid forest
mOptm <- occu(formula = ~day + dur + forest + forest*day # p formula
             ~elev + elev2 + forest + forest2 + elev2*forest + elev2*forest2 , #psi formula
             data = willowUnm) #the data object

mAlt3 <- occu(formula = ~day + dur + forest + forest*day # p formula
             ~elev + elev2 + forest + forest2 + elev*forest + elev*forest2 + elev2*forest + elev2*forest2 , #psi formula
             data = willowUnm) #the data object

#this is by far the best model, but elevation in the detection function is probably too much
mOverpred <- occu(formula = ~day + dur + forest + forest*day + elev # p formula
                 ~elev + elev2 + forest + forest2 + elev2*forest + elev2*forest2 , #psi formula
                 data = willowUnm) #the data object

# combine some representative models for displaying
fl <- fitList(
  "p(.)"                psi(.)"
  "p(day + dur + forest)" psi(elev + forest)"
  "p(day + dur + forest)" psi(elev + elev^2 + forest + forest^2)"
  "p(day + dur + forest + forest^2)" psi(elev + elev^2 + forest + forest^2)"
  "p(day + dur + forest + forest*day)" psi(elev)"
  "p(day + dur + forest + forest*day)" psi(elev + elev^2*(forest + forest^2))"
  "p(day + dur + forest + forest*day)" psi((elev + elev^2)*(forest + forest^2))"
  "p(day + dur + forest + forest*day + elev)" psi((elev + elev^2)*(forest + forest^2))"

# model output table to format
ms <- modSel(fl)

```



```

# full model summary
summary(mOptm)
# state model
mOptm@estimates@estimates$state
# detection model
mOptm@estimates@estimates$det

# test for VIF?
# so much structural collinearity that this probably doesn't matter
vif(mOptm, type = "state")
vif(mOptm, type = "det")

# GOF for best model....it's barely passable
# code below is parallelised, be careful all ye who lack 10 free cores
gof.boot <- mb.gof.test(mOptm, nsim = 1000, ncores = 10)
# save this and re-use output out of pity for my computer
write_rds(gof.boot, file = "gofBootstrap.rds")
# p-values generally vary between 0.4 and 0.9, but the difference to c-hat is negligible
# 10000 cores confirms a p-value around 0.7 but the plot is too ugly so this is not it
# gof.boot <- mb.gof.test(mOptm, nsim = 10000, ncores = 10)

# repeat for the overfit model
# fit is so temptingly good...but it just doesn't make sense
gof.boot.test <- mb.gof.test(mOverpred, nsim = 10000, ncores = 10)
write_rds(gof.boot.test, file = "gofBootstrapOverfit.rds")

# read in the saved for analysis
gof.boot <- read_rds("gofBootstrap.rds")
# even so, our model is very much closer to the tail of the chi^2 distribution and we're qu
ggplot() +
  geom_histogram(data = data.frame(t.star = gof.boot$t.star),
                 aes(x=t.star), color="black", fill="#fde725", alpha = 0.3, binwidth = 1) +
  geom_vline(aes(xintercept = gof.boot$chi.square), linewidth = 0.8, color = "#440154") +
  xlab("Pearson Chi-square statistic") +
  ylab("Count") +
  theme_bw() +
  ggtitle(bquote("Bootstrapped"~chi^2~fit statistic (1000 samples, p =~.(gof.boot$p.valu)

data(Switzerland)
gelev <- ggplot(data = Switzerland, aes(x=x, y=y,fill=elevation)) +
  geom_raster() +
  scale_fill_viridis_c(direction = 1,
                       option = "B") +
  theme_bw() +
  theme(axis.text = element_blank(),
        axis.line = element_blank(),
        axis.ticks = element_blank(),
        panel.grid = element_blank(),
        panel.border = element_blank(),

```



```

    legend.position = "bottom") +
  labs(x = "",
       y = "",
       fill = "Elevation (m)") +
  guides(fill = guide_colorbar(# draw border around the legend
                              frame.colour = "black",
                              barwidth = 10)) +

  coord_fixed()
gfor <- ggplot(data = Switzerland, aes(x=x, y=y, fill=forest)) +
  geom_raster() +
  scale_fill_viridis_c(direction = 1,
                      option = "D") +

  theme_bw() +
  theme(axis.text = element_blank(),
        axis.line = element_blank(),
        axis.ticks = element_blank(),
        panel.grid = element_blank(),
        panel.border = element_blank(),
        legend.position="bottom") +
  labs(x = "",
       y = "",
       fill = "Forest (%)") +
  guides(fill = guide_colorbar(# draw border around the legend
                              frame.colour = "black",
                              barwidth = 10)) +
  coord_fixed()

for_pred <- data.frame(elev = (Switzerland$elevation - 1182.574)/646.333,      # convert or
                      elev2 = ((Switzerland$elevation - 1182.574)/646.333)^2, # convert or
                      forest = Switzerland$forest/100,                    #want prop not %
                      forest2 = Switzerland$forest/100,                  #want prop not %
                      X = Switzerland$x,                                  #keep the coordinates
                      Y = Switzerland$y)                                  #keep the coordinates
cowplot::plot_grid(gelev,gfor,nrow=2)

willowPredSDM <- modavgPred(list(mOptm), # top model
                           newdata = for_pred, #spatially indexed data frame
                           parm.type = "psi", #predict from state model
                           c.hat = gof.boot$c.hat.est) #inflate SEs using Royle & Kery met
#add data to predictions manually
willow_sdm <- for_pred %>% mutate(Predicted = willowPredSDM$mod.avg.pred,
                                SE = willowPredSDM$uncond.se,
                                lower = willowPredSDM$lower.CL,
                                upper = willowPredSDM$upper.CL)

gpredM_1 <- ggplot(data = willow_sdm, aes(x=X, y=Y, fill=Predicted)) +
  geom_raster() +
  scale_fill_viridis_c(direction = 1,
                      option = "H") +

  # add actual observations if we have x,y data
  # geom_point(data = willowNum, aes(x=X, y=Y)) +

```

```

theme_bw() +
theme(axis.text = element_blank(),
      axis.line = element_blank(),
      axis.ticks = element_blank(),
      panel.grid = element_blank(),
      panel.border = element_blank(),
      legend.position="bottom") +
labs(x = "",
     y = "",
     fill = TeX(r'(Estimated  $\psi$ )')) +
guides(fill = guide_colorbar(# draw border around the legend
  frame.colour = "black",
  barwidth = 10)) +
coord_fixed()

gpredE <- ggplot(data = willow_sdm, aes(x=X, y=Y,fill=SE)) +
  geom_raster() +
  scale_fill_viridis_c(direction = 1,
    option = "H") +

  theme_bw() +
  theme(axis.text = element_blank(),
        axis.line = element_blank(),
        axis.ticks = element_blank(),
        panel.grid = element_blank(),
        panel.border = element_blank(),
        legend.position="bottom") +
  labs(x = "",
       y = "",
       fill = TeX(r'(Estimated  $\psi$  Error)')) +
  guides(fill = guide_colorbar(# draw border around the legend
    frame.colour = "black",
    barwidth = 10)) +
  coord_fixed()

cowplot::plot_grid(gelev,gfor,gpredM_1,gpredE,nrow=2)

gpredL <- ggplot(data = willow_sdm, aes(x=X, y=Y,fill=lower)) +
  geom_raster() +
  scale_fill_viridis_c(direction = 1,
    option = "H",
    limits= c(0,1)) +

  theme_bw() +
  theme(axis.text = element_blank(),
        axis.line = element_blank(),
        axis.ticks = element_blank(),
        panel.grid = element_blank(),
        panel.border = element_blank(),
        legend.position="left") +
  labs(x = "",
       y = "",
       fill = TeX(r'(Lower Bound  $\psi$ )')) +

```

```

guides(fill = guide_colorbar(# draw border around the legend
  frame.colour = "black")) +
coord_fixed()

gpredM_2 <- ggplot(data = willow_sdm, aes(x=X, y=Y,fill=Predicted)) +
  geom_raster() +
  scale_fill_viridis_c(direction = 1,
    option = "H",
    limits= c(0,1)) +
  # add actual observations if we have x,y data
  # geom_point(data = willowNum, aes(x=X, y=Y)) +
  theme_bw() +
  theme(axis.text = element_blank(),
    axis.line = element_blank(),
    axis.ticks = element_blank(),
    panel.grid = element_blank(),
    panel.border = element_blank(),
    legend.position="left") +
  labs(x = "",
    y = "",
    fill = TeX(r'(Estimated  $\psi$ ')) +
  guides(fill = guide_colorbar(# draw border around the legend
    frame.colour = "black")) +
  coord_fixed()

gpredH <- ggplot(data = willow_sdm, aes(x=X, y=Y,fill=upper)) +
  geom_raster() +
  scale_fill_viridis_c(direction = 1,
    option = "H",
    limits= c(0,1)) +

  theme_bw() +
  theme(axis.text = element_blank(),
    axis.line = element_blank(),
    axis.ticks = element_blank(),
    panel.grid = element_blank(),
    panel.border = element_blank(),
    legend.position="left") +
  labs(x = "",
    y = "",
    fill = TeX(r'(Upper Bound  $\psi$ ')) +
  guides(fill = guide_colorbar(# draw border around the legend
    frame.colour = "black")) +
  coord_fixed()

cowplot::plot_grid(gpredL, gpredM_2, gpredH,nrow=3)

#-----#
#psi ~ elev | mean(forest)
pred_psi_eleL <- data.frame(elev = seq(min(willowUnm@siteCovs$elev, na.rm=TRUE),

```

```

                                max(willowUnm@siteCovs$elev, na.rm=TRUE),
                                length = 30),
                                forest = quantile(probs = 0.25, willowUnm@siteCovs$forest, na.rm=
mutate(elev2 = elev^2,
        forest2 = forest^2)
predPsiEleL <- modavgPred(list(mOptm), newdata = pred_psi_eleL, parm.type = "psi", c.hat = g
pred_psi_eleL <- pred_psi_eleL %>% mutate(Predicted = predPsiEleL$mod.avg.pred,
                                SE = predPsiEleL$uncond.se,
                                lower = predPsiEleL$lower.CL,
                                upper = predPsiEleL$upper.CL,
                                elevR = 1182.574 + elev*646.333)
ggpsieleL <- ggplot(data = pred_psi_eleL, aes(x = elevR, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Elevation (m)") + ylim(0,1) + theme_bw()

pred_psi_eleM <- data.frame(elev = seq(min(willowUnm@siteCovs$elev, na.rm=TRUE),
                                max(willowUnm@siteCovs$elev, na.rm=TRUE),
                                length = 30),
                                forest = median(willowUnm@siteCovs$forest, na.rm=TRUE)) %>%
  mutate(elev2 = elev^2,
        forest2 = forest^2)
predPsiEleM <- modavgPred(list(mOptm), newdata = pred_psi_eleM, parm.type = "psi", c.hat = g
pred_psi_eleM <- pred_psi_eleM %>% mutate(Predicted = predPsiEleM$mod.avg.pred,
                                SE = predPsiEleM$uncond.se,
                                lower = predPsiEleM$lower.CL,
                                upper = predPsiEleM$upper.CL,
                                elevR = 1182.574 + elev*646.333)
ggpsieleM <- ggplot(data = pred_psi_eleM, aes(x = elevR, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Elevation (m)") + ylim(0,1) + theme_bw()

pred_psi_eleH <- data.frame(elev = seq(min(willowUnm@siteCovs$elev, na.rm=TRUE),
                                max(willowUnm@siteCovs$elev, na.rm=TRUE),
                                length = 30),
                                forest = quantile(probs = 0.75, willowUnm@siteCovs$forest, na.rm=
mutate(elev2 = elev^2,
        forest2 = forest^2)
predPsiEleH <- modavgPred(list(mOptm), newdata = pred_psi_eleH, parm.type = "psi", c.hat = g
pred_psi_eleH <- pred_psi_eleH %>% mutate(Predicted = predPsiEleH$mod.avg.pred,
                                SE = predPsiEleH$uncond.se,
                                lower = predPsiEleH$lower.CL,
                                upper = predPsiEleH$upper.CL,
                                elevR = 1182.574 + elev*646.333)
ggpsieleH <- ggplot(data = pred_psi_eleH, aes(x = elevR, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Elevation (m)") + ylim(0,1) + theme_bw()

#-----#

```

```

#psi ~ for | mean(elev)
pred_psi_forL <- data.frame(forest = seq(min(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         max(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         length = 30),
                           elev = quantile(probs = 0.25, willowUnm@siteCovs$elev, na.rm=TRUE),
                           mutate(elev2 = elev^2,
                                   forest2 = forest^2))
predPsiForL <- modavgPred(list(mOptm), newdata = pred_psi_forL, parm.type = "psi", c.hat = g
pred_psi_forL <- pred_psi_forL %>% mutate(Predicted = predPsiForL$mod.avg.pred,
                                         SE = predPsiForL$uncond.se,
                                         lower = predPsiForL$lower.CL,
                                         upper = predPsiForL$upper.CL,
                                         forestP = forest*100)
ggpsiforL <- ggplot(data = pred_psi_forL, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Forest Cover (%)") + ylim(0,1) + theme_bw()

pred_psi_forM <- data.frame(forest = seq(min(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         max(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         length = 30),
                           elev = median(willowUnm@siteCovs$elev, na.rm=TRUE)) %>%
  mutate(elev2 = elev^2,
         forest2 = forest^2)
predPsiForM <- modavgPred(list(mOptm), newdata = pred_psi_forM, parm.type = "psi", c.hat = g
pred_psi_forM <- pred_psi_forM %>% mutate(Predicted = predPsiForM$mod.avg.pred,
                                         SE = predPsiForM$uncond.se,
                                         lower = predPsiForM$lower.CL,
                                         upper = predPsiForM$upper.CL,
                                         forestP = forest*100)
ggpsiforM <- ggplot(data = pred_psi_forM, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Forest Cover (%)") + ylim(0,1) + theme_bw()

pred_psi_forH <- data.frame(forest = seq(min(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         max(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         length = 30),
                           elev = quantile(probs = 0.75, willowUnm@siteCovs$elev, na.rm=TRUE),
                           mutate(elev2 = elev^2,
                                   forest2 = forest^2))
predPsiForH <- modavgPred(list(mOptm), newdata = pred_psi_forH, parm.type = "psi", c.hat = g
pred_psi_forH <- pred_psi_forH %>% mutate(Predicted = predPsiForH$mod.avg.pred,
                                         SE = predPsiForH$uncond.se,
                                         lower = predPsiForH$lower.CL,
                                         upper = predPsiForH$upper.CL,
                                         forestP = forest*100)
ggpsiforH <- ggplot(data = pred_psi_forH, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Forest Cover (%)") + ylim(0,1) + theme_bw()

```

```

cowplot::plot_grid(ggpsieleL, ggpsieleM, ggpsieleH, ggpsiforL, ggpsiforM, ggpsiforH, nrow=2)

#-----#
#psi ~ elev | quantile(forest)
pred_psi_eleL <- data.frame(elev = seq(min(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         max(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         length = 30),
                           forest = quantile(probs = 0.25, willowUnm@siteCovs$forest, na.rm=TRUE),
                           mutate(elev2 = elev^2,
                                   forest2 = forest^2))
predPsiEleL <- modavgPred(list(mOptm), newdata = pred_psi_eleL, parm.type = "psi", c.hat = g)
pred_psi_eleL <- pred_psi_eleL %>% mutate(Predicted = predPsiEleL$mod.avg.pred,
                                         SE = predPsiEleL$uncond.se,
                                         lower = predPsiEleL$lower.CL,
                                         upper = predPsiEleL$upper.CL,
                                         elevR = 1182.574 + elev*646.333)
ggpsieleL <- ggplot(data = pred_psi_eleL, aes(x = elevR, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Elevation (m)") + ylim(0,1) + theme_bw()

pred_psi_eleM <- data.frame(elev = seq(min(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         max(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         length = 30),
                           forest = median(willowUnm@siteCovs$forest, na.rm=TRUE)) %>%
  mutate(elev2 = elev^2,
         forest2 = forest^2)
predPsiEleM <- modavgPred(list(mOptm), newdata = pred_psi_eleM, parm.type = "psi", c.hat = g)
pred_psi_eleM <- pred_psi_eleM %>% mutate(Predicted = predPsiEleM$mod.avg.pred,
                                         SE = predPsiEleM$uncond.se,
                                         lower = predPsiEleM$lower.CL,
                                         upper = predPsiEleM$upper.CL,
                                         elevR = 1182.574 + elev*646.333)
ggpsieleM <- ggplot(data = pred_psi_eleM, aes(x = elevR, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Elevation (m)") + ylim(0,1) + theme_bw()

pred_psi_eleH <- data.frame(elev = seq(min(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         max(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         length = 30),
                           forest = quantile(probs = 0.75, willowUnm@siteCovs$forest, na.rm=TRUE),
                           mutate(elev2 = elev^2,
                                   forest2 = forest^2))
predPsiEleH <- modavgPred(list(mOptm), newdata = pred_psi_eleH, parm.type = "psi", c.hat = g)
pred_psi_eleH <- pred_psi_eleH %>% mutate(Predicted = predPsiEleH$mod.avg.pred,
                                         SE = predPsiEleH$uncond.se,
                                         lower = predPsiEleH$lower.CL,
                                         upper = predPsiEleH$upper.CL,
                                         elevR = 1182.574 + elev*646.333)

```

```

ggpsieleH <- ggplot(data = pred_psi_eleH, aes(x = elevR, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Elevation (m)") + ylim(0,1) + theme_bw()

#-----#
#psi ~ for | quantile(elev)
pred_psi_forL <- data.frame(forest = seq(min(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         max(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         length = 30),
                           elev = quantile(probs = 0.25, willowUnm@siteCovs$elev, na.rm=TRUE),
                           mutate(elev2 = elev^2,
                                   forest2 = forest^2))
predPsiForL <- modavgPred(list(mOptm), newdata = pred_psi_forL, parm.type = "psi", c.hat = g
pred_psi_forL <- pred_psi_forL %>% mutate(Predicted = predPsiForL$mod.avg.pred,
                                         SE = predPsiForL$uncond.se,
                                         lower = predPsiForL$lower.CL,
                                         upper = predPsiForL$upper.CL,
                                         forestP = forest*100)
ggpsiforL <- ggplot(data = pred_psi_forL, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Forest Cover (%)") + ylim(0,1) + theme_bw()

pred_psi_forM <- data.frame(forest = seq(min(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         max(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         length = 30),
                           elev = median(willowUnm@siteCovs$elev, na.rm=TRUE)) %>%
  mutate(elev2 = elev^2,
         forest2 = forest^2)
predPsiForM <- modavgPred(list(mOptm), newdata = pred_psi_forM, parm.type = "psi", c.hat = g
pred_psi_forM <- pred_psi_forM %>% mutate(Predicted = predPsiForM$mod.avg.pred,
                                         SE = predPsiForM$uncond.se,
                                         lower = predPsiForM$lower.CL,
                                         upper = predPsiForM$upper.CL,
                                         forestP = forest*100)
ggpsiforM <- ggplot(data = pred_psi_forM, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Forest Cover (%)") + ylim(0,1) + theme_bw()

pred_psi_forH <- data.frame(forest = seq(min(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         max(willowUnm@siteCovs$forest, na.rm=TRUE),
                                         length = 30),
                           elev = quantile(probs = 0.75, willowUnm@siteCovs$elev, na.rm=TRUE),
                           mutate(elev2 = elev^2,
                                   forest2 = forest^2))
predPsiForH <- modavgPred(list(mOptm), newdata = pred_psi_forH, parm.type = "psi", c.hat = g
pred_psi_forH <- pred_psi_forH %>% mutate(Predicted = predPsiForH$mod.avg.pred,
                                         SE = predPsiForH$uncond.se,
                                         lower = predPsiForH$lower.CL,

```



```

upper = predPsiForH$upper.CL,
forestP = forest*100)
ggpsiforH <- ggplot(data = pred_psi_forH, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Forest Cover (%)") + ylim(0,1) + theme_bw()

cowplot::plot_grid(ggpsieleL, ggpsieleM, ggpsieleH, ggpsiforL, ggpsiforM, ggpsiforH, nrow=2)

#-----#
#p ~ dur | median(day & forest)
pred_p_dur <- data.frame(dur = seq(min(willowUnm@obsCovs$dur, na.rm=TRUE),
                                   max(willowUnm@obsCovs$dur, na.rm=TRUE),
                                   length = 30),
                        day = median(willowUnm@obsCovs$day, na.rm=TRUE),
                        forest = median(willowUnm@obsCovs$forest, na.rm=TRUE))
predPDur <- modavgPred(list(mOptm), newdata = pred_p_dur, parm.type = "detect", c.hat = gof)
pred_p_dur <- pred_p_dur %>% mutate(Predicted = predPDur$mod.avg.pred,
                                   SE = predPDur$uncond.se,
                                   lower = predPDur$lower.CL,
                                   upper = predPDur$upper.CL,
                                   forestP = forest*100)
pDurPlot <- ggplot(data = pred_p_dur, aes(x = dur, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Survey Duration (min)") + ylim(0,1) + theme_bw()
#-----#
#p ~ day | median(dur & forest)
pred_p_dayL <- data.frame(day = seq(min(willowUnm@obsCovs$day, na.rm=TRUE),
                                     max(willowUnm@obsCovs$day, na.rm=TRUE),
                                     length = 30),
                         dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
                         forest = quantile(probs = 0.25, willowUnm@obsCovs$forest, na.rm=TRUE))
predPDayL <- modavgPred(list(mOptm), newdata = pred_p_dayL, parm.type = "detect", c.hat = gof)
pred_p_dayL <- pred_p_dayL %>% mutate(Predicted = predPDayL$mod.avg.pred,
                                   SE = predPDayL$uncond.se,
                                   lower = predPDayL$lower.CL,
                                   upper = predPDayL$upper.CL,
                                   forestP = forest*100)
pDayPlotL <- ggplot(data = pred_p_dayL, aes(x = day, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Survey Day (8% Forested)") + ylim(0,1) + theme_bw()
#p ~ day | Q2(dur & forest)
pred_p_day <- data.frame(day = seq(min(willowUnm@obsCovs$day, na.rm=TRUE),
                                     max(willowUnm@obsCovs$day, na.rm=TRUE),
                                     length = 30),
                         dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
                         forest = quantile(probs = 0.5, willowUnm@obsCovs$forest, na.rm=TRUE))

```

```

predPDay <- modavgPred(list(mOptm), newdata = pred_p_day, parm.type = "detect", c.hat = gof
pred_p_day <- pred_p_day %>% mutate(Predicted = predPDay$mod.avg.pred,
                                   SE = predPDay$uncond.se,
                                   lower = predPDay$lower.CL,
                                   upper = predPDay$upper.CL,
                                   forestP = forest*100)

pDayPlot <- ggplot(data = pred_p_day, aes(x = day, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Survey Day (33% Forested)") + ylim(0,1) + theme_bw()
#p ~ day | Q4(dur & forest)
pred_p_dayH <- data.frame(day = seq(min(willowUnm@obsCovs$day, na.rm=TRUE),
                                   max(willowUnm@obsCovs$day, na.rm=TRUE),
                                   length = 30),
                        dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
                        forest = quantile(probs = 0.75, willowUnm@obsCovs$forest, na.rm=TRUE))
predPDayH <- modavgPred(list(mOptm), newdata = pred_p_dayH, parm.type = "detect", c.hat = gof
pred_p_dayH <- pred_p_dayH %>% mutate(Predicted = predPDayH$mod.avg.pred,
                                   SE = predPDayH$uncond.se,
                                   lower = predPDayH$lower.CL,
                                   upper = predPDayH$upper.CL,
                                   forestP = forest*100)

pDayPlotH <- ggplot(data = pred_p_dayH, aes(x = day, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Survey Day (57% Forested)") + ylim(0,1) + theme_bw()
#-----#
#p ~ for | Q2(day), median(dur)
pred_p_forL <- data.frame(forest = seq(min(willowUnm@obsCovs$forest, na.rm=TRUE),
                                       max(willowUnm@obsCovs$forest, na.rm=TRUE),
                                       length = 30),
                        dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
                        day = quantile(probs = 0.25, willowUnm@obsCovs$day, na.rm=TRUE))
predPForL <- modavgPred(list(mOptm), newdata = pred_p_forL, parm.type = "detect", c.hat = gof
pred_p_forL <- pred_p_forL %>% mutate(Predicted = predPForL$mod.avg.pred,
                                   SE = predPForL$uncond.se,
                                   lower = predPForL$lower.CL,
                                   upper = predPForL$upper.CL,
                                   forestP = forest*100)

pForPlotL <- ggplot(data = pred_p_forL, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Forest (%) on Day 38") + ylim(0,1) + theme_bw()
#p ~ for | median(dur & day)
pred_p_for <- data.frame(forest = seq(min(willowUnm@obsCovs$forest, na.rm=TRUE),
                                       max(willowUnm@obsCovs$forest, na.rm=TRUE),
                                       length = 30),
                        dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
                        day = quantile(probs = 0.5, willowUnm@obsCovs$day, na.rm=TRUE))
predPFor <- modavgPred(list(mOptm), newdata = pred_p_for, parm.type = "detect", c.hat = gof
pred_p_for <- pred_p_for %>% mutate(Predicted = predPFor$mod.avg.pred,

```

```

SE = predPFor$uncond.se,
lower = predPFor$lower.CL,
upper = predPFor$upper.CL,
forestP = forest*100)
pForPlot <- ggplot(data = pred_p_for, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Forest (%) on Day 52") + ylim(0,1) + theme_bw()
#p ~ for | Q4(day), median(dur)
pred_p_forH <- data.frame(forest = seq(min(willowUnm@obsCovs$forest, na.rm=TRUE),
  max(willowUnm@obsCovs$forest, na.rm=TRUE),
  length = 30),
  dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
  day = quantile(probs = 0.75, willowUnm@obsCovs$day, na.rm=TRUE))
predPForH <- modavgPred(list(mOptm), newdata = pred_p_forH, parm.type = "detect", c.hat = g
pred_p_forH <- pred_p_forH %>% mutate(Predicted = predPForH$mod.avg.pred,
  SE = predPForH$uncond.se,
  lower = predPForH$lower.CL,
  upper = predPForH$upper.CL,
  forestP = forest*100)
ggplot(data = pred_p_forH, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Forest (%) on Day 72") + ylim(0,1) + theme_bw()

# all together
cowplot::plot_grid(pDayPlotL, pDayPlot, pDayPlotH, pForPlotL, pForPlot, pForPlotH, nrow=2)
pDurPlot

# generate predictions for 4 quadrants of interest
willowPred <- willowNum %>% filter(id %in% c(25, 62, 150, 203)) %>%
  rename(elev2 = elevsq,
  forest2 = forestsq)
# predicting occurrence from the state process
predQuads <- modavgPred(list(mOptm), newdata = willowPred, parm.type = "psi", c.hat = gof.b
willowRes <- willowPred %>% mutate(Predicted = predQuads$mod.avg.pred,
  SE = predQuads$uncond.se,
  lower = predQuads$lower.CL,
  upper = predQuads$upper.CL,
  elev = round((646.333*elev+1182.574),0)) %>%
  select(-c(elev2, forest2, iLength))

```

```

## APPENDIX PART 2: Testing Overfit Model Parameter Effects
#-----#
#psi ~ elev | mean(forest)
pred_psi_eleL <- data.frame(elev = seq(min(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         max(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         length = 30),
                           forest = quantile(probs = 0.25, willowUnm@siteCovs$forest, na.rm=TRUE),
                           mutate(elev2 = elev^2,
                                   forest2 = forest^2))
predPsiEleL <- modavgPred(list(mOverpred), newdata = pred_psi_eleL, parm.type = "psi", c.hat = 0.5)
pred_psi_eleL <- pred_psi_eleL %>% mutate(Predicted = predPsiEleL$mod.avg.pred,
                                         SE = predPsiEleL$uncond.se,
                                         lower = predPsiEleL$lower.CL,
                                         upper = predPsiEleL$upper.CL,
                                         elevR = 1182.574 + elev*646.333)
ggpsieleL <- ggplot(data = pred_psi_eleL, aes(x = elevR, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Elevation (m)") + ylim(0,1) + theme_bw()

pred_psi_eleM <- data.frame(elev = seq(min(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         max(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         length = 30),
                           forest = median(willowUnm@siteCovs$forest, na.rm=TRUE)) %>%
  mutate(elev2 = elev^2,
         forest2 = forest^2)
predPsiEleM <- modavgPred(list(mOverpred), newdata = pred_psi_eleM, parm.type = "psi", c.hat = 0.5)
pred_psi_eleM <- pred_psi_eleM %>% mutate(Predicted = predPsiEleM$mod.avg.pred,
                                         SE = predPsiEleM$uncond.se,
                                         lower = predPsiEleM$lower.CL,
                                         upper = predPsiEleM$upper.CL,
                                         elevR = 1182.574 + elev*646.333)
ggpsieleM <- ggplot(data = pred_psi_eleM, aes(x = elevR, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Elevation (m)") + ylim(0,1) + theme_bw()

pred_psi_eleH <- data.frame(elev = seq(min(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         max(willowUnm@siteCovs$elev, na.rm=TRUE),
                                         length = 30),
                           forest = quantile(probs = 0.75, willowUnm@siteCovs$forest, na.rm=TRUE),
                           mutate(elev2 = elev^2,
                                   forest2 = forest^2))
predPsiEleH <- modavgPred(list(mOverpred), newdata = pred_psi_eleH, parm.type = "psi", c.hat = 0.5)
pred_psi_eleH <- pred_psi_eleH %>% mutate(Predicted = predPsiEleH$mod.avg.pred,
                                         SE = predPsiEleH$uncond.se,

```

```

lower = predPsiEleH$lower.CL,
upper = predPsiEleH$upper.CL,
elevR = 1182.574 + elev*646.333)
ggpsieleH <- ggplot(data = pred_psi_eleH, aes(x = elevR, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Elevation (m)") + ylim(0,1) + theme_bw()

#-----#
#psi ~ for | mean(elev)
pred_psi_forL <- data.frame(forest = seq(min(willowUnm@siteCovs$forest, na.rm=TRUE),
max(willowUnm@siteCovs$forest, na.rm=TRUE),
length = 30),
elev = quantile(probs = 0.25, willowUnm@siteCovs$elev, na.rm=TRUE),
mutate(elev2 = elev^2,
forest2 = forest^2)
predPsiForL <- modavgPred(list(mOverpred), newdata = pred_psi_forL, parm.type = "psi", c.hat = 0.5)
pred_psi_forL <- pred_psi_forL %>% mutate(Predicted = predPsiForL$mod.avg.pred,
SE = predPsiForL$uncond.se,
lower = predPsiForL$lower.CL,
upper = predPsiForL$upper.CL,
forestP = forest*100)
ggpsiforL <- ggplot(data = pred_psi_forL, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Forest Cover (%)") + ylim(0,1) + theme_bw()

pred_psi_forM <- data.frame(forest = seq(min(willowUnm@siteCovs$forest, na.rm=TRUE),
max(willowUnm@siteCovs$forest, na.rm=TRUE),
length = 30),
elev = median(willowUnm@siteCovs$elev, na.rm=TRUE)) %>%
mutate(elev2 = elev^2,
forest2 = forest^2)
predPsiForM <- modavgPred(list(mOverpred), newdata = pred_psi_forM, parm.type = "psi", c.hat = 0.5)
pred_psi_forM <- pred_psi_forM %>% mutate(Predicted = predPsiForM$mod.avg.pred,
SE = predPsiForM$uncond.se,
lower = predPsiForM$lower.CL,
upper = predPsiForM$upper.CL,
forestP = forest*100)
ggpsiforM <- ggplot(data = pred_psi_forM, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Forest Cover (%)") + ylim(0,1) + theme_bw()

pred_psi_forH <- data.frame(forest = seq(min(willowUnm@siteCovs$forest, na.rm=TRUE),
max(willowUnm@siteCovs$forest, na.rm=TRUE),
length = 30),
elev = quantile(probs = 0.75, willowUnm@siteCovs$elev, na.rm=TRUE),
mutate(elev2 = elev^2,
forest2 = forest^2)
predPsiForH <- modavgPred(list(mOverpred), newdata = pred_psi_forH, parm.type = "psi", c.hat = 0.5)

```

```

pred_psi_forH <- pred_psi_forH %>% mutate(Predicted = predPsiForH$mod.avg.pred,
                                          SE = predPsiForH$uncond.se,
                                          lower = predPsiForH$lower.CL,
                                          upper = predPsiForH$upper.CL,
                                          forestP = forest*100)
ggpsiforH <- ggplot(data = pred_psi_forH, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#21918c", alpha=0.1) +
  geom_line(size=1,color="#21918c") +
  ylab("P(Occupied)") + xlab("Forest Cover (%)") + ylim(0,1) + theme_bw()

cowplot::plot_grid(ggpsieleL, ggpsieleM, ggpsieleH, ggpsiforL, ggpsiforM, ggpsiforH, nrow=2)

#-----#
#p ~ elev | median(day & forest & dur)
pred_p_elev <- data.frame(elev = seq(min(willowUnm@obsCovs$elev, na.rm=TRUE),
                                     max(willowUnm@obsCovs$elev, na.rm=TRUE),
                                     length = 30),
                         day = median(willowUnm@obsCovs$day, na.rm=TRUE),
                         forest = median(willowUnm@obsCovs$forest, na.rm=TRUE),
                         dur = median(willowUnm@obsCovs$dur, na.rm=TRUE))
predPEle <- modavgPred(list(mOverpred), newdata = pred_p_elev, parm.type = "detect", c.hat = 1)
pred_p_elev <- pred_p_elev %>% mutate(Predicted = predPEle$mod.avg.pred,
                                     SE = predPEle$uncond.se,
                                     lower = predPEle$lower.CL,
                                     upper = predPEle$upper.CL,
                                     forestP = forest*100)
ggplot(data = pred_p_elev, aes(x = elev, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Elevation") + ylim(0,1) + theme_bw()

#-----#
#p ~ dur | median(day & forest)
pred_p_dur <- data.frame(dur = seq(min(willowUnm@obsCovs$dur, na.rm=TRUE),
                                     max(willowUnm@obsCovs$dur, na.rm=TRUE),
                                     length = 30),
                        day = median(willowUnm@obsCovs$day, na.rm=TRUE),
                        forest = median(willowUnm@obsCovs$forest, na.rm=TRUE),
                        elev = median(willowUnm@obsCovs$elev, na.rm=TRUE))
predPDur <- modavgPred(list(mOverpred), newdata = pred_p_dur, parm.type = "detect", c.hat = 1)
pred_p_dur <- pred_p_dur %>% mutate(Predicted = predPDur$mod.avg.pred,
                                   SE = predPDur$uncond.se,
                                   lower = predPDur$lower.CL,
                                   upper = predPDur$upper.CL,
                                   forestP = forest*100)
ggplot(data = pred_p_dur, aes(x = dur, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Survey Duration (min)") + ylim(0,1) + theme_bw()

#-----#
#p ~ day | Q2(forest) + median(everything else)
pred_p_dayL <- data.frame(day = seq(min(willowUnm@obsCovs$day, na.rm=TRUE),

```



```

        max(willowUnm@obsCovs$day, na.rm=TRUE),
        length = 30),
        dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
        forest = quantile(probs = 0.25, willowUnm@obsCovs$forest, na.rm=TRUE),
        elev = median(willowUnm@obsCovs$elev, na.rm=TRUE))
predPDayL <- modavgPred(list(mOverpred), newdata = pred_p_dayL, parm.type = "detect", c.hat =
pred_p_dayL <- pred_p_dayL %>% mutate(Predicted = predPDayL$mod.avg.pred,
        SE = predPDayL$uncond.se,
        lower = predPDayL$lower.CL,
        upper = predPDayL$upper.CL,
        forestP = forest*100)
pDayPlotL <- ggplot(data = pred_p_dayL, aes(x = day, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Survey Day (8% Forested)") + ylim(0,1) + theme_bw()
#p ~ day | Q2(dur & forest)
pred_p_day <- data.frame(day = seq(min(willowUnm@obsCovs$day, na.rm=TRUE),
        max(willowUnm@obsCovs$day, na.rm=TRUE),
        length = 30),
        dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
        forest = quantile(probs = 0.5, willowUnm@obsCovs$forest, na.rm=TRUE),
        elev = median(willowUnm@obsCovs$elev, na.rm=TRUE))
predPDay <- modavgPred(list(mOverpred), newdata = pred_p_day, parm.type = "detect", c.hat =
pred_p_day <- pred_p_day %>% mutate(Predicted = predPDay$mod.avg.pred,
        SE = predPDay$uncond.se,
        lower = predPDay$lower.CL,
        upper = predPDay$upper.CL,
        forestP = forest*100)
pDayPlot <- ggplot(data = pred_p_day, aes(x = day, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Survey Day (33% Forested)") + ylim(0,1) + theme_bw()
#p ~ day | Q4(forest) + median(everything else)
pred_p_dayH <- data.frame(day = seq(min(willowUnm@obsCovs$day, na.rm=TRUE),
        max(willowUnm@obsCovs$day, na.rm=TRUE),
        length = 30),
        dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
        forest = quantile(probs = 0.75, willowUnm@obsCovs$forest, na.rm=TRUE),
        elev = median(willowUnm@obsCovs$elev, na.rm=TRUE))
predPDayH <- modavgPred(list(mOverpred), newdata = pred_p_dayH, parm.type = "detect", c.hat =
pred_p_dayH <- pred_p_dayH %>% mutate(Predicted = predPDayH$mod.avg.pred,
        SE = predPDayH$uncond.se,
        lower = predPDayH$lower.CL,
        upper = predPDayH$upper.CL,
        forestP = forest*100)
pDayPlotH <- ggplot(data = pred_p_dayH, aes(x = day, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Survey Day (57% Forested)") + ylim(0,1) + theme_bw()
#-----#
#p ~ for | Q2(day), median(everything else)

```



```

pred_p_forL <- data.frame(forest = seq(min(willowUnm@obsCovs$forest, na.rm=TRUE),
                                         max(willowUnm@obsCovs$forest, na.rm=TRUE),
                                         length = 30),
                          dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
                          day = quantile(probs = 0.25, willowUnm@obsCovs$day, na.rm=TRUE),
                          elev = median(willowUnm@obsCovs$elev, na.rm=TRUE))
predPForL <- modavgPred(list(mOverpred), newdata = pred_p_forL, parm.type = "detect", c.hat
pred_p_forL <- pred_p_forL %>% mutate(Predicted = predPForL$mod.avg.pred,
                                     SE = predPForL$uncond.se,
                                     lower = predPForL$lower.CL,
                                     upper = predPForL$upper.CL,
                                     forestP = forest*100)
pForPlotL <- ggplot(data = pred_p_forL, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Forest (%) on Day 38") + ylim(0,1) + theme_bw()
#p ~ for / median(everything)
pred_p_for <- data.frame(forest = seq(min(willowUnm@obsCovs$forest, na.rm=TRUE),
                                         max(willowUnm@obsCovs$forest, na.rm=TRUE),
                                         length = 30),
                          dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
                          day = quantile(probs = 0.5, willowUnm@obsCovs$day, na.rm=TRUE),
                          elev = median(willowUnm@obsCovs$elev, na.rm=TRUE))
predPFor <- modavgPred(list(mOverpred), newdata = pred_p_for, parm.type = "detect", c.hat =
pred_p_for <- pred_p_for %>% mutate(Predicted = predPFor$mod.avg.pred,
                                     SE = predPFor$uncond.se,
                                     lower = predPFor$lower.CL,
                                     upper = predPFor$upper.CL,
                                     forestP = forest*100)
pForPlot <- ggplot(data = pred_p_for, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Forest (%) on Day 52") + ylim(0,1) + theme_bw()
#p ~ for / Q4(day), median(others)
pred_p_forH <- data.frame(forest = seq(min(willowUnm@obsCovs$forest, na.rm=TRUE),
                                         max(willowUnm@obsCovs$forest, na.rm=TRUE),
                                         length = 30),
                          dur = median(willowUnm@obsCovs$dur, na.rm=TRUE),
                          day = quantile(probs = 0.75, willowUnm@obsCovs$day, na.rm=TRUE),
                          elev = median(willowUnm@obsCovs$elev, na.rm=TRUE))
predPForH <- modavgPred(list(mOverpred), newdata = pred_p_forH, parm.type = "detect", c.hat
pred_p_forH <- pred_p_forH %>% mutate(Predicted = predPForH$mod.avg.pred,
                                     SE = predPForH$uncond.se,
                                     lower = predPForH$lower.CL,
                                     upper = predPForH$upper.CL,
                                     forestP = forest*100)
ggplot(data = pred_p_forH, aes(x = forestP, y = Predicted)) +
  geom_ribbon(aes(ymin=lower, ymax=upper), fill="#440154", alpha=0.1) +
  geom_line(size=1,color="#440154") +
  ylab("P(Detected)") + xlab("Forest (%) on Day 72") + ylim(0,1) + theme_bw()

```

```
# all together  
cowplot::plot_grid(pDayPlotL, pDayPlot, pDayPlotH, pForPlotL, pForPlot, pForPlotH, nrow=2)
```

References

1. Kumpula, S., Votka, E., Orell, M. & Rytönen, S. [Effects of forest management on the spatial distribution of the willow tit \(*Poecile montanus*\)](#). *Forest Ecology and Management* **529**, 120694 (2023).
2. Parry, W. & Broughton, R. K. [Nesting behaviour and breeding success of Willow Tits *Poecile montanus* in north-west England](#). *Ringing & Migration* **33**, 75–85 (2018).
3. Knaus, P. *et al.* [Swiss Breeding Bird Atlas 2013–2016. Distribution and Population Trends of Birds in Switzerland and Liechtenstein](#). (Swiss Ornithological Institute, Sempach, 2018).
4. Riecke, T. V., Gibson, D., Kéry, M. & Schaub, M. [Sharing detection heterogeneity information among species in community models of occupancy and abundance can strengthen inference](#). *Ecology and Evolution* **11**, 18125–18135 (2021).
5. Bani, L., Luppi, M., Rocchia, E., Dondina, O. & Orioli, V. [Winners and losers: How the elevational range of breeding birds on Alps has varied over the past four decades due to climate and habitat changes](#). *Ecology and Evolution* **9**, 1289–1305 (2019).
6. Sutherland, C. [Statsecol: A Package Associated With The Statistical Ecology MSc](#). (2024).
7. Bartón, K. [MuMIn: Multi-Model Inference](#). (2023).
8. R Core Team. [R: A Language and Environment for Statistical Computing](#). (2023).