Data dictionary

Source of every raw column: PDHS 2017-18, Kids' Recode file `PKKR71FL.DTA` (DHS Program), 12,708 children by 1,186 columns, pulled as described in `ACQUISITION.md`. This file lists the 26 columns used in the project, not all 1,186. Definitions are the variable labels stored in the file. Counts were computed from the raw file.

Column	Definition (DHS label)	Type	Unit	Codes / range	Missing in Sindh (of 2,278)	Caveats
`caseid`	case identification	text	identifier (text)		0	Built from cluster, household and woman line number. Repeats once per child of the same mother (4,421 repeats), so rows are not independent; never use alone as a key.
`midx`	index to birth history	integer	index (1-5)	1 to 5	0	Position of the child in the mother's birth history. `caseid` + `midx` is unique (0 duplicates).
`v000`	country code and phase	text	code		0	Country code and survey phase ('PK7'); constant in this file.
`v001`	cluster number	integer	cluster id	1 to 580	0	Sampling cluster. Used to hold out whole clusters in the train/test split.
`v002`	household number	integer	household number	1 to 29	0	Numbered within the cluster, so not unique on its own.
`v005`	women's individual sample weight (6 decimals)	integer	weight x 1,000,000	0 to 4.09519e+06	0	DHS weights carry 6 implied decimals, so divide by 1,000,000 (column `w`). Minimum value is 0, so some women have zero weight.
`v006`	month of interview	integer	month number	1 to 12	0	Interviews fall in Jan-Apr and Nov-Dec only; May-Oct are absent.
`v012`	respondent's current age	integer	years	15 to 49	0	Age of the mother, not the child.
`v022`	sample strata for sampling errors	integer	stratum id	1 to 16	0	Sampling strata, kept for weighted analysis.
`v024`	region	integer	category code	1=punjab; 2=sindh; 3=kpk; 4=balochistan; 5=gb; 6=ict; 7=ajk; 8=fata	0	Region; 2 = Sindh. Also contains GB, AJK, FATA and ICT, which are not provinces.
`v025`	type of place of residence	integer	category code	1=urban; 2=rural	0	1 = urban, 2 = rural.

Column	Definition (DHS label)	Type	Unit	Codes / range	Missing in Sindh (of 2,278)	Caveats
`v106`	highest educational level	integer	category code	0=no education; 1=primary; 2=secondary; 3=higher	0	Mother's highest education level, not the child's or father's.
`v113`	source of drinking water	integer	category code	11 to 97	0	Stored as int8 but the values (11-97) are source categories, not quantities; treat as categorical. Value labels are not stored in the file.
`v116`	type of toilet facility	integer	category code	11 to 97	0	Same as v113: int8 codes for toilet type, to be treated as categorical.
`v136`	number of household members (listed)	integer	persons	2 to 44	0	Number of household members listed; right-skewed (mean 9.6 in the Sindh sample, maximum 23).
`v190`	wealth index combined	integer	quintile 1-5	1=poorest; 2=poorer; 3=middle; 4=richer; 5=richest	0	National wealth index, so quintiles are not equal in size within Sindh (254 of 779 usable Sindh children are in the poorest quintile).
`b4`	sex of child	integer	category code	1=male; 2=female	0	1 = male, 2 = female.
`b5`	child is alive	integer	0/1	0=no; 1=yes	0	0 = child has died. The 719 dead children (123 in Sindh) have no height-for-age score.
`b8`	current age of child	decimal	years	0 to 4	123	Age in whole years; missing for dead children (719), so use `hw1` for age in months.
`bord`	birth order number	integer	birth order number	1 to 15	0	1 = first-born; up to 15.
`b11`	preceding birth interval (months)	decimal	months	7 to 236	544	Preceding birth interval; missing for first-born children (204 of 779 usable Sindh children). Right-skewed (skew 2.06), so I use log.
`hw1`	child's age in months	decimal	months	0 to 59	1431	Child's age at measurement; missing for most children who were not measured (8,209), but present for all 779 usable Sindh scores.

Column	Definition (DHS label)	Type	Unit	Codes / range	Missing in Sindh (of 2,278)	Caveats
`hw13`	result of measurement - height/weight	decimal	category code	0=measured; 1=dead; 2=sick; 3=not present; 4=refused; 5=mother refused; 6=other; 7=no measurement found in household	1	Result of measurement. 0 = measured (4,227); 7 = no measurement found in household (7,490); 1 = dead (719). Two 'measured' children have no score, and one child not marked 'measured' has one.
`hw70`	height/age standard deviation (new who)	decimal	z-score x 100	9996=height out of plausible limits; 9997=age in days out of plausible limits; 9998=flagged cases	1472	Divide by 100 to get the z-score (column `haz`). Codes 9996, 9997 and 9998 are flags; only 9998 appears (85 children, 27 in Sindh) and I set it to missing.
`m14`	number of antenatal visits during pregnancy	decimal	number of visits	0=no antenatal visits; 98=don't know	805	98 = don't know (31 children) and is not a real count; I set it to missing in `m14_clean`.
`v404`	currently breastfeeding	integer	0/1	0=no; 1=yes	0	Currently breastfeeding, answered by the mother. Check in the DHS recode manual which child it refers to before using it as a feature.

Columns I created (not in the raw file)

Column	Type	Unit	Definition	Caveats
`haz`	decimal	z-score (SD units)	`hw70 / 100`, with codes of 9990 or more set to missing	Raw `hw70` is kept unchanged. 4,141 valid values nationally, 779 in Sindh.
`stunted`	0/1	none	1 if `haz < -2`, else 0; missing where `haz` is missing	Weighted rate among usable Sindh children is 49.3% (unweighted 46.5%).
`w`	decimal	weight	`v005 / 1,000,000`	Use for every population rate; not for model fitting unless stated.
`m14_clean`	decimal	number of visits	`m14` with 98 set to missing	31 cells changed nationally.