PREDICT BEFORE YOU MODIFY: LEARNING IMPROVEMENT DYNAMICS FOR SELF-EVOLVING AGENTS

Zixuan Xie
University of Virginia
xie.zixuan@email.virginia.edu

Chang Xu
Microsoft Research
chanx@microsoft.com

Yuhua Jiang
Tsinghua University
yh-jiang24@mails.tsinghua.edu.cn

Li Zhao
Microsoft Research
lizo@microsoft.com

arXiv:2610.13991v1 [cs.LG] 26 Sep 2026

ABSTRACT

Self-evolving agents improve through repeated cycles of modification and evaluation. However, existing methods receive feedback on modifications only after costly evaluations, and aggregate scores may obscure distinctions between failures that require different repairs. We introduce predictive self-evolution through an editable Improvement Dynamics Model (IDM). Before evaluation, the IDM predicts task-level outcomes of a proposed modification and guides an optional revision. After evaluation, past modifications and their observed outcomes are used to improve the IDM, allowing predictive knowledge to accumulate across generations. The system can thus improve how it solves tasks, proposes modifications, and predicts their effects. Building on HyperAgents, we evaluate this approach across multilingual coding, paper review, robotics reward design, and Olympiad-level mathematical grading. Our approach outperforms HyperAgents across all four domains, with up to 46% higher average performance over generations. Gains also persist under matched token budgets that include both agent evolution and task evaluation, and extend to held-out tasks. Forecast accuracy improves as the IDM evolves, and the learned predictive knowledge transfers to improve evolution in a new domain.[1]

1 INTRODUCTION

The capabilities of modern AI agents depend not only on their foundation models, but also on the programs that determine how they reason, use tools, maintain memory, and interact with their environments. Recent work on agent self-evolution seeks to improve these programs automatically by repeatedly modifying them, evaluating the resulting agents on target tasks, and using the evaluation results to guide later modifications (Zhang et al., 2025a; 2026b). Yet, like Odysseus navigating without Athena, these systems rely on costly evaluations to discover the effects of their modifications. Predicting those effects could help refine proposals before evaluation.

Past evaluations provide a basis for such predictions. The Darwin Gödel Machine (DGM) (Zhang et al., 2025a) maintains an archive of evaluated coding agents that can serve as parents for new branches. Related methods share experience across branches or expose richer historical evidence (Weng et al., 2026; Lee et al., 2026). HyperAgents (Zhang et al., 2026b) extend DGM by combining a task agent and a meta agent in a single editable program. The task agent solves the target tasks and is evaluated on them, while the meta agent modifies both the task agent and itself. With access to the archive and prior evaluations, the meta agent can use experience from earlier generations to improve both task-solving behavior and the process that generates future modifications.

Recent methods use this experience to guide proposal generation or anticipate outcomes. DREvo (Guo et al., 2026) uses past modifications and their outcomes to guide new proposals, while AHE (Lin et al., 2026) records task-level expectations and checks them against subsequent evaluations.

[1] Code is available at
https://anonymous.4open.science/r/Predictive-self-evolution/.



Figure 1: **An Athena for self-evolution.** Like Athena guiding Odysseus, the IDM anticipates task-level outcomes to guide an optional revision before evaluation. Only the resulting child's task agent is evaluated. Final forecasts and observed outcomes provide evidence for improving the IDM across generations.

AgentSquare (Shang et al., 2025) ranks recombined agent candidates with an in-context performance predictor. These approaches do not, however, use predicted task-level outcomes as feedback for revising a draft before evaluation. We therefore seek to turn accumulated experience into predictive feedback that helps refine proposals before costly evaluation.

Using predictions to guide revision requires anticipating how a modification will affect individual tasks, not just whether it will improve the overall score. Building on HyperAgents (Zhang et al., 2026b), we introduce predictive self-evolution with an Improvement Dynamics Model (IDM), an editable program that invokes a frozen LLM to forecast task-level outcomes from the current agent, a proposed code change, and historical experience. These forecasts preserve distinctions relevant to revision: an incorrect attempt and a missing output, for example, may receive the same failure score but call for different repairs. The predicted aggregate score determines whether to request one additional revision from the meta agent, while the task-level forecasts guide that revision. The resulting descendant's task agent is then evaluated. To improve forecasts as the agents themselves evolve, the meta agent periodically edits the IDM's forecasting code and instructions using past modifications and discrepancies between their predicted and observed outcomes from across generations and branches. Candidate updates are adopted only if they improve prediction quality on subsequently collected outcomes. Figure 1 illustrates this process.

Following HyperAgents (Zhang et al., 2026b), we evaluate predictive self-evolution across four domains: multilingual coding (Gauthier, 2024), paper review (Zhao et al., 2026), robotics reward design (Genesis Authors, 2024), and Olympiad-level mathematical grading (Luong et al., 2025). Our contributions are as follows.

- **Predictive self-evolution.** We introduce an editable IDM that forecasts task-level outcomes of proposed modifications and guides selective revision before evaluation. Its forecasting program evolves from experience alongside the task and meta agents.
- **Effective use of evolution budgets.** Allocating part of the budget to predictive feedback improves evolution across four domains under matched token budgets covering evolution and task evaluation. Coding ablations support its value beyond an additional revision alone.
- **Transferable predictive knowledge.** Evolution produces predictive knowledge reusable beyond the agents that generated it. IDM forecasts improve with experience, and transferring only the evolved IDM improves mathematical-grading evolution over a freshly initialized IDM, with identical initial task and meta agents.

2 Related Work

Automatic agent design and self-evolution. Automatic agent design uses task feedback to search for effective programs and workflows built around foundation models. Automated Design of Agentic Systems (ADAS) (Hu et al., 2025) uses a meta agent to discover agent programs in code, while AFlow (Zhang et al., 2025b) searches over executable workflows using Monte Carlo tree search. Reusing earlier discoveries is central to these searches. The Darwin Gödel Machine (Zhang et al., 2025a) maintains an archive of evaluated coding agents that can serve as starting points for further self-modification, while Group-Evolving Agents (Weng et al., 2026) organize evolution around groups that share experience across agents. HyperAgents (Zhang et al., 2026b) extend evolution to the meta agent responsible for generating modifications, allowing the improvement procedure itself to change alongside the task agent. We extend HyperAgents with an editable IDM that evolves alongside the task and meta agents.

Learning from feedback and experience. Self-Refine (Madaan et al., 2023) uses self-generated feedback to revise the current output, while Reflexion (Shinn et al., 2023) retains verbal reflections to guide later trials. Other approaches organize experience for repeated reuse: Agentic Context Engineering (ACE) (Zhang et al., 2025c) maintains evolving contextual playbooks, and ReasoningBank (Ouyang et al., 2025) distills reusable reasoning strategies from successful and failed experiences. Knowledge-Centric Self-Improvement (KSI) (Wang et al., 2026) accumulates insights in a shared knowledge base that generic agents use across tasks. Beyond supplying context for task execution, feedback can also guide changes to the agent's prompts and programs. GEPA (Agrawal et al., 2026) reflects on execution trajectories to propose and test prompt updates and combine complementary improvements. For program modification, Meta-Harness (Lee et al., 2026) gives the optimizer access to previous candidates' source code, scores, and execution traces. HarnessFix (Chen et al., 2026) and Self-Harness (Zhang et al., 2026a) use execution traces to diagnose failures and validate targeted harness repairs, whereas DREvo (Guo et al., 2026) reassesses historical evidence against the current program before distilling it into search directions.

Predictive models for agent improvement. Predictive models have long been used to guide search and reduce evaluation costs, including in surrogate-assisted evolutionary optimization (Jin, 2011) and predictor-based neural architecture search (Luo et al., 2018). At the program level, Neural Change Prediction (Plein et al., 2026) learns from synthetic code mutations and their observed effects to predict changes in program outputs. At the task-execution level, WorldEvolver (Zhang et al., 2026c) forecasts environment transitions to guide actions and updates predictive memory from discrepancies between forecasts and observations. For agent optimization, predictions can support candidate selection or make the expected effects of edits explicit. AgentSquare (Shang et al., 2025) uses an in-context performance predictor to rank candidates formed by recombining existing agent modules, reducing the need for direct evaluation. AHE (Lin et al., 2026) records expected fixes and regressions for each edit and checks these predictions against subsequent task-level outcomes. Our IDM instead uses forecasts of task-level evaluation outcomes as feedback for revising a proposed agent-program modification before evaluation. The meta agent also edits the IDM's forecasting code and instructions using past modifications and prediction errors.

3 Predictive Self-Evolution

3.1 Archive-Based Self-Evolution

Agents and task evaluation. Following HyperAgents (Zhang et al., 2026b), an *agent* is any computable program. A *Hyperagent* combines a *task agent* that solves target tasks with a *meta agent* that can modify both the task agent and itself. For a fixed target domain d, let $\mathcal{T}_d$ denote its finite set of evaluation tasks. Evaluating a Hyperagent h runs its task agent under the domain-specific evaluation protocols of HyperAgents (Zhang et al., 2026b). Let $s_\tau(h)$ denote the resulting score on task $\tau \in \mathcal{T}_d$, with higher scores indicating better performance. We define the aggregate evaluation score as

$$y(h) \doteq \frac{1}{|\mathcal{T}_d|} \sum_{\tau \in \mathcal{T}_d} s_\tau(h). \tag{1}$$

Task scores may be binary or continuous and are averaged over repeated trials where required by the evaluation protocol. Domain-specific evaluation protocols and score aggregation are detailed in Appendix A.2.

Evolution process. At generation t, the archive $\mathcal{A}_t$ forms a tree rooted at the evaluated initial Hyperagent h_0, storing agents, scores, and parent–child relations. A parent h_{p_t} is sampled using the fixed HyperAgents selection rule (Zhang et al., 2026b). Its meta agent uses the archive and prior evaluations to propose a code diff δ_t. Applying this diff to a copy of the parent produces a child h_{t+1}, which is evaluated and added to the archive. Earlier agents remain available as parents. Our method adds predictive feedback to guide an optional revision of the diff before child evaluation.

3.2 Improvement Dynamics Model

The IDM I is an editable program that invokes a frozen LLM to forecast task-level outcomes before evaluation. A single IDM serves all archive branches within a run. Its forecasting code and instructions evolve from past modifications and observed outcomes (Figure 2). Let $\mathbf{o}(h)$ denote the task-level outcomes recorded when evaluating a Hyperagent h. At generation t, the IDM receives the archive $\mathcal{A}_t$, the selected parent h_{p_t} and its observed outcomes $\mathbf{o}(h_{p_t})$, and a proposed code diff δ. Writing $h_{p_t}^{\delta}$ for the child that would result from applying this diff, we denote the IDM's forecast by

$$\mathbf{f}_t(I, \delta) \doteq I(\mathcal{A}_t, h_{p_t}, \mathbf{o}(h_{p_t}), \delta)\,. \tag{2}$$

The forecast $\mathbf{f}_t(I, \delta)$ contains task-level outcome probabilities and, where applicable, continuous performance estimates. These forecasts distinguish outcomes that may receive the same task score but call for different repairs, such as an incorrect solution and a missing output. Domain-specific prediction targets and their conversion to task scores are detailed in Appendix A.4.

Let $\widehat{s}_{t,\tau}(I, \delta)$ denote the expected task score derived from the forecast for task τ. Following the aggregation used in task evaluation, the predicted score of the proposed child is

$$\widehat{y}_t(I, h_{p_t}^{\delta}) \doteq \frac{1}{|\mathcal{T}_d|} \sum_{\tau \in \mathcal{T}_d} \widehat{s}_{t,\tau}(I, \delta). \tag{3}$$

The predicted score determines whether to request one additional revision, while the task-level forecast guides that revision.

3.3 IDM-Guided Hyperagent Evolution

As illustrated in the upper part of Figure 2, each generation t begins with the meta agent in the selected parent h_{p_t} proposing a draft diff $\delta_t^{\mathrm{draft}}$. The current IDM I remains fixed during this generation and produces the draft forecast $\mathbf{f}_t(I, \delta_t^{\mathrm{draft}})$. We correct the predicted score by subtracting an online estimate b of the current IDM's prediction bias. Calibration details are provided in Appendix A.4.2. A fixed revision rule shared across all branches requests one additional revision when

$$\widehat{y}_t\left(I, h_{p_t}^{\delta_t^{\mathrm{draft}}}\right) - b < y(h_{p_t}). \tag{4}$$

The revision rule allocates an additional revision to drafts whose bias-corrected predicted scores fall below the parent's observed score. When revision is requested, the meta agent receives the draft forecast and produces a revised diff δ_t. Otherwise, $\delta_t = \delta_t^{\mathrm{draft}}$. Following a revision, the IDM forecasts the final diff once more so that the recorded prediction corresponds to the modification actually evaluated. To limit computation, we allow at most one revision before obtaining fresh feedback from child evaluation.

The final diff and its forecast $\mathbf{f}_t(I, \delta_t)$ are recorded before evaluating the task agent in the resulting child $h_{t+1} = h_{p_t}^{\delta_t}$. This evaluation proceeds regardless of the final predicted score. The evaluated child is added to the archive, and the completed generation yields the record

$$z_t \doteq (\mathcal{A}_t, h_{p_t}, \mathbf{o}(h_{p_t}), \delta_t, \mathbf{f}_t(I, \delta_t), \mathbf{o}(h_{t+1}))\,. \tag{5}$$

The record preserves the inputs available to the IDM before evaluation and pairs the final forecast with the observed child outcomes for subsequent IDM updates.



Figure 2: **Pipeline of predictive self-evolution.** Upper: the IDM forecasts a draft and guides at most one revision; revised diffs are forecast again before evaluation. The final forecast and observed outcomes form a record, and the child enters the archive. Lower: accumulated records support candidate IDM updates, which replace the current IDM only after validation on subsequently collected records.

3.4 Evolving the IDM

Task performance guides the evolution of task and meta agents, but does not directly measure the IDM's prediction accuracy. We therefore update the IDM separately from the task and meta agents and share it across archive branches, allowing records from different branches to improve the same forecasting program. As illustrated in the lower part of Figure 2, every $K \geq 2$ generations, the meta agent in the selected Hyperagent uses the accumulated records to edit the current IDM's forecasting code and instructions, producing a candidate. We validate the candidate on the next K records, collected while the current IDM remains deployed. Once the block is complete, the candidate makes its forecasts using the recorded pre-evaluation inputs, without access to later archive updates or the corresponding child outcomes.

To replace the current IDM, a candidate must reduce prediction loss in the task forecasts used to guide revision. We measure this loss using Brier loss (Brier, 1950) for probabilities and squared error for continuous values, with domain-specific definitions given in Appendix A.4. For the score that determines whether to revise, we also require that centered mean squared error (CMSE) (Taylor, 2001) does not increase. CMSE measures score prediction error after removing each IDM's mean bias on the validation block. If both conditions hold, the candidate replaces the current IDM; otherwise, the current IDM remains deployed. Upon replacement, the candidate's mean bias on this block initializes the online calibration offset b described in Section 3.3.

4 Experiments

We evaluate whether predictive self-evolution improves agent performance under generation and token budgets. We then examine forecast accuracy during evolution, cross-domain transfer of predictive knowledge, and the contributions of individual components through coding ablations.

4.1 EXPERIMENTAL SETUP

Initialization. We use the initial Hyperagent from HyperAgents (Zhang et al., 2026b), adding instructions that distinguish Hyperagent modifications from IDM updates and specify the feedback available in each phase. The initial IDM is instructed to predict task-level outcomes from proposed modifications and available evidence. Implementation details and instruction templates are provided in Appendix A.

Domains and evaluation protocol. Following HyperAgents (Zhang et al., 2026b), we evaluate predictive self-evolution across four domains: Polyglot coding (Gauthier, 2024), paper review (Zhao et al., 2026), robotics reward design in Genesis (Genesis Authors, 2024), and Olympiad-level mathematical grading using IMO-GradingBench (Luong et al., 2025). Polyglot is evaluated independently, paper review and robotics are optimized jointly, and mathematical grading is the target setting for IDM transfer. Each method is evaluated over five complete runs per setting, following HyperAgents (Zhang et al., 2026b). Each run lasts 40 generations. Within each setting, methods share the same initial Hyperagent, underlying task-agent and meta-agent LLMs, task splits, evaluation protocol, and parent-selection rule. Domain-specific evaluation protocols are detailed in Appendix A, and IDM prediction formats and losses in Appendix A.4.

Baselines and variants. We refer to our method as *Selective IDM* in the experiments. HyperAgents serves as the common baseline across the domains. It evaluates the modified agent without requesting an additional revision from the meta agent. On Polyglot, Reflective HyperAgents revises every draft once without IDM feedback. We also evaluate two variants of our method on this benchmark. Frozen Selective IDM retains selective revision and online bias calibration but fixes the IDM to its initial implementation. IDM Reflection uses feedback from the evolving IDM to revise every draft once. For mathematical grading, Selective IDM starts from the initial IDM, while Transferred IDM starts from an IDM evolved jointly on paper review and robotics. Both conditions use the same evolution procedure and initial task and meta agents.

Metrics and budgets. Task performance is measured by the evaluation score defined for each domain. The joint score is the equally weighted mean of paper-review validation accuracy and robotics training fitness. To assess evolution efficiency, we use the normalized area under the budget curve (AUBC), which captures the benefit of discovering strong agents earlier. Let F_t denote the highest score among evaluated descendants available after generation t. For a generation budget B, we define

$$\mathrm{AUBC}(B) \doteq \frac{1}{B}\sum_{t=0}^{B-1} F_t, \qquad F_0 = 0. \tag{6}$$

For matched-token comparisons, we compute AUBC at a common budget equal to the reference baseline's median full-run token cost. The reference is HyperAgents for the main comparisons and Reflective HyperAgents for the coding ablations. Token costs cover agent evolution and task evaluation. Token accounting and budget matching are detailed in Appendix B.2. Performance metrics are computed within each run before aggregation, and we report medians over five complete runs. Individual-run results are provided in Appendix B.3.

4.2 IMPROVING AGENT EVOLUTION

Coding. Using predicted outcomes to guide revision before evaluation helps Selective IDM discover stronger agents earlier. On Polyglot, it achieves a median AUBC of 0.306 over 40 generations, compared with 0.210 for HyperAgents (Figure 3(a)). Under matched token budgets, median AUBC remains 10.9% higher than that of HyperAgents (Figure 3(b)). This gain supports using part of the token budget for predictive feedback before evaluating modified agents.

On 166 held-out coding tasks, agents selected from Selective IDM runs achieve a median gain of 13.25 percentage points over the common initial agent, compared with 5.42 points for HyperAgents (Figure 3(c)). These results show that the gains from predictive self-evolution extend to tasks not used for modification or agent selection.



Figure 3: **More effective coding evolution with gains on held-out tasks.** (a) AUBC as the generation budget increases. (b) AUBC under matched token budgets, including tokens used for both agent evolution and task evaluation. (c) Improvement in resolve rate over the common initial agent on 166 held-out coding tasks, measured in percentage points (pp). The initial agent's resolve rate is 16.27%. Curves and bars show medians over five runs. Shading and error bars indicate 95% run-level bootstrap confidence intervals, computed pointwise in (a).

Paper review and robotics. Joint evolution tests whether an IDM can guide improvement across tasks with different evaluation signals. We jointly optimize paper review and robotics reward design, with equal weight on paper-review validation accuracy and robotics fitness. The predicted joint score determines whether to request a revision, while task-level forecasts from both domains guide the revision. Over 40 generations, Selective IDM achieves higher median AUBC than HyperAgents for both domains and the joint objective (Figure 4(a)). On paper review, median AUBC improves by 5.9% over HyperAgents. Median joint AUBC also improves by 3.9%. The advantage persists across all three measures under matched token budgets (Figure 4(b)). Together with the coding results, these findings support using an IDM to guide evolution across different task objectives.

4.3 Improving Forecasts during Evolution

We first examine whether IDM updates improve predictions for subsequent modifications. On Polyglot, we compare candidate and current IDMs on the same modification records collected after candidate construction. Across five runs, candidates achieve lower Brier loss in 19 of 28 comparisons, including both adopted and rejected candidates (Figure 5(a)). Editing the IDM using past experience can improve its predictions beyond the modifications used to construct the update.

We next compare successive deployed IDMs on a fixed set of historical modifications from generations 1–5 of selected runs. The inputs, observed outcomes, and scoring rules remain the same across versions. In these comparisons across four domains, the final deployed version has lower task-level prediction loss than the initial IDM, with reductions of 8.7%–24.4% (Figure 5(b)). These results support accumulating reusable predictive knowledge through IDM evolution. Appendices B.4 and B.5 examine modification information, forecast-guided revision, and IDM evolution.

4.4 Transferring Predictive Knowledge across Domains

To test whether predictive experience remains useful in a new domain, we transfer an IDM evolved jointly on paper review and robotics to mathematical grading. We compare HyperAgents with two conditions: Selective IDM starts from the initial IDM, whereas Transferred IDM uses the same



Figure 4: **Predictive guidance improves joint evolution across different task objectives.** AUBC under (a) a budget of 40 generations and (b) matched token budgets. Paper and Robotics track the best evaluated descendant for each domain. Joint tracks the highest joint score attained by a single evaluated descendant. Bars show medians over five runs, and error bars indicate 95% run-level bootstrap confidence intervals. AUBC values are multiplied by 100. The vertical axes are truncated.



Figure 5: **IDM predictions improve during evolution.** (a) Candidate and current IDMs are compared on subsequent validation records in 28 comparisons across five Polyglot runs, including rejected candidates. Blue points indicate lower candidate Brier loss. (b) Successive deployed IDMs are evaluated on fixed modifications from generations 1–5 of selected runs, with initial loss normalized to 100. Markers indicate each version's first deployment. Mathematical grading uses Selective IDM.

evolved IDM in all five transfer runs. Only the IDM is transferred, while all three conditions use the same initial task and meta agent implementations. Both conditions continue updating the IDM.

Selective IDM achieves higher median AUBC than HyperAgents under both generation and token budgets. Transferred IDM improves further, achieving 3.4% higher median AUBC than Selective IDM under the generation budget and 2.3% higher under the matched token budget for mathematical grading (Figure 6(a,b)). The benefit extends to held-out tasks, where Transferred IDM increases median accuracy by 4 percentage points over Selective IDM and 8 points over HyperAgents (Figure 6(c)). These results support using the IDM to carry predictive experience across domains and guide the evolution of newly initialized agents.



Figure 6: **Predictive experience transfers to mathematical grading.** AUBC under (a) 40 generations and (b) a matched token budget for mathematical grading. (c) Accuracy on 100 held-out tasks for agents selected by validation performance. Bars show medians over five runs, with 95% run-level bootstrap confidence intervals. AUBC values are multiplied by 100. The vertical axes are truncated.



Figure 7: **Effects of predictive feedback, IDM updates, and revision strategy.** Curves show median AUBC over five runs on Polyglot as the generation budget increases. The left panel shows the complete trajectory; the right panel enlarges the outlined region for budgets of 20–40 generations.

4.5 Ablations and Revision Strategies

On Polyglot, we compare IDM Reflection with Reflective HyperAgents to assess predictive feedback beyond revision alone. Both methods revise every draft once. IDM Reflection achieves a higher median AUBC at 40 generations, supporting the value of predictive feedback (Figure 7). This benefit extends beyond the best agents to the quality of generated descendants (Appendix B.1). We next compare Selective IDM with Frozen Selective IDM, which retains selective revision and online bias calibration but keeps the forecasting program fixed. Updating the IDM yields a higher median AUBC.

Both Selective IDM and IDM Reflection use an evolving IDM, but Selective IDM gains an early AUBC advantage. At 40 generations, it achieves the highest median AUBC among the four revision configurations while requesting a median of 27 additional revision passes per run, compared with 40 for IDM Reflection. Its median AUBC remains highest under a matched token budget (Appendix B.2).

5 Conclusion

We introduced predictive self-evolution with an editable IDM that learns from past modifications and their outcomes to guide revision before evaluation. By making the forecasting program itself an object of evolution, the system can accumulate and reuse predictive knowledge as the agents continue

to change. Experiments across four domains show more effective evolution under matched budgets and support the transfer of predictive knowledge to a new domain. Forecast accuracy also improves with experience. Extending the IDM toward a world model of agent evolution could help identify modification sequences whose early steps offer little immediate gain but enable greater improvements in later generations.

AI USE STATEMENT

In this work, we used generative AI tools for method implementation and analysis and interpretation of results. We have not used generative AI tools to develop research ideas or design the methodology or experiments, and synthetic dataset generation and mathematical proofs are not applicable to this work. Additionally, we used generative AI tools for figure preparation and manuscript drafting and editing. We have reviewed all AI-assisted work and take responsibility for the final content, including AI-assisted text, code, and analyses.

ETHICS STATEMENT

We evaluate agent self-evolution on existing benchmarks, with robotics experiments conducted in simulation. Paper-review and mathematical-grading results concern benchmark performance, not suitability for replacing human judgment. Deployment beyond these settings would require safeguards for generated code and human oversight of consequential decisions.

REPRODUCIBILITY STATEMENT

Section 3 specifies the evolution procedure and IDM updates. Appendix A documents initialization, instruction templates, model configurations, task splits, evaluation protocols, prediction losses, and statistical reporting. Appendices B.3 and B.2 provide individual-run results and token-budget accounting, respectively. Our code repository is at `https://anonymous.4open.science/r/Predictive-self-evolution/`.

REFERENCES

Lakshya A. Agrawal, Shangyin Tan, Dilara Soylu, Noah Ziems, Rishi Khare, Krista Opsahl-Ong, Arnav Singhvi, Herumb Shandilya, Michael J. Ryan, Meng Jiang, Christopher Potts, Koushik Sen, Alexandros G. Dimakis, Ion Stoica, Dan Klein, Matei Zaharia, and Omar Khattab. GEPA: Reflective prompt evolution can outperform reinforcement learning. In *The Fourteenth International Conference on Learning Representations*, 2026.

Glenn W. Brier. Verification of forecasts expressed in terms of probability. *Monthly Weather Review*, 78(1):1–3, 1950.

Mengzhuo Chen, Junjie Wang, Zhe Liu, Yawen Wang, and Qing Wang. From failed trajectories to reliable LLM agents: Diagnosing and repairing harness flaws. *Arxiv Preprint*, 2026.

Paul Gauthier. o1 tops aider's new polyglot leaderboard, December 2024. URL `https://aider.chat/2024/12/21/polyglot.html`.

Genesis Authors. Genesis: A generative and universal physics engine for robotics and beyond, December 2024. URL `https://github.com/Genesis-Embodied-AI/genesis-world`.

Hanghui Guo, Weijie Shi, Zhangze Chen, Shengxiang Xu, Yishu Wang, Yimei Zhang, Wangze Ni, Jia Zhu, and Shimin Di. DREvo: Distilling recalibrated historical experience for harness self-evolution. *Arxiv Preprint*, 2026.

Shengran Hu, Cong Lu, and Jeff Clune. Automated design of agentic systems. In *The Thirteenth International Conference on Learning Representations*, 2025.

Yaochu Jin. Surrogate-assisted evolutionary computation: Recent advances and future challenges. *Swarm and Evolutionary Computation*, 1(2):61–70, 2011.

Yoonho Lee, Roshen Nair, Qizheng Zhang, Kangwook Lee, Omar Khattab, and Chelsea Finn. Meta-Harness: End-to-end optimization of model harnesses. *Arxiv Preprint*, 2026.

Jiahang Lin, Shichun Liu, Chengjun Pan, Lizhi Lin, Shihan Dou, Zhiheng Xi, Xuanjing Huang, Hang Yan, Zhenhua Han, Tao Gui, and Yu-Gang Jiang. Agentic harness engineering: Observability-driven automatic evolution of coding-agent harnesses. *Arxiv Preprint*, 2026.

Renqian Luo, Fei Tian, Tao Qin, Enhong Chen, and Tie-Yan Liu. Neural architecture optimization. In *Advances in Neural Information Processing Systems*, volume 31, 2018.

Thang Luong, Dawsen Hwang, Hoang H Nguyen, Golnaz Ghiasi, Yuri Chervonyi, Insuk Seo, Junsu Kim, Garrett Bingham, Jonathan Lee, Swaroop Mishra, Alex Zhai, Huiyi Hu, Henryk Michalewski, Jimin Kim, Jeonghyun Ahn, Junhwi Bae, Xingyou Song, Trieu Hoang Trinh, Quoc V Le, and Junehyuk Jung. Towards robust mathematical reasoning. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 35418–35442, Suzhou, China, November 2025. Association for Computational Linguistics.

Aman Madaan, Niket Tandon, Prakhar Gupta, Skyler Hallinan, Luyu Gao, Sarah Wiegreffe, Uri Alon, Nouha Dziri, Shrimai Prabhumoye, Yiming Yang, Shashank Gupta, Bodhisattwa Prasad Majumder, Katherine Hermann, Sean Welleck, Amir Yazdanbakhsh, and Peter Clark. Self-Refine: Iterative refinement with self-feedback. In *Advances in Neural Information Processing Systems*, volume 36, 2023.

Siru Ouyang, Jun Yan, I-Hung Hsu, Yanfei Chen, Ke Jiang, Zifeng Wang, Rujun Han, Long T. Le, Samira Daruki, Xiangru Tang, Vishy Tirumalashetty, George Lee, Mahsan Rofouei, Hangfei Lin, Jiawei Han, Chen-Yu Lee, and Tomas Pfister. ReasoningBank: Scaling agent self-evolving with reasoning memory. *Arxiv Preprint*, 2025.

Laura Plein, Souhila Zidane, Jordan Samhi, and Andreas Zeller. Neural change prediction: Relating software changes to their effects and vice versa. *Arxiv Preprint*, 2026.

Yu Shang, Yu Li, Keyu Zhao, Likai Ma, Jiahe Liu, Fengli Xu, and Yong Li. AgentSquare: Automatic LLM agent search in modular design space. In *The Thirteenth International Conference on Learning Representations*, 2025.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. Reflexion: Language agents with verbal reinforcement learning. In *Advances in Neural Information Processing Systems*, volume 36, 2023.

Karl E. Taylor. Summarizing multiple aspects of model performance in a single diagram. *Journal of Geophysical Research: Atmospheres*, 106(D7):7183–7192, 2001.

Xuefei Julie Wang, Lauren Hyoseo Yoon, Chengrui Qu, Amanda Zichang Wang, Atharva Sehgal, Eric Mazumdar, and Yisong Yue. Knowledge-centric self-improvement. *Arxiv Preprint*, 2026.

Zhaotian Weng, Antonis Antoniades, Deepak Nathani, Zhen Zhang, Xiao Pu, and Xin Eric Wang. Group-evolving agents: Open-ended self-improvement via experience sharing. *Arxiv Preprint*, 2026.

Hangfan Zhang, Shao Zhang, Kangcong Li, Chen Zhang, Yang Chen, Yiqun Zhang, Lei Bai, and Shuyue Hu. Self-harness: Harnesses that improve themselves. *Arxiv Preprint*, 2026a.

Jenny Zhang, Shengran Hu, Cong Lu, Robert Lange, and Jeff Clune. Darwin Gödel machine: Open-ended evolution of self-improving agents. *Arxiv Preprint*, 2025a.

Jenny Zhang, Bingchen Zhao, Wannan Yang, Jakob Foerster, Jeff Clune, Minqi Jiang, Sam Devlin, and Tatiana Shavrina. Hyperagents. *Arxiv Preprint*, 2026b.

Jiayi Zhang, Jinyu Xiang, Zhaoyang Yu, Fengwei Teng, Xiong-Hui Chen, Jiaqi Chen, Mingchen Zhuge, Xin Cheng, Sirui Hong, Jinlin Wang, Bingnan Zheng, Bang Liu, Yuyu Luo, and Chenglin Wu. AFlow: Automating agentic workflow generation. In *The Thirteenth International Conference on Learning Representations*, 2025b.

Qizheng Zhang, Changran Hu, Shubhangi Upasani, Boyuan Ma, Fenglu Hong, Vamsidhar Kamanuru, Jay Rainton, Chen Wu, Mengmeng Ji, Hanchen Li, Urmish Thakker, James Zou, and Kunle Olukotun. Agentic context engineering: Evolving contexts for self-improving language models. *Arxiv Preprint*, 2025c.

Xuan Zhang, Wenxuan Zhang, See-Kiong Ng, and Yang Deng. Self-evolving world models for LLM agent planning. *Arxiv Preprint*, 2026c.

Bingchen Zhao, Jenny Zhang, Chenxi Whitehouse, Minqi Jiang, Michael Shvartsman, Abhishek Charnalia, Despoina Magka, Tatiana Shavrina, Derek Dunfield, Oisin Mac Aodha, and Yoram Bachrach. APRES: An agentic paper revision and evaluation system. *Arxiv Preprint*, 2026.

A Experimental Details

Our implementation builds on the released HyperAgents codebase (Zhang et al., 2026b). We retain its parent-selection rule and domain evaluators.

A.1 Initialization and Instructions

Following HyperAgents (Zhang et al., 2026b), we keep the initial programs simple to leave room for strategies to develop through evolution. The instructions specify each component's role, available inputs and tools, and required outputs, with separate meta-agent instructions distinguishing Hyperagent modification from IDM updates. We use this initialization approach across domains, adapting task descriptions, inputs, and required outputs to each domain. The initial instruction templates are shown below.

A.1.1 Initial Components

Task agent. For paper review, robotics, and mathematical grading, the initial task agent receives domain-specific inputs through the following instruction:

```
You are an agent.

Task input:
{inputs}

Return one JSON object. The response value must be a string containing
your answer.
Do not wrap the JSON in Markdown fences or XML tags.
{
    "response": "your answer"
}
```

The coding task agent additionally receives repository-editing instructions with access to shell and file-editing tools.

Meta agent. The meta agent receives the codebase location and access to previous evaluation results. When available, archived predictions and observed outcomes are also accessible, and a prediction-error report is included in the request. The initial instruction includes:

```
Modify any part of the codebase at `{repo_path}`. Evaluation results
and prior generation outputs are stored at `{eval_path}`.

A read-only audited reaction-history substrate is available at
`{reaction_archive_path}`; inspect it only when useful.

This is the task-improvement phase: the modification you produce now
is what gets evaluated on the benchmark, so it must change how tasks
are solved. `intervention_model.py` forecasts the evaluation state a
```

```
modification produces and is revised in a separate phase; edits to it
are discarded here.
```

For IDM updates, the same meta agent starts a fresh session with the current IDM, archived modifications and their predicted and observed outcomes, and a prediction-error report when available. Edits are restricted to the IDM. The update instruction includes:

```
The benchmark modification for this generation has already been
evaluated; edits you make now are not scored on the benchmark and take
effect for later generations. Edits to any other file are discarded.
```

IDM. Across domains, the IDM is instructed to predict evaluation outcomes from the proposed modification and its expected behavioral consequences. A representative initial system prompt is:

```
You are the IDM of a self-evolving agent.

Predict the evaluation outcomes of the proposed code modification.
Ground your predictions in the affected code and its expected
behavioral consequences. Include a brief explanation.
Do not write code.
```

A.1.2 Revision Feedback to the Meta Agent

An additional revision pass continues the same meta-agent session after a draft has been produced, preserving the draft and interaction history. Reflective HyperAgents requests this pass for every draft without invoking the IDM, using the following instruction:

```
Reconsider the draft modification using only the information already
available. Check for likely failure modes and revise the draft if
warranted. No new evaluation feedback is available.
```

When the revision rule requests an additional revision pass, Selective IDM uses the same reconsideration instruction and appends the IDM feedback:

```
Prospective IDM prediction (information unavailable to the reflection
control; use it as a hypothesis, not as evaluation feedback):

--- BEGIN IDM PREDICTION ---
{delivered forecast}
--- END IDM PREDICTION ---
```

IDM Reflection uses the same forecast feedback for every draft. Prediction formats, losses, calibration, and update validation are described in Appendix A.4.

A.2 Domains and Evaluation Protocols

We use the domain evaluators of HyperAgents (Zhang et al., 2026b), with task splits and evaluation scores summarized in Table 1. The task scores $s_\tau(h)$ in equation 1 are specified below.

Table 1: Task splits and scores used in our experiments. Robotics counts refer to repeated reward-design trials on the same control task.

Domain	Train	Validation	Held-out	Evolution score
Polyglot coding	60	–	166	Resolve rate
Paper review	100	100	–	Validation accuracy
Robotics reward design	6	–	–	Training fitness
Mathematical grading	100	100	100	Validation accuracy

Coding. Polyglot (Gauthier, 2024) requires the task agent to produce a patch that passes the task's test suite. The task score $s_\tau(h)$ is 1 if the submitted patch passes the benchmark tests and 0 otherwise. We report pass@1 resolve rate, with no feedback from the final benchmark evaluation returned during the attempt. Evaluation starts with a fixed subset of 10 evolution tasks, shared across methods, and proceeds to full evaluation if at least four preliminary tasks are resolved. Archive scores use all 60 tasks as the denominator, with unevaluated tasks contributing zero. For coding, both the predicted score and the observed parent score in equation 4 are computed on the same ten preliminary tasks. Forecast evaluation uses only tasks with observed outcomes, matching predictions and observations on the same instances. After evolution, we select the evaluated descendant with the highest evolution score in each run, breaking ties by the earliest generation. The selected agent is evaluated on 166 disjoint held-out tasks, which are not used for modification or selection.

Joint paper review and robotics. Paper review and robotics are optimized within the same evolution run. For paper review, the task agent receives a research paper and predicts acceptance or rejection (Zhao et al., 2026). The task score $s_\tau(h)$ is 1 if the prediction matches the recorded conference decision and 0 otherwise.

For robotics reward design, the task agent generates a Python reward function for quadruped velocity tracking in Genesis (Genesis Authors, 2024). Each trial trains a new control policy using proximal policy optimization. The task score $s_\tau(h)$ is the trial fitness, which aggregates the fixed tracking score $\exp[-4(v_x - v_x^*)^2]$, where v_x and v_x^* are the achieved and commanded forward velocities, following the upstream evaluation procedure. The robotics score averages these task scores, with task-agent failures scored as zero and identified infrastructure failures excluded.

Each Hyperagent's joint score averages its paper-review validation accuracy and robotics training fitness with equal weight. Preliminary evaluation uses 10 training and 10 validation papers and three robotics trials. If both domains obtain positive preliminary training scores, evaluation expands to 100 training papers, 100 validation papers, and six robotics trials. Otherwise, the preliminary paper-review validation accuracy and mean robotics fitness are multiplied by $10/100$ and $3/6$, respectively, before computing the joint score.

Mathematical grading. IMO-GradingBench (Luong et al., 2025) provides an Olympiad-level problem, a proposed solution, reference solutions, and grading guidelines. The task agent assigns a grade from $\{0, 1, 6, 7\}$, corresponding to incorrect, partially correct, almost correct, and correct solutions, respectively. The task score $s_\tau(h)$ is 1 if the predicted grade exactly matches the expert grade and 0 otherwise. Preliminary evaluation uses 10 training and 10 validation tasks and expands to 100 tasks in each split if at least one training prediction matches the expert grade. Validation accuracy guides evolution. For held-out evaluation, we select the descendant with the highest validation accuracy among those evaluated on all 100 validation tasks in each run, breaking ties by the earliest generation.

A.3 Experimental Conditions

Each experimental condition consists of five runs of 40 generations. Within each setting, methods use the same initial task and meta agents, task splits, evaluators, and parent-selection rule. They also share the same model assignments and initial model-call configurations. The underlying LLM weights remain fixed throughout evolution. For conditions with an evolving IDM, update proposals are scheduled every $K = 5$ generations.

Parent selection. We use the parent-selection rule of HyperAgents (Zhang et al., 2026b). The initial Hyperagent and valid evaluated descendants are eligible for selection. At generation t, let $\bar{y}_t$ denote the mean of the three highest evaluation scores among eligible parents, using all available scores when fewer than three are eligible. For an archived Hyperagent h, let $n_t(h)$ denote the number of its direct children recorded in the archive. We sample the parent with probability proportional to

$$w_t(h) = \exp\left[-\left(\frac{n_t(h)}{8}\right)^3\right] \frac{1}{1+\exp[-10\,(y(h)-\bar{y}_t)]}, \tag{7}$$

where $y(h)$ is the aggregate evaluation score defined in equation 1. The weights are normalized over eligible parents. This rule favors higher-scoring Hyperagents while reducing repeated expansion of parents that have already produced many children.

Models and generation settings. Table 2 summarizes the initial model assignments. GPT-5.4 calls use high reasoning effort. Across domains, the shared LLM interface defaults to an output limit of 16,384 tokens per call. Temperature is set to 0.0 for Claude and left unspecified for GPT-4o and o3-mini. The shared tool framework defaults to a maximum of 40 tool calls per attempt.

Table 2: Initial LLM assignments across experimental settings.

Setting	Task agent	Meta agent and IDM
Polyglot coding	o3-mini	Claude Sonnet 4.6
Joint: paper review	GPT-4o	GPT-5.4
Joint: robotics	GPT-5.4	GPT-5.4
Mathematical grading	GPT-4o	GPT-5.4

Baselines and variants. On Polyglot, we compare Selective IDM with HyperAgents, Reflective HyperAgents, and two IDM variants, as summarized in Table 3. HyperAgents proceeds from a proposed modification to evaluation without an additional revision pass. Reflective HyperAgents and IDM Reflection both revise every draft once using the same reconsideration instruction, with IDM Reflection additionally receiving the IDM forecast. Frozen Selective IDM fixes the forecasting program while retaining selective revision and online bias calibration. On Polyglot, all IDMs share the same initialization.

Table 3: Baselines and variants compared on Polyglot. "Always" requests one revision for every draft. "Selective" requests one revision according to the revision rule.

Method	IDM feedback	Revision rule	IDM updates
HyperAgents	No	None	–
Reflective HyperAgents	No	Always	–
IDM Reflection	Yes	Always	Yes
Frozen Selective IDM	Yes	Selective	No
Selective IDM	Yes	Selective	Yes

Joint evolution compares HyperAgents with Selective IDM. Mathematical grading compares HyperAgents, Selective IDM, and Transferred IDM, a variant of Selective IDM initialized with an IDM evolved jointly on paper review and robotics. Only the IDM is transferred. Both conditions use the same initial task and meta agents, start with fresh calibration state and interaction history, and continue updating the IDM.

We selected an evolved IDM based on source-domain prediction improvements and a preference for fewer domain-specific heuristics. This selection preceded the mathematical-grading experiments, and the same IDM initializes all five transfer runs. Its evolved forecasting instructions include:

```
Start from the parent's recorded state or metric for each
instance, but treat that as a baseline to update rather
than a label to copy.
```

```
...
Do not anchor on parent labels or opaque instance IDs when
the same changed code governs many instances together.
```

These instructions are transferred unchanged, without adding mathematical-grading-specific heuristics. Tool-budget finalization and final-answer handling are aligned with those of the initial IDM.

A.4 IDM Implementation and Evaluation

The IDM predicts task outcomes using domain-specific formats and losses. Its forecasting program is editable, while the outcome definitions and prediction losses remain fixed.

A.4.1 Prediction Formats and Losses

Prediction outputs. For coding, paper review, and mathematical grading, the IDM returns a normalized probability distribution over the outcome classes in Table 4 for each evaluation task. The predicted task score is the probability of `resolved` for coding and `correct` for paper review and mathematical grading.

Table 4: Categorical outcomes predicted by the IDM.

Domain	Outcome	Meaning
Coding	`resolved`	A patch is produced and passes the benchmark tests.
	`unresolved`	A patch is produced but does not pass the benchmark tests.
	`incomplete`	The task-agent run does not finish.
	`empty_patch`	The task-agent run finishes without producing a patch.
Paper review and mathematical grading	`correct`	The task agent predicts the correct decision or grade.
	`incorrect`	The task agent returns a valid but incorrect decision or grade.
	`invalid`	The task-agent response is missing or unusable.

For each robotics trial, the IDM predicts the probability p_{invalid} that the generated reward function is unusable and the expected fitness m conditional on the reward function being usable, with both values in $[0, 1]$. Since an unusable reward function receives zero fitness, the predicted trial score is $(1 - p_{\text{invalid}})m$.

In paper review, robotics, and mathematical grading, the IDM is instructed to provide brief structured explanations alongside its forecasts, while explanations are optional in coding. Only the numerical forecasts are scored.

Task-level prediction losses. For categorical predictions, let $\mathcal{C}_d$ denote the outcome classes in domain d, $\mathbf{p} = (p_c)_{c \in \mathcal{C}_d}$ the predicted probability distribution, and c^* the observed outcome. The multiclass Brier loss (Brier, 1950) is

$$\ell_{\text{Brier}}(\mathbf{p}, c^*) \doteq \sum_{c \in \mathcal{C}_d} \left(p_c - \mathbf{1}\{c = c^*\}\right)^2 . \tag{8}$$

Coding uses this loss directly. Paper review and mathematical grading use half of this loss, placing it in $[0, 1]$ and matching the range of the robotics loss below.

For robotics, let s denote the observed trial fitness and let z_{invalid} be 1 if the reward function is unusable and 0 otherwise. The prediction loss is

$$\ell_{\text{robotics}} \doteq \frac{1}{2}\left[\left(p_{\text{invalid}} - z_{\text{invalid}}\right)^2 + \left((1 - p_{\text{invalid}})m - s\right)^2\right] . \tag{9}$$

The two terms measure error in the invalidity probability and predicted trial fitness, respectively.

Aggregate prediction loss. For domain d, let N_d denote the number of scored predictions across the evaluation block. For IDM I, let $\ell_{d,i}(I)$ denote the loss of prediction i, using the corresponding domain loss defined above. The mean prediction loss within the domain is

$$\mathcal{L}_d(I) \doteq \frac{1}{N_d} \sum_{i=1}^{N_d} \ell_{d,i}(I). \tag{10}$$

For coding and mathematical grading, $\mathcal{L}(I) = \mathcal{L}_d(I)$. For joint evolution, we give the two domains equal weight:

$$\mathcal{L}(I) \doteq \frac{1}{2} \left[\mathcal{L}_{\text{paper}}(I) + \mathcal{L}_{\text{robotics}}(I) \right]. \tag{11}$$

A.4.2 Update Validation and Calibration

Following Section 3.4, we compare candidate and current IDMs on the same K records, collected after candidate construction while the current IDM remains deployed. Let $\mathcal{V}_k$ index the validation records for update k, and let $\mathcal{S}_j$ denote the observed evaluation instances in record j. We write $y(h; \mathcal{S}_j)$ and $\widehat{y}_j(I, h; \mathcal{S}_j)$ for observed and predicted scores computed on this set, with equal domain weights in joint evolution. For either IDM I, we compute score prediction errors before applying the calibration offset, and define the block's mean bias and centered mean squared error as

$$\begin{aligned} e_j(I) &\doteq \widehat{y}_j\left(I, h_{p_j}^{\delta_j}; \mathcal{S}_j\right) - y(h_{j+1}; \mathcal{S}_j), \\ b_k(I) &\doteq \frac{1}{K} \sum_{j \in \mathcal{V}_k} e_j(I), \\ \text{CMSE}_k(I) &\doteq \frac{1}{K} \sum_{j \in \mathcal{V}_k} \left(e_j(I) - b_k(I)\right)^2. \end{aligned} \tag{12}$$

CMSE measures the residual score prediction error after removing the mean bias within the block (Taylor, 2001). The candidate replaces the current IDM only if it lowers the aggregate prediction loss $\mathcal{L}(I)$ without increasing CMSE. The comparison requires complete, valid forecasts from both IDMs for all required instances. Outcome probabilities must form normalized distributions, and numerical predictions must be finite. Figure 5(a) includes all 28 comparisons with complete, valid forecasts from both IDMs within the five 40-generation Polyglot runs. Six archived comparisons from post-budget continuations are excluded.

The calibration offset is initialized to $b = 0$ at the start of a run. Before each revision decision, b is re-estimated as the mean signed score prediction error over valid past records from the current IDM. Errors are computed from uncalibrated predicted scores, with positive values indicating overprediction. For coding, this online estimate uses predictions and observed outcomes on the same fixed ten-task set as the revision decision, even when additional tasks are evaluated. Upon promotion, the candidate's validation-block bias $b_k(I)$ initializes b until valid online records from the new IDM become available. Frozen Selective IDM follows the same online calibration rule while keeping its forecasting program fixed.

A.5 Budgets, Metrics, and Statistical Reporting

We compute task-performance and prediction-error metrics within each evolution run before summarizing results across runs.

AUBC. Generation-based AUBC follows equation 6. Under both generation and token budgets, the performance frontier excludes the initial Hyperagent and starts at zero. It changes only after a descendant's evaluation completes and remains constant between evaluations.

Token budgets count input and output tokens used for agent evolution and task evaluation, including IDM forecasting, updates, and validation. For each comparison, the common budget is the median total token cost of five complete 40-generation runs of the reference baseline. We use HyperAgents as the reference for the main comparisons and Reflective HyperAgents for the coding ablations. This anchors the comparison to the typical cost of a complete baseline run while reducing sensitivity to unusually high or low run costs.

Table 5: **Quality of generated coding descendants.** Values are percentages, reported as medians over five runs. Each metric is computed within a run over all 40 generations.

Method	Mean resolve rate (%)	Full-evaluation generations (%)
HyperAgents	17.00	5.0
Reflective HyperAgents	29.25	35.0
IDM Reflection	36.50	57.5
Frozen Selective IDM	28.25	30.0
Selective IDM	29.50	45.0

Let B denote the common token budget and $F_r(c)$ the best-so-far score in run r at cumulative token use c. We compute

$$\mathrm{AUBC}_{\mathrm{token},r}(B) \doteq \frac{1}{B}\int_0^B F_r(c)\,\mathrm{d}c. \tag{13}$$

If a run finishes below the token budget, its final frontier value is held constant up to the budget. Budget values and additional matched-token comparisons are provided in Appendix B.2.

Statistical reporting. We report medians over five complete runs. Where shown, 95% bootstrap confidence intervals are obtained by resampling runs with replacement. For curves, entire runs are resampled together across budget points, and the intervals are pointwise. Coding and mathematical-grading task-performance plots use 1,000 resamples. Intervals in Table 7 use an exact percentile bootstrap with runs resampled independently within each method.

B Additional Results and Analysis

B.1 Quality of Generated Descendants

For each coding run, we compute every descendant's resolve rate on the same ten preliminary tasks and average these rates over all 40 generations, including generations that solve no tasks. We also measure the fraction of generations that reach full evaluation by solving at least four of the ten tasks. Table 5 summarizes all five configurations.

Selective IDM improves the quality of descendants produced throughout coding evolution. The median run-level mean resolve rate increases from 17.00% for HyperAgents to 29.50% for Selective IDM, while the median fraction of generations reaching full evaluation rises from 5.0% to 45.0%. These gains show that predictive guidance improves not only the best agents tracked by AUBC, but also the broader set of descendants generated during evolution.

Predictive feedback also improves descendant quality when both methods revise every draft once. IDM Reflection achieves a median run-level mean resolve rate of 36.50%, compared with 29.25% for Reflective HyperAgents, and more generations reach full evaluation. Selective IDM likewise exceeds Frozen Selective IDM on both measures, supporting the contribution of IDM updates to the quality of generated descendants.

B.2 Token Costs and Matched-Token Ablations

Following HyperAgents (Zhang et al., 2026b), we report token costs for agent evolution and task evaluation, estimated from interaction logs. Table 6 summarizes mean costs over five complete 40-generation runs. Using HyperAgents as the reference gives matched-token budgets of 44.21M for coding, 111.98M for joint evolution, and 69.36M for mathematical grading.

For the coding ablations, Reflective HyperAgents serves as the reference, giving all four configurations a common budget of 145.79M tokens. Selective IDM achieves the highest median AUBC under this budget, exceeding Reflective HyperAgents, Frozen Selective IDM, and IDM Reflection by 3.9%, 2.9%, and 3.6%, respectively (Figure 8). Its mean cost over complete 40-generation runs is also 18.0% lower than that of IDM Reflection. These results support using an evolving IDM to allocate

Table 6: **Token costs of complete evolution runs.** Values are mean estimated token counts over five 40-generation runs, in millions. Initialization, independent held-out evaluation, and post-hoc analyses are excluded.

Setting	Method	Mean tokens (M)
Coding	HyperAgents	49.45
	Reflective HyperAgents	138.56
	Frozen Selective IDM	134.62
	IDM Reflection	207.58
	Selective IDM	170.22
Joint	HyperAgents	101.67
	Selective IDM	140.61
Math	HyperAgents	69.46
	Selective IDM	99.13
	Transferred IDM	104.15



Figure 8: **Selective IDM retains its advantage under a matched token budget.** Bars show median AUBC over five runs on Polyglot at a common budget of 145.79M tokens. The vertical axis is truncated.

revision effort selectively, improving performance under a matched budget while reducing the cost relative to unconditional IDM-guided revision.

B.3 Run-Level Results

The individual-run results complement the aggregate comparisons in Section 4. Figures 9, 10, and 11 report AUBC under 40-generation and matched-token budgets. Each method contributes five complete runs; circles show individual results and horizontal segments mark their median.

Coding. Selective IDM's advantage over HyperAgents extends across the five runs. All five Selective IDM runs exceed the HyperAgents median under both budgets (Figure 9). Selective IDM also achieves the highest median AUBC among the revision strategies under both budgets. Table 7 reports the differences in median AUBC relative to Reflective HyperAgents, Frozen Selective IDM, and IDM Reflection.



Figure 9: **Individual-run results for coding.** AUBC on Polyglot under (a) 40 generations and (b) a common budget of 145.79M estimated tokens. The token budget is the median cost of five complete Reflective HyperAgents runs and is shared by all five methods. AUBC values are multiplied by 100. The vertical axes are truncated.

Table 7: **Median coding AUBC differences: Selective IDM minus each comparator.** Each entry is Selective IDM minus the comparator, followed by its 95% run-level bootstrap interval. Values are absolute AUBC differences multiplied by 100, not relative percentage gains. The token budget is 145.79M for all methods.

Comparator	40 generations	Matched tokens
Reflective HyperAgents	4.42 [−6.54, 9.25]	1.21 [−6.32, 4.79]
Frozen Selective IDM	2.67 [−3.29, 7.62]	0.92 [−4.73, 2.64]
IDM Reflection	1.71 [−14.17, 5.46]	1.13 [−9.78, 2.85]

Joint evolution. Selective IDM achieves higher median AUBC for paper review, robotics, and the joint objective under both budgets (Figure 10). The gains are observed in both constituent domains as well as in the joint score used to guide evolution.

Mathematical grading. Transferred IDM achieves the highest median AUBC under both budgets (Figure 11). Under each budget, four of the five transfer runs exceed the median of Selective IDM initialized from scratch. The benefit of predictive experience is therefore observed across multiple target-domain runs initialized with the same source-domain IDM.

B.4 Contribution of Modification Information

The IDM forecasts the consequences of a proposed change using evidence from the modification itself. To examine the value of this information, we compare normal forecasts with a *No-diff* condition that withholds the diff and modified source code while retaining parent code, parent outcomes, and historical records. The comparison covers generations 10, 20, and 30 from each of five joint evolution runs, yielding 15 modifications, with the same IDM version, model configuration, and recorded outcomes used for each paired comparison.

Access to modification information reduces mean prediction loss by 16.18% for paper review and 19.98% for robotics, yielding a 16.25% reduction in joint loss (Figure 12). These gains support grounding forecasts in the proposed code change, which provides information about its consequences beyond the parent's observed performance and historical outcomes.



Figure 10: **Individual-run results for joint evolution.** AUBC for paper review, robotics, and the joint objective under (a) 40 generations and (b) a common budget of 111.98M estimated tokens. AUBC values are multiplied by 100. The vertical axes are truncated.



Figure 11: **Individual-run results for mathematical grading.** AUBC under (a) 40 generations and (b) a common budget of 69.36M estimated tokens. AUBC values are multiplied by 100. The vertical axes are truncated.

B.5 Evolution Case Studies

Figure 13 illustrates how task-solving strategies and forecasting rules evolve within a coding run. Along the lineage leading to the final best agent, modifications provide source code and tests before editing, avoid repeated test attempts when no tests are available, and preserve spaces in text-transposition tasks. These changes address both the agent's general workflow and the requirements of specific tasks.

The IDM also develops more explicit criteria for forecasting modification outcomes. Its first update requires a concrete justification for assigning success probabilities above 70%, while the second increases the predicted risk of unfinished runs. Mean prediction loss decreases across the deployed versions. This example illustrates how evolution can refine both task-solving behavior and the forecasting rules used to guide subsequent modifications.



Figure 12: **Modification information improves IDM forecasts.** Relative reduction in mean prediction loss compared with No-diff, which withholds the diff and modified source code while retaining parent code, parent outcomes, and historical records. Comparisons use the same deployed IDM for each of 15 evaluated modifications from five joint evolution runs. Joint loss weights the two domains equally before computing the relative reduction.

Forecast-guided revision. Figure 14 illustrates how predictive feedback guides different kinds of revision. In Coding, a prompt edit left instruction text outside a string literal, introducing a syntax error. The meta agent had noticed the damage but reached its tool-call limit before completing the repair. The IDM assigned a probability of 0.88 to `incomplete` across the task set, and its forecast triggered revision. The meta agent responded by checking the file's syntax and repairing the string boundaries. The final version passed the syntax check and resolved 11 tasks.

In an earlier joint-evolution run, a Paper review modification normalized one form of backslash-newline artifact in extracted paper text. The IDM noted that this format-specific change would likely leave most instances unaffected. During revision, the meta agent inspected saved paper inputs and found embedded prompt-template text that remained after the initial cleanup. It extended the truncation markers to remove these templates and examples. Together, the cases illustrate how forecasts can guide both execution repair and the scope of a proposed modification.

Learning to use historical experience. IDM evolution can also change how past outcomes inform future predictions. In the Coding case in Figure 15, the evolved program adds code that reads archived task outcomes, computes per-task outcome frequencies, and includes these summaries in subsequent forecast inputs. Its updated instructions use these frequencies as priors while allowing specific evidence from the proposed modification to change the prediction. A later deployed forecast explicitly invokes these priors.

The figure also compares the original and updated IDMs on the same historical modification for Python Beer Song. In this comparison, the success probability decreases from 57% to 32%, while the probability of a patch failing its tests increases from 34% to 58%. The submitted patch failed its tests, so the highest-probability prediction changes from incorrect to correct. On a separate validation block collected after the update was proposed, the updated IDM also reduces Brier loss from 0.6169 to 0.5951. This case illustrates how evolution can encode historical experience in the forecasting program and improve its assessment of modification outcomes.



Figure 13: **Task strategies and forecasting rules evolve within the same run.** (a) Best and mean archive scores, together with the lineage leading to the final best agent. (b) Mean online prediction loss during each IDM version's deployment period. Annotations summarize selected changes to the task agent and the IDM.

Using forecasts to revise modifications

	Draft modification	IDM feedback	Revision
Coding Syntax	Prompt edit left instructions outside the string literal, breaking Python syntax.	P(incomplete) = 0.88 for every task.	**Repair string boundaries** and check Python syntax.
Paper Input text	Normalize one form of backslash-newline artifact in extracted paper text.	Format-specific fix; most instances likely remain unchanged.	**Add truncation markers** for embedded prompt templates and examples.

Figure 14: **Forecast-guided revision across tasks.** In Coding, a forecast of widespread incomplete execution prompts syntax repair. In Paper review, a forecast of limited applicability is followed by an expanded preprocessing change.

Learning to use task-specific experience

Coding

Historical evaluation records	New IDM code	Later use (generation 36)
Recorded task-level results from earlier agent modifications.	Read archived outcomes. Compute per-task rates. Add rates to forecast input.	"Based on the instance priors, I'll forecast staying close to historical rates."

Same historical modification: Python / Beer Song

Observed outcome: Patch failed tests.

Retrospective comparison

Forecast	Old IDM	Updated IDM
Success probability	57%	32%
Test-failure probability	34%	58%
Highest-probability outcome	Success (incorrect)	Tests fail (correct)

Figure 15: **Learning to use historical outcomes in forecasting.** The evolved IDM adds per-task outcome summaries to its forecast inputs; the quotation shows their use in a later online forecast. The lower panel separately compares the original and updated IDMs on the same historical modification. The updated IDM's highest-probability prediction matches the observed test failure.