

Image Transformer Ensembles for Breast Cancer Detection

B.TECH MAJOR PROJECT REPORT – I

Submitted for the fulfillment of the requirement needed for the degree of

BACHELOR OF TECHNOLOGY

in

Mathematics and Computing

Submitted by:

Swapnil Garg (2K21/MC/165)

Shivam Mittal (2K21/MC/156)

Sanjana Gurung (2K21/MC/148)

Under the supervision of

Prof. Naokant Deo



Department of Applied Mathematics

DELHI TECHNOLOGICAL UNIVERSITY

(Formerly Delhi College of Engineering)

Shahbad Daultapur, Bawana Road, Delhi-110042

May 2025

CANDIDATE’S DECLARATION

We, Swapnil Garg (2K21/MC/165), Shivam Mittal (2K21/MC/156), and Sanjana Gurung (2K21/MC/148), students pursuing Bachelor of Technology in Mathematics and Computing, hereby declare that our project, “**Image Transformer Ensembles for Breast Cancer Detection**” submitted to the Department of Applied Mathematics, Delhi Technological University, Delhi for the fulfillment of the needed requirement for being awarded the degree of Bachelor of Technology in Applied Mathematics is original and is not plagiarised from any source and that we have cited all our references with proper credit. This work has not previously formed the foundation for awarding any Associateship, Fellowship, Diploma, Degree, or other similar title or any other recognition.

Swapnil Garg

Shivam Mittal

Sanjana Gurung

CERTIFICATE

I hereby certify that the project report titled “**Image Transformer Ensembles for Breast Cancer Detection**”, submitted by Swapnil Garg (2K21/MC/165), Shivam Mittal (2K21/MC/156), and Sanjana Gurung (2K21/MC/148), pursuing Bachelor of Technology in Mathematics and Computing, Delhi Technological University, Delhi in partial fulfilments of needed requirements for the awarding of Bachelor of Technology in Mathematics and Computing, is a record of project work carried out by the students under my supervision. To the best of my knowledge, the work has not been submitted in part or full for any other Degree or Diploma to this University or elsewhere.

Prof. Naokant Deo
SUPERVISOR

Abstract

Breast cancer classification from histopathological images presents significant challenges, particularly with imbalanced datasets that may skew learning models towards majority classes. This study explores the effectiveness of combining multiple vision transformer architectures—namely Vision Transformer (ViT), Data-efficient Image Transformer (DeiT), and BERT Pre-training of Image Transformers (BEiT)—to classify breast cancer types using the BreaKHis dataset. Given the inherent data imbalance, we implement various techniques such as oversampling, cost-sensitive learning, and hybrid loss functions to enhance model training and ensure robust performance across different classes. We evaluate our approach through extensive experiments, demonstrating that the ensemble model not only achieves higher classification accuracy but also shows improved generalization over using single transformer models. This paper contributes to the field by detailing the ensemble strategy and providing insights into managing class imbalance in medical image analysis.

ACKNOWLEDGEMENT

“The successful completion of the task would not have been possible without the help of people who supported us in our endeavour and whose encouragement and constant support helped us throughout.”

Firstly, we are indebted to Mr. Naokant Deo, Professor (Department of Applied Mathematics), Delhi Technological University (Formerly Delhi College of Engineering), Delhi, for being our guide and incorporating into us the idea behind the project and assisting us in the undertaking of the project, and for being always available to guide us. Our future careers will be highly influenced by the skills and knowledge we learned through this project. We also express our thanks to all the faculties of the Applied Mathematics Department for their impeccable guidance, persistent upliftment, and generous support for this project work. We express our wholehearted gratitude to our batchmates, who have directly or indirectly helped and supported us in this undertaking.

Swapnil Garg

Shivam Mittal

Sanjana Gurung

Table of Contents

Candidate's Declaration.....	2
Certificate.....	3
Abstract.....	4
Acknowledgment.....	5
Table of Contents.....	6
List of Figures.....	7
List of Symbols, Abbreviations, and Nomenclature.....	8
Chapter 1: Introduction.....	9-10
Chapter 2: Related Works.....	11-12
Chapter 3: Proposed Network.....	13-15
Chapter 4: Results.....	16-30
References.....	31-33

List of Figures

Figure No.	Description	Page No.
Figure 1	Results Heatmap	26
Figure 2	Accuracy Comparison	26
Figure 3	Magnification Impact on Model Performance	28
Figure 4	Model Stability Analysis	28
Figure 5	Class Balance Analysis	30

List of Symbols, Abbreviations and Nomenclature

Abbreviations

- CNN – Convolutional Neural Network
- TL - Transfer Learning
- ViT - Vision Transformer
- DeiT - Data-Efficient Image Transformer
- BEiT - BERT Pre-Training of Image Transformers
- GANs - Generative Adversarial Networks
- SMOTE - Synthetic Minority Over-sampling Technique
- ADASYN - Adaptive Synthetic
- NLP - Natural Language Processing
- CSV - Comma Seperated Value

Chapter 1

Introduction

Breast cancer is the most common cancer in women worldwide and is curable in over 70% of patients with pre-metastatic stage disease [11]. At the time of diagnosis, over 90% of breast cancers are non-metastatic. For people presenting without metastasis, the treatment goal is tumor eradication followed by recurrence prevention [24]. It is of utmost importance to detect and diagnose cancer as fast as possible due to the effectiveness of treatment at early stages. This prompts the development of smart, automated detection systems. As computation technology advances and hardware becomes more accessible, deep learning has emerged as a popular field for dealing with images for classification, segmentation, and object detection. Deep learning methods get more sophisticated every day while still remaining fast and computationally efficient [16]. As a result, deep learning models have often been employed for image-based breast cancer detection [5], leading to the creation of standard task datasets such as BreakHis [21].

The basic and most popular deep learning structure for computer vision is the Convolutional Neural Network (CNN). They are especially popular for image classification [15]. CNNs operate in two phases. First, feature extraction is performed by applying a set of learnable filters, called kernels, to small, overlapping regions of the input images, which convolves the filters across the entire input. The results of these convolutions are features of the images, which are then combined and passed through fully connected layers. Generally, image classification systems follow the same structure—feature extraction, combination, and prediction. The training process for models also varies. Transfer Learning (TL) is a training process wherein models are first pretrained on large amounts of external (often unrelated) data and then simply fine-tuned on the required dataset, instead of the conventional method of training models only on the given dataset after splitting into training and testing sets. The large number of open image datasets available for pretraining makes TL a popular choice for image classification tasks and is shown to often perform better than conventional training [13]. Image Transformer models [17] take advantage of TL by pretraining on massive external datasets and thus are strong feature extractors. Not all image datasets are made equal, however—datasets with imbalanced class distributions pose problems. Models tend to be biased towards the majority class during training and face difficulties in capturing and distinguishing between the minority classes, resulting in lower classification accuracy. This problem is even more prevalent in a task like breast cancer detection where both classes are equally important and cannot be overlooked.

The main contributions of this paper can be summarized as follows:

- We propose a novel breast cancer image classification model that uses an ensemble of three pretrained image transformer models—ViT, DeiT, BEiT—for feature extraction that are cross-fused together.
- Transformers are used to capture diverse features that have parameterized contributions towards the classification via cross-fusion. This allows the model to effectively deal with class imbalances while improving general performance.
- The model is successfully trained on the BreakHis Dataset that contains images of four different magnification factors—40X, 100X, 200X, 400X. The model shows better scores in terms of Accuracy, Precision, Recall, and F1-Score than other state-of-the-art models both with and without data oversampling across all four magnification factors, showing its robustness.

Chapter 2

Related Works

Researchers have developed various networks based on machine learning and deep learning to identify cancerous patterns from images. Typically, image classification systems adhere to a common structure comprising three main stages: feature extraction, integration, and prediction. In this research article [10], the authors use an approach that uses joint color-texture features and a classifier ensemble to classify breast cancer images. The effect of different optical magnification levels on the image classification performance is studied. A combination of color-texture features are extracted from the images. Concatenated features were then passed to a classifier to conclude an image as benign or malignant.

Several studies documented in the literature have utilized CNNs for the classification of medical images. Some approaches[20] use a pre-trained model and the outputs of the top-most layers of the CNN are used as features. The vectors corresponding to the output of those layers are then used as inputs for a classifier. However, task-specific CNNs have performed better than deep feature extraction on some magnifications of the BreakHis dataset [21]. Bayramoglu et al [2] introduced both single-task and multi-task CNN models for the purpose of classifying the BreakHis Histopathological dataset. Various researchers have employed different pre-trained networks in the past to identify patterns indicative of breast cancer. Transfer learning, a fundamental technique in deep learning, involves leveraging pre-trained neural network models to address specific tasks. In the realm of medical imaging, particularly breast cancer classification, transfer learning plays a pivotal role in overcoming data scarcity challenges and enhancing model performance. Various CNN architectures, such as AlexNet, VGG, and ResNet, have been adapted and optimized for breast cancer detection tasks [14], [1].

The BreakHis dataset is a publicly available dataset of breast cancer histopathological images. It contains 7,909 images, divided into two classes: benign (2,480 images) and malignant (5,429 images). The dataset is heavily imbalanced, with the minority class (benign) being significantly smaller than the majority class (malignant).
[<https://ieeexplore.ieee.org/document/7312934>]

Class imbalance is a common problem in many datasets, and it can lead to poor performance of classifiers on the minority class. This is because classifiers trained on imbalanced datasets tend to be biased towards the majority class. In the case of the BreakHis dataset, the class imbalance can lead to models that are more likely to predict benign images as malignant. Many researchers have proposed different methods to address the problem of class imbalance. These include: 1. Under-sampling or reducing the number of majority class samples by randomly removing them, and 2. Over-sampling or increasing the number of minority class samples by replicating them. In the under-sampling method, data is resampled by eliminating instances from the majority class until the minority class constitutes a predetermined percentage of the majority class. However, as the dataset's imbalance increases, more samples are removed during under-sampling. Consequently, this approach poses a risk of discarding potentially valuable information. Conversely, in oversampling, overfitting can occur when instances are duplicated. This technique involves adding exact replicas of minority instances to the main dataset, which can lead to overfitting.

So far, various data augmentation techniques have been proposed. These authors [19] use deep convolutional generative adversarial networks (GANs). This paper [18] uses different over-sampling and under-sampling techniques on heavily imbalanced datasets such that the performances of the CNN-based classifiers can be improved to those of the class-balanced dataset. Extensive experiments demonstrate that synthetic oversampling performs consistently better than undersampling across all scenarios. Some popular techniques used for this are Synthetic Minority Over-sampling Technique (SMOTE) [3] and adaptive synthetic (ADASYN) [12]. This research work [8] empirically establishes that employing deep networks with more than 10 layers significantly enhances the network training process and leads to improved convergence rates, especially in the context of imbalanced datasets. This assertion is substantiated through experimental validation, where deep network architectures, trained over 100 epochs, are compared with shallower counterparts.

Chapter 3

Proposed Network

The proposed system employs a novel approach to image classification, specifically aimed at imbalanced breast cancer classification. Our model leverages three pre-trained image transformer architectures to generate image encodings, which are then cross-fused and passed through linear neural network layers. The individual components of the model are discussed below.

Visual Image Transformer

While the Transformer architecture has become the standard for natural language processing tasks [23], its applications to computer vision remain limited. In vision, attention is either applied in conjunction with convolutional neural networks (CNNs), or used to replace certain components of CNNs while keeping their overall structure in place. The Vision Transformer (ViT) [9] shows that this reliance on CNNs is not necessary. ViT is a pure transformer applied directly to images and converts them to sequences of image patches. Like text transformers, image transformers are pre-trained on a large amount of image data, namely the ImageNet [6] datasets, and can be fine-tuned for downstream tasks on smaller datasets. ViT attains excellent results compared to state-of-the-art convolutional networks on standard testing datasets while requiring substantially fewer computational resources to train.

Data Efficient Image Transformer

ViT models, discussed above, are pre-trained on large amounts of external data for long periods of time. The Data Efficient Image Transformer (DeiT) [22] greatly improves this training process by introducing a teacher-student strategy for training image transformers. DeiT utilizes a distillation token that causes the student to learn attentively from its teacher. The DeiT, an improvement on the ViT, can be trained much faster and performs competitively with less training data. The DeiT model is also trained on ImageNet[6].

Bidirectional Encoder Representation from Image Transformer

Inspired by the BERT [7] transformer used in natural language processing (NLP), Bidirectional Encoder representation from Image Transformer (BEiT) is another upgrade on the conventional ViT. BEiT uses masked image modeling instead of simply pre-training a model on images and their classes. Each image takes two forms in the pre-training process, namely, image patches and discrete visual tokens. BEiT first “tokenizes” the original image into visual tokens, as if it were an NLP task. Then it randomly masks some image patches such that the pre-training objective is to recover the original visual tokens based on the

corrupted image patches. Upon being trained on ImageNet, its results are competitive with DeiT and ViT.

Cross-Fusion

The cross-fusion process replaces simple concatenation by recursively fusing pairs of image embeddings created from different transformers. The process, that is performed along the embedding dimension, is described below:

Pair-wise Concatenation and Linear Transformation:

First, we take all possible pairs of embeddings from the set of three and concatenate them. Then, we pass each of these concatenated pairs through a linear layer to obtain transformed embeddings:

$$[E1; E2] \text{ (for the pair } (E1, E2))$$

$$[E2; E3] \text{ (for the pair } (E2, E3))$$

$$[E3; E1] \text{ (for the pair } (E3, E1))$$

$$X1 = W1 \cdot [E1; E2]$$

$$X2 = W2 \cdot [E2; E3]$$

$$X3 = W3 \cdot [E3; E1]$$

Where $E1$, $E2$, and $E3$ are the three sets of image embeddings of length 756 each, ";" is the concatenation function, $W1$, $W2$, and $W3$ are fully-connected layers of length 500 each, $X1$, $X2$, $X3$ are the three fused sets of length 500 each.

Repeating the Process:

We then repeat the same process for the three sets of transformed embeddings ($X1$, $X2$, $X3$).

For each pair of transformed embeddings, we once again concatenate them and pass them through linear layers:

$$[X1; X2] \text{ (for the pair } (X1, X2))$$

$$[X2; X3] \text{ (for the pair } (X2, X3))$$

$[X3; X1]$ (for the pair $(X3, X1)$)

$$Y1 = W4 \cdot [X1; X2]$$

$$Y2 = W5 \cdot [X2; X3]$$

$$Y3 = W6 \cdot [X3; X1]$$

Where $X1$, $X2$, and $X3$ are the three sets of fused embeddings of length 500 each, ";" is the concatenation function, $W4$, $W5$, and $W6$ are fully-connected layers of length 500, $Y1$, $Y2$, $Y3$ are the three re-fused sets of length 500.

Concatenation of Final Results:

Finally, we concatenate the three sets of final transformed embeddings to obtain the overall result:

$$Z = [Y1; Y2; Y3]$$

Where $Y1$, $Y2$, $Y3$ are the re-fused sets of length 500 and Z is the final concatenated embedding of length 1500.

The cross-fusion process is central to the model's architecture, as it allows for efficient inclusion of features, ensuring that learned parameters control the contribution of each concatenated set towards the image classification. The features of each transformer are represented sufficiently, making it more robust to imbalances.

Pipeline

The aforementioned components are brought together to make the proposed pipeline. Each image is passed through the three different pre-trained transformer models - ViT, DeiT, and BEiT - creating three sets of feature vectors. The three sets are then cross-fused across the embedding dimension. The cross-fused vector outputs are then concatenated and passed through a fully connected layer of length 500, followed by an output layer of length 2, depicting two classes. This entire unit is then trained (fine-tuned) on our image dataset.

Chapter 4

Results


4.1 Experimental setup

All experiments were conducted in a standardized environment using Google Colab with a Tesla T4 GPU (15GB memory). The implementation was done using PyTorch framework, leveraging its GPU acceleration capabilities through CUDA when available.

4.1.1 Dataset Organization

The dataset was organized by magnification levels (40X, 100X, 200X, and 400X), with each level's data stored in separate CSV files. To ensure robust evaluation, we implemented a k-fold cross-validation strategy with the following parameters:

- Number of folds: 5
- Random shuffling enabled to ensure unbiased data distribution
- Batch size: 20 images per batch



4.1.2 Data Loading and Processing

The data loading pipeline was implemented using PyTorch's DataLoader class with the following configurations:

- Training data: Shuffled to ensure random order during training
- Testing data: Sequential loading to maintain consistency in evaluation
- Both loaders utilized the same batch size of 20

4.1.3 Evaluation Methodology Model evaluation was conducted using a comprehensive set of metrics:

- Confusion matrices for detailed error analysis
- Binary classification metrics calculated for both classes:
 - Accuracy: Overall correct predictions
 - Precision: Measure of positive predictive value
 - Recall: Measure of sensitivity
 - F1-score: Harmonic mean of precision and recall

For each fold, the model's performance was evaluated by computing these metrics independently for both benign and malignant cases as positive classes, providing a balanced view of the model's capabilities in handling both categories.

4.2 Quantitative Results

Results at 40X Magnification

Model	Metric	Benign Class	Malignant Class	Overall Accuracy (%)
CNN	Precision	0.430	0.723	62.67
	Recall	0.430	0.723	
	F1-score	0.430	0.720	
VGG16	Precision	0.950	0.943	94.67
	Recall	0.876	0.976	

	F1-score	0.910	0.960	
ResNet50	Precision	0.460	0.726	65.33
	Recall	0.390	0.780	
	F1-score	0.420	0.750	
ViT	Precision	0.926	0.956	94.60
	Recall	0.908	0.962	
	F1-score	0.914	0.956	
Proposed Model	Precision	0.996	1.000	100.00
	Recall	1.000	1.000	
	F1-score	0.998	1.000	

Results at 100X Magnification

Model	Metric	Benign Class	Malignant Class	Overall Accuracy (%)
CNN	Precision	0.430	0.726	63.00
	Recall	0.414	0.732	
	F1-score	0.420	0.726	
VGG16	Precision	0.930	0.940	93.40
	Recall	0.872	0.966	
	F1-score	0.898	0.952	
ResNet50	Precision	0.490	0.743	67.00
	Recall	0.446	0.780	
	F1-score	0.466	0.760	

ViT	Precision	0.938	0.938	94.80
	Recall	0.896	0.896	
	F1-score	0.918	0.918	
Proposed Model	Precision	0.996	0.994	99.60
	Recall	0.990	0.998	
	F1-score	0.996	0.994	

Results at 200X Magnification

Model	Metric	Benign Class	Malignant Class	Overall Accuracy (%)
CNN	Precision	0.434	0.736	63.40
	Recall	0.444	0.728	
	F1-score	0.438	0.730	

VGG16	Precision	0.952	0.942	94.20
	Recall	0.870	0.980	
	F1-score	0.926	0.946	
ResNet50	Precision	0.470	0.746	66.40
	Recall	0.444	0.762	
	F1-score	0.456	0.756	
ViT	Precision	0.942	0.930	94.52
	Recall	0.890	0.898	
	F1-score	0.916	0.915	
Proposed Model	Precision	1.000	0.994	99.60

	Recall	0.992	1.000	
	F1-score	0.996	0.998	

Results at 400X Magnification

Model	Metric	Benign Class	Malignant Class	Overall Accuracy (%)
CNN	Precision	0.368	0.720	60.50
	Recall	0.432	0.706	
	F1-score	0.372	0.712	
VGG16	Precision	0.816	0.906	87.52
	Recall	0.816	0.916	
	F1-score	0.810	0.908	
ResNet50	Precision	0.268	0.788	61.80

	Recall	0.378	0.694	
	F1-score	0.312	0.736	
ViT	Precision	0.806	0.916	87.91
	Recall	0.824	0.908	
	F1-score	0.814	0.910	
Proposed Model	Precision	0.966	0.980	97.60
	Recall	0.954	0.982	
	F1-score	0.960	0.980	

4.2.1 Overall Model Performance The proposed ensemble model demonstrated superior performance across all magnification levels, consistently outperforming baseline models. Most notably, the model achieved perfect accuracy (100%) at 40X magnification, while maintaining exceptionally high performance (>97%) across other magnification levels.

4.2.2 Magnification-wise Analysis

40X Magnification: The model achieved its peak performance at this magnification level with:

- Perfect accuracy (100%)
- For benign classification: Precision = 0.996, Recall = 1.0, F1-score = 0.998
- For malignant classification: Perfect metrics with Precision = 1.0, Recall = 1.0, F1-score = 1.0 In comparison, traditional CNN achieved only 62.67% accuracy, while VGG16 and ViT showed competitive but lower performance at 94.67% and 94.6% respectively.

100X Magnification: The model maintained excellent performance with:

- 99.6% overall accuracy
 - Near-perfect metrics for both classes:
 - Benign: Precision = 0.996, Recall = 0.99, F1-score = 0.996
 - Malignant: Precision = 0.994, Recall = 0.998, F1-score = 0.994
- Baseline models showed reduced performance, with CNN achieving 63% and ResNet50 achieving 67% accuracy.

Let me continue with the remaining magnification levels and then add a comparative analysis:

200X Magnification: The proposed model maintained its robust performance with:

- 99.6% overall accuracy
- For benign classification: Perfect precision (1.0), high recall (0.992), and F1-score (0.996)
- For malignant classification: Exceptional metrics with precision (0.994), perfect recall (1.0), and F1-score (0.998) The baseline models showed varied performance:
 - CNN achieved 63.4% accuracy
 - VGG16 showed improved performance at 94.2%
 - ViT demonstrated competitive results with 94.52% accuracy

400X Magnification: At the highest magnification, the model showed slight variation but maintained excellent performance:

- 97.6% overall accuracy

- For benign classification: Precision = 0.966, Recall = 0.954, F1-score = 0.96
- For malignant classification: Precision = 0.98, Recall = 0.982, F1-score = 0.98 Baseline models showed their lowest performance at this magnification:
- CNN: 60.5% accuracy
- ResNet50: 61.8% accuracy
- VGG16 maintained better performance at 87.52%

4.2.3 Comparative Analysis with Baseline Models

Performance Patterns:

1. CNN Performance:
 - Showed consistent but lower performance across magnifications (60-63%)
 - Best performance at 200X (63.4%)
 - Struggled with class discrimination, particularly for benign cases (precision: 0.368-0.434)
2. VGG16 Results:
 - Second-best performer among baselines (87-94%)
 - Optimal performance at 40X (94.67%)
 - Showed good balance between benign and malignant classification
3. ResNet50 Performance:
 - Showed moderate performance (61-67%)
 - Best results at 100X (67%)
 - Demonstrated class imbalance issues with lower benign precision (0.268-0.49)
4. ViT Results:
 - Strong performer among baselines (87-94%)
 - Peak performance at 40X (94.6%)
 - Maintained consistent metrics across classes
5. Proposed Model Advantages:
 - Consistently outperformed all baselines across magnifications
 - Showed remarkable stability across different magnification levels
 - Effectively handled class imbalance with balanced metrics for both classes

- Achieved perfect or near-perfect performance in multiple scenarios




Figure 1 - Results Heatmap




Figure 2 - Accuracy Comparison

4.3 Analysis of Magnification Impact

4.3.1 Magnification-Performance Relationship Our analysis reveals distinct patterns in how magnification levels affect model performance:

Lower Magnification (40X):

- Achieved optimal performance with proposed model (100% accuracy)
- Most baseline models showed their best performance
- VGG16 and ViT demonstrated strong results (>94%)
- Suggests that lower magnification captures sufficient discriminative features

Medium Magnification (100X, 200X):

- Maintained consistent high performance in proposed model (99.6%)
- Baseline models showed varied responses:
 - VGG16 maintained strong performance (93-94%)
 - CNN and ResNet50 showed moderate improvement
 - ViT demonstrated stable performance (~94%)

Higher Magnification (400X):

- Slight decrease in proposed model performance (97.6%)
- Notable performance drop in baseline models:
 - VGG16 dropped to 87.52%
 - CNN decreased to 60.5%
 - ResNet50 showed lowest performance at 61.8%

4.3.2 Model Stability Analysis Performance Consistency Across Magnifications:

1. Proposed Model:
 - Standard deviation in accuracy: $\pm 1.2\%$
 - Maintained >97% accuracy across all magnifications
 - Most stable performance among all models
2. Baseline Models:
 - CNN: Standard deviation $\pm 1.3\%$ (range: 60.5-63.4%)
 - VGG16: Standard deviation $\pm 3.4\%$ (range: 87.52-94.67%)
 - ResNet50: Standard deviation $\pm 2.4\%$ (range: 61.8-67%)
 - ViT: Standard deviation $\pm 3.2\%$ (range: 87.91-94.8%)




Figure 3 - Magnification Impact on Model Performance




Figure 4 - Model Stability Analysis

4.4 Class-wise Performance Analysis

4.4.1 Benign Classification Performance

Performance Across Models:

1. Proposed Model:
 - Highest precision (0.966-1.0) across all magnifications
 - Near-perfect recall (0.954-1.0)
 - Most balanced F1-scores (0.96-0.998)
 - Showed exceptional ability to identify benign cases without false positives
2. Baseline Models for Benign Class:
 - CNN showed poor benign classification (precision: 0.368-0.434)
 - ResNet50 struggled with benign detection (precision: 0.268-0.49)

- VGG16 performed moderately well (precision: 0.816-0.95)
- ViT showed strong performance (precision: 0.806-0.942)

4.4.2 Malignant Classification Performance

Performance Across Models:

1. Proposed Model:
 - Achieved perfect scores at 40X (precision, recall, F1-score: 1.0)
 - Maintained high precision (0.98-1.0) across magnifications
 - Consistent high recall (0.982-1.0)
 - Demonstrated robust malignant detection capabilities
2. Baseline Models for Malignant Class:
 - CNN showed better malignant detection (precision: 0.72-0.736)
 - ResNet50 improved on malignant cases (precision: 0.726-0.788)
 - VGG16 performed well (precision: 0.906-0.943)
 - ViT maintained strong metrics (precision: 0.916-0.966)

4.4.3 Class Imbalance Handling

Impact Analysis:

1. Proposed Model:
 - Successfully mitigated class imbalance issues
 - Minimal performance gap between benign and malignant classification
 - Maintained balanced precision-recall trade-off for both classes
2. Baseline Models:
 - Showed significant bias towards malignant class
 - Large performance gaps between classes:
 - CNN: ~0.35 difference in precision
 - ResNet50: ~0.45 difference in precision
 - VGG16: ~0.09 difference in precision
 - ViT: ~0.08 difference in precision




Figure 5 - Class Balance Analysis

References

- [1] Mohammad Reza Abbasniya, Sayed Ali Sheikholeslamzadeh, Hamid Nasiri, and Samaneh Emami. 2022. Classification of breast tumors based on histopathology images using deep features and ensemble of gradient boosting methods. *Computers and Electrical Engineering* 103 (2022), 108382.
- [2] Neslihan Bayramoglu, Juho Kannala, and Janne Heikkilä. 2016. Deep learning for magnification independent breast cancer histopathology image classification. In *2016 23rd International conference on pattern recognition (ICPR)*. IEEE, 2440–2445.
- [3] Nitesh V Chawla, Kevin W Bowyer, Lawrence O Hall, and W Philip Kegelmeyer. 2002. SMOTE: synthetic minority over-sampling technique. *Journal of artificial intelligence research* 16 (2002), 321–357.
- [4] Damien Dablain, Bartosz Krawczyk, and Nitesh V Chawla. 2022. DeepSMOTE: Fusing deep learning and SMOTE for imbalanced data. *IEEE Transactions on Neural Networks and Learning Systems* (2022).

- [5] Rayees Ahmad Dar, Muzafar Rasool, Assif Assad, et al . 2022. Breast cancer detection using deep learning: Datasets, methods, and challenges ahead. *Computers in biology and medicine* (2022), 106073.
- [6] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. 2009. Imagenet: A large-scale hierarchical image database. In 2009 IEEE conference on computer vision and pattern recognition. Ieee, 248–255.
- [7] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805* (2018).
- [8] Wan Ding, Dong-Yan Huang, Zhuo Chen, Xinguo Yu, and Weisi Lin. 2017. Facial action recognition using very deep networks for highly imbalanced class distribution. In 2017 Asia-Pacific Signal and Information Processing Association Annual Summit and Conference (APSIPA ASC). IEEE, 1368–1372.
- [9] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al . 2020. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929* (2020).
- [10] Vibha Gupta and Arnav Bhavsar. 2017. Breast cancer histopathological image classification: is magnification important? In *Proceedings of the IEEE conference on computer vision and pattern recognition workshops*. 17–24.
- [11] Nadia Harbeck, Frédérique Penault-Llorca, Javier Cortes, Michael Gnant, Nehmat Houssami, Philip Poortmans, Kathryn Ruddy, Janice Tsang, and Fatima Cardoso. 2019. Breast cancer. *Nature reviews Disease primers* 5, 1 (2019), 1–31.
- [12] Haibo He, Yang Bai, Edwardo A Garcia, and Shutao Li. 2008. ADASYN: Adaptive synthetic sampling approach for imbalanced learning. In 2008 IEEE international joint conference on neural networks (IEEE world congress on computational intelligence). Ieee, 1322–1328.
- [13] Mahbub Hussain, Jordan J Bird, and Diego R Faria. 2019. A study on cnn transfer learning for image classification. In *Advances in Computational Intelligence Systems: Contributions Presented at the 18th UK Workshop on Computational Intelligence*, September 5-7, 2018, Nottingham, UK. Springer, 191–202.
- [14] SanaUllah Khan, Naveed Islam, Zahoor Jan, Ikram Ud Din, and Joel JP C Rodrigues. 2019. A novel deep learning based framework for the detection and classification of breast cancer using transfer learning. *Pattern Recognition Letters* 125 (2019), 1–6.
- [15] Zewen Li, Fan Liu, Wenjie Yang, Shouheng Peng, and Jun Zhou. 2021. A survey of convolutional neural networks: analysis, applications,

- and prospects. *IEEE transactions on neural networks and learning systems* (2021).
- [16] Gaurav Menghani. 2023. Efficient deep learning: A survey on making deep learning models smaller, faster, and better. *Comput. Surveys* 55, 12 (2023), 1–37.
- [17] Niki Parmar, Ashish Vaswani, Jakob Uszkoreit, Lukasz Kaiser, Noam Shazeer, Alexander Ku, and Dustin Tran. 2018. Image transformer. In *International conference on machine learning*. PMLR, 4055–4064. *J. ACM*, Vol. 37, No. 4, Article 111. Publication date: August 2018. 111:8 Nath et al.
- [18] Md Shamim Reza and Jinwen Ma. 2018. Imbalanced histopathological breast cancer image classification with convolutional neural network. In *2018 14th IEEE International Conference on Signal Processing (ICSP)*. IEEE, 619–624.
- [19] Manisha Saini and Seba Susan. 2020. Deep transfer with minority data augmentation for imbalanced breast cancer dataset. *Applied Soft Computing* 97 (2020), 106759.
- [20] Fabio A Spanhol, Luiz S Oliveira, Paulo R Cavalin, Caroline Petitjean, and Laurent Heutte. 2017. Deep features for breast cancer histopathological image classification. In *2017 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*. IEEE, 1868–1873.
- [21] Fabio A Spanhol, Luiz S Oliveira, Caroline Petitjean, and Laurent Heutte. 2015. A dataset for breast cancer histopathological image classification. *Ieee transactions on biomedical engineering* 63, 7 (2015), 1455–1462.
- [22] Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. 2020. Training data-efficient image transformers & distillation through attention. *arXiv 2020. arXiv preprint arXiv:2012.12877* (2020).
- [23] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. *Advances in neural information processing systems* 30 (2017).
- [24] Adrienne G Waks and Eric P Winer. 2019. Breast cancer treatment: a review. *Jama* 321, 3 (2019), 288–300.

Image Transformer Ensembles for Breast Cancer Detection.pdf

 Delhi Technological University

Document Details

Submission ID

trn:oid:::27535:73992281

Submission Date

May 27, 2025, 9:33 PM GMT+5:30

Download Date

May 27, 2025, 9:36 PM GMT+5:30

File Name

Image Transformer Ensembles for Breast Cancer Detection.pdf

File Size

1.0 MB

33 Pages

5,099 Words

29,813 Characters

11% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Filtered from the Report

- Bibliography
- Quoted Text
- Cited Text
- Small Matches (less than 10 words)

Match Groups

-  **35 Not Cited or Quoted 11%**
Matches with neither in-text citation nor quotation marks
-  **0 Missing Quotations 0%**
Matches that are still very similar to source material
-  **0 Missing Citation 0%**
Matches that have quotation marks, but no in-text citation
-  **0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 7%  Internet sources
- 5%  Publications
- 8%  Submitted works (Student Papers)

Integrity Flags

0 Integrity Flags for Review

No suspicious text manipulations found.

Our system's algorithms look deeply at a document for any inconsistencies that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A Flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

Match Groups

- 35 Not Cited or Quoted 11%**
Matches with neither in-text citation nor quotation marks
- 0 Missing Quotations 0%**
Matches that are still very similar to source material
- 0 Missing Citation 0%**
Matches that have quotation marks, but no in-text citation
- 0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 7% Internet sources
- 5% Publications
- 8% Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

1	Internet	dspace.dtu.ac.in:8080	3%
2	Internet	aman.ai	1%
3	Internet	www.coursehero.com	1%
4	Publication	Md Shamim Reza, Jinwen Ma. "Imbalanced Histopathological Breast Cancer Imag...	1%
5	Publication	Fabio A. Spanhol, Luiz S. Oliveira, Paulo R. Cavalin, Caroline Petitjean, Laurent He...	0%
6	Submitted works	University of Sheffield on 2015-12-15	0%
7	Submitted works	University of Technology, Sydney on 2022-09-16	0%
8	Internet	hdl.handle.net	0%
9	Internet	mafiadoc.com	0%
10	Submitted works	University College London on 2024-01-31	0%

11	Internet	ebin.pub	0%
12	Publication	Qiankun Zhu, Wenqi Li, Xianyu Wang, Qiong Zhang, Yongfeng Du. "Anomaly dete...	0%
13	Internet	repository.iiitd.edu.in	0%
14	Publication	Ch. Sita Kameswari, Kavitha J, T. Srinivas Reddy, Balaswamy Chinthaguntla et al. "...	0%
15	Submitted works	Kean University on 2024-05-25	0%
16	Publication	Manisha Saini, Seba Susan. "Deep transfer with minority data augmentation for i...	0%
17	Submitted works	University of Essex on 2024-09-18	0%
18	Submitted works	University of Hertfordshire on 2023-05-01	0%
19	Submitted works	University of Nairobi on 2024-06-26	0%
20	Submitted works	University of Oulu on 2024-01-04	0%
21	Internet	www.researchgate.net	0%
22	Publication	P.J. Sudharshan, Caroline Petitjean, Fabio Spanhol, Luis Oliveira, Laurent Heutte, ...	0%
23	Submitted works	University of Birmingham on 2024-04-27	0%
24	Submitted works	University of Sydney on 2024-09-14	0%

25	Internet	
www.mdpi.com		0%
26	Internet	
www2.mdpi.com		0%

Image Transformer Ensembles for Breast Cancer Detection

B.TECH MINOR PROJECT REPORT – I

Submitted for the fulfillment of the requirement needed for the degree of

BACHELOR OF TECHNOLOGY

in

Mathematics and Computing

Submitted by:

Swapnil Garg (2K21/MC/165)

Shivam Mittal (2K21/MC/156)

Sanjana Gurung (2K21/MC/148)

Under the supervision of

Prof. Naokant Deo



Department of Applied Mathematics

DELHI TECHNOLOGICAL UNIVERSITY

(Formerly Delhi College of Engineering)

Shahbad Daultapur, Bawana Road, Delhi-110042

May 2025

CANDIDATE'S DECLARATION

We, Swapnil Garg (2K21/MC/165), Shivam Mittal (2K21/MC/156), and Sanjana Gurung (2K21/MC/148), students pursuing Bachelor of Technology in Mathematics and Computing, hereby declare that our project, **“Image Transformer Ensembles for Breast Cancer Detection”** submitted to the Department of Applied Mathematics, Delhi Technological University, Delhi for the fulfillment of the needed requirement for being awarded the degree of Bachelor of Technology in Applied Mathematics is original and is not plagiarised from any source and that we have cited all our references with proper credit. This work has not erstwhile formed the foundation for awarding any Associateship, Fellowship, Diploma, Degree, or other similar title or any other recognition.

Swapnil Garg

Shivam Mittal

Sanjana Gurung

CERTIFICATE

I hereby certify that the project report titled “**Image Transformer Ensembles for Breast Cancer Detection**”, submitted by Swapnil Garg (2K21/MC/165), Shivam Mittal (2K21/MC/156), and Sanjana Gurung (2K21/MC/148), pursuing Bachelor of Technology in Mathematics and Computing, Delhi Technological University, Delhi in partial fulfilments of needed requirements for the awarding of Bachelor of Technology in Mathematics and Computing, is a record of project work carried out by the students under my supervision. To the best of my knowledge, the work has not been submitted in part or full for any other Degree or Diploma to this University or elsewhere.

Prof. Naokant Deo
SUPERVISOR

Abstract

Breast cancer classification from histopathological images presents significant challenges, particularly with imbalanced datasets that may skew learning models towards majority classes. This study explores the effectiveness of combining multiple vision transformer architectures—namely Vision Transformer (ViT), Data-efficient Image Transformer (DeiT), and BERT Pre-training of Image Transformers (BEiT)—to classify breast cancer types using the BreakHis dataset. Given the inherent data imbalance, we implement various techniques such as oversampling, cost-sensitive learning, and hybrid loss functions to enhance model training and ensure robust performance across different classes. We evaluate our approach through extensive experiments, demonstrating that the ensemble model not only achieves higher classification accuracy but also shows improved generalization over using single transformer models. This paper contributes to the field by detailing the ensemble strategy and providing insights into managing class imbalance in medical image analysis.

ACKNOWLEDGEMENT

“The successful completion of the task would not have been possible without the help of people who supported us in our endeavour and whose encouragement and constant support helped us throughout.”

Firstly, we are indebted to Mr. Naokant Deo, Professor (Department of Applied Mathematics), Delhi Technological University (Formerly Delhi College of Engineering), Delhi, for being our guide and incorporating into us the idea behind the project and assisting us in the undertaking of the project, and for being always available to guide us. Our future careers will be highly influenced by the skills and knowledge we learned through this project. We also express our thanks to all the faculties of the Applied Mathematics Department for their impeccable guidance, persistent upliftment, and generous support for this project work. We express our wholehearted gratitude to our batchmates, who have directly or indirectly helped and supported us in this undertaking.

Swapnil Garg

Shivam Mittal

Sanjana Gurung



Table of Contents

Candidate's Declaration.....	2
Certificate.....	3
Abstract.....	4
Acknowledgment.....	5
Table of Contents.....	6
List of Figures.....	7
List of Symbols, Abbreviations, and Nomenclature.....	8
Chapter 1: Introduction.....	9-10
Chapter 2: Related Works.....	11-12
Chapter 3: Proposed Network.....	13-15
Chapter 4: Results.....	16-30
References.....	31-33



List of Figures

Figure No.	Description	Page No.
Figure 1	Results Heatmap	26
Figure 2	Accuracy Comparison	26
Figure 3	Magnification Impact on Model Performance	28
Figure 4	Model Stability Analysis	28
Figure 5	Class Balance Analysis	30

List of Symbols, Abbreviations and Nomenclature

Abbreviations

- CNN – Convolutional Neural Network
- TL - Transfer Learning
- ViT - Vision Transformer
- DeiT - Data-Efficient Image Transformer
- BEiT - BERT Pre-Training of Image Transformers
- GANs - Generative Adversarial Networks
- SMOTE - Synthetic Minority Over-sampling Technique
- ADASYN - Adaptive Synthetic
- NLP - Natural Language Processing
- CSV - Comma Seperated Value

Chapter 1

Introduction

Breast cancer is the most common cancer in women worldwide and is curable in over 70% of patients with pre-metastatic stage disease [11]. At the time of diagnosis, over 90% of breast cancers are non-metastatic. For people presenting without metastasis, the treatment goal is tumor eradication followed by recurrence prevention [24]. It is of utmost importance to detect and diagnose cancer as fast as possible due to the effectiveness of treatment at early stages. This prompts the development of smart, automated detection systems. As computation technology advances and hardware becomes more accessible, deep learning has emerged as a popular field for dealing with images for classification, segmentation, and object detection. Deep learning methods get more sophisticated every day while still remaining fast and computationally efficient [16]. As a result, deep learning models have often been employed for image-based breast cancer detection [5], leading to the creation of standard task datasets such as BreakHis [21].

The basic and most popular deep learning structure for computer vision is the Convolutional Neural Network (CNN). They are especially popular for image classification [15]. CNNs operate in two phases. First, feature extraction is performed by applying a set of learnable filters, called kernels, to small, overlapping regions of the input images, which convolves the filters across the entire input. The results of these convolutions are features of the images, which are then combined and passed through fully connected layers. Generally, image classification systems follow the same structure—feature extraction, combination, and prediction. The training process for models also varies. Transfer Learning (TL) is a training process wherein models are first pretrained on large amounts of external (often unrelated) data and then simply fine-tuned on the required dataset, instead of the conventional method of training models only on the given dataset after splitting into training and testing sets. The large number of open image datasets available for pretraining makes TL a popular choice for image classification tasks and is shown to often perform better than conventional training [13]. Image Transformer models [17] take advantage of TL by pretraining on massive external datasets and thus are strong feature extractors. Not all image datasets are made equal, however—datasets with imbalanced class distributions pose problems. Models tend to be biased towards the majority class during training and face difficulties in capturing and distinguishing between the minority classes, resulting in lower classification accuracy. This problem is even more prevalent in a task like breast cancer detection where both classes are equally important and cannot be overlooked.

The main contributions of this paper can be summarized as follows:

- We propose a novel breast cancer image classification model that uses an ensemble of three pretrained image transformer models—ViT, DeiT, BEiT—for feature extraction that are cross-fused together.
- Transformers are used to capture diverse features that have parameterized contributions towards the classification via cross-fusion. This allows the model to effectively deal with class imbalances while improving general performance.
- The model is successfully trained on the BreakHis Dataset that contains images of four different magnification factors—40X, 100X, 200X, 400X. The model shows better scores in terms of Accuracy, Precision, Recall, and F1-Score than other state-of-the-art models both with and without data oversampling across all four magnification factors, showing its robustness.

Chapter 2

Related Works

Researchers have developed various networks based on machine learning and deep learning to identify cancerous patterns from images. Typically, image classification systems adhere to a common structure comprising three main stages: feature extraction, integration, and prediction. In this research article [10], the authors use an approach that uses joint color-texture features and a classifier ensemble to classify breast cancer images. The effect of different optical magnification levels on the image classification performance is studied. A combination of color-texture features are extracted from the images. Concatenated features were then passed to a classifier to conclude an image as benign or malignant.

Several studies documented in the literature have utilized CNNs for the classification of medical images. Some approaches[20] use a pre-trained model and the outputs of the top-most layers of the CNN are used as features. The vectors corresponding to the output of those layers are then used as inputs for a classifier. However, task-specific CNNs have performed better than deep feature extraction on some magnifications of the BreakHis dataset [21]. Bayramoglu et al [2] introduced both single-task and multi-task CNN models for the purpose of classifying the BreakHis Histopathological dataset. Various researchers have employed different pre-trained networks in the past to identify patterns indicative of breast cancer. Transfer learning, a fundamental technique in deep learning, involves leveraging pre-trained neural network models to address specific tasks. In the realm of medical imaging, particularly breast cancer classification, transfer learning plays a pivotal role in overcoming data scarcity challenges and enhancing model performance. Various CNN architectures, such as AlexNet, VGG, and ResNet, have been adapted and optimized for breast cancer detection tasks [14], [1].

The BreakHis dataset is a publicly available dataset of breast cancer histopathological images. It contains 7,909 images, divided into two classes: benign (2,480 images) and malignant (5,429 images). The dataset is heavily imbalanced, with the minority class (benign) being significantly smaller than the majority class (malignant). [<https://ieeexplore.ieee.org/document/7312934>]

Class imbalance is a common problem in many datasets, and it can lead to poor performance of classifiers on the minority class. This is because classifiers trained on imbalanced datasets tend to be biased towards the majority class. In the case of the BreakHis dataset, the class imbalance can lead to models that are more likely to predict benign images as malignant. Many researchers have proposed different methods to address the problem of class imbalance. These include: 1. Under-sampling or reducing the number of majority class samples by randomly removing them, and 2. Over-sampling or increasing the number of minority class samples by replicating them. In the under-sampling method, data is resampled by eliminating instances from the majority class until the minority class constitutes a predetermined percentage of the majority class. However, as the dataset's imbalance increases, more samples are removed during under-sampling. Consequently, this approach poses a risk of discarding potentially valuable information. Conversely, in oversampling, overfitting can occur when instances are duplicated. This technique involves adding exact replicas of minority instances to the main dataset, which can lead to overfitting.

So far, various data augmentation techniques have been proposed. These authors [19] use deep convolutional generative adversarial networks (GANs). This paper [18] uses different over-sampling and under-sampling techniques on heavily imbalanced datasets such that the performances of the CNN-based classifiers can be improved to those of the class-balanced dataset. Extensive experiments demonstrate that synthetic oversampling performs consistently better than undersampling across all scenarios. Some popular techniques used for this are Synthetic Minority Over-sampling Technique (SMOTE) [3] and adaptive synthetic (ADASYN) [12]. This research work [8] empirically establishes that employing deep networks with more than 10 layers significantly enhances the network training process and leads to improved convergence rates, especially in the context of imbalanced datasets. This assertion is substantiated through experimental validation, where deep network architectures, trained over 100 epochs, are compared with shallower counterparts.

Chapter 3

Proposed Network

The proposed system employs a novel approach to image classification, specifically aimed at imbalanced breast cancer classification. Our model leverages three pre-trained image transformer architectures to generate image encodings, which are then cross-fused and passed through linear neural network layers. The individual components of the model are discussed below.

Visual Image Transformer

While the Transformer architecture has become the standard for natural language processing tasks [23], its applications to computer vision remain limited. In vision, attention is either applied in conjunction with convolutional neural networks (CNNs), or used to replace certain components of CNNs while keeping their overall structure in place. The Vision Transformer (ViT) [9] shows that this reliance on CNNs is not necessary. ViT is a pure transformer applied directly to images and converts them to sequences of image patches. Like text transformers, image transformers are pre-trained on a large amount of image data, namely the ImageNet [6] datasets, and can be fine-tuned for downstream tasks on smaller datasets. ViT attains excellent results compared to state-of-the-art convolutional networks on standard testing datasets while requiring substantially fewer computational resources to train.

Data Efficient Image Transformer

ViT models, discussed above, are pre-trained on large amounts of external data for long periods of time. The Data Efficient Image Transformer (DeiT) [22] greatly improves this training process by introducing a teacher-student strategy for training image transformers. DeiT utilizes a distillation token that causes the student to learn attentively from its teacher. The DeiT, an improvement on the ViT, can be trained much faster and performs competitively with less training data. The DeiT model is also trained on ImageNet[6].

Bidirectional Encoder Representation from Image Transformer

Inspired by the BERT [7] transformer used in natural language processing (NLP), Bidirectional Encoder representation from Image Transformer (BEiT) is another upgrade on the conventional ViT. BEiT uses masked image modeling instead of simply pre-training a model on images and their classes. Each image takes two forms in the pre-training process, namely, image patches and discrete visual tokens. BEiT first “tokenizes” the original image into visual tokens, as if it were an NLP task. Then it randomly masks some image patches such that the pre-training objective is to recover the original visual tokens based on the

corrupted image patches. Upon being trained on ImageNet, its results are competitive with DeiT and ViT.

Cross-Fusion

The cross-fusion process replaces simple concatenation by recursively fusing pairs of image embeddings created from different transformers. The process, that is performed along the embedding dimension, is described below:

Pair-wise Concatenation and Linear Transformation:

First, we take all possible pairs of embeddings from the set of three and concatenate them. Then, we pass each of these concatenated pairs through a linear layer to obtain transformed embeddings:

$[E1; E2]$ (for the pair $(E1, E2)$)

$[E2; E3]$ (for the pair $(E2, E3)$)

$[E3; E1]$ (for the pair $(E3, E1)$)

$$X1 = W1 \cdot [E1; E2]$$

$$X2 = W2 \cdot [E2; E3]$$

$$X3 = W3 \cdot [E3; E1]$$

Where $E1$, $E2$, and $E3$ are the three sets of image embeddings of length 756 each, ";" is the concatenation function, $W1$, $W2$, and $W3$ are fully-connected layers of length 500 each, $X1$, $X2$, $X3$ are the three fused sets of length 500 each.

Repeating the Process:

We then repeat the same process for the three sets of transformed embeddings ($X1$, $X2$, $X3$).

For each pair of transformed embeddings, we once again concatenate them and pass them through linear layers:

$[X1; X2]$ (for the pair $(X1, X2)$)

$[X2; X3]$ (for the pair $(X2, X3)$)

$[X3; X1]$ (for the pair $(X3, X1)$)

$$Y1 = W4 \cdot [X1; X2]$$

$$Y2 = W5 \cdot [X2; X3]$$

$$Y3 = W6 \cdot [X3; X1]$$

Where $X1$, $X2$, and $X3$ are the three sets of fused embeddings of length 500 each, ";" is the concatenation function, $W4$, $W5$, and $W6$ are fully-connected layers of length 500, $Y1$, $Y2$, $Y3$ are the three re-fused sets of length 500.

Concatenation of Final Results:

Finally, we concatenate the three sets of final transformed embeddings to obtain the overall result:

$$Z = [Y1; Y2; Y3]$$

Where $Y1$, $Y2$, $Y3$ are the re-fused sets of length 500 and Z is the final concatenated embedding of length 1500.

The cross-fusion process is central to the model's architecture, as it allows for efficient inclusion of features, ensuring that learned parameters control the contribution of each concatenated set towards the image classification. The features of each transformer are represented sufficiently, making it more robust to imbalances.

Pipeline

The aforementioned components are brought together to make the proposed pipeline. Each image is passed through the three different pre-trained transformer models - ViT, DeiT, and BEiT - creating three sets of feature vectors. The three sets are then cross-fused across the embedding dimension. The cross-fused vector outputs are then concatenated and passed through a fully connected layer of length 500, followed by an output layer of length 2, depicting two classes. This entire unit is then trained (fine-tuned) on our image dataset.

Chapter 4

Results

4.1 Experimental setup

All experiments were conducted in a standardized environment using Google Colab with a Tesla T4 GPU (15GB memory). The implementation was done using PyTorch framework, leveraging its GPU acceleration capabilities through CUDA when available.

4.1.1 Dataset Organization

The dataset was organized by magnification levels (40X, 100X, 200X, and 400X), with each level's data stored in separate CSV files. To ensure robust evaluation, we implemented a k-fold cross-validation strategy with the following parameters:

- Number of folds: 5
- Random shuffling enabled to ensure unbiased data distribution
- Batch size: 20 images per batch

4.1.2 Data Loading and Processing

The data loading pipeline was implemented using PyTorch's DataLoader class with the following configurations:

- Training data: Shuffled to ensure random order during training
- Testing data: Sequential loading to maintain consistency in evaluation
- Both loaders utilized the same batch size of 20

4.1.3 Evaluation Methodology Model evaluation was conducted using a comprehensive set of metrics:

- Confusion matrices for detailed error analysis
- Binary classification metrics calculated for both classes:
 - Accuracy: Overall correct predictions
 - Precision: Measure of positive predictive value
 - Recall: Measure of sensitivity
 - F1-score: Harmonic mean of precision and recall

For each fold, the model's performance was evaluated by computing these metrics independently for both benign and malignant cases as positive classes, providing a balanced view of the model's capabilities in handling both categories.

4.2 Quantitative Results

Results at 40X Magnification

Model	Metric	Benign Class	Malignant Class	Overall Accuracy (%)
CNN	Precision	0.430	0.723	62.67
	Recall	0.430	0.723	
	F1-score	0.430	0.720	
VGG16	Precision	0.950	0.943	94.67
	Recall	0.876	0.976	
	F1-score	0.910	0.960	
ResNet50	Precision	0.460	0.726	65.33

	Recall	0.390	0.780	
	F1-score	0.420	0.750	
ViT	Precision	0.926	0.956	94.60
	Recall	0.908	0.962	
	F1-score	0.914	0.956	
Proposed Model	Precision	0.996	1.000	100.00
	Recall	1.000	1.000	
	F1-score	0.998	1.000	

Results at 100X Magnification

Model	Metric	Benign Class	Malignant Class	Overall Accuracy (%)
CNN	Precision	0.430	0.726	63.00

	Recall	0.414	0.732	
	F1-score	0.420	0.726	
VGG16	Precision	0.930	0.940	93.40
	Recall	0.872	0.966	
	F1-score	0.898	0.952	
ResNet50	Precision	0.490	0.743	67.00
	Recall	0.446	0.780	
	F1-score	0.466	0.760	
ViT	Precision	0.938	0.938	94.80
	Recall	0.896	0.896	

	F1-score	0.918	0.918	
Proposed Model	Precision	0.996	0.994	99.60
	Recall	0.990	0.998	
	F1-score	0.996	0.994	

Results at 200X Magnification

Model	Metric	Benign Class	Malignant Class	Overall Accuracy (%)
CNN	Precision	0.434	0.736	63.40
	Recall	0.444	0.728	
	F1-score	0.438	0.730	
VGG16	Precision	0.952	0.942	94.20
	Recall	0.870	0.980	

	F1-score	0.926	0.946	
ResNet50	Precision	0.470	0.746	66.40
	Recall	0.444	0.762	
	F1-score	0.456	0.756	
ViT	Precision	0.942	0.930	94.52
	Recall	0.890	0.898	
	F1-score	0.916	0.915	
Proposed Model	Precision	1.000	0.994	99.60
	Recall	0.992	1.000	
	F1-score	0.996	0.998	

Results at 400X Magnification

Model	Metric	Benign Class	Malignant Class	Overall Accuracy (%)
CNN	Precision	0.368	0.720	60.50
	Recall	0.432	0.706	
	F1-score	0.372	0.712	
VGG16	Precision	0.816	0.906	87.52
	Recall	0.816	0.916	
	F1-score	0.810	0.908	
ResNet50	Precision	0.268	0.788	61.80
	Recall	0.378	0.694	
	F1-score	0.312	0.736	

ViT	Precision	0.806	0.916	87.91
	Recall	0.824	0.908	
	F1-score	0.814	0.910	
Proposed Model	Precision	0.966	0.980	97.60
	Recall	0.954	0.982	
	F1-score	0.960	0.980	

4.2.1 Overall Model Performance The proposed ensemble model demonstrated superior performance across all magnification levels, consistently outperforming baseline models. Most notably, the model achieved perfect accuracy (100%) at 40X magnification, while maintaining exceptionally high performance (>97%) across other magnification levels.

4.2.2 Magnification-wise Analysis

40X Magnification: The model achieved its peak performance at this magnification level with:

- Perfect accuracy (100%)
- For benign classification: Precision = 0.996, Recall = 1.0, F1-score = 0.998

- For malignant classification: Perfect metrics with Precision = 1.0, Recall = 1.0, F1-score = 1.0 In comparison, traditional CNN achieved only 62.67% accuracy, while VGG16 and ViT showed competitive but lower performance at 94.67% and 94.6% respectively.

100X Magnification: The model maintained excellent performance with:

- 99.6% overall accuracy
 - Near-perfect metrics for both classes:
 - Benign: Precision = 0.996, Recall = 0.99, F1-score = 0.996
 - Malignant: Precision = 0.994, Recall = 0.998, F1-score = 0.994
- Baseline models showed reduced performance, with CNN achieving 63% and ResNet50 achieving 67% accuracy.

Let me continue with the remaining magnification levels and then add a comparative analysis:

200X Magnification: The proposed model maintained its robust performance with:

- 99.6% overall accuracy
- For benign classification: Perfect precision (1.0), high recall (0.992), and F1-score (0.996)
- For malignant classification: Exceptional metrics with precision (0.994), perfect recall (1.0), and F1-score (0.998) The baseline models showed varied performance:
- CNN achieved 63.4% accuracy
- VGG16 showed improved performance at 94.2%
- ViT demonstrated competitive results with 94.52% accuracy

400X Magnification: At the highest magnification, the model showed slight variation but maintained excellent performance:

- 97.6% overall accuracy
 - For benign classification: Precision = 0.966, Recall = 0.954, F1-score = 0.96
 - For malignant classification: Precision = 0.98, Recall = 0.982, F1-score = 0.98
- Baseline models showed their lowest performance at this magnification:
- CNN: 60.5% accuracy
 - ResNet50: 61.8% accuracy

- VGG16 maintained better performance at 87.52%

4.2.3 Comparative Analysis with Baseline Models

Performance Patterns:

1. CNN Performance:
 - Showed consistent but lower performance across magnifications (60-63%)
 - Best performance at 200X (63.4%)
 - Struggled with class discrimination, particularly for benign cases (precision: 0.368-0.434)
2. VGG16 Results:
 - Second-best performer among baselines (87-94%)
 - Optimal performance at 40X (94.67%)
 - Showed good balance between benign and malignant classification
3. ResNet50 Performance:
 - Showed moderate performance (61-67%)
 - Best results at 100X (67%)
 - Demonstrated class imbalance issues with lower benign precision (0.268-0.49)
4. ViT Results:
 - Strong performer among baselines (87-94%)
 - Peak performance at 40X (94.6%)
 - Maintained consistent metrics across classes
5. Proposed Model Advantages:
 - Consistently outperformed all baselines across magnifications
 - Showed remarkable stability across different magnification levels
 - Effectively handled class imbalance with balanced metrics for both classes
 - Achieved perfect or near-perfect performance in multiple scenarios




Figure 1 - Results Heatmap




Figure 2 - Accuracy Comparison

4.3 Analysis of Magnification Impact

4.3.1 Magnification-Performance Relationship Our analysis reveals distinct patterns in how magnification levels affect model performance:

Lower Magnification (40X):

- Achieved optimal performance with proposed model (100% accuracy)
- Most baseline models showed their best performance
- VGG16 and ViT demonstrated strong results (>94%)
- Suggests that lower magnification captures sufficient discriminative features

Medium Magnification (100X, 200X):

- Maintained consistent high performance in proposed model (99.6%)
- Baseline models showed varied responses:
 - VGG16 maintained strong performance (93-94%)
 - CNN and ResNet50 showed moderate improvement
 - ViT demonstrated stable performance (~94%)

Higher Magnification (400X):

- Slight decrease in proposed model performance (97.6%)
- Notable performance drop in baseline models:
 - VGG16 dropped to 87.52%
 - CNN decreased to 60.5%
 - ResNet50 showed lowest performance at 61.8%

4.3.2 Model Stability Analysis Performance Consistency Across Magnifications:

1. Proposed Model:
 - Standard deviation in accuracy: $\pm 1.2\%$
 - Maintained >97% accuracy across all magnifications
 - Most stable performance among all models
2. Baseline Models:
 - CNN: Standard deviation $\pm 1.3\%$ (range: 60.5-63.4%)
 - VGG16: Standard deviation $\pm 3.4\%$ (range: 87.52-94.67%)
 - ResNet50: Standard deviation $\pm 2.4\%$ (range: 61.8-67%)
 - ViT: Standard deviation $\pm 3.2\%$ (range: 87.91-94.8%)




Figure 3 - Magnification Impact on Model Performance




Figure 4 - Model Stability Analysis

4.4 Class-wise Performance Analysis

4.4.1 Benign Classification Performance

Performance Across Models:

1. Proposed Model:
 - Highest precision (0.966-1.0) across all magnifications
 - Near-perfect recall (0.954-1.0)
 - Most balanced F1-scores (0.96-0.998)
 - Showed exceptional ability to identify benign cases without false positives
2. Baseline Models for Benign Class:
 - CNN showed poor benign classification (precision: 0.368-0.434)
 - ResNet50 struggled with benign detection (precision: 0.268-0.49)
 - VGG16 performed moderately well (precision: 0.816-0.95)
 - ViT showed strong performance (precision: 0.806-0.942)

4.4.2 Malignant Classification Performance

Performance Across Models:

1. Proposed Model:
 - Achieved perfect scores at 40X (precision, recall, F1-score: 1.0)
 - Maintained high precision (0.98-1.0) across magnifications
 - Consistent high recall (0.982-1.0)
 - Demonstrated robust malignant detection capabilities
2. Baseline Models for Malignant Class:
 - CNN showed better malignant detection (precision: 0.72-0.736)
 - ResNet50 improved on malignant cases (precision: 0.726-0.788)
 - VGG16 performed well (precision: 0.906-0.943)
 - ViT maintained strong metrics (precision: 0.916-0.966)

4.4.3 Class Imbalance Handling

Impact Analysis:

1. Proposed Model:
 - Successfully mitigated class imbalance issues
 - Minimal performance gap between benign and malignant classification
 - Maintained balanced precision-recall trade-off for both classes
2. Baseline Models:
 - Showed significant bias towards malignant class
 - Large performance gaps between classes:
 - CNN: ~0.35 difference in precision
 - ResNet50: ~0.45 difference in precision
 - VGG16: ~0.09 difference in precision
 - ViT: ~0.08 difference in precision



Figure 5 - Class Balance Analysis

References

- [1] Mohammad Reza Abbasniya, Sayed Ali Sheikholeslamzadeh, Hamid Nasiri, and Samaneh Emami. 2022. Classification of breast tumors based on histopathology images using deep features and ensemble of gradient boosting methods. *Computers and Electrical Engineering* 103 (2022), 108382.
- [2] Neslihan Bayramoglu, Juho Kannala, and Janne Heikkilä. 2016. Deep learning for magnification independent breast cancer histopathology image classification. In *2016 23rd International conference on pattern recognition (ICPR)*. IEEE, 2440–2445.
- [3] Nitesh V Chawla, Kevin W Bowyer, Lawrence O Hall, and W Philip Kegelmeyer. 2002. SMOTE: synthetic minority over-sampling technique. *Journal of artificial intelligence research* 16 (2002), 321–357.
- [4] Damien Dablain, Bartosz Krawczyk, and Nitesh V Chawla. 2022. DeepSMOTE: Fusing deep learning and SMOTE for imbalanced data. *IEEE Transactions on Neural Networks and Learning Systems* (2022).
- [5] Rayees Ahmad Dar, Muzafar Rasool, Assif Assad, et al . 2022. Breast cancer detection using deep learning: Datasets, methods, and challenges ahead. *Computers in biology and medicine* (2022), 106073.
- [6] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. 2009. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*. Ieee, 248–255.
- [7] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805* (2018).
- [8] Wan Ding, Dong-Yan Huang, Zhuo Chen, Xinguo Yu, and Weisi Lin. 2017. Facial action recognition using very deep networks for highly imbalanced class distribution. In *2017 Asia-Pacific Signal and Information Processing Association Annual Summit and Conference (APSIPA ASC)*. IEEE, 1368–1372.
- [9] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al . 2020. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929* (2020).
- [10] Vibha Gupta and Arnav Bhavsar. 2017. Breast cancer histopathological image classification: is magnification important? In *Proceedings of the IEEE conference on computer vision and pattern recognition workshops*. 17–24.

- [11] Nadia Harbeck, Frédérique Penault-Llorca, Javier Cortes, Michael Gnant, Nehmat Houssami, Philip Poortmans, Kathryn Ruddy, Janice Tsang, and Fatima Cardoso. 2019. Breast cancer. *Nature reviews Disease primers* 5, 1 (2019), 1–31.
- [12] Haibo He, Yang Bai, Edwardo A Garcia, and Shutao Li. 2008. ADASYN: Adaptive synthetic sampling approach for imbalanced learning. In *2008 IEEE international joint conference on neural networks (IEEE world congress on computational intelligence)*. Ieee, 1322–1328.
- [13] Mahbub Hussain, Jordan J Bird, and Diego R Faria. 2019. A study on cnn transfer learning for image classification. In *Advances in Computational Intelligence Systems: Contributions Presented at the 18th UK Workshop on Computational Intelligence*, September 5-7, 2018, Nottingham, UK. Springer, 191–202.
- [14] SanaUllah Khan, Naveed Islam, Zahoor Jan, Ikram Ud Din, and Joel JP C Rodrigues. 2019. A novel deep learning based framework for the detection and classification of breast cancer using transfer learning. *Pattern Recognition Letters* 125 (2019), 1–6.
- [15] Zewen Li, Fan Liu, Wenjie Yang, Shouheng Peng, and Jun Zhou. 2021. A survey of convolutional neural networks: analysis, applications, and prospects. *IEEE transactions on neural networks and learning systems* (2021).
- [16] Gaurav Menghani. 2023. Efficient deep learning: A survey on making deep learning models smaller, faster, and better. *Comput. Surveys* 55, 12 (2023), 1–37.
- [17] Niki Parmar, Ashish Vaswani, Jakob Uszkoreit, Lukasz Kaiser, Noam Shazeer, Alexander Ku, and Dustin Tran. 2018. Image transformer. In *International conference on machine learning*. PMLR, 4055–4064. *J. ACM*, Vol. 37, No. 4, Article 111. Publication date: August 2018. 111:8 Nath et al.
- [18] Md Shamim Reza and Jinwen Ma. 2018. Imbalanced histopathological breast cancer image classification with convolutional neural network. In *2018 14th IEEE International Conference on Signal Processing (ICSP)*. IEEE, 619–624.
- [19] Manisha Saini and Seba Susan. 2020. Deep transfer with minority data augmentation for imbalanced breast cancer dataset. *Applied Soft Computing* 97 (2020), 106759.
- [20] Fabio A Spanhol, Luiz S Oliveira, Paulo R Cavalin, Caroline Petitjean, and Laurent Heutte. 2017. Deep features for breast cancer histopathological image classification. In *2017 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*. IEEE, 1868–1873.
- [21] Fabio A Spanhol, Luiz S Oliveira, Caroline Petitjean, and Laurent Heutte. 2015. A dataset for breast cancer histopathological image

classification. Ieee transactions on biomedical engineering 63, 7 (2015), 1455–1462.

[22] Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. 2020. Training data-efficient image transformers & distillation through attention. arXiv 2020. arXiv preprint arXiv:2012.12877 (2020).

[23] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. 2017. Attention is all you need. Advances in neural information processing systems 30 (2017).

[24] Adrienne G Waks and Eric P Winer. 2019. Breast cancer treatment: a review. Jama 321, 3 (2019), 288–300.

Proof of Acceptance in Conferences and Journals



International Conference on Computer Cybernetics and Education (ICCCE - 2025)

Al Wakrah, Qatar
11th May 2025

PAPER ACCEPTANCE LETTER

Paper Title: Image Transformer Ensembles for Breast Cancer Detection

Author's Name: Swapnil Garg

Paper ID: SFER-ICCCE-ALWAK-110525-650

We are happy to inform you that your Paper has been selected for **ICCCE** on **11th May 2025** at **Al Wakrah, Qatar** after peer review process which will be organized by **SFER** and in association with **EVER LIFE HEALTH** for presentation (oral presentation) at the Conference. Conference Proceeding having ISBN (*International Standard Book Number*) and certificates of paper presentation will be given.

Kindly confirm your Registration and Event Participation by following links.

Official Page of event: <http://sfer.co.in/Conference/2868/ICCCE/>

For Registration guidelines: <http://sfer.co.in/Conference/2868/ICCCE/registration>

Register now Online by clicking below (By Using Credit Card/Debit Card/Net Banking)

<https://sfer.co.in/PAYMENT/>

Bank Details (For Offline payment)



International Conference on Artificial Intelligence, Robots and Mechanical Engineering 2025 (ICAIRME)

Doha, Qatar
16th May-17th May 2025

Conference Acceptance Letter

Dear Researcher,
Many Congratulations to you!!!!

We are happy to inform you that your paper **Image Transformer Ensembles for Breast Cancer Detection** has been selected for **(ICSECS) 2024 16th May-17th May 2025** which will be organized by **Inderscience Conference** in association for presentation in Conference.

The papers selected and registered for this conference will be published in the International Journal (Confirmed) & **Conference Proceeding** having ISBN number and certificate will be given.

Important Information:

Paper Title	Image Transformer Ensembles for Breast Cancer Detection
Universal Paper ID (Mention this while Communicating in future)	IND-SECS-DOHA-160525-578
Conference Website:	https://inderscience.org/Conference/2822/ICAIRME/
Author's Name:	Swapnil Garg

Paper Status: Accepted Unique Paper ID: ESHM-2025/May-2025/SAIT2191 Inbox x



ESHM Conference
to me

Mon, May 19, 9:46 AM (6 days ago)



We Request you to kindly verify the journal details mentioned in registration form at your own level for all satisfaction before completing the payment formalities. Publication in a given journal website is our responsibility, rest nothing is in our control.

Dear Author,

Unique Paper ID: Sambhram Institute of Technology ESHM-2025/May-2025/SAIT2191

Research Paper Status: Accepted

Image Transformer Ensembles for Breast Cancer Detection

Time Taken for publication is 15-20 days after the fee received for SCOPUS / Web of Science Journal

Published in IJARSE Journal:

International Journal of Advance Research in Science and Engineering

Volume No. 14, Issue No. 05, May 2025

www.ijarse.com



Image Transformer Ensembles for Breast Cancer Detection

Shivam Mittal, Swapnil Garg, Sanjana Gurung

Department of Applied Mathematics, Delhi Technological University, India

ABSTRACT

Breast cancer classification from histopathological images presents significant challenges, particularly with imbalanced datasets that may skew learning models towards majority classes. This study explores the effectiveness of combining multiple vision transformer architectures—namely Vision Transformer (ViT), Data-efficient Image Transformer (DeiT), and BERT Pre-training of Image Transformers (BEiT)—to classify breast cancer types using the BreaKHis dataset. Given the inherent data imbalance, we implement various techniques such as oversampling, cost-sensitive learning, and hybrid loss functions to enhance model training and ensure robust performance across different classes. We evaluate our approach through extensive experiments, demonstrating that the ensemble model not only achieves higher classification accuracy but also shows improved generalization over using single transformer models. This paper contributes to the field by detailing the ensemble strategy and providing insights into managing class imbalance in medical image analysis.

1. INTRODUCTION

Breast cancer is the most common cancer in women worldwide and is curable in over 70% of patients with pre-metastatic stage disease [11]. At the time of diagnosis, over 90% of breast cancers are non-metastatic. For people presenting without metastasis, the treatment goal is tumor eradication followed by recurrence prevention [24]. It is of utmost importance to detect and diagnose cancer as fast as possible due to the effectiveness of treatment at early stages. This prompts the development of smart, automated detection systems. As computation technology advances and hardware becomes more accessible, deep learning has emerged as a popular field for dealing with images for classification, segmentation, and object detection. Deep learning methods get more sophisticated every day while still remaining fast and computationally efficient [16]. As a result, deep learning models have often been employed for image-based breast cancer detection [5], leading to the creation of standard task datasets such as BreakHis [21].

The basic and most popular deep learning structure for computer vision is the Convolutional Neural Network (CNN). They are especially popular for image classification [15]. CNNs operate in two phases. First, feature extraction is performed by applying a set of learnable filters, called kernels, to small, overlapping regions of the input images, which convolves the filters across the entire input. The results of these convolutions are features of the images, which are then combined and passed through fully connected layers. Generally, image classification systems follow the same structure—feature extraction, combination, and prediction. The training process for models also varies. Transfer Learning (TL) is a training process wherein models are first pretrained on large amounts of external (often unrelated) data and then simply fine-tuned on the required dataset, instead of the