


BED AND HAUNCH MATERIAL SHALL BE SELECT FILL WITH THE FOLLOWING VARIATION:	
SIEVE (mm)	% PASSING
19.000	100
2.360	100-50
0.600	90-20
0.300	60-10
0.150	25-0
0.075	10-0
SHRINKAGE LIMIT ≤ 10 FOR %PASSING 0.075mm	



TRENCH DIMENSIONS				
D*	a	b	c	W
$D \leq 150$	75	100	100	≤ 350
$150 < D \leq 300$	100	150	150	450-600
$300 < D \leq 450$	100	200	150	700-850
$450 < D$	100	300	150	> 1050

*D = DIAMETER OF LARGEST EXTERNAL SURFACE
 ABOVE PIPE.



N.T.S.

*REFER TO STANDARD DRAWING
CMDG-D-011 FOR FULL DETAILS AND NOTES

GRADED TRENCH SCHEDULE						
ID	LENGTH (m)	TYPICAL PIT SPACING	NO. PITS	LOCATION	PRODUCT DETAILS	PRODUCT CODE
GT1	125.2	19.5	5	NETBALL COURTS	RECYFIX PRO 200 CLASS B 125, TYPE 010 WITH FIBRETEC SLOTTED GRATING	47246
GT2	141.2	17.0	4	NETBALL COURTS	RECYFIX PRO 200 CLASS B 125, TYPE 010 WITH FIBRETEC SLOTTED GRATING	47246
GT3	141.2	17.0	7	NETBALL COURTS	RECYFIX PRO 200 CLASS B 125, TYPE 010 WITH FIBRETEC SLOTTED GRATING	47246
GT4	141.2	17.0	7	NETBALL COURTS	RECYFIX PRO 200 CLASS B 125, TYPE 010 WITH FIBRETEC SLOTTED GRATING	47246
GT5	15.2	N.A.	1	MULTI-USE COURT	RECYFIX PRO 100 CLASS B 125, TYPE 010 WITH STAINLESS STEEL ANTI-SLIP HEELGUARD GRATING	47307
GT6	31.4	N.A.	1	AMENITIES BUILDING	RECYFIX PRO 200 CLASS D 400, TYPE 010 WITH HEELGUARD G-TEC DUCTILE IRON GRATING	47245
GT7	3.6	N.A.	1	NETBALL WALKWAY	RECYFIX PRO 100 CLASS B 125, TYPE 010 WITH STAINLESS STEEL ANTI-SLIP HEELGUARD GRATING	47307
GT8	6	N.A.	1	NETBALL STAIRS	RECYFIX PRO 100 CLASS B 125, TYPE 010 WITH STAINLESS STEEL ANTI-SLIP HEELGUARD GRATING	47307
GT9	3.5	N.A.	1	NETBALL WALKWAY	RECYFIX PRO 100 CLASS B 125, TYPE 010 WITH STAINLESS STEEL ANTI-SLIP HEELGUARD GRATING	47307

NOTES:

- ALL GRADED TRENCH DEPTHS ARE 200 mm.
- PIT SPACINGS ARE AVERAGE FIGURES, PITS TO BE SET OUT IN ACCORDANCE WITH LAYOUT PLANS AND PIT SCHEDULE.
- PRODUCT TO BE AS NOMINATED OR CLASS B APPROVED EQUIVALENT.