

Room No	Room Name	Door No	PWD	Door Leaf Dimensions				Width Multi	Doorset	Operation	Threshold Detail	Signage	Lock/Latch	Security	Closer	Catch	Seals	Kick	Rev
				Height	Width 1	Width 2	Thick												
0.01	Front Entry	D1	AS1428.1	2001	1070	575	45		AG-AG-1	Swing x2	11/A-720002	SI-26	Electronic mortice lock or magnetic lock with free egress or release on alarm	Swipe card on outside	Mechanical hold open on cat & kitten leaves	Flushbolts on kitten leaf	nil	nil	1
0.02	Covered Outdoor	D1	n/a	2005	1184	1084	45		TG-Slide1	OXX	1/A-720005	nil	nil	nil	n/a	Flush bolts	Weather	nil	1
0.02	Covered Outdoor	D2	n/a	2005	1165	1065	45		TG-Slide1	OXX	1/A-720005	nil	nil	nil	n/a	Flush bolts	Weather	nil	1
0.02	Covered Outdoor	D3	n/a	2005	1165	1065	45		TG-Slide1	OXX	2/A-720005	nil	nil	nil	n/a	Flush bolts	Weather	nil	1
0.02	Covered Outdoor	D4	n/a	2005	1165	1065	45		TG-Slide1	OXX	1/A-720005	nil	nil	nil	n/a	Flush bolts	Weather	nil	1
0.02	Covered Outdoor	D5	n/a	2005	1178	1078	45		TG-Slide1	OXX	1/A-720005	nil	nil	nil	n/a	Flush bolts	Weather	nil	1
0.02	Covered Outdoor	D6	AS1428.1	2040	920	520	45		TG-TV-1	Swing x2	7/A-720005	nil	Electronic mortice lock with free egress	Swipe card on Courtyard side	Mechanical	Flush bolts	Weather	nil	1
0.02	Covered Outdoor	D7	n/a	2040	790		40		SC-1	Swing	nil	SI-30	Passage set with handle on outside only						
0.03	External Circulation	D1	AS1428.1	2040	920		45		TG-1	Swing	2/A-720005	nil	Electronic mortice lock free access to Courtyard & fail safe on alarm	Swipe card on Courtyard side	Mechanical	nil	Acoustic	nil	1
0.03	External Circulation	D2	AS1428.1	2040	920		45		TG-1	Swing	2/A-720005	nil	Electronic mortice lock free access to Courtyard & fail safe on alarm	Swipe card on Courtyard side	Mechanical	nil	Acoustic	nil	1
0.04	Dining	D1	AS1428.1	2040	920	520	45		TG-TV-1	Swing x2	7/A-720005	nil	Electronic mortice lock with free egress	Swipe card on outside	Mechanical	Flushbolts on kitten leaf	Weather	nil	3
0.04	Dining	D2	AS1428.1	2040	920	520	45		TG-TV-1	Swing x2	7/A-720005	nil	Electronic mortice lock with free egress	Swipe card on outside	Mechanical	Flushbolts on kitten leaf	Weather	nil	3
0.08	Boardroom	D1	AS1428.1	2040	920	520	40		TV-TV-1	Swing x2	3/A-720010	SI-1	Electronic mortice lock with free egress	Swipe card on outside	Mechanical on cat leaf	Flushbolts on kitten leaf	Acoustic	nil	1
0.09	Health Room	D1	AS1428.1	2040	920		40		TV-1	Swing	3/A-720010	SI-1	Electronic mortice lock with privacy snib & anti-lockout	Swipe card on outside	Mechanical	nil	Acoustic	nil	1
0.10	Training 1	D1	AS1428.1	2040	920	520	40		TV-TV-1	Swing x2	3/A-720010	SI-1	Electronic mortice lock with free egress	Swipe card on outside	Mechanical on cat leaf	Flushbolts on kitten leaf	Acoustic	nil	1
0.10	Training 1	D2	n/a	2955	2220	2220	50		AL-Slide-1	XXX	Door Track	nil	Latch only	nil	nil	Flushbolts on kitten leaf	Acoustic	nil	5
0.11	Training 2	D1	AS1428.1	2040	920	520	40		TV-TV-1	Swing x2	3/A-720010	SI-1	Electronic mortice lock with free egress	Swipe card on outside	Mechanical on cat leaf	Flushbolts on kitten leaf	Acoustic	nil	1
0.12	Store	D1	AS1428.1	2040	920	520	40		TV-TV-1	Swing x2	3/A-720010	SI-2	Electronic mortice lock with free egress	Swipe card on outside	nil	Flushbolts on kitten leaf	Acoustic	150h SS Kick x2	1
0.13	Comms	D1	AS1428.1	2040	920		40		TV-1	Swing	nil	SI-2	Mortice Lock - Key entry escape lock	Swipe card on outside	Mechanical	nil	Bat wing	nil	5
0.14	Shower	D1	AS1428.1	2040	920		40		TV-1	Swing	nil	SI-20	Mortice Lock - Anti-lockout Privacy	nil	nil	nil	Bat wing	150h SS Kick x2	1
0.15	PWD	D1	AS1428.1	2040	920		40		TV-1	Swing	nil	SI-21	Mortice Lock - Anti-lockout Privacy	nil	Mechanical	nil	Bat wing	150h SS Kick x2	1
0.16	Female	D1	n/a	2040	920		40		TV-1	Swing	nil	SI-22	Passage set	nil	Mechanical	nil	Bat wing	150h SS Kick x2	1
0.17	Male	D1	n/a	2040	920		40		TV-1	Swing	nil	SI-23	Passage set	nil	Mechanical	nil	Bat wing	150h SS Kick x2	1
0.17	Store	D2	n/a	2040	620		40		SC-1	Swing	nil	SI-2	Mortice Lock - Nightlatch with cylinder & fixed handle on outside	nil	nil	nil	150h SS Kick x2	3	
0.18	First Aid	D1	AS1428.1	2040	920	520	40		TV-TV-1	Swing x2	nil	SI-2	Electronic mortice lock with free egress	Swipe card on outside	Mechanical on cat leaf	Flushbolts on kitten leaf	Bat wing	nil	5
0.19	Cleaner	D1	n/a	2040	620		40		TV-1	Swing	nil	SI-2	Mortice Lock - Nightlatch with cylinder & fixed handle on outside	nil	nil	nil	Bat wing	150h SS Kick x2	1
0.20	MSB	D1	n/a	2000	1100	1100	40		SC-SC-1	Swing x2	2/A-720002	nil	Mortice Lock - Nightlatch with cylinder & fixed handle on outside	nil	Sequenced mechanical hold open	Flushbolts on kitten leaf	Smoke	nil	6
0.21	DB	D1	n/a	2000	920	920	40		SC-SC-1	Swing x2	1/A-720002	nil	Mortice Lock - Nightlatch with cylinder & fixed handle on outside	nil	Sequenced mechanical hold open	Flushbolts on kitten leaf	Smoke	nil	6
0.22	West Entry	D1	n/a	2040	920		45		TV-2	Swing	3/A-720002	SI-26	Electronic mortice lock with free egress	Swipe card on outside	Mechanical	nil	Weather	nil	1
0.23	Workspace (west)	D1	AS1428.1	2040	920	520	45		TG-TV-1	Swing x2	3/A-720010	nil	Electronic mortice lock with free egress	Swipe card on outside	Mechanical on cat leaf	Flushbolts on kitten leaf	Acoustic	nil	1
0.24	Office 1	D1x	AS1428.1	2040	920		40		TV-1	Swing	Raven RP96	nil	Passage set	nil	Mechanical	nil	Acoustic	nil	5
0.27	Meeting 5	D1	AS1428.1	2040	920		40		TV-1	Swing	Raven RP96	SI-1	Passage set	nil	Mechanical	nil	Acoustic	nil	5
0.28	Meeting 6	D1	AS1428.1	2040	920		40		TV-1	Swing	Raven RP96	SI-1	Passage set	nil	Mechanical	nil	Acoustic	nil	5
0.29	Workspace (north)	D1	AS1428.1	2010	920	920	40		AG-AG-1	Swing x2	7/A-720002	SI-26	Electronic mortice lock with free egress	Swipe card on outside	Mechanical on cat leaf	Flushbolts on kitten leaf	Weather	nil	1
0.30	Meeting 3	D1	AS1428.1	2040	920		40		TV-1	Swing	Raven RP96	SI-1	Passage set	nil	Mechanical	nil	Acoustic	nil	5
0.31	Meeting 4	D1	AS1428.1	2040	920		40		TV-1	Swing	Raven RP96	SI-1	Passage set	nil	Mechanical	nil	Acoustic	nil	5
0.32	Meeting 2	D1	AS1428.1	2040	920		40		TV-1	Swing	Raven RP96	SI-1	Passage set	nil	Mechanical	nil	Acoustic	nil	5
0.33	Office 2	D1	AS1428.1	2040	920		40		TV-1	Swing	Raven RP96	nil	Passage set	nil	Mechanical	nil	Acoustic	nil	5
0.34	Meeting 1	D1	AS1428.1	2040	920		40		TV-1	Swing	Raven RP96	SI-1	Passage set	nil	Mechanical	nil	Acoustic	nil	5
0.51	Link	D1	n/a						Turnstile	Turnstile	nil	nil	Swipe card access only	Swipe card on both sides	n/a	nil	nil	nil	1
0.54	Stair 1	D1	n/a	2040	920		45		TG-1	Swing	6/A-720002	SI-26	Electronic mortice lock with free egress	Swipe card on outside	Mechanical	nil	Weather	nil	1

DOORSET LEGEND

AG-AG-1	Leaves: External alum glazed door pair, P'coated Frame: G.James 600 series alum framed glazed wall, P'coated
AL-Slide-1.	GLYDE 'Sereine' Bottom-rolling Acoustic Sliding Doors with 4 sliding door leaves centre parting - refer Appendix with bottom rollers & track. Leaf Finishes: 1 leaf white board, 3 leaves autex cube 12mm Frame: 19mm timber frame with timber batten architraves, refer A-60 series dwgs
SC-1	Leaf: Internal solid core door leaf, Painted Frame: 19mm timber frame with timber batten architraves, refer A-60 series dwgs
SC-SC-1	Leaves: External solid core door pair with non-combustable lining on inside face to comply with NCC 2022 D3D8 (4), painted Frame: 4 sided steel door frame to encapsulate fc cladding, refer A-60 series dwgs
TG-1	Leaf: External Glazed timber door leaf, clear finish Frame: 19mm timber frame with timber batten architraves, refer to A-60 series dwgs
TG-Slide-1.	External glazed timber leaves (2x sliding, 1x fixed) with top hung mechanism and AS1428.1 compliant track at sill, PT-T1.
TG-TV-1	Leaves: External glazed timber door leaf + solid core leaf with MTV-1 to both sides, clear finished Frame: 19mm timber frame with timber batten architraves, refer A-60 series dwgs
Turnstile	External Full Height Turnstile - Assa Abloy FT100 Series; Passage Width:670m
TV-1	Leaf: Internal Solid core door leaf with MTV-1 to both sides, PT-T1 Frame: 19mm timber frame with timber batten architraves, refer A-60 series dwgs
TV-2	Leaf: External Solid core leaf with MTV-1 to inside face and zincalume (1.15 bmt) sheet fully bonded to outside face & folded to cover all 4 edges and vision panel. Frame: 19mm timber frame with timber batten architraves, refer to A-60 series dwgs
TV-TV-1	Leaves: Internal Solid core door pair with MTV-1 to both sides Frame: 19mm timber frame with timber batten architraves, refer A-60 series dwgs

DOOR NOTES

- Refer to Door Schedule for door leaf sizes and thicknesses and acoustic ratings
- Refer to Architectural Specification (0453 Doors and Access Panels) for door leaf construction and to manufacturer's data and recommendations for specified types.
- Provide hinges in accordance with Architectural Specification (0456 Door Hardware) and manufacturer recommendations. Unless otherwise documented provide ball bearing butt hinges to SC and TG doorsets, and fast fix ball bearing hinges to AG doorsets. Satin stainless steel finish to all hinges.
- Contractor to complete and submit Door Hardware Schedule for approval by Architect prior to ordering hardware.
- Where keying is documented, key to Stanwell master key system.
- Provide shop drawings for each doorset.
- Door closers are to be installed fully within the top rail depth of glazed and framed leaves, with no overhang over glazing permitted.
- Unless otherwise documented, kickplates to be full width 1,2mm thick 150mm high 304 grade satin stainless steel. Bond and screwed at corners and centrally top and bottom.
- Confirm on site with Architect the mounting location and setout of all door stops and holders prior to installation.
- Refer Technical Reference Sheet for Signage specification.
- Refer to A-60 series drawings for door finishes.
- Decals: provide decals as shown, MDE-1

rev date description

T1 11/03/2026 For Tender

initial

JB

DETAILS NOTES

- All aluminium flashings @ floor level to be min. 1.6 thick. Flashings to be installed with end dams at each end and fully sealed at the corners and vertical framing junctions. Flashings must be continuous and wrap around steel columns where they exist. Water hose test required for weatherproofing validation and flood test required for sub-sill after installation of sub-jamb & sub-sill.
- For all screw fixings between timber or aluminium framed cladding and the substrate, apply a blob of sealant before installation and seal screw heads after. Use stainless steel screws/anchors only.
- Install separation tape between dissimilar materials to prevent corrosion.

FACADE LEGEND

WP-2	Ext. bonded membrane
Folded aluminium flashing	
WP-1 or 3	Floor Waterproof Membrane
WP-4	Ext. non-bonded membrane
Roof sarking	

Drawings include colour information. A black & white copy may not have all the information. This background is coloured blue.

brian hooper**architect**
m3architecture
ph: +61 7 3831 4644
11 saint james street petrie tce q 4000
info@m3architecture.com
www.m3architecture.com

client **stanwell**

project **Stanwell New Projects Office**
Switchyard Road,
Stanwell, QLD, 4702

title **Door Types**

drawn bg
checked jb
date March 2026
scale As indicated at A1
drawing **25010 / cd A-730001 / T1**

copyright ©
These designs, plans, specifications and the copyright herein are the property of the architect and must not be used, reproduced, or copied wholly or in part without the written permission of m3architecture Pty Ltd abn 23 079 044 545.
Use figured dimensions in preference to scale.
If there are any questions contact the architect.

1:20 at A1
0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0m

