

Stanwell

Stanwell New Projects Office
Switchyard Road,
Stanwell, QLD, 4702

25010 / cd Spec A / T2

Appendix A - T-Sheet

Revision	Date	Description	Issued by
T1	11/03/2026	For Tender	JB
T2	21/05/2026	T-Sheet Update	JB

PRELIMINARY
NOT FOR CONSTRUCTION

Technical Reference Sheet

Project	Stanwell NPO Projects Office			
Project No	25010			
Revision	Date	Description		
T1	11/03/2026	For Tender		
T2	21/05/2026	T-Sheet Update		
Categories				
AM	Architectural Metal Work			
BX	Balustrades & stair elements (BA: Balustrade, BH: Handrails, BN: Nosings & BT: TGSI)			
CX	Ceilings (CE Ceiling External, CI Ceiling Internal)			
D00	Door - Refer to door schedules			
FL	Floors			
G1	Group 1 Proprietary Item - supplied & installed by Contractor			
G2	Group 2 Proprietary Item - supplied by Client & installed by Contractor			
G3	Group 3 Proprietary Item - supplied & installed by Client			
J-xx	Joinery (JO-BD bench dry, JO-BW bench wet, JO-LE lectern, JO-SE seat, JO-ST storage)			
MXx	Materials & applied finishes			
PF	Plumbing Fixtures			
Rx	Roof (RD downpipes, RF roof types, RG roof gutters, RS roof sumps, RV roof vents)			
SI	Signage			
W00	Window - refer to window schedule			
WXX	Wall type - refer to wall schedule			
WP	Waterproof Membrane Systems			
Legend				
	Items to be confirmed	Blue text		
	Current revision changes	Changed (red), deleted (strike through) and yellow highlight		
	Prior revision changes	Text		
Code	Description	Specification Description	Contractor Deliverable(s)	Rev T2
AM - Architectural Metalwork				
Notes:		1 Refer to architectural specification and drawings. 2 Refer to structural documents. 3 Provide shop drawings for approval prior to manufacture. 4 Provide samples of components for approval prior to manufacture. 5 Provide certification of architectural metalwork to comply with AS1170 in conjunction with facade system. 6 All welds shall be 6mm SP continuous fillet weld. SP denotes structural purpose in accordance with AS 1554. Welding consumables to have nominal tensile strength of 490MPa. All visible welds to be ground smooth and flush with adjacent surfaces prior to finishing. Confirm suitability of weld finish prior to finishing. 7 Prepare all surfaces, by hand if required, to provide a smooth and clean finish, including, but limited to all galvanised and painted finishes. 8 Provide all structural certification as required by certifier, including, but not limited to crowd-loading. (For D&C Procurement)		
AM-1	Vertical External Cladding	Description: Custom folded cladding fabricated from 0.7 BMT zincalume sheet Subframe and fixing: Refer to Façade Engineer's documents. Profiles - Refer A-760001: a Triangle profile b Sawtooth Profile c Sawtooth Profile (mirror reverse of AM-1b) d Triangle profile corner configuration e Sawtooth Profile corner configuration f Sawtooth Profile corner configuration (mirror reverse of AM-1e) Prequalified supplier: Stratco: Cindy Lee: 0400 223 079: cindy.lee@stratcoqld.com.au Prequalified supplier and installer: Sustainable Cladding & Roofing: Ryan Finlay: 0432 189 879: ryan@sustainablecladding.com.au	Shop Drawings: provide shop drawings to Façade Engineer's requirements and Architectural Specification. Prototype: On site for complex junctions. Certificate: As required for Performance Solution Report; Form 12; refer also to Façade Engineer's Documents.	T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
AM-2	Horizontal External Flashing	Description: Custom folded horizontal flashing fabricated from 0.7 BMT zinalume sheet Joints: Joints to typically align with grids @ 4200mm centres .Fabricate flashing in lengths to suit. Fixings: Fix flashings along upturned edge with roofing screws at centres to prevent oilcanning. Profiles & Finishes - Refer A-760001: a Row 1 (Base+ portions of other rows) - PT-EGb (Yellow) b Row 2, 3 & 4 - Zinalume c Row 5 (Roof) - Zinalume (parapet capping to be 1.2mm BMT) Prequalified supplier: Stratco: Cindy Lee: 0400 223 079: cindy.lee@stratcoqld.com.au Prequalified supplier and installer: Sustainable Cladding & Roofing: Ryan Finlay: 0432 189 879: ryan@sustainablecladding.com.au	Shop Drawings: provide shop drawings to Façade Engineer's requirements and Architectural Specification. Prototype: On site for complex junctions. Certificate: As required for Performance Solution Report; Form 12; refer also to Façade Engineer's Documents.	T1
AM-3	Vertical External Flashing	Description: Custom folded vertical flashing fabricated from 0.7 BMT zinalume sheet wrapped around 240x45 hardwood rail. Fixing: Provide 50x50 alum fixing angle to Engineer' details. Detail: Refer to detail on 7 on A-760001 Finish: a PT-EGb (Yellow) b Zinalume Prequalified supplier: Stratco: Cindy Lee: 0400 223 079: cindy.lee@stratcoqld.com.au Prequalified supplier and installer: Sustainable Cladding & Roofing: Ryan Finlay: 0432 189 879: ryan@sustainablecladding.com.au	Shop Drawings: provide shop drawings to Façade Engineer's requirements and Architectural Specification. Prototype: On site for complex junctions. Certificate: As required for Performance Solution Report; Form 12; refer also to Façade Engineer's Documents.	T1
AM-4	Perforated Ceiling Panel	Description: Removable perforated ceiling panel mounted in external ceilings Selection: Webforge 3mm thick perforated aluminium panel with 4.8mm round holes at 6.4mm staggered pitch centres; 51% open area. Subframe: fully welded 50x50x3mm alum angle perimeter frame with intermediate cross members as required to support the panel. Panel Fixings: exposed button head socket screws with seated washers to perimeter & intermediate supports. Finish: PT-PCy (yellow powdercoat) Dimensions: a: 900x600 b: 1158x600 c: 600x600	Shop Drawings: for each panel, including subframe and fixings. Certificate: Form 15 and Form 12 for ceiling framing.	T1
AM-5	Verandah Roof Nose Flashing	Description: Custom folded nose flashing fabricated from 0.7 BMT zinalume sheet. Fixing: Provide 50x50 alum fixing angle to Engineer' details. Detail: Refer to profile on A-710001 and detail on Finish: Prequalified supplier: Stratco: Cindy Lee: 0400 223 079: cindy.lee@stratcoqld.com.au Prequalified supplier and installer: Sustainable Cladding & Roofing: Ryan Finlay: 0432 189 879: ryan@sustainablecladding.com.au	Shop Drawings: required, including fixings and separation of dissimilar metals. Certificate: Form 15 for roof sheeting; Form 12.	T1
AM-10	Plant Room Screen	Description: Decorative metal screen fixed to 65 SHS posts (to engineer's details) Horizontal rails: Top rail: 90x40x1.6mm aluminium angle, PT-PCy (yellow) Mid rails: 50x50x6 aluminium T-section, clear anodised Bottom rail: 90x40x1.6 aluminium angle, PT-PCy (yellow) Verticals: Row 1 - 40x70x1.6 aluminium angle, clear anodized, spaced 50mm apart, fixed on 70 leg Row 2 - 40x40x1.6 aluminium angle, clear anodized, spaced 25mm apart. Row 3 - 40x70x1.6 aluminium angle, clear anodized, spaced 50mm apart, fixed on 70 leg Row 4 - 50x40x1.6 aluminium angle, clear anodized, spaced 30mm apart, fixed on 50 leg End rails - Turn Top and Bottom rails 90x40x1.6 angles down/up to meet/create continuous frame both sides of opening, PT-PCy (yellow)	Shop Drawings: for full screen, setout, fixings and footings. Certificate: Form 12	T1
BX - Balustrades, Handrails, Stair Nosings, Tactile indicators				

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
Notes: 1 Refer to architectural specification and drawings. 2 Refer to structural documents. 3 Provide shop drawings for approval prior to manufacture. 4 Provide samples of components for approval prior to manufacture. 5 All balustrades, handrails, nosings and tactile indicators to comply with NCC Clause D2.16 and AS1428.1. 6 Tactile indicators shall be installed to comply with AS 1428.4.1 (2009) & AS 1428.1 (2009). 7 Where slip resistance is specified, provide slip resistance testing to AS4586. 8 All welds shall be 6mm SP continuous fillet weld. SP denotes structural purpose in accordance with AS 1554. Welding consumables to have nominal tensile strength of 490MPa. All visible welds to be ground smooth and flush with adjacent surfaces prior to finishing. Confirm suitability of weld finish prior to finishing. 9 Prepare all surfaces, by hand if required, to provide a smooth and clean finish, including, but limited to all galvanised and painted finishes. 10 Ensure that dissimilar metals are separated with neoprene spaces. 11 Provide all structural certification as required by certifier, including, but not limited to crowd-loading. (For D&C Procurement)				
BH-1	Handrail - Entry Walkway, Stair 1, Stair 2 & North Entry	Description: 900 high 40dia CHS handrail with 40dia posts, wall brackets & 40dia mid rails, refer to drawings for configurations. Handrail Termination: Extend handrail 300mm past last post and turn down. Refer to 50-series drawings. Supports: Posts @ 1200 max ctrs to be bolted to PFC edge beam with concealed sleeve fixing to eng details. Finish: PT-PCy (yellow) Lighting: PUC integrated lighting; refer to Electrical Engineer's documents.	Shop Drawings: including fixings and light integration; refer to Electrical Engineer's documents. Certificate: Structural loading and installation.	T1
BT-1	Tactile Ground Surface Indicators - Comcork	Selection: Comcork Tactiles Dimensions: 300x600 tiles Supplier / Contact: All Seas Flooring/ Roxanne Pearson/ e: flooring@allseasgroup.com/ ph:0408120101 Location: Stair 1 Landing Colour: Black Fixings: All mats should be butt joined and installed using Mapei G19. Slip Resistance: P4/ R11.	Installation: to AS1428.4.1	T1
BT-2	Tactile Ground Surface Indicators - Individual buttons	Selection: Tactile Systems Discrete Stainless Steel Composite with Carb Infill Colour: Black Dimensions: 25mm stem Supplier / Contact: Tactile Systems Australia Ph: 07 5580 6993 Email:sales@tactilesystems.com.au Location: Stair 1 & 2 Installation: to comply with AS1429.1	Installation: to AS1428.4.1	T1
CX - Ceilings				
Notes: 1 Refer to architectural specification and drawings. 2 Linings described below are from bottom lining (finished surface) to top linings. 3 Provide samples of components for approval prior to manufacture. 4 Where used in a wet area, ensure ceilings are moisture resistant. 5 Provide ceiling framing system to suit application, i.e. accounting for bracing and loading of linings, insulation, wind loads and seismic loads. Typically use Rondo Key Lock Concealed Ceiling System to suit. 6 Where walls are shown to connect to underside of ceiling, partition sub-contractor to design & construct ceiling framing for wall restraint below to AS 4600. 7 Design, construct & certify ceiling systems with seismic restraint to conform to AS 1170.4 and Earthquake design category I . Refer structural documents for seismic design criteria.				
CA-1	Ceiling Access Panel (Internal Perforated)	Description: Perforated Ceiling Access Panel Selection: Stratopanel access panel 12.5 12/25 R Dimensions: 600 x 600mm. Finish: to match ceiling. Joints: seamless Supplier: Knauf	Coordination: Position of Access Panel to be coordinated with ceiling battens, ceiling mounted services and structural framing.	T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
CA-2	Ceiling Access Panel (Flush)	Description: Flush Ceiling Access Panel Selection: Trafalgar non-fire rated metal access panel with concealed frame & cam lock Flange type: Wet Wall to suit set bead for flush set installation Dimensions: 600 x 600mm. Finish: to match ceiling. Supplier / Contact: Trafalgar	Coordination: Position of Access Panel to be coordinated with ceiling battens, ceiling mounted services and structural framing.	T1
CA-3	Ceiling Access Panels (acoustic Plant Room Floor)	Description: Floor mounted access panel to open downwards Selection: Trafalgar acoustic access panel Dimensions: 530mm x 530mm Acoustic Rating: Rw 34 Installation: Co-ordinate position of access panels in ceiling below to allow both to open. Refer detail on A-750001	Coordination: Position of Access Panel to be coordinated with ceiling battens, ceiling mounted services and structural framing.	T1
CA-4	Ceiling Access Panels (external perforated)	Description: Ceiling Access Panel within Type CE-1 (perforated fc) Selection: Trafalgar Tile Insert 316ss frame (allow for CE-1 insert; concealed fixing by Contractor) Dimensions: 600 x 600mm. Finish: to match ceiling, including perforation pattern. Supplier: Trafalgar	Coordination: Position of Access Panel to be coordinated with ceiling battens, ceiling mounted services and structural framing.	T1
CA-5	Ceiling Access Panels (internal flush)	Description: Ceiling Access Panel within Type CI-4 (16mm fire rated PB) Selection: Trafalgar acoustic access panel Dimensions: 600 x 600mm. Acoustic Rating: Rw 31 Finish: to match ceiling. Supplier: Trafalgar	Coordination: Position of Access Panel to be coordinated with ceiling battens, ceiling mounted services and structural framing.	T1
CBH-1	Ceiling Acoustic Bulkhead	Description: Acoustic Bulkhead made of perforated FC and integrated LED light, refer to sheet A750001 Dimensions: a: 2358cos L x 1158cos W x 750 H b: 1570 L x 1158cos W x 450 H Lighting: integrated strip LED; refer to Electrical Engineer's documents.	Certificate: framing Form 15; Form 12. Sample: 1no CBH-1 for approval.	T1
CE-1	Ceiling External (Perforated) - Covered Outdoor Area	Description: Perforated FC ceiling with decorative battens supported on concealed suspension system. Selection: Décor Decorlux FC Perforated with DecorSorb integrated acoustic backing. Thickness: 9mm Dimensions: 2400x1200 mm. Finish: Smooth Paint finish; refer to drawings and PT codes Profile: AL250-S-120 (to match 12/25R) Edges: Square Battens: MTR-1b & MTR-1c , refer to A-210002 Installation: in accordance with manufacturer's details. Fixings: no visible fixings. Framing: Light weight steel framing, Acoustic/ Insulation: Bradford Acoustigard 75mm 14kg/m ³ R1.8 Borders: Solid 50mm (nominal) Acoustic Performance: refer to acoustic engineer's report. Supplier/ Contact: Ross Palmer/ e:ross.palmer@decorsystems.com.au/ ph: 0432 168 343	Shop Drawings: include framing and sheet set out. Sample: nom 4.2m wide bay for approval. Certificate: framing Form 15; Form 12.	T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
CE-2	Ceiling External (Flush) - External Circulation	Description: FC ceiling with decorative battens supported on concealed suspension system. Selection: James Hardie Versilux Lining Dimensions: 1200 x 3000 Thickness: 9mm Finish: Smooth Paint finish; refer to drawings and PT codes Colour: Refer 21 series drawings. Joints: Butt join. Battens: MTR-1b & MTR-1c , refer to A-210002 Fixings: no visible fixings. Framing: Light weight steel framing Insulation: Install WP-4 to Rear Entry, Front Entry & Stair 1 ceilings only Acoustic Performance: n/a. Supplier: James Hardie	Shop Drawings: include framing and sheet set out. Sample: nom 4.2m wide bay for approval. Certificate: framing Form 15; Form 12.	T1
CI-1	Ceiling Internal (Perforated) - Workplace, Kitchen, Training Room, First Aid Room, Health Room	Description: Perforated plasterboard ceiling with decorative battens supported on concealed suspension system. Selection: Knauf Stratopanel 12/25R with acoustic backing. Dimensions: 1200x2400mm Thickness: 12.5mm Finish: Paint finish; refer to drawings and PT codes Battens: MTR-1b, MTR-1c , refer to A-210002 Fixings: no visible fixings. Framing: Light weight steel framing Supplier / Contact: Knauf/ Damien Morrison. m: 0401 893 996. e: damien.morrison@knauf.com. Acoustic/ Insulation: Bradford Acoustigard 75mm 14kg/m3 R1.8 Acoustic Performance: refer to acoustic engineer's report. Supplier: Knauf	Shop Drawings: include framing and sheet set out. Sample: nom 4.2m wide bay for approval. Certificate: framing Form 15; Form 12.	T1
CI-2	Ceiling Internal (Flush MR) - Shower, PWD toilet, Male & Female Bathroom	Description: Moisture Resistant Plasterboard ceiling supported on concealed suspension system. Selection: Knauf Wetstop 13 Dimensions: 2400x1200 mm Thickness: 13mm Finish: Paint finish; refer to drawings and PT codes Battens: MTR-1b & MTR-1c , refer to A-210002	Shop Drawings: include framing and sheet set out. Certificate: framing Form 15; Form 12.	T1
CI-3	Ceiling Internal (Flush) - Meeting Rooms, Comms Room, Storage, South Circulation	Description: Plasterboard ceiling supported on concealed suspension system. Selection: Knauf Sheetrock HD Dimensions: 1200mm x 2400mm Thickness: 13mm Finish: Paint finish; refer to drawings and PT codes Battens: MTR-1b & MTR-1c , refer to A-210002 Supplier: Knauf	Shop Drawings: include framing and sheet set out. Certificate: framing Form 15; Form 12.	T1
CI-4	Ceiling Internal (Flush) - Meeting Rooms, Boardroom, Offices	Description: Plasterboard ceiling supported on concealed suspension system. Selection: Knauf Firestop Dimensions: 1200mm x 2400mm Thickness: 16mm Finish: Paint finish; refer to drawings and PT codes Battens: MTR-1b & MTR-1c , refer to A-210002 Supplier: Knauf	Shop Drawings: include framing and sheet set out. Certificate: framing Form 15; Form 12.	T1
FL - Floors				
Notes:		1 Refer to architectural specification and drawings. 2 Refer to structural documents. 3 Provide samples of components for approval prior to manufacture. 4 Install floor finishes in accordance with the manufacturers' requirements, including substrate suitability, preparation, installation, finishing and cleaning. 5 Contractor to prepare all substrates in accordance with relevant Australian Standards. 6 Where existing substrates are used allow to prepare substrate to meet manufacturers' requirements. E.g. allow to grind and skim coat existing floor slab under all new finishes to achieve a true surface suitable for the new floor finish.		

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
		7 All timber products to be supplied with FSC, AFS or PEFC certification - chain of custody certification to be provided for approval. 8 Where slip resistance is specified, provide slip resistance testing to AS4586.		
Structural Floors (FL-10-10)				
FL-1	CFC	Description: Compressed Fibre Cement Floor Selection: 18mm thick James Hardie Hardie Panel installed in accordance with Manufacturer's details. Insulation: Kingspan Kooltherm K10 PLUS; 31mm thick; R1.1; continuous; mechanically fixed below joists; refer structural engineer's documents. Sealer: where CFC will remain exposed provide an appropriate sealer to finish.		T1
FL-2	Entry Mat	Selection: Birrus Ultramat 10mm Slimline with continuous stainless steel angle perimeter trim Type: Open Construction Substrate: Install non-shrink grout substrate over FC floor to achieve 10mm recess for mat. Waterproof Membrane: WP-3 Drainage: Provide tundish and drainage piping through floor to manufacturer's requirements. To free drain to subfloor. Insert: Cut Pile Colour: Latte Extrusion Finish: Bronze Anodised Supplier/ Contact: Birrus/ Tony Cossor/ ph:0424 285 114/ e: info@buildingstuff.net.au		T1
FL-3	Open Mesh Decking	Selection: GRP Heel Guard Moulded Grating with steel framing to Engineer's details Thickness: 38mm Cutting: The under side has a 40x40 grid pattern, and the sheets must be cut to maintain a continuous perimeter bar. Cut sizes must be a multiple of 40mm + 7mm bar in both directions. Co-ordinate support frame configuration to suit cut sheet sizes. Colour: Light Grey Slip rating: P5 Stair 1 Stair Tread Selection: GRP Heal Guard Stair Treads with integrated nosing Colour: Light Grey with Yellow nosings Installation: Provide steel riser between stringers with angle supports for treads. Refer to detail on A-500001	Certificate: Slip resistance.	T1
FL-4	External Concrete Pathways	Selection: Standard grey cement mix with light acid wash finish. Slip Rating: P4 Sealer: CSS Streetscape Sealer (including to integral hobs)	Sample: On site sample with light acid wash finish. Certification: Wet pendulum test and certificate.	T1
FL-5	CFC Plant Deck (non trafficable)	Description: Compressed Fibre Cement Floor Selection: 18mm thick James Hardie Hardie Panel installed in accordance with Manufacturer's details. Sealer: where CFC will remain exposed provide an appropriate sealer to finish.		T1
Carpet (FL-11 to 20)				
FL-11	Carpet tiles (Workplace, Meetings Rooms)	Description: Carpet tile direct stick on substrate Selection: Shaw Contract Accent Tile 5T475 Colour: Barossa Earth 57752 Size: 610 x 610 Laying Pattern: Random Skirting: MTR-1a, finish refer to A-60 drawings Lead Time: 12 weeks, if not in stock Supplier/ Contact: Shaw Contract/ Chrystal Timms; ph: 498 002 777; e: chrystal.timms@shawcontract.com.	Certificate: provide flammability testing with proposed adhesive.	T1
FL-12	Carpet tiles (Kitchen, Boardroom, Health Room, Training Room, First Aid)	Description: Carpet tile direct stick on substrate Selection: Shaw Contract Accent Tile 5T475 Colour: Blue Mountains 57496 Size: 610 x 610 Laying Pattern: Random Skirting: MTR-1a, finish refer to A-60 drawings Lead Time: 12 weeks, if not in stock Supplier/ Contact: Shaw Contract/ Chrystal Timms; ph: 498 002 777; e: chrystal.timms@shawcontract.com.	Certificate: provide flammability testing with proposed adhesive.	T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
Resilient Finishes (FL-21 to 30)				
FL-21	Cork floor (Kitchen, Boardroom, Training Room, Workplace, Health Room, First Aid Room)	Resilient floor finish direct stick to substrate, butt joints Selection: Comcork WalkEasy Thickness: 2.5mm (max. 5mm including skim coat) Colour: a: Midnight Blue (dark blue) b: Mocha (brown) Sheet size & pattern: 1800mm x 900mm sheets laid in brick pattern. Confirm setout on site before installation. Substrate: FL-1 with skim coat of Ardex Feather finish to supplier's specifications. Sealer: Polyurethane (Peerless JAL Dr. Schutz or approved similar) Skirting: MTR-1a, finish refer to A-60 drawings Slip Resistance: P3 Material Group Number: 3 Lead Time: 4 weeks Supplier / Contact: All Seas Flooring/ Roxanne Pearson/ e: flooring@allseasgroup.com/ ph:0408120101		T1
FL-22	Cork floor - wet area (Male Bathroom, Female Bathroom, PWD toilet)	Resilient floor finish direct stick to substrate, butt joints and cold weld between different colours Selection: Comcork WalkEasy Thickness: 2.5mm (max. 5mm including skim coat) Colour: a: Midnight Blue (dark blue) b: Ivory (beige) c: Denim (light blue) Sheet size & layout: 1800mm x 900mm laid in brick pattern. Confirm setout on site before installation. Substrate: FL-1 with waterproof membrane with skim coat of Ardex Feather finish to supplier's specifications; junctions to comply with NCC Waterproof Membrane: WPM-1 Sealer: Polyurethane (Peerless JAL Dr. Schutz or approved similar) Skirting: Coving to match floor material, 200mm height. Installation: Refer to Comcork Flooring Installation Instructions Slip Resistance: P3 Material Group Number: 3 Lead Time: 4 weeks Supplier / Contact: All Seas Flooring/ Roxanne Pearson/ e: flooring@allseasgroup.com/ ph:0408120101		T1
FL-23	Cork floor - wet area to falls (Male Bathroom)	Resilient floor finish installed over screed to falls and waterproof membrane, butt joints and cold weld between different colours Selection: Comcork: WalkEasy Thickness: 2.5mm (max. 5mm including skim coat) Colour: Midnight Blue (dark blue) Sheet size & layout: 1800mm x 900mm laid in brick pattern. Confirm setout on site before installation. Substrate: FL-1 with waterproof membrane with skim coat of Ardex Feather finish to supplier's specifications; junctions to comply with NCC Waterproof Membrane: WPM-1 Sealer: Polyurethane (Peerless JAL Dr. Schutz or approved similar) Skirting: Coving to match floor material, 200mm height. Installation: Refer to Comcork Flooring Installation Instructions Slip Resistance: P3 Material Group Number: 3 Lead Time: 4 weeks Supplier / Contact: All Seas Flooring/ Roxanne Pearson/ e: flooring@allseasgroup.com/ ph:0408120101	Certification: Waterproofing installation certificate	T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
FL-24	Cork floor - wet area to falls (Shower room)	Resilient floor finish installed over screed to falls and waterproof membrane, butt joints and cold weld between different colours Selection: Comcork: Textured thickness 3.2mm Colour: Ivory (beige) Sheet size & layout: 1800mm x 900mm laid in brick pattern. Confirm setout on site before installation. Substrate: FL-1 with waterproof membrane with skim coat of Ardex Feather finish to supplier's specifications; junctions to comply with NCC Waterproof Membrane: WPM-1 Sealer: Polyurethane (Peerless JAL Dr. Schutz or approved similar) Skirting: Coving to match floor material, 200mm height. Installation: Refer to Comcork Flooring Installation Instructions Slip Resistance: P4 Material Group Number: 3 Lead Time: 4 weeks Supplier / Contact: All Seas Flooring/ Roxanne Pearson/ e: flooring@allseasgroup.com/ ph:0408120101	Certification: Waterproofing installation certificate	T1
FL-25	Cork floor - Antistatic (Comms Room)	Anti-static resilient floor finish direct stick to substrate, butt joints and cold weld between different colours Selection: Walkeasy Anti-static Thickness: 2.5mm (max. 5mm including skim coat) Colour: Sky Blue (blue) Sheet size & pattern: 1800mm x 900mm sheets laid in brick pattern. Confirm setout on site before installation. Substrate: FL-1 with skim coat of Ardex Feather finish to supplier's specifications. Sealer: Polyurethane (Peerless JAL Dr. Schutz or approved similar) Skirting: MTR-1a, finish refer to A-60 drawings Installation: Refer to Comcork Flooring Installation Instructions Slip Resistance: P3 Material Group Number: 3 Lead Time: 4 weeks Supplier / Contact: All Seas Flooring/ Roxanne Pearson/ e: flooring@allseasgroup.com/ ph:0408120101		T1
Pavers (FL-31 to 35)				
FL-31	Polished Concrete floor pavers	Selection: Adbri Mansory Euro Honed 4x4 Colour: Athens Finish: Honed Dimensions: 400x400x40 Sealer: CCS Streetscape Grout: Mapei Kerapoxy / 132 Beige 2000 Laying Pattern: 1/3 running bond; confirm with architect on site. Substrate: FL-1 with waterproof membrane; junctions to comply with NCC Waterproof Membrane: WPM-3 to external courtyard only Skirting: MTR-1a, finish refer to A-60 drawings Slip Resistance: P4 Lead Time: 8 to weeks Supplier / Contact: Adbri Mansory/ Eddie Briffa/ e:eddie.briffa@adbri.com.au/ ph:07 33824100 - 0403721941	Certification: Wet pendulum test and certificate.	T1
Miscellaneous				
FL-36	Anti-Slip Tape Self Adhesive	Anti-slip tape to be applied aligned with the external edge of the beam. Selection: Floor Safe Self Adhesive Anti-slip Tape Colour: White Dimensions: 50mm wide Slip Resistance: P5 Supplier / Contact: Floor Safe/ https://floorsafe.com.au/		T1
G1 - Group 1 Proprietary Item Supplied & Installed by Contractor				
Notes:		1 Refer to architectural specification and drawings. 2 Provide suitable framing in walls, floor and ceiling for support / fixing of G1 components. 3 Refer services documents. 4 Install in accordance with the manufacturers' requirements, including substrate suitability, preparation, installation, finishing and cleaning.		

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
G1-BBQ-1	Electric barbecue	Selection: Infinity Teppanyaki 900 BBQ Lid: Flat Lid Removable 15AMP Control: a: Left side control b: Right side control Supplier: Cookout/ sales@cookout.com.au/ ph:5549 0560	Shop drawings: confirm installation requirements for joinery shop drawings.	T1
G1-BIN-1	Bin - 60L	Selection: MultiSort Recycling Range 60L Product Code: MS-60RCG (base) Size: 515D x 282W x 645+25H Lid: a: Lid Red with diamond aperture (general waste), MS-60RCG-LANREO b: Lid Yellow with circular aperture (recycling /containers for change), MS-60RCG-RECY c: Lid Blue with paper slot (paper/cardboard recycling), MS-60RCG-PCB Supplier: Source Separation Systems/ e: info@sourceseparationsystems.com.au/ ph: 1300 739 913		T1
G1-BIN-2	Bin - 120L	Selection: Sulo Bin 120L. Size: 545D x 480W x 930H. Bin Colour: Green Lid: a: Lid Red b: Lid Yellow Supplier: Sulo/ e: sulosales@pactgroup.com/ ph: 1300 364 388		T1
G1-BIN-3	Bin - Joinery	Selection: Hideaway Waste Bin Compact Soft-Close (Door Pull) Product Code: No: 503.52.783 Capacity: 2x35 Ltr Bucket Size: 368W x 615H x 518D Additional: 1x Hideaway Coloured Liner Holders- For Bin Pails Red - No: 503.51.965 1x Hideaway Coloured Liner Holders- For Bin Pails Yellow - No: 503.51.968 Supplier: Hafele/ Hideaway Bins.		T1
G1-BIN-4	Bin - female sanitary bin	Selection: Initial Feminine Hygiene Unit Capacity: 17.5 L Dimensions: H 396mm x W 499mm x D 167mm Type: Pedal Supplier: Initial		T1
G1-BL-1	Blind - Glare	Selection: Vertilux Easydrive BGS Roller Blind Configuration: Single Base rail: Ovolo 27.5mm Roll Direction: Reverse (forward roll) Fixing: Ceiling mounted Fabric: a: Status 5%™ Transparent Colour: Quartz b: Chanell Translucent Colour: Lustre Size: Final sizes must be confirmed by a site check measure Supplier/ Contact: Vertilux/ Wynn Perry; ph: 0421 383 407; e: wynn.perry@vertilux.com.au.		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
G1-BL-2	Blind - Glare Multilink	Selection: Vertilux Easydrive BGS Roller Blind Configuration: Multilinked Base rail: Ovolo 27.5mm Roll Direction: Reverse (forward roll) Fixing: Ceiling mounted Fabric: Status 5%™ Transparent Colour: Quartz Size: Final sizes must be confirmed by a site check measure Supplier/ Contact: Vertilux/ Wynn Perry; ph: 0421 383 407; e: wynn.perry@vertilux.com.au.		T1
G1-BL-3	Blind - Motorized	Selection: Vertilux Motorised Roller System Configuration: Multilinked Controls: RTS motors with remote control Fabric: Status 5%™ Transparent Colour: Quartz Base rail: Ovolo 27.5mm / 35mm flat for drop higher than 4000mm Roll Direction: Reverse (forward roll) Fixing: Ceiling mounted. Packers 112x19 required on sloped ceilings, all Roller Blinds to be mounted horizontally. Refer to sheet A750001 Size: Final sizes must be confirmed by a site check measure Supplier/ Contact: Vertilux/ Wynn Perry; ph: 0421 383 407; e: wynn.perry@vertilux.com.au.		T1
G1-CM-1	Coffee Machine	Selection: Franke Coffee Machine A600 FM EC 1G 2P H1 + Milk Cooling Unit SU12 2M EC - Dual milk (2x 4.5L) Supplier / Contact: BloomTec/ Avril Bloomfield: ph:0408 790 427; e:0408 790 427	Coordination: hydraulic supply and drainage to be coordinate with joinery.	T1
G1-CPD-1	Cupboard	Selection: Planex Single Sided Linea Cabinet Dimensions: 1800W x 500D x 1000H Finish: White with cream Acupanel Type: a: Standard b: Custom with 4 rear cut outs for GPOs, refer to details A-750015 Lead time: 4 weeks Supplier / Contact: Planex/ Alex Jardel/ e:alex.jh@planex.com.au/ ph: 03 87951100		T1
G1-CPD-2	Cupboard	Selection: Planex Single Sided Linea Cabinet Dimensions: 1200W x 500D x 1000H Finish: White with cream Acupanel Lead time: 4 weeks Supplier / Contact: Planex/ Alex Jardel/ e:alex.jh@planex.com.au/ ph: 03 87951100		T1
G1-DW-1	Dishwasher - Training Kitchen	Selection: Fisher & Paykel Series 9 Contemporary Double DishDrawer™ Dishwasher Product code: DD60D4NX9 Dimensions: 599W x 573D x 820-880H Finish: Stainless Steel Supplier/ Contact: Harvey Norman / Kathleen Martin / 07 3297 3700 / kathleen.martin@au.harveynorman.com		T1
G1-DW-2	Dishwasher black - Boardroom	Selection: Fisher & Paykel Series 9 Contemporary Double DishDrawer™ Dishwasher Product code: DD60D4NB9 Dimensions: 599W x 573D x 820-880H Finish: Black Stainless Steel Supplier/ Contact: Harvey Norman / Kathleen Martin / 07 3297 3700 / kathleen.martin@au.harveynorman.com		T1
G1-DW-3	Dishwasher commercial - Kitchen	Selection: Miele Commercial Integrated Dishwasher Product code: PFD 101 I Dimensions: 598W x 570D x 805H Front: MLAM-8 Supplier/ Contact: Harvey Norman / Kathleen Martin / 07 3297 3700 / kathleen.martin@au.harveynorman.com		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
G1-FB-1	Fire blanket	Selection: Wall mounted fire blanket to fire consultant's requirements. Installation: 1200mm above skirting	Signage: to AS 2444-2001	T1
G1-FE-1	Fire extinguisher - 4.5kg wall mounted	Selection: Wall mounted fire extinguisher to fire consultant's requirements. Installation: 50mm above skirting Type: DCP	Signage: to AS 2444-2001	T1
G1-FE-2	Fire extinguisher - 4.5kg in recessed cabinet	Selection: Flush set recessed fire extinguisher cabinet Dimensions: Nominally 230 wide, 160 deep, height to suit timber trims. Panel infill: 9mm FC sheet, finish refer to A-60 drawings Opening: Push latch opening system Installation: Panel face to be flush with timber battens. Height of panel from skirting to batten at sill datum Door signage: 'FIRE EXTINGUISHER" letter 32mm height, according with AS 2444-2001 Type: DCP Supplier/ Contact: Checkpoint/ Jacob Granger/ 0477 331 615/ jacob@checkpointgroup.com.au	Shop Drawings: for cabinet and fixing. Signage: to AS 2444-2001	T1
G1-FE-3	Fire extinguisher - 5kg wall mounted	Selection: Wall mounted fire extinguisher to fire consultant's requirements. Installation: 50mm above skirting Type: CO2	Signage: to AS 2444-2001	T1
G1-HD-1	Hand Dryer	Selection: Dyson Airblade V. Finish: Nickel. Supplier: Dyson.		T1
G1-LKCP-1	Access Control Panel - Lockers (Kitchen)	Selection: Access panel (Reader and Touch Display) of Smart Lockers System Yellow Box Supplier: Yellow Box	Shop Drawings: for integration of Yellow Box system with locker joinery. Coordination: access system with locker joinery.	T1
G1-MIR-1	Mirror	Selection: Viridian DécorMirror™ Safe - 6mm Clear. Dimensions: Size to fit, refer drawings	Certificate: safety glazing certificate.	T1
G1-MIR-2	Mirror (PWD Staff Amenities) (PF-HB-2 & PF-HB-3)	Selection: Viridian DécorMirror™ Safe - 6mm Clear. Dimension: 950x350. Finish: Silver-backed clear float Grade A safety glass thickness to AS1288.1; confirm measurements on site & setout of tiles prior to fabrication. Fixing: adhesive mounted to substrate wall. ensure compatible adhesive and install as per manufacturers recommendations. Edges: external edges and angled corners to be protected with mirror polished stainless steel trim to AS1288.	Certificate: safety glazing certificate.	T1
G1-MW-1	Microwave	Selection: Bosch Series 2 Built-In Microwave Oven 59 x 38 cm Black Product Code: BEL653MB4A Capacity: 25L Supplier/ Contact: Harvey Norman / Kathleen Martin / 07 3297 3700 / kathleen.martin@au.harveynorman.com		T1
G1-OV-1	Oven	Selection: Bosch Series 8 Built-in oven 60 x 60 cm Black Product Code: HBG976MB1A Supplier/ Contact: Harvey Norman / Kathleen Martin / 07 3297 3700 / kathleen.martin@au.harveynorman.com		T1
G1-PTD-1	Paper Towel Dispenser	Selection: Roll Hand Towel Dispenser - White Enamel - to suit SCOTT® Roll towel 100m (4419) & 140m (44199) - Kimberly Clark Professional Supplier: Blackwoods		T1
G1-PTD-2	Paper Towel Dispenser and Bin	Selection: ASI JD Macdonald Paper Towel Dispenser & Waste Bin 7.6L Recessed, Traditional Collection Product Code: 10-0462-AD Supplier: ASI JD Macdonald		T1
G1-PTD-3	Paper Towel Dispenser and Bin	Selection: ASI JD Macdonald Paper Towel Dispenser & Waste Bin 46L Recessed, Traditional Collection Product Code: 10-0469-AD Supplier: ASI JD Macdonald		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
G1-REF-1	Fridge Single Door	Selection: SKOPE ActiveCore BME 1 Glass Door Display or Storage Fridge 584L - BME600N-A		T1
G1-REF-2	Fridge Double Door	Selection: SKOPE ActiveCore BME 2 Glass Door Display or Storage Fridge 1079L - BME1200N-A		T1
G1-REF-3	Bar Fridge Stainless Steel	Selection: Husky 118L Single Solid Door Alfresco Outdoor Drinks Chiller Finish: Stainless Steel Product code: ALFC1SD840 Dimensions: 838H x 556W x 541D		T1
G1-REF-4	Bar Fridge Black	Selection: Husky 118L Single Solid Door Alfresco Outdoor Drinks Chiller Finish: Black Product code: ALFC1SDBLK840 Dimensions: 838H x 556W x 541D		T1
G1-RH-1	Rangehood	Selection: refer to Mechanical Engineer's documents.		T1
G1-SD-1	Soap Dispenser	Selection: Edco - Soap Dispenser - Stainless Steel - Vertical - 1100ml Supplier: Blackwoods		T1
G1-SE-1	Seat	Selection: Quatro Design Bondi with timber Dimensions: D 3200 mm x H 485 mm Seat: Spotted Gum Concrete colour: Kalgoorlie Supplier/ Contact: Quatro Design/ Rikki-Lee McAndrew: ph: 0266721190 : e:rmcandrew@quatrodesign.com.au		T1
G1-SHF-1	Dexion Shelving	Selection: Dexion Ultima Longspan 2. Shelving: Timber. Standard Finish: Stone White Beams & Anthracite Uprights. Size: a: 2400W x 760D x 2000H b: 1800W x 760D x 2000H Shelves: 5. Lead time: 4 weeks Supplier/ Contact: Dexion/ Ben Woods; ph: 9830 5041; e: ben.woods@dexion.com.au.		T1
G1-TP-1	Toilet partition system - Female Bathroom	Partitioning System System: same as Laminex Privacy Plus System Front panel and divisions height: 2700mm Front panel divisions & doors substrate: 13mm Egger Compact Laminate Front panel and divisions colour: Misty Blue Doors colour: Apline White Hardware and Components: same as Laminex System from Metlam (https://metlam.com.au/) Hardware finish: Satin Chrome		T1
G1-TP-2	Toilet partition system - Male Bathroom	Laminex Waterloo Partitioning Systems System: Privacy Plus System Front panel and divisions height: 2700mm Front panel divisions & doors substrate: 13mm Laminex Compact Laminate Front panel and divisions colour: French Navy Natural Finish Doors colour: White Natural Finish Hardware and Components finish: Matte Black		T1
G1-TRH-1	Toilet roll holder (see PF-WC codes)	Selection: Metlam ML256 Double Toilet Roll Holder - AS1428.1compliant - ML256S: Satin Stainless Steel finish		T1
G2 - Group 2 Proprietary Loose Item Supplied by Client & Installed by Contractor				
Notes: 1 Refer to architectural specification and drawings. 2 Provide suitable framing in walls, floor and ceiling for support / fixing of G2 components.				

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
		3 Confirm time frame for supply of items by the client to the contractor. 4 Refer services documents. 5 Install in accordance with the manufacturers' requirements, including substrate suitability, preparation, installation, finishing and cleaning.		
G2-LF-1	Landscape Feature - Grinding Ball	Description: Reclaimed power station steel grinding ball Installation: Allow for sandstone rubble pad 300mm deep x 1500mm diameter Supply: The Client has the required number of grinding balls on site and will supply them to the contractor as required.		T1
G3 - Group 3 Proprietary Loose Furniture Supplied & Installed by Contractor (unless noted otherwise)				T2
Notes:		1 Refer to architectural specification and drawings. 2 Provide suitable framing in walls, floor and ceiling for support / fixing of G3 components. Provide all servicing as documented. 3 Contractor to allow for long lead times on certain furniture fittings. 4 Install in accordance with the manufacturers' requirements, including substrate suitability, preparation, installation, finishing and cleaning.		T2
G3-CHR-1 QTY: 111	Chair - task	Selection: Sylphy High Back Chair by Okamura, black body, black mesh back and upholstered seat Seat Back Height: High Back Body Color: Black Seat Back: Mesh Hanger: Without Hanger Lumbar Support: Without Lumbar Support Arm: Adjustable Base: Polished Aluminium Material: Plain Knit Color: FMP1 Black Lead Time: 16 weeks Supplier / Contact: UCI/ Nicky Scriggins/ e:nick.scriggins@uci.com.au/ ph:07 3854 1600		T2
G3-CHR-2 QTY: 40	Chair - sled	Selection: Schiavello Taurini Chair Seat: Upholstered. Fabric: Woven Image, Design Edge, colour 365 Legs: Chrome. Lead time: 6-8 weeks Supplier/ Contact: Schiavello/ Debora Abreu, ph: dabreu@schiaavello.com; e: dabreu@schiaavello.com		T2
G3-CHR-3 QTY: 48	Chair (Kitchen)	Selection: Mexica Chair Seat and back finish: Plywood with natural Oak finish Seat height: 430mm Frame type: 4 legs Oak frame Frame finish: Natural Oak in natural finish Arm detail: no arms Lead time: 16-20 weeks Supplier/ Contact: Inner Space WA/ Luc O'Brien/ e:l.obrien@innerspacewa.com.au/ ph:0421 675 411 - 02 8072 9340		T2
G3-CHR-4 QTY: 16	Stool (Kitchen)	Selection: Mexica Stool Seat and back finish: Plywood with natural Oak finish Seat height: 760mm Frame type: 4 solid timber legs with stool foot rest Frame finish: Natural Oak in natural finish Arm detail: no arms Lead time: 16-20 weeks Supplier/ Contact: Inner Space WA/ Luc O'Brien/ e:l.obrien@innerspacewa.com.au/ ph:0421 675 411 - 02 8072 9340		T2

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
G3-CHR-5 QTY: 6 a: 6 b: 7 c: 8 d: 4	Stool (Kitchen and Workplace)	Selection: Schiavello Toro Round High Stool Height/ Finishes: a:650mm Limewood Natural Applied Finish b:650mm Ozone Medium - Oak Timber Paint (blue) c:450mm Limewood Natural Applied Finish d:450mm Ozone Medium - Oak Timber Paint (blue) Lead time: 6-8 weeks Supplier/ Contact: Schiavello/ Debora Abreu, ph: dabreu@schiaavello.com; e: dabreu@schiaavello.com		T2
G3-CHR-6 QTY: 16	Chair (Boardroom)	Selection: Shibusa High Back by Okamura Back: Full Upholstered Seat & Backrest: Black Leather PF72 Flame: Black Lead time: 16 weeks Supplier / Contact: UCI/ Nicky Scriggins/ e:nick.scriggins@uci.com.au/ ph:07 3854 1600		T2
G3-CHR-7 QTY: 6	Armchair (Boardroom/Circulation/ Health Room)	Selection: Schiavello Valli Float Sofa 1 Seater Low Back Seat: Upholstered. Legs: Black Seat and internal fabric: Maharam Mode 466337 033 Denim External fabric: Maharam Mode 466337 035 Jetty Lead time: 6-8 weeks Supplier/ Contact: Schiavello/ Debora Abreu, ph: dabreu@schiaavello.com; e: dabreu@schiaavello.com		T2
G3-CHR-8 QTY: 2	Armchair (Workplace)	Selection: Schiavello Valli Float Sofa 1 Seater High Back Seat: Upholstered. Legs: Black Seat and internal fabric: Maharam Mode 466337 033 Denim External fabric: Maharam Mode 466337 035 Jetty Lead time: 6-8 weeks Supplier/ Contact: Schiavello/ Debora Abreu, ph: dabreu@schiaavello.com; e: dabreu@schiaavello.com		T2
G3-CHR-9 QTY: 3	Sofa (Workplace)	Selection: Schiavello Focus Booth High Back Customized "Face to Face" booth with bench seat ottoman on each side and central table, all surrounded by a 1350 high fabric covered screen, fabric covered with applied PET embossed feature pinboard panel to the interior face of the 2450 (table) screen. Equal to Schiavello Focus Booth Type F, external plan dimension, Equal to Schiavello Focus Booth Type F, external plan dimension 2000mm x 2300mm Seat: Upholstered. Seat and internal fabric: Maharam Mode 466337 033 Denim External fabric: Maharam Mode 466337 035 Jetty Benchtop: Laminate White Legs: Black Lead time: 6-8 weeks Supplier/ Contact: Schiavello/ Debora Abreu, ph: dabreu@schiaavello.com; e: dabreu@schiaavello.com		T2
G3-CHR-10 QTY: 40	Chair Tablet (Training)	Selection: Altus Side Chair – Upholstered Seat & PP Back with Tablet Arm Protective Under-seat Cover Fabric: Wortley Access Carbon (black) Capacity: 140kg Recommended Weight Tablet: Right side Lead time: 10-12 weeks Supplier/ Contact: NPS Commercial Furniture/ Lisa Roberts: ph: 07 4779 4711: e:lisa@npscommercialfurniture.com.au.		T2
G3-CHR-11 QTY: 1	Armchair (First Aid)	Selection: Executive Recliner Chair Fabric: Vinyl Colour: Navy Lead time: 16 weeks Supplier: Dalcross/ Kiama Walton/ e:kiama@dalcross.com.au/ ph:1300 367 035		T2

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
G3-CHR-12 QTY: 36	Chair (Outdoor)	Selection: Fermob Surprising Chair Product Code: 1125 Stacking capacity: x 10 Colour: Maya Blue (light blue) Lead time: 14-16 weeks Supplier: Fermob Sydney/ Marnie Hammond, e:marnie@fermobsydney.com.au; ph:412447777		T2
G3-CHR-13 QTY: 4	Armchair (Covered Outdoor)	Selection: Muuto Settle Lounge Chair Upholstery: Ribbed Weave 5 Structure colour: Taupe Lead time: 14-16 weeks Supplier/ Contact: Living Edge Brisbane/ Laure Maillé/ e: laure.maille@livingedge.com.au/ ph:0499321537	Confirm the fabric sample with architect prior order.	T2
G3-CHR-14 QTY: 9	Stool (Covered Outdoor)	Selection: Telegraph Stool Matched Pair Size: Diam 250-300mm x 420h approx. Lead time: 2 weeks Supplier/ Contact: Five Miles/ studio@fivemileradius.org/ ph:07 3096 0585		T2
G3-CHR-15 QTY: 12	High Stool (Covered Outdoor)	Selection: Muuto Linear Steel Bar Stool Height: 750mm Colour: Pale Blue Supplier/ Contact: Living Edge Brisbane/ Laure Maillé/ e: laure.maille@livingedge.com.au/ ph:0499321537		T2
G3-CP-1	Control Panel	Control Panel for AV Display @ 1100 AFFL and AV interface plate @ 300 AFFL Supplied & Installed by Client		T2
G3-LE-1 QTY: 1	Lectern	Selection: Silhouette Sit+Stand Teacher Lectern Dimensions: 533d x 762w - 660 - 1041h Benchtop: White Edge: 90° Corners Platinum Structure: Platinum Optional: Screen Supplier/ Contact: Arki Environments/ Reuben Woobury; e: reuben@arkienvironments.com; ph: 0477 477 369		T2
G3-HM-1	Health Monitor	Existing Health Monitor supplied by client Supplied & Installed by Client		T2
G3-MUB-1 QTY: 112	Mobile Underbench Unit	Selection: Zeta 3 Drawer Colour: Black Size: 600H x 300W x 500D. Lead time: 4 weeks Supplier / Contact: UCI/ Nicky Scriggins/ e:nick.scriggins@uci.com.au/ ph:07 3854 1600		T2
G3-POD-1 QTY: 4	Acoustic Pod	Selection: Framery One Finishes: Exteriors Sand/ Interiors Sand/ Carpet Dark Blue/ Seating Fabric Dark Blue/ Table Top White Size: 122W x100D x 204H Lead time: 16-18 weeks Supplier/ Contact: NPS Commercial Furniture/ Lisa Roberts: ph: 07 4779 4711: e:lisa@npscommercialfurniture.com.au.		T2
G3-POD-2 QTY: 1	Acoustic Pod - PWD	Selection: Framery Four Framery PWD compliance Finishes: Exteriors Sand/ Interiors Sand/ Carpet Dark Blue/ Seating Fabric Dark Blue/ Table Top White PWD compliance items: Low threshold with an external platform/ Pull bar on the door/T-shaped turning space/Folding table and sofas Size: 235.2W x 129.2D x 232.9H Lead time: 16-18 weeks Supplier/ Contact: NPS Commercial Furniture/ Lisa Roberts: ph: 07 4779 4711: e:lisa@npscommercialfurniture.com.au.		T2
G3-PR-1	Printer	Supplied & Installed by Client		T2

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
G3-RBP-1	Room Booking Panel - Rooms	Room Booking Panel; refer to electrical engineer's documents. <u>Supplied & Installed by Client</u>		T2
G3-SC-1	Retractable screen	Selection: Motorised Screen by client Dimensions: nominally 120" 16:9 Supplier/ Contact: Programmed		T2
G3-TBL-1 QTY: a: 6 b: 2 c: 1	Table - Kitchen and Workplace	Selection: Joggle Table by Imposter Size: 900x2400 Benchtop: 25mm Laminex White Laminate Steel structure: White Powdercoat Legs: Timber 60mm diameter Legs height: a: 695mm b: 1025mm c: 895mm Lead Time: 6-8 weeks Supplier/ Contact: Inner Space WA/ Luc O'Brien/ e:l.obrien@innerspacewa.com.au/ ph:0421 675 411 - 02 8072 9340		T2
G3-TBL-2 QTY: 1	Table - Boardroom	Selection: Agile fixed height work bench Boardroom Size: 7200x1500 (3 legs required) Benchtop: Forbo Marmoleum Vivace 3403 Asian Tiger Edge: Shark nose in solid timber, natural finish Legs: Black Lead time: 6-8 weeks Supplier/ Contact: Schiavello/ Debora Abreu, ph: dabreu@schiaavello.com; e: dabreu@schiaavello.com		T2
G3-TBL-4 QTY: a: 2 b: 3 c: 1 d: 1 e: 1	Table - Meeting Room	Selection: Meeting Table Eona Benchtop: 25mm Laminate Laminex Charcoal Natural Finish with matching ABS Edge Legs: 4 Leg Frame EC-1211.085 Legs Colour: Black Powdercoat Sizes: a: 900x900 b: 1500x900 c: 2000x900 d: 2700x900 e: 3500x900 Lead time: 4-6weeks Supplier/ Contact: NPS Commercial Furniture/ Lisa Roberts: ph: 07 4779 4711: e:lisa@npscommercialfurniture.com.au.		T2
G3-TBL-5 QTY: 2	Side Table - Workplace	Selection: Muuto Relate Side Table Colour: Blue Grey Lead Time: 16-18 weeks Supplier/ Contact: Living Edge Brisbane/ Laure Maille/ e: laure.maille@livingedge.com.au/ ph:0499321537		T2
G3-TBL-6 QTY: 4	Side Table - Health Room. South Circulation, Boardroom	Selection: Mushroom Side Table Size: Diam 550 x 400h Base and Plate: Solid Oak Finish: Natural Oil 1505 Lead Time: 14-16 Weeks Supplier/ Contact: NPS Commercial Furniture/ Lisa Roberts: ph: 07 4779 4711: e:lisa@npscommercialfurniture.com.au.		T2
G3-TBL-7 QTY: 9	Table - Covered Outdoor Area	Selection: Fermob Luxembourg Aluminium Table Product code: 4136 Size: 1650x1000 Colour: Maya Blue TBC Lead Time: 14-16 weeks Supplier/ Contact: Fermob Sydney/ Marnie Hammond, e:marnie@fermobsydney.com.au; ph:412447777		T2

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
G3-TBL-8 QTY: 4	High table - Covered Outdoor Area	Selection: Muuto Linear Steel Café Table Colour: Pale Blue Size: Diam. 700 x 1050H Lead time: 14-16 weeks Supplier/ Contact: Living Edge Brisbane/ Laure Maillé/ e: laure.maille@livingedge.com.au/ ph:0499321537		T2
G3-TBL-9 QTY: 7	Coffee Table - Covered Outdoor Area and Training Kitchen	Selection: Muuto Linear Steel Coffee Table Colour: Pale Blue Size: Diam. 70 x 40 H Lead time: 14-16 weeks Supplier/ Contact: Living Edge Brisbane/ Laure Maillé/ e: laure.maille@livingedge.com.au/ ph:0499321537		T2
G3-TR-1 QTY: 1	Trolley	Selection: Advanta Loria Trolley, for training room stackable chairs Size: 655x950x970h Lead Time: 4 weeks Supplier/ Contact: NPS Commercial Furniture/ Lisa Roberts: ph: 07 4779 4711: e:lisa@npscommercialfurniture.com.au.		T2
G3-TV-1	LCD Screen Television	Size: nominally: a: Size 100" b: Size nom 60"; to be confirmed by Principal c: Size nom 48"; to be confirmed by Principal Refer to Electrical Engineer's documents. Supplied & Installed by Client		T2
G3-WKS-1 QTY: a: 2 b: 3 c: 1	Back to Back Workstation - 8 people	Selection: Schiavello Krossi Sit to Stand Back to Back Cluster Workstation with electric adjustable height Desks: 8 desks 1800x750 Benchtop: White Benchtop thickness: 25mm, white edge Frame: Powdercoat Black Other: Soft wiring allowance - 1 x CMS NW series 4 GPO (mounted on underside of desk) + 1 x CMS KonexUS unit above the desk with 1x GPO + USB A/C Fast-Charge Outlets (65W). Signage: 60 mm diameter acrylic plaque with engraved numbering, numbering to be coordinated with client. Screen: Bridge mounted Screen material: 24mm PET Autex Cube, height 900mm Screen colours: a: Cavalier (purple) b: Falling Water (light blue) c: Beehive (mustard) Lead time: 6-8 weeks Note: Monitor screens and brackets supplied by client Supplier / Contact: Schiavello/ Debora Abreu, ph: dabreu@schiaavello.com; e: dabreu@schiaavello.com		T2

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
G3-WKS-2 QTY: 8 a: 8 b: 8 c: 8 d: 5	Linear Workstation - Single	Selection: Schiavello Krossi Sit to Stand Workstation with electric adjustable height Dimensions: 1800x750 Benchtop: White Benchtop thickness: 25mm, white edge Frame: Powdercoat Black Other: Soft wiring allowance - 1 x CMS NW series 4 GPO (mounted on underside of desk) + 1 x CMS KonexUS unit above the desk with 1x GPO + USB A/C Fast-Charge Outlets (65W). Signage: 60 mm diameter acrylic plaque with engraved numbering, numbering to be coordinated with client. Screen: Bracket mounted Screen material: 24mm PET Autex Cube, height 900mm Screen colours: a: Cavalier (purple) b: Falling Water (light blue) c: Beehive (mustard) d: Muralla (dark blue) Lead time: 6-8 weeks Note: Monitor screens and brackets supplied by client Supplier / Contact: Schiavello/ Debora Abreu, ph: dabreu@schiaavello.com; e: dabreu@schiaavello.com		T2
G3-WKS-3 QTY: 3	Back to Back Workstation - 10 people	Selection: Schiavello Krossi Sit to Stand Back to Back Cluster Workstation with electric adjustable height Desks: 10 desks 1800x750 Benchtop: White Benchtop thickness: 25mm, white edge Frame: Powdercoat Black Other: Soft wiring allowance - 1 x CMS NW series 4 GPO (mounted on underside of desk) + 1 x CMS KonexUS unit above the desk with 1x GPO + USB A/C Fast-Charge Outlets (65W). Signage: 60 mm diameter acrylic plaque with engraved numbering, numbering to be coordinated with client. Screen: Bracket mounted Screen material: 24mm PET Autex Cube, height 900mm Screen colour: Muralla (dark blue) Lead time: 6-8 weeks Note: Monitor screens and brackets supplied by client Supplier / Contact: Schiavello/ Debora Abreu, ph: dabreu@schiaavello.com; e: dabreu@schiaavello.com		T2
G3-WKS-4 QTY: 4	Desk - Offices, Cooms Room and First Aid	Selection: Schiavello Krossi Sit to Stand Workstation with electric adjustable height Desk: 1800x750 Benchtop: White Benchtop thickness: 25mm, white edge Frame: Powdercoat Black Signage: 60 mm diameter acrylic plaque with engraved numbering, numbering to be coordinated with client. Other: Soft wiring allowance - Soft wiring allowance - 1 x CMS NW series 4 GPO (mounted on underside of desk) + 1 x CMS KonexUS unit above the desk with 1x GPO + USB A/C Fast-Charge Outlets (65W). Lead time: 6-8 weeks Note: Monitor screens and brackets supplied by client Supplier / Contact: Schiavello/ Debora Abreu, ph: dabreu@schiaavello.com; e: dabreu@schiaavello.com		T2
JO - Joinery Notes: 1 Refer to architectural specification and drawings. 2 Provide shop drawings for approval prior to manufacture. 3 Provide samples of components for approval prior to manufacture. 4 Confirm all sizes, dimensions and clearances on site prior to manufacture. 5 Joinery is to be installed level. 6 Joinery is to be installed over floor finishes unless where shown otherwise on the floor finishes plan. 7 Joinery finishes are to be installed in accordance with the manufacturers requirements 8 All timber products to be supplied with FSC, AFS or PEFC certification - chain of custody certification to be provided for approval. 9 All joinery fixings to be concealed unless noted otherwise. 10 All joinery to be securely fixed to walls/floors. Ensure appropriate framing within walls/floors for support of joinery items.				

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
11 Where joinery abuts a wall provide a shadow line equal to the width of the adjacent skirting or 16mm wide (which ever is largest) unless noted otherwise. Where joinery abuts a wall provide a 50mm deep 25mm wide shadow line unless noted otherwise. Finish to match kicker. 12 Joinery doors to have Blum or Hafele soft close hinge system. Hinges to be overmounted to conceal gable ends. All cupboard doors to have stick-on buffers for noise reduction: clear nylon applied to front of carcass edges. Must not be externally visible. 13 Joinery drawers to be Blum or Hafele with: soft close system, heavy duty runners, metal drawer trays with high back and sides, colour to match joinery carcass unless noted otherwise. All drawers to have stick-on buffers for noise reduction: clear nylon applied to front of carcass edges. Must not be externally visible. 14 Shelves inside cupboards to be adjustable 50mm increments unless noted otherwise. Adjustable shelf supports to be bright chrome finish. 15 All exposed Laminate edges to have 2mm ABS edge strips in colour to match Laminate UNO. 16 Joinery locks for drawers and cupboards (where noted) are to be Carbine CCL cupboard lock and Lockwood 590 cylinder. Keyed alike compatible with master keying system 17 Handles to be Kethy DL2132P/ Lenth: 76mm colour black 18 Push Door Catch, to be Hafele Concealed Short Version, with Magnet, K Push Tech. Anthracite no. 35612300 (Male Bathroom), White no. 35612700 (Kitchen) 19 HPL = High Pressure Laminate				
JO-BD-1	Dry Bench - Printer 1 Bench	Freestanding bench with legs & overhead shelf Bench Top: 25 mm th. MDF. Laminate finish MLAM-4 Gables: 25 mm th. MDF. Laminate finish - MLAM-4 Face Panels: 18mm th. MDF. Laminate finish - MLAM-4 Shelf Panels: 18mm th. MDF. Laminate finish - MLAM-4 Shelf Overhead: 25 mm th. MDF. Laminate finish - MLAM-4 Handle: Refer notes above Carcass (non-visible areas): 16mm th. MR prefinished board - white. Legs: Adjustable metal legs structure, diam. 40mm Legs colour: Black Edges: Matching ABS edge strips		T1
JO-BD-2	Dry Bench - Printer 2 Bench	Freestanding bench with legs Bench Top: 25 mm th. MDF. Laminate finish - MLAM-4 Gables: 25 mm th. MDF. Laminate finish - MLAM-4 Face Panels: 18mm th. MDF. Laminate finish - MLAM-4 Shelf Panels: 18mm th. MDF. Laminate finish - MLAM-4 Handle: Refer notes above Carcass (non-visible areas): 16mm th. MR prefinished board - white. Legs: Adjustable metal legs structure, diam. 40mm Legs colour: Black Edges: Matching ABS edge strips		T1
JO-BD-3	Dry Bench - Printer 3 Bench	Freestanding bench with metal legs Bench Top: 25 mm th. MDF. Laminate finish - MLAM-4 Legs: Adjustable metal legs structure, diam. 40mm Legs colour: Black		T1
JO-BD-4	Dry Bench - Meeting Room	Storage joinery unit. Bench Top: MLAM-10 Gables: MLAM-10 Edges: Matching ABS edge strips Kick: 100mm high MLAM-10 Other Fittings and Fixtures: 2x Cable entry cover diam. 60mm black Bracket to fix the table to the joinery		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
JO-BD-5	Dry Bench - Meeting Room	Built-in bench including storage under. Bench Top: 25mm th. MR MDF. Laminate finish - MLAM-4 Face Panels: 18mm th. MR MDF. Laminate finish - MLAM-4 Shelf Panels: 18mm th. MR MDF. Laminate finish - MLAM-4 Handle: n/a Carcass (non-visible areas): 16mm th. MR prefinished board - white. Kick: 18mm th. MR MDF. Laminate finish MLAM-7 Edges: Matching ABS edge strips Dimensions: Refer to drawings. a: Training 1 b: Training 2 Other Fittings and Fixtures: - Cable entry cover (no lid) diam.35mm on Face Panel doors refer to detail 3/A-780003		T1
JO-BW-1	Wet Bench Island - Kitchen	Built-in island bench including sink, bar fridge, drawers and joinery cupboards under. Bench Top: MST-1 Gables: MST-1 Shelf Capping: MST-1 Face Panels: 18mm th. MR MDF. Laminate finish - MLAM-4 Shelf Panels: 18mm th. MR MDF. Laminate finish - MLAM-4 Back Panel: MTR-3 Handle: Refer notes above Carcass (non-visible areas): 16mm th. MR prefinished board - white. Kick: MLAM-7 Edges: Matching ABS edge strips Other Fittings and Fixtures: - LED strip light under shelf capping, rebated in additional face panel over underside of carcass - G1-BIN-1		T1
JO-BW-2	Wet Bench - Kitchen	Built-in bench including 2x sinks, 2x dishwashers, bins, 3x microwaves, oven, boiling water unit, drawers and joinery cupboards under. Bench Top: MST-1 Splashback: MSB-1a Gable: MLAM-8 Appliances Column Gables: MLAM-8 Face Panels: MLAM-8 Shelf Panels: MLAM-8 Handle: Refer notes above Carcass (non-visible areas): 16mm th. MR prefinished board - white. Kick: MLAM-8 Edges: Matching ABS edge strips Grill: Ventilation grille required by Zip tap, check spec sheet. Hafele aluminium ventilation grille required by microwave and oven guide installation, dimensions (L x W): 550 x 80 mm (code 57525937) area 200cm2. Other Fittings and Fixtures: - LED strip light under overhead cupboards, rebated in additional face panel over underside of carcass	DDA - Confirm accessible sink and microwave.	T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
JO-BW-3	Wet Bench - Boardroom	Built-in bench with sink, zip tap, dishwasher, bar fridge, bins, drawers and joinery cupboards under. Bench Top: MSSF-1 Splashback: MSB-1b Face Panels: 18mm th. MR MDF. Laminate finish MLAM-2 Shelf Panels: 18mm th. MR MDF. Laminate finish MLAM-2 Handle: Refer notes above Carcass (non-visible areas): 18mm th. MR MDF. Laminate finish MLAM-2 Kick: 18mm th. MR MDF. Laminate finish MLAM-2 Edges: Matching ABS edge strips Grill: Ventilation grille required by Zip tap, check spec sheet.		T1
JO-BW-4	Wet Bench - Health Room	Built-in bench including sink, bins, bar fridge and zip tap, drawers and joinery cupboards under. Bench Top: MST-1 Splashback: MSB-1c Face Panels: 18mm th. MR MDF. Laminate finish - MLAM-4 Shelf Panels: 18mm th. MR MDF. Laminate finish - MLAM-4 Handle: Refer notes above Carcass (non-visible areas): 16mm th. MR prefinished board - white. Kick: MLAM-7 Edges: Matching ABS edge strips Grill: Ventilation grille required by Zip tap, check spec sheet.		T1
JO-BW-5	Wet Bench - Training Kitchen Room	Built-in bench including sink, bins, zip tap, 2x bar fridges, drawers and joinery cupboards under, and with overhead cupboards. Bench Top: 25mm th. MR MDF. Laminate finish MLAM-5 Splashback: 16mm th. MR MDF. Laminate finish MLAM-5 Face Panels: 18mm th. MR MDF. Laminate finish - MLAM-5 Shelf Panels: 18mm th. MR MDF. Laminate finish - MLAM-5 Overhead Face Panel: 18mm th. MR MDF. Laminate finish - MLAM-5 Handle: Refer notes above Carcass (non-visible areas): 16mm th. MR prefinished board - white. Kick: 18mm th. MR MDF. Laminate finish MLAM-2 Edges: Matching ABS edge strips Grill: Ventilation grille required by Zip tap, check spec sheet. Other Fittings and Fixtures: - LED strip light under overhead cupboards, rebated in additional face panel over underside of carcass		T1
JO-BW-6	Wet Bench - First Aid	Built-in bench including sink, bins, bar fridge, drawers and joinery cupboards under. Bench Top: MST-1 Splashback: MSB-1c Face Panels: 18mm th. MR MDF. Laminate finish - MLAM-4 Shelf Panels: 18mm th. MR MDF. Laminate finish - MLAM-4 Handle: Refer notes above Carcass (non-visible areas): 16mm th. MR prefinished board - white. Kick: MLAM-7 Edges: Matching ABS edge strips Other Fittings and Fixtures: Cupboards with lockers, refer notes above.		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
JO-BW-7	Wet Bench - BBQ	Built-in bench with washup sink, 2x BBQs, drawers and joinery cupboards under. Bench Top: MST-1 Splashback: MST-1 Gable: MST-1 Face Panels: 18mm th. MR MDF. Laminate finish - MLAM-1 Shelf Panels: 18mm th. MR MDF. Laminate finish - MLAM-1 Handle: Refer notes above Kick: MLAM-7 Carcass (non-visible areas): 16mm th. MR prefinished board - white. Edges: Matching ABS edge strips Other Fittings and Fixtures: Cupboards with lockers, refer notes above. Decal Bin icon 100mm height Decal Recycling icon 100 height		T1
JO-BW-8	Wet Bench - Female	Built-in vanity Bench Top: 25 mm th. MR MDF. Post formed Laminate finish - MLAM-3 Integrated splashback: 25 mm th. MR MDF. Post formed Laminate finish - MLAM-3 Shelf: MLAM-3		T1
JO-BW-9	Wet Bench - Male	Built-in vanity and joinery cupboards under. Bench Top: 25 mm th. MR MDF. Post formed Laminate finish- MLAM-2 Integrated splashback: 25 mm th. MR MDF. Post formed Laminate finish- MLAM-2 Shelf: MLAM-2 Face Panels: MLAM-6 Cupboard Top & Bottom: MLAM-6 Kick: coved skirting with same floor material		T1
JO-LKR-1	Lockers	Built-in lockers integrated with Yellow Box System (G3-LKCP-1) Face Panels: 18mm th. MR MDF. Laminate finish - MLAM-9 Carcass (non-visible areas): 16mm th. MR prefinished board - white. Kick: MLAM-9 Number of lockers: 60 units Other Fittings and Fixtures: Signage Numbers SI-3		T1
JO-SE-1	Seat - Covered outdoor	Built-in seat with mattress and back cushion, attached with velcro. Integrated GPOs. Seat and back: Upholstered cushion seat fixed securely to base / carcass. Upholstery: Fabric laid over cushion with top layer being 30mm thick Dunlop Foams FR23-130 soft cushion and remainder of cushion to be Dunlop Foams ST35-200 firm density foam. Stitching in colour to match upholstery. Stitching to be hidden/concealed where possible. Avoid stitching along leading edges of seat and backrest. Fabric to be adequately stretched and bonded to inner such that there is no wrinkling or creasing in finished upholstery. Fabric Selection: Vinyl from Pelle Leathers, Article Versatile, colour Alpha - 4116 (blue) Kick: MST-1 Carcass (non-visible areas): 16mm th. MR prefinished board - white. Top Trim: MST-1		T1
JO-SE-2	Seat - Training Kitchen	Built-in seat with mattress and back cushion, attached with velcro. Integrated GPOs. Seat and back: Upholstered cushion seat fixed securely to base / carcass. Upholstery: Fabric laid over cushion with top layer being 30mm thick Dunlop Foams FR23-130 soft cushion and remainder of cushion to be Dunlop Foams ST35-200 firm density foam. Stitching in colour to match upholstery. Stitching to be hidden/concealed where possible. Avoid stitching along leading edges of seat and backrest. Fabric to be adequately stretched and bonded to inner such that there is no wrinkling or creasing in finished upholstery. Fabric Selection: Vinyl from Pelle Leathers, Article Versatile, colour Chianti - 4127 (burgundy) Kick: 18mm th. MR MDF. Laminate finish MLAM-2 Carcass (non-visible areas): 16mm th. MR prefinished board - white. Top Trim: 18mm th. MR MDF. Laminate finish MLAM-5		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
JO-SH-1	Shelves	Fixed shelves inside cupboards Shelves: 25mm th. MR MDF. Laminate finish - MLAM-4 Edges: Matching ABS edge strips Depth: 400mm Width: confirm measurements on site a: 4 shelves fixed 300mm apart, with the first shelf 500mm from the floor b: 2 shelves fixed 300mm apart, with the first shelf 1500mm from the floor		T1
JO-ST-1	Cupboard HWU, Fire Extinguisher and Fire Blanket	Hot Water Unit, Fire Extinguisher and Fire Blanket cupboard Face Panels: 18mm th. MR MDF. Laminate finish - MLAM-4 Carcass (non-visible areas): 16mm th. MR prefinished board - white. Push Door Catch, to be Hafele Concealed Short Version, with Magnet, K Push Tech. white Other Fittings and Fixtures: Push Door Catch, to be Hafele Concealed Short Version, with Magnet, K Push Tech. white G1-FE-1 G1-FB-1		T1
JO-ST-2	Storage - Kitchen	Built-in storage including hanging rail and shelf. And built-in storage including microwaves, benchtop, drawers and cupboards Bench Top: MST-1 Face Panels: 18mm th. MR MDF. Laminate finish - MLAM-4 Shelf Panels: 18mm th. MR MDF. Laminate finish - MLAM-4 Left gable: Harwood timber painted (PT-IGg) Handle: Refer notes above Carcass (non-visible areas): 16mm th. MR prefinished board - white. Kick: MLAM-4 Edges: Matching ABS edge strips Grill: Hafele aluminium ventilation grille required by microwaves guide installation, dimensions (L x W): 550 x 80 mm (code 57525937) area 200cm2. Other Fittings and Fixtures: Hanging rail		T1
JO-ST-3	Storage - Covered outdoor seat	Built-in storage including fire extinguisher Bench Top: MST-1 Face Panels: MST-1 Carcass (non-visible areas): 16mm th. MR prefinished board - white. Other Fittings and Fixtures: G1-FE-2		T1
MX - Materials & Applied Finishes				
Notes: 1 Refer to architectural specification and drawings. 2 Provide samples of components for approval prior to manufacture. 3 All timber products to be supplied with FSC, AFS or PEFC certification - chain of custody certification to be provided for approval. 4 Install finishes in accordance with the manufacturers' requirements, including substrate suitability, preparation, installation, finishing and cleaning. 5 Paint systems and colour codes to be read as follows: MPT-XYZ. X = System (E=External acrylic, I=Internal acrylic, M=MIO micaceous iron oxide, O=Oil based enamel, P=Powder coat, R=Road marking, S=Sealer, T=Timber finish, X=Other, as per below selections) Y = Gloss Level (G=Gloss, S=Semi-Gloss, L=Low Sheen, M=Matt/Flat) z = Colour (a, b, c, etc. as per selections below) 6 z = post-fix letter used to denote a paint system and colour applied to a material				

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
MAL-1	Acoustic Lining	Selection: Autex Cube Thickness: 12mm Dimensions: 1220 mm x 2440 mm Note: Edge quirked on the side of the panel when adjacent to the 42x11 batten. Refer detail 2- A610001/1 Colours: a: Muralla (dark blue) b: Cavalier (purple) c: Savoye (grey) Supplier / Contact: Autex		T1
MDE-1	Decal Film on Glass	Selection: 3M Scotchcal cut to graphics shown on drawings (Refer A-60 series internal elevations) Colour: light grey Installation: Internal face of glass Size: UNO 100mm wide, bottom edge 895 AFFL	Shop drawings: required	T1
MLAM-1	Laminate Wall Lining (PWD and Shower Room)	Selection: Laminex Aquapanel Sheets Colour: Moleskin Finish: Natural Sheet Size: 2400 x 1200 Thickness: 2.7mm Supplier / Contact: Laminex/ Mikaela Alderton; ph: 0407 750 035; e:mikaela.alderton@laminex.com.au		T1
MLAM-2	Laminate HPL	Selection: Laminex Laminate (HPL) Substrate: MDF MR HD E ₀ refer joinery description and wall detail for thickness Colour: French Navy, finish Natural Thickness: 0.7mm Supplier / Contact: Laminex/ Mikaela Alderton; ph: 0407 750 035; e:mikaela.alderton@laminex.com.au		T1
MLAM-3	Laminate HPL	Selection: Egger Laminate (HPL) Substrate: MDF MR HD E ₀ refer joinery description and wall detail for thickness Colour: Misty Blue, finish Thickness: 0.8mm Supplier/Contact: Forest/ Kellie Cross; ph: 0409192227; e :kcross@forest.one		T1
MLAM-4	Laminate Panel	Selection: Laminex Large Format Commercial (prefinished board) Colour: Ghostgum, finish Natural Substrate: MDF MR HD E0 refer joinery description for thickness Supplier / Contact: Laminex/ Mikaela Alderton; ph: 0407 750 035; e:mikaela.alderton@laminex.com.au		T1
MLAM-5	Laminate HPL	Selection: HPL O2+ Stellar Colour: Shiraz Substrate: MDF MR HD E0, 18mm thickness Supplier / Contact: Catalyste/ Martha Hernandez: ph:0431 113 811; e:martha@catalyste.au		T1
MLAM-6	Compacted Laminate Panel	Selection: Multipurpose Compact Laminate (prefinished board) Colour: French Navy, finish Natural Substrate: Black, 18mm thickness Supplier / Contact: Laminex/ Mikaela Alderton; ph: 0407 750 035; e:mikaela.alderton@laminex.com.au		T1
MLAM-7	Laminate Panel	Selection: Large Format Commercial (prefinished board) Colour: Black, finish Flint Substrate: MDF MR HD E0, 18mm thickness Supplier / Contact: Laminex/ Mikaela Alderton; ph: 0407 750 035; e:mikaela.alderton@laminex.com.au		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
MLAM-8	Laminate HPL	Selection: HPL Lamitak Colour: Amethyst Substrate: MDF MR HD E0, 18mm thickness Supplier / Contact: Catalyste/ Martha Hernandez: ph:0431 113 811; e:martha@catalyste.au		T1
MLAM-9	Laminate HPL	Selection: HPL Lamitak Colour: Periwinkle Substrate: MDF MR HD E0, 18mm thickness Supplier / Contact: Catalyste/ Martha Hernandez: ph:0431 113 811; e:martha@catalyste.au		T1
MLAM-10 (JO-BD-4)	Laminate Panel	Selection: Large Format Commercial (prefinished board) Colour: Charcoal, finish Flint Substrate: MDF MR HD E0, 18mm thickness Supplier / Contact: Laminex/ Mikaela Alderton; ph: 0407 750 035; e:mikaela.alderton@laminex.com.au		T1
MSB-1	Glass Splashback	Selection: Innovative Glass Splashback Thickness: 6mm Colours: a: purple (Kitchen) to match Dulux "Shadow Dance" (S48A4) b: dark blue (Boardroom) to match Dulux "Steadfast" S40D7 c: white (Health Room, Training Kitchen, First Aid Room) to match Dulux "Vivid White" (SW1G1) Supplier / Contact: Innovative Splashbacks/ Elli Thyer/ e:elli@innovativesplashbacks.com.au/ ph:0418 548 743		T1
MSB-2	Splash Back - Acrylic Lining	Selection: Innovative Acrylic splashbacks Sheet max size: 2030 x 3050mm Colours: a: blue (Female Bathroom) to match Dulux "Glide Time" S37B5 b: dark blue (Male Bathroom) to match Dulux "Steadfast" S40D7 Supplier / Contact: Innovative Splashbacks/ Elli Thyer/ e:elli@innovativesplashbacks.com.au/ ph:0418 548 743		T1
MST-1	Stone	Selection: Caesarstone Crystalline Silica Free Colour: 6141 Ocean Foam Thickness: 20mm Edge: 40mm Pencil Round Laminated (4mm radius)		T1
MSSF-1	Solid Surface	Selection: Staron Solid Surface Colour: Ultramarine SU067 (blue) Thickness: 12mm solid surface Sheet Size: 3680x760mm Edge: 38mm edge profile (4mm radius) Supplier/ Contact: Austaron Surfaces / Velya Kirmach/ e: velyade.kirmach@austaron.com.au/ ph: 0436 436 700		T1
MTR-1	Timber Trim - Skirtings, Battens & Wall Trims	Square Dressed All Round Araucaria Paint Finish Supplier: Finlaysons a: Skirting Size: 187x11 b: Batten Size: 42x11 c: Batten Size: 42x19 d: Trim Size: variesx19 refer to details for sizes		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
MTR-2	Timber Trim - Decorative	Selection: Porta Cirque Profile Grade: Select Grade Product Code: LINB7821 Material: Tasmanian Oak Size: 91x21mm Cover: 78mm Finish: Whittle Waxes, Evolution Hardwax Oil, Satin Application: Apply 2 coats in accordance with manufacturer's specification including preparation before first and second coats. Allow final coat to cure for 8-10 days. Where applied to trafficable surfaces include Whittle Waxes 2K Booster before application		T1
MTR-3	Courtyard Bridge Kerb	Selection: Blackbutt timber Timber Finish: Dressed Finish: PT-T1		T1
MTV-1	Timber Veneer	Selection: Blackbutt Veneer Quarter Cut Finish: PT-T1 Batching: all veneers to come from a single batch; to be approved by the Architect	Sample: batching samples to be approved by the architect	T1
MWB-1	Whiteboard (Meeting Rooms)	Selection: Formica Magnetic Metallic Laminate fully bonded to 18mm thick MR MDF substrate. Thickness: 1.0 mm Colour: Glossy White Frame: Rebated aluminium angle to full perimeter with mitred joints at corners. Refer detail: xxxEE		T1
PF - Plumbing Fixtures				
Notes:		DELETE SECTION IF G1, G2, G3 CODES ARE USED FOR PLUMBING FIXTURES 1 Refer to architectural specification and drawings. 2 Provide suitable framing in walls, floor and ceiling for support / fixing of PF components 3 Refer services documents.		
PF-BWU-1	Instantaneous Boiling Water Unit (Kitchen)	Selection: HydroTap G5 BC100 Classic Accessible Chrome Product code: H5D705Z00AU Additional: Font Kit Chrome (92329Z00) Installation: Provide power supply and water plumbing and drainage connections as required. Coordinate discrete cabinetry cutouts as required for ventilation. Coordinate cutouts in benchtop as required. Install Classic Accessible Mixer sideways to comply with AS1428.2. Supplier/ Contact: Zip Water/ Steve Pollard/ e:steve.pollard@zipwater.com/ ph:0491157381		T1
PF-BWU-2	Instantaneous Boiling Water Unit (Boardroom, Training Kitchen and Health Room)	Selection: HydroTap G5 BCHA20 4-in-1 Classic tap with Cube Mixer Chrome Description: Boiling, Chilled, Filtered water plus Hot and Cold washing up water from two separate taps Type of use: Commercial Product code: H51921Z00AU Additional: Font Kit Chrome (92329Z00) Supplier/ Contact: Zip Water/ Steve Pollard/ e:steve.pollard@zipwater.com/ ph:0491157381	Coordinate: tapware to be integrated with PF-SK-1b and PF-SK-2b	T1
PF-BWU-3	Instantaneous Boiling Water Unit (Training Kitchen)	Selection: HydroTap G5 BCHA40 4-in-1 Classic tap with Cube Mixer Chrome Description: Boiling, Chilled, Filtered water plus Hot and Cold washing up water from two separate taps Type of use: Commercial Product code: H51922Z00AU Additional: Font Kit Chrome (92329Z00) Supplier/ Contact: Zip Water/ Steve Pollard/ e:steve.pollard@zipwater.com/ ph:0491157381		T1
PF-FW-1	Linear Strip Drain with integrated sill	Selection: Stormtech 65ARTDiS Threshold with Sill Dimensions: Channel width 75mm; channel depth customisable (refer to drawings, cos); length as required. Product code: 65ARTDiS Material: Stainless Steel Refer to Hydraulic Engineer and Façade Engineer's documents.		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
PF-HB-1	Hand Basin (Female and Male Bathroom)	Selection: Caroma Carboni II Semi Recessed Basin - White 1TH Dimensions: 415mm L x 415mm W Product code: 865915W Material: White Vitreous China Installation: As per manufacturer's recommendations and to approved joinery shop drawings. Tapware: Caroma Pin Lever Basin Mixer - Chrome - Lead Free Product code: 872550C5AF Supplier / Contact: GWA Group / Hannah Hansen / e:hhansen@gwagroup.com.au/ ph: 0447814693		T1
PF-HB-2	Hand Basin (Shower Room)	Selection: Caroma Cube Extension Wall Basin Left Hand Shelf (1 Tap Hole) 864215W Bottle Trap: Caroma Modina Bottle Trap 687290C Installation: All items to comply with and be installed to AS1428.1-2009. As per manufacturer's recommendations. Tapware: Caroma Pin Lever Care Basin Mixer 5S - Chrome (Lead Free) Product code: 872563C5AF Supplier / Contact: GWA Group / Hannah Hansen / e:hhansen@gwagroup.com.au/ ph: 0447814693 Mirror: G1-MIR-2 Soap Dispenser: G1-SD-1		T1
PF-HB-3	Hand Basin (PWD)	Selection: Caroma Cube Extension Wall Basin Right Hand Shelf (1 Tap Hole) 864115W Bottle Trap: Caroma Modina Bottle Trap 687290C Installation: All items to comply with and be installed to AS1428.1-2009. As per manufacturer's recommendations. Waste pipe to be installed in wall cavity (not inside room) Tapware: Caroma Pin Lever Care Basin Mixer 5S - Chrome (Lead Free) Product code: 872563C5AF Supplier / Contact: GWA Group / Hannah Hansen / e:hhansen@gwagroup.com.au/ ph: 0447814693 Mirror: G1-MIR-2 Soap Dispenser: G1-SD-1		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
PF-SHR-1	PWD Shower	Shower Fixture: Care Support Accessible Shower Set with Inverted T Rail - LH Product Code: 91126C4E Finish: chrome shower head, chrome hose. Supplier/Contact: GWA Group Hannah Hansen hhansen@gwagroup.com.au 0447814693 Hose Restrictor Bracket: Con-serv Hose restrictor bracket. Product code: HR 015 C. Finish: Chrome. Supplier: Con-Serv; ph: 0736305744. Mixer: Care Plus Shower Mixer Standard Handle H/C. Product Code: 91107C. Finish: Chrome Supplier/Contact: GWA Group / Hannah Hansen / e:hhansen@gwagroup.com.au/ ph: 0447814693 Folding Seat: Hand Rail Industries 460x900mm folding shower seat. Product Code: #522. Finish: 304 grade stainless steel rails, White acrylic seat with stainless steel frame. Supplier: Hand Rail Industries. Soap Dispenser: G1-SD-1. Shower Curtain: Silent Gliss Shower Curtain Rail. Curtain track (Product Code #6100) with full height nylon curtain (weighted bottom). Curtain Fabric: Uni FR DELIPERL 59138 (Colour 8110 Grey). Supplier/Contact: Bliss Commercial Pty Ltd 07 3187 7375. Grated Drain: Stormtech Custom made L shaped stainless steel heel safe. 65 Width x 25 Depth, AR Grate Style. Coat Hook: Bradley Single SS Robe Hook. Model no: 9611 Finish: Satin Stainless Steel. Notes: Installation: All items to comply with and be installed to AS1428.1-2009.	Support: Provide extra framing as required.	T1
PF-SK-1	Sink (Boardroom, Health Room, First Aid, Covered outdoor area)	Selection: Caroma Urbane II Single Bowl Sink Dimensions: 460mm L x 400mm W x 209mm D Product code: CO0100SS Finish: Stainless steel 304 grade stainless steel Waste: Stainless steel basket waste included Tapware: a: Caroma Round Blade Sink Mixer- Chrome - Lead Free Product code: CL10017.C4AF Supplier / Contact: GWA Group / Hannah Hansen / e:hhansen@gwagroup.com.au/ ph: 0447814693 b: Refer to PF-BWU-2		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
PF-SK-2	Sink (Kitchen)	Selection: Caroma Urbane II 1.5 Bowl 1TH LHB Dimensions: 1020mm L x 490mm W x 271mm D Product code: CO0150SS.1L Finish: Stainless steel 304 grade stainless steel Waste: Stainless steel basket waste included Installation: As per manufacturer's recommendations and approved joinery shop drawings. Tapware: a: Caroma Urbane II Sink Mixer - Chrome - Lead Free Product code: 99671C56AF Supplier / Contact: GWA Group / Hannah Hansen / e:hhansen@gwagroup.com.au/ ph: 0447814693		T1
PF-SK-3	Sink PWD (Kitchen)	Selection: Caroma Evolution Care Single End Bowl Overmount 1TH LB with 1 taphole. Dimensions: 800mm L x 460mm W x 145mm D. Product code: 4062.1L Finish: Stainless steel Waste: Stainless steel basket waste included Installation: Overmount with Heat Protection Pads (A0152). As per the manufacturer's recommendations and approved joinery shop drawings. Tapware: Caroma Care Plus Sink Mixer with Care Handle H/C - LF Product code: 91115C4AF Supplier / Contact: GWA Group / Hannah Hansen / e:hhansen@gwagroup.com.au/ ph: 0447814693		T1
PF-TAP-1	Cleaner's Tap	Selection: Concealed Spindle Bib Tap FI 50mm Extended with Aerated Outlet – Jumper Valve Product Code: CS322F Supplier / Contact: Enware		T1
PF-UR-1	Urinal (Male Bathroom)	Selection: Costume Made Britex UTRO Wall Hung Urinal Trough Size: nominally 3650; check on site Water Entry: Rear Waste: Urinal Waste Outlet with Dome Cover 50 x 45mm G304 Flush: 3x FSM2 - Smart Saniflush Sensor Electronic Supplier / Contact: Britex	Coordination: refer also to Hydraulic and Electrical Engineers' Documents.	T1
PF-WC-1	Toilet (Standard)	Selection: Caroma Urbane II CleanFlush® Wall Faced Close Coupled Toilet Suite (Bottom Inlet) with GermGard with Urbane II toilet seat - White Product code: 46250W Dimensions: 360w (back) 350w (front) x 655d x 842h (cistern) 440h (bowl) Finish: Vitreous China - white Fixing: S or P trap installation options available - coordinate plumbing & setout on site. Supplier / Contact: GWA Group / Hannah Hansen / e:hhansen@gwagroup.com.au/ ph: 0447814693 Toilet Roll Holder: G1-TRH-1		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
PF-WC-2	Toilet (Ambulant)	Selection: Caroma Urbane II CleanFlush® Wall Faced Close Coupled Toilet Suite (Bottom Inlet) with GermGard with Urbane II toilet seat - White Product code: 46250W Dimensions: 360w (back) 350w (front) x 655d x 842h (cistern) 440h (bowl) Finish: Vitreous China - white Fixing: Install to comply with AS1428.1 for ambulant applications. S or P trap installation options available - coordinate plumbing & setout on site. Supplier / Contact: GWA Group / Hannah Hansen / e:hhansen@gwagroup.com.au/ ph: 0447814693 Grab Rails: Wellbeing Ambulant Grab Rail 450 x 450mm 90° – Pair Product code: EC45AMBWH (suits both left and right hand application) Dimensions: 450w x 450h Finish: Powdercoat white Fixing: Install as pairs to comply with AS1428.1 for ambulant applications. Concealed fixings. At partitions fix grabrails with through SS bolts and fasten with SS domed nuts. Supplier / Contact: Enware Toilet Roll Holder: G1-TRH-1		T1
PF-WC-3	PWD toilet	Selection: Caroma Care 800 Cleanflush Wall Faced Suite with Backrest and Pedigree II Care Single Flap Seat (Grey), raised height buttons. Product code: 901900BAG Dimensions: 800mm d +/- 10mm x 885h (cistern) 460-480h (seat) Finish: Vitreous China - white with white seat. Fixing: Install to comply with AS1428.1 for accessible applications. S or P trap installation options available - coordinate plumbing & setout on site. Supplier / Contact: GWA Group / Hannah Hansen / e:hhansen@gwagroup.com.au/ ph: 0447814693 Grab rails: Enware Wellbeing Accessible Toilet Grab Rail with 90deg Bend and Enware Wellbeing 300mm Straight Grab Rail . Ensure grab rail selections suit pan orientation. Product Codes: ECASS965L90WH (Left hand 90deg) ECASS965R90WH (Right hand 90deg) EC300WH (300mm rail) Finish: White Powdercoat Finish Note: grab rails to not clash with toilet roll holder clearance zone required by AS1428.1. Toilet Roll Holder: G1-TRH-1		T1
PT-XYZ - Paint & Applied Finishes Notes: 1 Refer to specifications and drawings. 2 Install finishes in accordance with the manufacturers' requirements, including substrate suitability, preparation, installation, finishing and cleaning. 3 Refer to DULUX Project Specification/Schedule (in Architectural Specification - Appendix for systems application. 5 Paint systems and colour codes to be read as follows: PT-XYZ. X = System A = High-build external render-look Acratex C = Specialty Coating E = External acrylic I = Internal acrylic K = Keim Mineral Paint NO = Nosing O = Solvent based enamel or Oil based enamel PC = Powder coat R = Road / Line marking S = Sealer T = Timber finish X = Other, as per below selections Y = Gloss Level (G=Gloss, S=Satin, L=Low Sheen, M=Matt/Flat) z = Colour (a, b, c, etc. as per selections below) 6 Provide 1m x 1m sample painted on site on the applicable substrate of each colour for approval.				

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
	Colours:			
	a	White: Dulux "Vivid White" (SW1G1)	LRV 94	T1
	b	Yellow: Dulux "Aztec Glimmer" (S13H7)	LRV 51	T1
	c	Purple 1: Dulux "Regalia" (S42H8)	LRV 10	T1
	d	Grey: Dulux "Shadow Dance" (S48A4)	LRV 26	T1
	e	Dark Blue: Dulux "Steadfast" S40D7	LRV 13	T1
	f	Blue: Dulux "Glide Time" S37B5	LRV 20	T1
	g	Purple 2: Dulux "Unexplained" S43C6 (to match MLAM-8)	LRV 18	T1
	h	Burgundy: Dulux "Belly Fire" S04D8	LRV 10	T1
	i	Green: Dulux "Leaf Tea" S22D8	LRV 23	T1
	j	Lilac: Dulux "Sky High" S42D4	LRV 34	T1
	Mineral Paint			T1
	k	Yellow: Dulux "Aztec Glimmer" (S13H7)		T1
	Powdercoat			T1
	w	White: Dulux Duralloy "White" Satin		T1
	y	Yellow: Dulux Duratec Intensity "Sunshine" Gloss		T1
	z	Grey: Dulux Duratec Zeus "Shale Grey" Matt		T1
PT-GAL	Hot Dipped Galvanising	Substrate: External Mild Steel as noted on drawings. Note: typically steel is protected with Protective Paint system, refer to Architectural Specification and Structural Engineer's documents.		T1
PT-EL	Paint - External Acrylic Low Sheen	Substrate: External FC wall Selection: Dulux Weathershield, refer to Dulux's specifications Substrate: External FC ceiling Selection: Dulux Weathershield, refer to Dulux's specifications		T1
PT-EG	Paint - External Acrylic Gloss	Substrate: External exposed mild steel Selection: Dulux Protective Coatings, refer to Dulux's specifications Substrate: Zincalume flashing Selection: Dulux Weathershield, refer to Dulux's specifications Substrate: External steel door frames Selection: Dulux Aquanamel, refer to Dulux's specifications Substrate: Solid core doors, timber trims and skirtings Selection: Dulux Aquanamel, refer to Dulux's specifications		T1
PT-IL	Paint - Internal Acrylic Low Sheen	Substrate: Internal FC walls Selection (General): Dulux Wash&Wear, refer to Dulux's specifications Substrate: Internal FC wet area walls. Selection (Wet Areas): Dulux Wash&Wear +Plus Kitchen & Bathroom, refer to Dulux's specifications		T1
PT-IG	Paint - Internal Acrylic Gloss	Substrate: Solid core doors, timber trims and skirtings Selection: Dulux Aquanamel, refer to Dulux's specifications		T1
PT-IM	Paint - Internal Acrylic Ceiling Flat	Substrate: Internal PBD ceilings Selection (White): Dulux Professional Ceiling Flat White, refer to Dulux's specifications Selection (Colour): Dulux Wash&Wear, refer to Dulux's specifications Substrate: Internal PBD wet area ceilings. Selection (Wet Areas): Dulux Ceiling White +PLUS Kitchen&Bathroom , refer to Dulux's specifications		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
PT-KM	Paint - Mineral Paint	Substrate: Blockwork wall Selection: Porter's Paints Mineral Paint, refer to Dulux's specifications		T1
PT-NO	Concrete Paving Paint (stair nosings)	Substrate: Concrete Stairs. Selection: Dulux Protective Coatings Luxafloor® LGE, , refer to Dulux's specifications		T1
PT-PC	Powdercoat (for colours refer to w, y, z above)	Substrate: External aluminium systems, Aluminium trims Selection: Refer above for colours selection, refer to Dulux's Powdercoat specifications		T1
PT-T1	Timber Framed Glazing, Glazed Timber Framed Doors, Timber Veneer Doors	Substrate: Blackbutt timber framed glazing Selection: Intergrain Universal Timber Oil, refer to Dulux's specifications		T1
PT-T2	Internal timber linings	Substrate: Blackbutt Shiplap walls, joinery timber lining Selection: Whittle Waxes, Evolution Hardwax Oil Finish: Satin Application: Apply 2 coats in accordance with manufacturer's specification including preparation before first and second coats. Allow final coat to cure for 8-10 days. Where applied to trafficable surfaces include Whittle Waxes 2K Booster before application.		T1
RX - Roof				
Notes: 1 Refer to architectural specification and drawings. 2 Refer services documents. 3 RF = Roof Types described from top surface to bottom surface				
RA-1	Roof Access Static Line	Selection: Metal Deck static line system Supplier: Kattsafe; design and installation to be certified by the supplier. Refer to Appendix G - Building Access System; design and installation to be coordinated by the Architect.	Certification: Design and Installation certification	T1
RA-2	Roof Access Ladder Bracket	Selection: Roof mount ladder bracket Supplier: Kattsafe; design and installation to be certified by the supplier. Design and installation to be coordinated by the Architect.	Certification: Design and Installation certification	T1
RD-1	Roof Downpipe - Twin typical	Selection: Twin circular downpipes (DP + Overflow) and integral sump DP Size: 2x 150mm dia; 1.6mm thick Grade 316 SS. Sump: 600W x 300L x 100D - refer performance solution Fixing: concealed at head within ceiling space and at base below finished floor level. Finish: Stainless Steel, Grade 316		T1
RD-2	Roof Downpipe - Twin typical	Selection: Twin circular downpipes (DP + Overflow) and integral sump DP Size: 2x 150mm dia; 1.6mm thick Grade 316 SS. Sump: 600W x 3600L x 100D - refer performance solution Fixing: concealed at head within ceiling space and at base below finished floor level. Finish: Stainless Steel, Grade 316	Certification: Refer to Hydraulic PBDB	T1
RF-1	Main Building Roof - trusses	Selection: Stratco Topdek 700 0.48 bmt, installed over insulation with Ashgrid spacers mounted on timber battens over timber trusses with 17.5mm ply between trusses and battens. 200mm min buildup to accommodate box gutter and acoustic requirements. Finish: Colorbond: Surfmist Fixing: Concealed fixings Sarking: CSR Bradford Enviroseal HTS installed between the roof sheeting and ashgrid spacers, over the insulation. Joints taped to manufacturer's recommendation. Thermal Requirements: R6.36 including ceiling Insulation: nominally R4.2 175mm Anticon Blanket		T2

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
RF-2	Main Building Roof - 200d steel purlins	Selection: Stratco Topdek 700 0.48 bmt, installed on steel purlins with 17.5mm ply fixed to underside. Insulation between purlins. 200mm min buildup to accommodate box gutter and acoustic requirements. Refer to structural documents. Finish: Colorbond: Surfmist Fixing: Concealed fixings Sarking: CSR Bradford Enviroseal HTS installed between the roof sheeting and purlins, over the insulation. Joints taped to manufacturer's recommendation. Thermal Requirements: R3.15 including ceiling Insulation: nominally Bradford R2.5 140mm Gold Batt		T2
RF-5	Awning Roof	Selection: Lysaght Imperial 325 Seams: Single standing seam; 25mm high ribs. Pans: nom 325mm wide Material: 0.55mm BMT Zinalume Substrate: HC9 drainage mat over ProctorPassive wraptite membrane to 17.5mm F8 ply with MCA H3.2 treatment. Fixing: Concealed fixings Thermal Requirements: n/a Insulation: n/a Prequaliified supplier and installer: Sustainable Cladding & Roofing: Ryan Finlay: 0432 189 879: ryan@sustainablecladding.com.au		T1
RG-1	Roof Box Gutter	Description: Box gutter fabricated from fabricated from heavy gauge stainless steel 316 grade sheet, with integral sumps. Anti-splash flashing to roof side. Gutter to be supported on proprietary gutter board set to falls and suspended with straps or angles and drop down bolts. Box Gutter Size: 600mm wide x 200mm deep Box Gutter Fall: Min 1 in 200 fall to sump Box gutter sump (typical): 300mm d x 600mm L x 300mm w sump to be fully welded to gutter. Integral connection to downpipe & overflow. Box gutter sump (corner): 300mm d x 600mm L x 4200mm w sump to be fully welded to gutter. Integral connection to downpipe & overflow. Overflow: integral overflow connection to additional overflow rwdp. Refer to Performance Based Design Brief for valley gutter alternative solution and detailed requirements.	Certification: Refer to Hydraulic PBDB	T1
SI - Signage				
Notes:		1 Refer to architectural specification, door schedule and drawings for text and location. 2 Provide shop drawings for approval prior to manufacture. 3 Confirm all sign locations on site with Architect before installation. 4 Install statutory signage in accordance with the NCC and AS1428.1. 5 Braille signage to be mounted on wall by default. Alternative door mounting by approval of the architect. 6 Architectural signage number system to be coordinate with the client		
ARCHITECTURAL SIGNAGE				
SI-1	Room Number Signage	Selection: Individual Acrylic letters Font: Helvetica Size: 70mm height Thickness: 3mm Colour: Black Note: Numbering to be coordinated with client.		T1
SI-2	Room Name Signage	Selection: Individual Acrylic letters Font: Helvetica (all capital letters) Size: 30mm height Thickness: 3mm Colour: Black a: COMMS b: FIRST AID ROOM c: CLEANER b: STORE		T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
SI-3	Numbers Decal (Kitchen Lockers)	Selection: Individual adhesive backed vinyl letters for the 60 lockers. Font: Helvetica Size: 30mm height Colour: White Note: Numbering to be coordinated with client.		T1
SI-10 SI-11 SI-12 SI-13 SI-14 SI-15 SI-16 SI-17 SI-18 SI-19 SI-20 SI-21 SI-22 SI-23 SI-24	Connecting to Country Decal	Selection: Circular vinyl and centered lettering on the inside of glazing. (Facing internally) Dimension: Diam. 400mm Back colour: Pantone 1235C (yellow) Font colour: Pantone Black C Font style: Bold Font heights: Main text 7mm / Reference 4mm Text: Refer to Appendix H Location: Refer to A-60 Series elevations for locations	Provide shop drawings for approval	T1
STATUTORY SIGNAGE				
SI-20	Unisex Accessible Shower 	Selection: Pictobraille Unisex Accessible Shower Braille & Tactile sign. Dimensions: 180 x 235mm. Finish: Black symbols and text with braille on 1.2mm UV Stable White Polypropylene backing plate.	Certification: - NCC D4D7(1)(a)(i)(A) - NCC D4D7(c) - AS 1428.1 Sample: to confirm location on site	T1
SI-21	Unisex Accessible Sanitary Compartment (LH Transfer) 	Selection: Pictobraille Unisex Accessible Toilet Left Hand Transfer Braille & Tactile sign. Dimensions: 180 x 235mm. Finish: Black symbols and text with braille on 1.2mm UV Stable White Polypropylene backing plate.	Certification: NCC D4D7(1)(a)(i)(A); NCC D4D7(c); AS 1428.1 Sample: To confirm location on site	T1
SI-22	Female Sanitary 	Selection: Pictobraille Female Toilet Braille & Tactile sign. Dimensions: 180 x 235mm. Finish: Black symbols and text with braille on 1.2mm UV Stable White Polypropylene backing plate.	Certification: NCC D4D7(1)(a)(i)(A); NCC D4D7(c); AS 1428.1 Sample: To confirm location on site	T1
SI-23	Male Sanitary 	Selection: Pictobraille Male Toilet Braille & Tactile sign. Dimensions: 180 x 235mm. Finish: Black symbols and text with braille on 1.2mm UV Stable White Polypropylene backing plate.	Certification: NCC D4D7(1)(a)(i)(A); NCC D4D7(c); AS 1428.1 Sample: To confirm location on site	T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
SI-24	Female Ambulant Sanitary Compartment 	Selection: Pictobraille Female Ambulant Toilet Braille & Tactile sign. Dimensions: 180 x 235mm. Finish: Black symbols and text with braille on 1.2mm UV Stable White Polypropylene backing plate.	Certification: NCC D4D7(1)(a)(i)(A); NCC D4D7(c); AS 1428.1 Sample: To confirm location on site	T1
SI-25	Male Ambulant Sanitary Compartment 	Selection: Pictobraille Male Ambulant Toilet Braille & Tactile sign. Dimensions: 180 x 235mm. Finish: Black symbols and text with braille on 1.2mm UV Stable White Polypropylene backing plate.	Certification: NCC D4D7(1)(a)(i)(A); NCC D4D7(d); AS 1428.1 Sample: To confirm location on site	T1
SI-26	Exit Door Identification 	Selection: Pictobraille Slim Exit Level sign. Dimensions: 180 x 60mm. Finish: Black symbols and text with braille on 1.2mm UV Stable White Polypropylene backing plate. If mounted to glass provide black vinyl film behind sign.	Confirmation required by Building Certifier	T1
SI-30	Fire Indicator Panel (FIP)	Location: FIP Door; refer to Door Schedule. Text: "FIRE PANEL". Type: 50mm high, individual adhesive backed vinyl letters. Colour: Black		T1
SI-31	Fire Detection System	Block panel diagram	Confirmation required by Building Certifier	T1
SI-32	Certificate of Classification Document Holder	Frame / mount to locate Certificate of Classification : - A4 Snap lock frame - Portrait orientation - extruded clear anodised aluminium frame with snap lock/release boarder. - Corners mitred (ie not with an ugly static corner junction) - Anti glare protector PVC cover sheet - mechanically fixed or adhesive fixed as preferred by client College to print and mount Certificate of Classification to comply with legislative requirement. Refer to A-60 Series elevations for locations	Queensland Building Act 1975 Form 11	T1
WP - Waterproof Membranes				
Notes: 1 Refer to architectural specification and drawings. 2 Install in accordance with the manufacturers' requirements, including substrate suitability, preparation, installation, finishing and cleaning. 3 Floor waste: provide over and under membrane sealed to floor waste with puddle flanges.				
WP-1	Internal Wet Areas - Direct Stick Flooring	Description: Vulkem H2 Plus applied above screed and to walls. Supplier: Tremco Primer: As per Appendix D: Waterproofing Specification (Tremco CPG Product Specification) Installation: Include all fillets, bond breakers and sealants to the Tremco Specification. Contact: Justin Allingham: 0497 777 474: justin.allingham@tremco.com.au	Warranty (materials): 15 years Certificate: installation	T1
WP-2	External Wall Bonded Membrane	Description: Solitex Extansa Adhero applied to external face of RAB board in external walls. Supplier: Pro Clima Installation: Refer to manufacturer's installation details (incl.for lapping of sheets) and façade engineer's specification. Fixings: Fix using screws with plastic/steel proprietary washers generally and with an aluminium rail & tape at edges to comply with manufacturer's details. Flashing: Include Tescon Extoseal tape to all penetrations, sill head and jamb junctions, and for patching, as per the facade engineer's specification.	Warranty (materials): 10 years	T1

Technical Reference Sheet

Code	Description	Specification Description	Contractor Deliverable(s)	Rev
WP-3	External Deck Paver - Direct Stick	Description: Vulkem H2 Plus. Supplier: Tremco Primer: As per Appendix D: Waterproofing Specification (Tremco CPG Product Specification) Installation: Include all fillets, bond breakers and sealants to the Tremco Specification. Contact: Justin Allingham: 0497 777 474: justin.allingham@tremco.com.au	Warranty (materials): 10 years Certificate: Installation	T1
WP-4	External Wall/Cling Non-Bonded Membrane	Description: Solitex Extansa. Supplier: Pro Clima Installation: Refer to manufacturer's installation details (incl.for lapping of sheets) and façade engineer's specification. Fixings: Fix using screws with plastic/steel proprietary washers generally and with an aluminium rail & tape at edges to comply with manufacturer's details. Flashing: Include Tescon Extoseal tape to all penetrations, sill head and jamb junctions, and for patching, as per the facade engineer's specification.	Warranty (materials): 10 years	T1