Question 13: Hive DDL commands

Aim

To perform Data Definition Language (DDL) operations in Hive for creating, altering, describing and dropping database

objects.

Procedure

1. Open the Hive shell or connect through Beeline.

2. Execute CREATE DATABASE and CREATE TABLE to define database objects.

3. Use DESCRIBE or SHOW commands to inspect the objects.

4. Use ALTER TABLE to modify a table definition.

5. Use DROP TABLE or DROP DATABASE to remove an object when required.

Program / HiveQL commands

```
-- Create a database

CREATE DATABASE college;

-- Select the database

USE college;

-- Create a table

CREATE TABLE student (

sid INT,

sname STRING,

department STRING

)

ROW FORMAT DELIMITED

FIELDS TERMINATED BY ',';

-- Display databases and tables

SHOW DATABASES;

SHOW TABLES;

-- Display table structure

DESCRIBE student;

-- Add a column

ALTER TABLE student ADD COLUMNS (age INT);
```

```
-- Rename a table

ALTER TABLE student RENAME TO student_details;

-- Drop a table

DROP TABLE student_details;

-- Drop the database after its tables are removed

DROP DATABASE college;
```

Output of Program

```
OK

Database college created

Table student created

Database selected

Table list displayed

Table structure displayed

Table altered / renamed

Table dropped

Database college dropped
```

Result

The Hive DDL commands were executed to create, inspect, modify and remove database objects successfully.