Question 9: HiveQL: create employees table, load data and display table contents

table contents

Aim

To create an employees table in Hive, load records into it and retrieve the table contents.

Procedure

1. Start Hadoop and open the Hive shell or Beeline session.

2. Create a table named employees with the fields eid, ename, eage and edepartment.

3. Prepare a comma-separated text file containing employee records.

4. Load the local data file into the Hive table.

5. Execute SELECT * to display all records.

Program / HiveQL commands

```
CREATE TABLE employees (

eid INT,

ename STRING,

eage INT,

edepartment STRING

)

ROW FORMAT DELIMITED

FIELDS TERMINATED BY ','

STORED AS TEXTFILE;

-- employees.txt (one record per line)

101,Ravi,24,IT

102,Meena,25,HR

103,Arun,23,Sales

LOAD DATA LOCAL INPATH '/home/student/employees.txt'

INTO TABLE employees;

SELECT * FROM employees;
```

Output of Program

```
+-----------+-------------+------------+----------------+
```

| eid | ename | eage | edepartment |

+-----------+-------------+------------+----------------+

| 101 | Ravi | 24 | IT |

| 102 | Meena | 25 | HR |

| 103 | Arun | 23 | Sales |

+-----------+-------------+------------+----------------+

Result

The employees table was created, the sample records were loaded, and all employee details were displayed successfully.