

# Rajalakshmi Engineering College

Name: Mithul P

Email: 241501111@rajalakshmi.edu.in

Roll no: 241501111

Phone: 9445310017

Branch: REC

Department: I AI & ML FA

Batch: 2028

Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_MCQ

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : MCQ

1. Consider the singly linked list: 15 -> 16 -> 6 -> 7 -> 17. You need to delete all nodes from the list which are prime.

What will be the final linked list after the deletion?

**Answer**

15 -> 16 -> 6

**Status : Correct**

**Marks : 1/1**

2. Given the linked list: 5 -> 10 -> 15 -> 20 -> 25 -> NULL. What will be the output of traversing the list and printing each node's data?

**Answer**

5 10 15 20 25

**Status :** Correct

**Marks :** 1/1

3. The following function reverse() is supposed to reverse a singly linked list. There is one line missing at the end of the function.

What should be added in place of "/\*ADD A STATEMENT HERE\*/", so that the function correctly reverses a linked list?

```
struct node {
    int data;
    struct node* next;
};
static void reverse(struct node** head_ref) {
    struct node* prev = NULL;
    struct node* current = *head_ref;
    struct node* next;
    while (current != NULL) {
        next = current->next;
        current->next = prev;
        prev = current;
        current = next;
    }
    /*ADD A STATEMENT HERE*/
}
```

**Answer**

\*head\_ref = prev;

**Status :** Correct

**Marks :** 1/1

4. Consider the singly linked list: 13 -> 4 -> 16 -> 9 -> 22 -> 45 -> 5 -> 16 -> 6, and an integer K = 10, you need to delete all nodes from the list that are less than the given integer K.

What will be the final linked list after the deletion?

**Answer**

13 -> 16 -> 22 -> 45 -> 16

**Status :** Correct

**Marks :** 1/1

5. Which of the following statements is used to create a new node in a singly linked list?

```
struct node {  
    int data;  
    struct node * next;  
}  
typedef struct node NODE;  
NODE *ptr;
```

**Answer**

```
ptr = (NODE*)malloc(sizeof(NODE));
```

**Status :** Correct

**Marks :** 1/1

6. The following function takes a singly linked list of integers as a parameter and rearranges the elements of the lists.

The function is called with the list containing the integers 1, 2, 3, 4, 5, 6, 7 in the given order. What will be the contents of the list after the function completes execution?

```
struct node {  
    int value;  
    struct node* next;  
};  
  
void rearrange (struct node* list) {  
    struct node *p,q;  
    int temp;  
    if (! List || ! list->next) return;  
    p=list; q=list->next;  
    while(q) {  
        temp=p->value; p->value=q->value;  
        q->value=temp;p=q->next;  
        q=p?p->next:0;
```

**Answer**

2, 1, 4, 3, 6, 5, 7

**Status :** Correct

**Marks :** 1/1

7. Consider an implementation of an unsorted singly linked list. Suppose it has its representation with a head pointer only. Given the representation, which of the following operations can be implemented in  $O(1)$  time?

- i) Insertion at the front of the linked list
- ii) Insertion at the end of the linked list
- iii) Deletion of the front node of the linked list
- iv) Deletion of the last node of the linked list

**Answer**

I and III

**Status :** Correct

**Marks :** 1/1

8. Linked lists are not suitable for the implementation of?

**Answer**

Binary search

**Status :** Correct

**Marks :** 1/1

9. In a singly linked list, what is the role of the "tail" node?

**Answer**

It stores the last element of the list

**Status :** Correct

**Marks :** 1/1

10. Given a pointer to a node X in a singly linked list. If only one point is given and a pointer to the head node is not given, can we delete node X from the given linked list?

**Answer**

Possible if X is not last node.

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: Mithul P

Email: 241501111@rajalakshmi.edu.in

Roll no: 241501111

Phone: 9445310017

Branch: REC

Department: I AI & ML FA

Batch: 2028

Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 1

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

Janani is a tech enthusiast who loves working with polynomials. She wants to create a program that can add polynomial coefficients and provide the sum of their coefficients.

The polynomials will be represented as a linked list, where each node of the linked list contains a coefficient and an exponent. The polynomial is represented in the standard form with descending order of exponents.

#### ***Input Format***

The first line of input consists of an integer  $n$ , representing the number of terms in the first polynomial.

The following  $n$  lines of input consist of two integers each: the coefficient and the exponent of the term in the first polynomial.

The next line of input consists of an integer m, representing the number of terms in the second polynomial.

The following m lines of input consist of two integers each: the coefficient and the exponent of the term in the second polynomial.

### **Output Format**

The output prints the sum of the coefficients of the polynomials.

### **Sample Test Case**

Input: 3

2 2

3 1

4 0

3

2 2

3 1

4 0

Output: 18

### **Answer**

```
#include<stdio.h>
#include<stdlib.h>
struct node{
    int co,ex;
    struct node *next;
};
struct node* headerp1=NULL;
struct node* headerp2=NULL;
void insertp1(int co,int ex){

    struct node* temp = (struct node*)malloc(sizeof(struct node));
    if (headerp1 == NULL ){
        temp->co=co;
        temp->ex=ex;
        temp->next=NULL;
        headerp1=temp;
        return;
    }

    struct node* temp1=headerp1;
```

```

while(temp1->next!=NULL){
    temp1=temp1->next;
}

temp->co=co;
temp->ex=ex;
temp->next=NULL;
temp1->next=temp;
}
void insertp2(int co,int ex){

    struct node* temp2 = (struct node*)malloc(sizeof(struct node));
    if (headerp2 == NULL ){
        temp2->co=co;
        temp2->ex=ex;
        temp2->next=NULL;
        headerp2=temp2;
        return;
    }

    struct node* temp3=headerp2;
    while(temp3->next!=NULL){
        temp3=temp3->next;
    }

    temp2->co=co;
    temp2->ex=ex;
    temp2->next=NULL;
    temp3->next=temp2;
}
int sum(){
    int s1=0,s2=0;
    struct node* temp4=headerp1;
    while(temp4!=NULL){
        s1+=temp4->co;
        temp4=temp4->next;
    }
    struct node* temp5=headerp2;
    while(temp5!=NULL){
        s2+=temp5->co;
        temp5=temp5->next;
    }
}

```



```
}  
    return s1+s2;  
}
```

```
int main(){  
    int n;  
    scanf("%d",&n);  
    for(int i=0;i<n;i++){  
        int co,ex;  
        scanf("%d %d",&co,&ex);  
        insertp1(co,ex);  
    }  
    int n1;  
    scanf("%d",&n1);  
    for(int i=0;i<n1;i++){  
        int cop2,ex2;  
        scanf("%d %d",&cop2,&ex2);  
        insertp2(cop2,ex2);  
    }  
    printf("%d",sum());  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Mithul P

Email: 241501111@rajalakshmi.edu.in

Roll no: 241501111

Phone: 9445310017

Branch: REC

Department: I AI & ML FA

Batch: 2028

Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 2

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

Arun is learning about data structures and algorithms. He needs your help in solving a specific problem related to a singly linked list.

Your task is to implement a program to delete a node at a given position. If the position is valid, the program should perform the deletion; otherwise, it should display an appropriate message.

#### ***Input Format***

The first line of input consists of an integer N, representing the number of elements in the linked list.

The second line consists of N space-separated elements of the linked list.

The third line consists of an integer x, representing the position to delete.

Position starts from 1.

### **Output Format**

The output prints space-separated integers, representing the updated linked list after deleting the element at the given position.

If the position is not valid, print "Invalid position. Deletion not possible."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

8 2 3 1 7

2

Output: 8 3 1 7

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
void insert(int);
```

```
void display_List();
```

```
void deleteNode(int);
```

```
struct node {
```

```
    int data;
```

```
    struct node* next;
```

```
} *head = NULL, *tail = NULL;
```

```
void insert(int a)
```

```
{
```

```
    struct node* temp=(struct node*)malloc(sizeof(struct node));
```

```
    if(head==NULL){
```

```
        temp->data=a;
```

```
        temp->next=NULL;
```

```
        head=temp;
```

```
        return;
```

```
    }
```

```
    tail=head;
```

```

    while(tail->next!=NULL){
        tail=tail->next;
    }
    temp->data=a;
    temp->next=NULL;
    tail->next=temp;
}

void deleteNode(int x){
    tail=head;
    if(tail==NULL){printf("Invalid position. Deletion not possible.");
        return;
    }//empty list
    struct node* temp=NULL;
    int i=1;
    if (x==1){
        head=head->next;
        display_List();
        return;
    }

    for(int i=1;i<x && tail!=NULL;i++){
        temp=tail;
        tail=tail->next;
    }
    if(tail==NULL){printf("Invalid position. Deletion not possible.");
        return;
    }
    temp->next=tail->next;
    display_List();
}

void display_List(){
    tail=head;
    while(tail!=NULL){
        printf("%d ",tail->data);
        tail=tail->next;
    }
}

int main() {
    int num_elements, element, pos_to_delete;

```

```
scanf("%d", &num_elements);  
for (int i = 0; i < num_elements; i++) {  
    scanf("%d", &element);  
    insert(element);  
}  
  
scanf("%d", &pos_to_delete);  
  
deleteNode(pos_to_delete);  
  
return 0;  
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Mithul P

Email: 241501111@rajalakshmi.edu.in

Roll no: 241501111

Phone: 9445310017

Branch: REC

Department: I AI & ML FA

Batch: 2028

Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 3

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

Imagine you are working on a text processing tool and need to implement a feature that allows users to insert characters at a specific position.

Implement a program that takes user inputs to create a singly linked list of characters and inserts a new character after a given index in the list.

#### ***Input Format***

The first line of input consists of an integer N, representing the number of characters in the linked list.

The second line consists of a sequence of N characters, representing the linked list.

The third line consists of an integer index, representing the index(0-based) after

which the new character node needs to be inserted.

The fourth line consists of a character value representing the character to be inserted after the given index.

### ***Output Format***

If the provided index is out of bounds (larger than the list size):

1. The first line of output prints "Invalid index".
2. The second line prints "Updated list: " followed by the unchanged linked list values.

Otherwise, the output prints "Updated list: " followed by the updated linked list after inserting the new character after the given index.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

a b c d e

2

X

Output: Updated list: a b c X d e

### ***Answer***

```
#include<stdio.h>
#include<stdlib.h>
struct node {
    char a;
    struct node* next;
};
struct node* header=NULL;
void print(){
    struct node* temp1=header;
    printf("Updated list: ");
    while(temp1!=NULL){
        printf("%c ",temp1->a);
```

```
temp1=temp1->next;
}
}

void insert(char x,int a){
    struct node* temp=(struct node*)malloc(sizeof(struct node));
```

```
    if(a==1000)
    {
        temp->a=x;
        temp->next=NULL;
        if(header==NULL){
            header=temp;
            return;
        }
```

```
        struct node* temp1=header;
        while(temp1->next!=NULL){
            temp1=temp1->next;
        }
        temp1->next=temp;
        return;
    }
```

```
    struct node* temp1=header;
    if(a==1){
        temp->a=x;
        temp->next=header;
        header=temp;
        print();
        return;
    }
    for(int i=1;i<a+1;i++){
        if(temp1==NULL||temp1->next==NULL){
            printf("Invalid index\n");
            print();
            return;
        }
```

```
        temp1=temp1->next;
```



```
}  
temp->a=x;  
temp->next=temp1->next;  
temp1->next=temp;
```

```
print();  
}
```

```
int main(){  
    int n;  
    scanf("%d",&n);  
    for(int i=0;i<n;i++){  
        char a;  
        scanf(" %c",&a);  
        insert(a,1000);  
    }  
    int b;  
    char c;  
    scanf("%d %c",&b,&c);  
    insert(c,b);  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Mithul P

Email: 241501111@rajalakshmi.edu.in

Roll no: 241501111

Phone: 9445310017

Branch: REC

Department: I AI & ML FA

Batch: 2028

Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 4

Attempt : 1

Total Mark : 10

Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

As part of a programming assignment in a data structures course, students are required to create a program to construct a singly linked list by inserting elements at the beginning.

You are an evaluator of the course and guide the students to complete the task.

##### ***Input Format***

The first line of input consists of an integer N, which is the number of elements.

The second line consists of N space-separated integers.

##### ***Output Format***

The output prints the singly linked list elements, after inserting them at the beginning.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

78 89 34 51 67

Output: 67 51 34 89 78

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node* next;  
};
```

```
void insertAtFront(struct Node** head, int x){  
    struct Node* temp=(struct Node*)malloc(sizeof(struct Node));  
    temp->data=x;  
    temp->next=*head;  
    *head=temp;
```

```
}  
void printList(struct Node* head){  
    struct Node* temp=head;  
    while(temp!=NULL){  
        printf("%d ",temp->data);  
        temp=temp->next;  
    }  
}
```

```
int main(){  
    struct Node* head = NULL;  
  
    int n;  
    scanf("%d", &n);
```

```
for (int i = 0; i < n; i++) {  
    int activity;  
    scanf("%d", &activity);  
    insertAtFront(&head, activity);  
}  
  
printList(head);  
struct Node* current = head;  
while (current != NULL) {  
    struct Node* temp = current;  
    current = current->next;  
    free(temp);  
}  
return 0;  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Mithul P

Email: 241501111@rajalakshmi.edu.in

Roll no: 241501111

Phone: 9445310017

Branch: REC

Department: I AI & ML FA

Batch: 2028

Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 5

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

Imagine you are tasked with developing a simple GPA management system using a singly linked list. The system allows users to input student GPA values, insertion should happen at the front of the linked list, delete record by position, and display the updated list of student GPAs.

#### ***Input Format***

The first line of input contains an integer  $n$ , representing the number of students.

The next  $n$  lines contain a single floating-point value representing the GPA of each student.

The last line contains an integer position, indicating the position at which a student record should be deleted. Position starts from 1.

### **Output Format**

After deleting the data in the given position, display the output in the format "GPA: " followed by the GPA value, rounded off to one decimal place.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 4

3.8

3.2

3.5

4.1

2

Output: GPA: 4.1

GPA: 3.2

GPA: 3.8

### **Answer**

```
#include<stdio.h>
#include<stdlib.h>
struct node{
    float x;
    struct node* next;
};
typedef struct node node;
node* head=NULL;
void insert(float x){
    node* temp=(node*)malloc(sizeof(node));
    temp->x=x;
    if(head==NULL){
        temp->next=NULL;
        head=temp;
        return;
    }
    temp->next=head;
    head=temp;
}
void print(int a){
```

```
node* temp=head;
int c=1;
while(temp!=NULL){
    if(c!=a){
        printf("GPA: %.1f\n",temp->x);
        temp=temp->next;
        c++;
    }
}
int main(){
    int n;
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        float m;
        scanf("%f",&m);
        insert(m);
    }
    int d;
    scanf("%d",&d);
    print(d);
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Mithul P

Email: 241501111@rajalakshmi.edu.in

Roll no: 241501111

Phone: 9445310017

Branch: REC

Department: I AI & ML FA

Batch: 2028

Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 6

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

John is tasked with creating a program to manage student roll numbers using a singly linked list.

Write a program for John that accepts students' roll numbers, inserts them at the end of the linked list, and displays the numbers.

#### ***Input Format***

The first line of input consists of an integer N, representing the number of students.

The second line consists of N space-separated integers, representing the roll numbers of students.

#### ***Output Format***



The output prints the space-separated integers singly linked list, after inserting the roll numbers of students at the end.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

23 85 47 62 31

Output: 23 85 47 62 31

### **Answer**

```
#include<stdio.h>
#include<stdlib.h>
struct node {
    int x;
    struct node* next;
};
typedef struct node node;
node* head=NULL;
void insert(int x){
    node* temp=(node*)malloc(sizeof(node));
    temp->x=x;
    temp->next=NULL;
    if(head!=NULL)
        temp->next=head;
    head=temp;
    printf("%d ",temp->x);
}
int main(){
    int n;
    scanf("%d",&n);
    for (int i=0;i<n;i++){
        int x;
        scanf("%d",&x);
        insert(x);
    }
}
```

241501111

**Status : Correct**

241501111

241501111

**Marks : 10/10**

241501111

241501111

241501111

241501111

241501111

241501111

241501111

241501111

241501111

241501111

241501111

241501111

241501111