

Provenant

The firewall between AI agents and their tools.

PARALLAX 2026 · AGENTSHIELD TRACK

BUILT BY TEAM

Parivartan

Mithun · Kundan
Huzefa · Nithya

Your agent reads an email. The email gives the orders.

AT RISK


Files, secrets, your inbox, cloud and databases.

THE ATTACKER

Anyone who can put text in front of your agent.

WAYS IN

Email, web pages, documents, MCP tools.



WITHOUT PROVENANT

Sent.

agent

```
send_email(to: account-recovery@login-check…,
           attach: invoices[0..4])
→ delivered
```

Five invoices leave. Judged from the world state, not the logs.

WITH PROVENANT

Denied.

provenant

```
DENY  send_email → account-recovery@login-check…
      destination came from the email, not from you
risk HIGH (17) · 7 signals
```

Provenant now
Incoming call · High-risk email
“Don’t click. Verify the sender.”

THE PRINCIPLE

The model proposes. Policy decides.



What the agent reads flows back through the gate. Every decision is hash-chained and signed.

DEFENSE IN DEPTH

Six checks. Zero model calls.

01 · PROVENANCE

An address the agent read can't receive your data.

That's why the phishing send is denied.

real Claude Code · permissions bypassed

```
> rm -rf ./*
  DENY  blocked by the Provenant hook

> cat .env
  DENY  secret file
```

02 · 03

Injection + shell

After injected text, side effects need a human. Root deletes, pipe-to-shell, credential files.

04 · 05 · 06

Network, grants, pins

Encoded IPs blocked and pinned. Single-use grants. Changed MCP tools withheld.

DROPS INTO

Claude Code · Claude Desktop · Cursor · VS Code · any stdio MCP server

`provenant setup` shows a plan, backs up, asks first. `rollback` undoes it.

LIVE DEMO

Watch it happen.


LIVE

operator laptop

```
$ provenant mail demo
  scanner      risk HIGH (17) · 7 signals
  send_email   account-recovery@login-check.example  DENY


$ provenant mail demo --call
  calling your phone · labelled Provenant alert

$ provenant check "rm -rf ~"
  DENY  same engine Claude Code uses
```



Reserved .example domains only. Nothing is emailed. The call is placed only with --call and a yes.

EVALUATION · REGENERATED FROM CODE



225/225

attacks contained. 18 categories. Never ALLOW.

DENY 168 · REQUIRE APPROVAL 57

53/53	**9/9**	**235**	**−72%**	**0.15ms**	**41**
legit actions allowed	live checks	tests passing	tool-result tokens	decision p50	self-found gaps
zero false positives	real MCP + proxy	incl. clean install	one benchmark	no model call	all fixed

NOT PROVEN YET paraphrased destinations · pattern-based shell analysis · remote HTTP MCP · field tests of phone approval and the Windows installer. Evidence, not proof of no bypass.

JUDGING CRITERIA

Every criterion. Covered.

01 — SLIDE 2

Threat relevance

Prompt injection via email, web and MCP. Threat model T1–T16 names assets and attackers.

02 — SLIDES 3·7

Verified effectiveness

Same phish: sent without us, denied with us. 225/225 contained, 9/9 live checks.

03 — SLIDES 4·5

Technical implementation

Deterministic engine, single-use HMAC grants, SQLite approvals, hash-chained audit. 235 tests.

04 — SLIDES 5·7

Innovation

Provenance taint: what the agent read can't choose where your data goes. 41 self-found gaps fixed.

05 — SLIDES 5·6

UI / UX

One-line install with plan, backup and consent. Rollback. Live console. Approval inside Claude.

06 — SLIDES 6·7

Safety and privacy

Fails closed. Local-first, no telemetry, secrets masked. .example domains; calls need a yes.

07 — SLIDE 5

Feasibility and impact

Works today in Claude Code, Desktop, Cursor and VS Code. pip wheel, 0.15 ms, −72% tokens.

08 — SLIDE 6

Presentation and demo

Live on stage: a phish, a blocked send, the phone rings. 55-second video as fallback.

```
PS> irm https://raw.githubusercontent.com/MithunSidhaarth/provenant/main/install.ps1 | iex
```

Parivartan
Mithun · Kundan · Huzefa · Nithya