PROVENANT · PARALLAX 2026 · TEAMMATE 2 BRIEFING

Teammate 2 (P2): architecture, MCP and Claude integration, enforcement

Slides 4 to 7. 2 minutes. P1 hands to you with: "So how can step three be guaranteed, when the model already obeyed?"

What you need to know

Product	Provenant: a deterministic firewall between AI agents and their tools. Every tool call gets ALLOW, DENY or REQUIRE_APPROVAL. The model is never the security boundary.
Team	P1 problem and use case (slides 1-3) · P2 architecture and enforcement (4-7) · P3 mithun: live demo, evaluation, limits, close (8-11). 6.5 minutes total.
Numbers you may quote	225/225 attacks contained · 53/53 legitimate actions allowed · 9/9 live proxy checks · 235 unit tests · decision p50 about 0.16 ms · 41 gaps found and fixed in red-team round 2.
Never say	Unhackable, 100% secure, stops all prompt injection, tamper-proof. Phone approval for held calls is built but not tested with a real call.
If stuck	"Great question, [owner] built that part." Hand over; never guess. Answers: team/QA_BANK.md.
Your job	Make the judges believe step three is guaranteed: one deterministic gate, every entry point, fail closed. Then hand to mithun.

Slide 4: The model is never the security boundary (0:30)

Because the decision isn't made by a model. Every tool call the agent proposes goes through one deterministic check, written in plain Python, with no AI in it. It returns one of three answers.

ALLOW: it runs once, under a single-use grant tied to that exact call. DENY: it never reaches the tool. REQUIRE APPROVAL: it waits for a person.

And it fails closed. If nothing matches, if the policy file is broken, if anything throws, the answer is DENY.

Slide 5: One gate, every entry point (0:35)

There are three ways in, all on the left. MCP clients like Claude Desktop, Cursor and VS Code. Claude Code, through its hooks. And our own gated tool server.

They all call the same function, Guard dot check. On the right: real tools only run after ALLOW plus a grant. Held calls sit in a small database with an expiry and can be used once. Every decision is written to an audit log where each record is chained to the previous one by hash and signed, so edits show up.

The loop at the bottom matters most. What the agent reads goes back through the gate, so reading a malicious email changes what the agent is allowed to do next.

Slide 6: Drops into the agents people already use (0:30)

No code changes for the user. provenant setup shows a plan, backs up each config, asks, then wraps every MCP server. Only allowed calls reach the server. We also pin each tool's definition. If a server changes a tool's description after you approved it, a "rug pull", the new definition is withheld.

For Claude Code we use its hooks. DENY blocks the call, and REQUIRE APPROVAL becomes Claude's own "ask the human" prompt. We ran real Claude Code with permission checks switched off, told it to delete everything and read .env, and the hook blocked both.

Slide 7: Defense in depth, all deterministic (0:25)

Six independent checks. I'll name two. Provenance: an address the agent copied from something it read can't receive your data. That's exactly why the phishing send is denied. And single-use grants: an approved call can't be replayed or swapped for different arguments.

Enough slides. *(turn to mithun)* [mithun] will show it live.

If a judge asks you something

- "What if the attacker paraphrases the address?" Provenance compares values, so a reworded address can slip that one rule. The other rules still apply: after the agent reads injected text, every side effect needs a human. It's on our limits slide.
- "Why not use an LLM to judge?" An LLM judge can be prompt-injected by the same text. We have an optional model, but it can only make decisions stricter, never allow anything, and it's off by default.
- "How fast?" About 0.16 milliseconds per decision on our test machine. The proxy adds about 14 ms per call.
- "Can the agent approve its own call?" provenant approve refuses to run without a real terminal, so an agent running commands can't approve. We call that a speed bump, not a proof.
- "Remote MCP servers?" Not yet. Only local stdio servers are proxied today.
- "Which models does it work with?" Any. It never looks inside the model; it only sees tool calls.

Do not say

- "Uses AI to detect attacks." The deciding part has no AI in it.
- "Tamper-proof logs." They are tamper-evident: edits are detected, but deleting the end leaves a shorter valid chain unless the head is anchored.