

```

"use client";
import { useState, useEffect } from 'react';
import { toast } from 'react-toastify';
import { Server, Cpu, Memory, HardDrive, Network, Shield, Settings, Plus, Trash2, Save } from 'lucide-react';

export default function NFVServerForm() {
  const [formData, setFormData] = useState({
    serverName: '',
    networkFunctionType: 'vRouter',
    serverPurpose: 'Edge Computing',
    vcpuCores: 2,
    memoryGB: 4,
    storageGB: 50,
    operatingSystem: 'Linux',
    bandwidthMbps: 100,
    highAvailability: false,
    autoScaling: false,
    autoScalingMin: 1,
    autoScalingMax: 2,
    vnics: [{
      id: Date.now().toString(),
      name: 'eth0',
      ipAddress: '',
      subnetMask: '255.255.255.0',
      vlanId: 1
    }]
  });

  const [isSubmitting, setIsSubmitting] = useState(false);
  const [activeTab, setActiveTab] = useState('basic');

  // Generate server name based on network function type
  useEffect(() => {
    const prefix = formData.networkFunctionType === 'vRouter' ? 'r' :
      formData.networkFunctionType === 'vFirewall' ? 'fw' : 'epc';
    const randomNum = Math.floor(Math.random() * 1000).toString().padStart(3, '0');
    setFormData(prev => ({
      ...prev,
      serverName: `${prefix}-${randomNum}`
    }));
  }, [formData.networkFunctionType]);

  const handleInputChange = (e) => {

```

```

const { name, value, type, checked } = e.target;
setFormData(prev => ({
  ...prev,
  [name]: type === 'checkbox' ? checked : value
})));
});

const handleVNICChange = (id, field, value) => {
  setFormData(prev => ({
    ...prev,
    vnics: prev.vnics.map(vnic =>
      vnic.id === id ? { ...vnic, [field]: value } : vnic
    )
  })));
};

const addVNIC = () => {
  setFormData(prev => ({
    ...prev,
    vnics: [
      ...prev.vnics,
      {
        id: Date.now().toString(),
        name: `eth${prev.vnics.length}`,
        ipAddress: '',
        subnetMask: '255.255.255.0',
        vlanId: 1
      }
    ]
  })));
};

const removeVNIC = (id) => {
  if (formData.vnics.length <= 1) {
    toast.error('At least one vNIC is required');
    return;
  }
  setFormData(prev => ({
    ...prev,
    vnics: prev.vnics.filter(vnic => vnic.id !== id)
  })));
};

const validateForm = () => {
  // Validate IP addresses

```

```

    for (const vnic of formData.vnics) {
      if (!vnic.ipAddress.match(/^(\\d{1,3}\\.){3}\\d{1,3}$/)) {
        toast.error(`Invalid IP address for ${vnic.name}`);
        return false;
      }
    }
  }

  if (formData.autoScaling && formData.autoScalingMax <
formData.autoScalingMin) {
    toast.error('Max instances must be ≥ min instances');
    return false;
  }

  return true;
};

const handleSubmit = async (e) => {
  e.preventDefault();
  if (!validateForm()) return;

  setIsSubmitting(true);
  try {
    const response = await fetch('/api/nfv-servers', {
      method: 'POST',
      headers: { 'Content-Type': 'application/json' },
      body: JSON.stringify(formData)
    });

    if (!response.ok) throw new Error('Server error');
    toast.success('NFV Server created successfully!');
  } catch (error) {
    toast.error(error.message);
  } finally {
    setIsSubmitting(false);
  }
};

// Get network function type icon
const getNetworkFunctionIcon = () => {
  switch(formData.networkFunctionType) {
    case 'vRouter': return <Network className="h-6 w-6 text-blue-500" />;
    case 'vFirewall': return <Shield className="h-6 w-6 text-red-500" />;
    case 'vEPC': return <Server className="h-6 w-6 text-purple-500" />;
    default: return <Server className="h-6 w-6 text-blue-500" />;
  }
}

```

```

};

// Calculate resource usage percentages
const cpuPercentage = (formData.vcpuCores / 64) * 100;
const memoryPercentage = (formData.memoryGB / 512) * 100;
const storagePercentage = (formData.storageGB / 4096) * 100;

return (
  <div className="max-w-5xl mx-auto p-6 bg-gray-50 rounded-xl shadow-lg">
    <div className="flex items-center space-x-4 mb-8">
      {getNetworkFunctionIcon()}
      <h1 className="text-3xl font-bold text-gray-800">Create NFV Server</h1>
    </div>

    {/* Progress visualization */}
    <div className="flex items-center justify-between mb-8">
      <div className="flex flex-col items-center w-1/4">
        <div className="flex items-center justify-center w-16 h-16 bg-blue-50 rounded-full">
          <Cpu className="h-8 w-8 text-blue-500" />
        </div>
        <p className="mt-2 text-sm text-gray-600">vCPU</p>
        <div className="w-full bg-gray-200 rounded-full h-2 mt-2">
          <div className="bg-blue-500 h-2 rounded-full" style={{ width:
`${cpuPercentage}%` }}></div>
        </div>
        <p className="text-xs text-gray-500 mt-1">{formData.vcpuCores} / 64
cores</p>
      </div>

      <div className="flex flex-col items-center w-1/4">
        <div className="flex items-center justify-center w-16 h-16 bg-green-50 rounded-full">
          <Memory className="h-8 w-8 text-green-500" />
        </div>
        <p className="mt-2 text-sm text-gray-600">Memory</p>
        <div className="w-full bg-gray-200 rounded-full h-2 mt-2">
          <div className="bg-green-500 h-2 rounded-full" style={{ width:
`${memoryPercentage}%` }}></div>
        </div>
        <p className="text-xs text-gray-500 mt-1">{formData.memoryGB} / 512
GB</p>
      </div>

      <div className="flex flex-col items-center w-1/4">

```

```

        <div className="flex items-center justify-center w-16 h-16 bg-amber-50
rounded-full">
            <HardDrive className="h-8 w-8 text-amber-500" />
        </div>
        <p className="mt-2 text-sm text-gray-600">Storage</p>
        <div className="w-full bg-gray-200 rounded-full h-2 mt-2">
            <div className="bg-amber-500 h-2 rounded-full" style={{ width:
`${storagePercentage}%` }}></div>
        </div>
        <p className="text-xs text-gray-500 mt-1">{formData.storageGB} / 4096
GB</p>
    </div>

    <div className="flex flex-col items-center w-1/4">
        <div className="flex items-center justify-center w-16 h-16 bg-purple-50
rounded-full">
            <Network className="h-8 w-8 text-purple-500" />
        </div>
        <p className="mt-2 text-sm text-gray-600">Network</p>
        <p className="text-lg font-semibold text-gray-
700">{formData.bandwidthMbps} Mbps</p>
        <p className="text-xs text-gray-500">{formData.vnics.length} vNICs</p>
    </div>

    <form onSubmit={handleSubmit} className="space-y-8">
        { /* Navigation Tabs */ }
        <div className="flex border-b border-gray-200">
            <button
                type="button"
                className={`px-6 py-3 font-medium flex items-center space-x-2
${activeTab === 'basic' ? 'border-b-2 border-blue-500 text-blue-600' : 'text-
gray-500'}` }
                onClick={() => setActiveTab('basic')}
            >
                <Server className="h-5 w-5" />
                <span>Basic Info</span>
            </button>
            <button
                type="button"
                className={`px-6 py-3 font-medium flex items-center space-x-2
${activeTab === 'specs' ? 'border-b-2 border-blue-500 text-blue-600' : 'text-
gray-500'}` }
                onClick={() => setActiveTab('specs')}
            >

```

```

        <Cpu className="h-5 w-5" />
        <span>VM Specifications</span>
    </button>
    <button
        type="button"
        className={`px-6 py-3 font-medium flex items-center space-x-2
${activeTab === 'network' ? 'border-b-2 border-blue-500 text-blue-600' : 'text-
gray-500'}`}
        onClick={() => setActiveTab('network')}
    >
        <Network className="h-5 w-5" />
        <span>Network Config</span>
    </button>
    <button
        type="button"
        className={`px-6 py-3 font-medium flex items-center space-x-2
${activeTab === 'features' ? 'border-b-2 border-blue-500 text-blue-600' : 'text-
gray-500'}`}
        onClick={() => setActiveTab('features')}
    >
        <Settings className="h-5 w-5" />
        <span>NFV Features</span>
    </button>
</div>

{/* Basic Information */}
<div className={` ${activeTab === 'basic' ? 'block' : 'hidden'}`}>
    <div className="bg-white p-6 rounded-lg shadow-sm">
        <h2 className="text-xl font-semibold mb-6 text-gray-800 flex items-
center">
            <Server className="mr-2 h-5 w-5 text-blue-500" />
            Basic Information
        </h2>

        <div className="grid grid-cols-1 md:grid-cols-2 gap-6">
            <div>
                <label className="block text-sm font-medium text-gray-700 mb-
1">Server Name</label>
                <div className="relative">
                    <input
                        type="text"
                        value={formData.serverName}
                        readOnly

```

```

        className="input input-bordered w-full bg-gray-50 border
border-gray-300 text-gray-900 rounded-lg focus:ring-blue-500 focus:border-blue-
500 block p-2.5"
      />
      <div className="absolute inset-y-0 right-0 flex items-center
px-3 pointer-events-none text-gray-500 text-sm">
        Auto-generated
      </div>
    </div>
  </div>

  <div>
    <label className="block text-sm font-medium text-gray-700 mb-
1">Network Function Type</label>
    <select
      name="networkFunctionType"
      value={formData.networkFunctionType}
      onChange={handleInputChange}
      className="bg-white border border-gray-300 text-gray-900
rounded-lg focus:ring-blue-500 focus:border-blue-500 block w-full p-2.5"
    >
      <option value="vRouter">vRouter (Virtual Router)</option>
      <option value="vFirewall">vFirewall (Virtual Firewall)</option>
      <option value="vEPC">vEPC (Virtual Evolved Packet
Core)</option>
    </select>
  </div>

  <div>
    <label className="block text-sm font-medium text-gray-700 mb-
1">Server Purpose</label>
    <select
      name="serverPurpose"
      value={formData.serverPurpose}
      onChange={handleInputChange}
      className="bg-white border border-gray-300 text-gray-900
rounded-lg focus:ring-blue-500 focus:border-blue-500 block w-full p-2.5"
    >
      <option value="Edge Computing">Edge Computing</option>
      <option value="Core Network">Core Network</option>
      <option value="Load Balancer">Load Balancer</option>
    </select>
  </div>

  <div>

```

```

        <label className="block text-sm font-medium text-gray-700 mb-1">Operating System</label>
        <select
            name="operatingSystem"
            value={formData.operatingSystem}
            onChange={handleInputChange}
            className="bg-white border border-gray-300 text-gray-900 rounded-lg focus:ring-blue-500 focus:border-blue-500 block w-full p-2.5"
        >
            <option value="Linux">Linux</option>
            <option value="Windows">Windows</option>
        </select>
    </div>
</div>
</div>
</div>

{/* VM Specifications */}
<div className={` ${activeTab === 'specs' ? 'block' : 'hidden'} `}>
    <div className="bg-white p-6 rounded-lg shadow-sm">
        <h2 className="text-xl font-semibold mb-6 text-gray-800 flex items-center">
            <CPU className="mr-2 h-5 w-5 text-blue-500" />
            VM Specifications
        </h2>

        <div className="grid grid-cols-1 md:grid-cols-3 gap-6">
            <div>
                <label className="block text-sm font-medium text-gray-700 mb-1">vCPU Cores</label>
                <div className="flex items-center">
                    <input
                        type="range"
                        name="vcpuCores"
                        min="1"
                        max="64"
                        value={formData.vcpuCores}
                        onChange={handleInputChange}
                        className="w-full h-2 bg-gray-200 rounded-lg appearance-none cursor-pointer"
                    />
                    <span className="ml-3 text-gray-700 font-medium min-w-[40px] text-center">
                        {formData.vcpuCores}
                    </span>
                </div>
            </div>

```



```

        </div>
        <p className="mt-1 text-xs text-gray-500">Range: 1-64 cores</p>
    </div>

    <div>
        <label className="block text-sm font-medium text-gray-700 mb-1">Memory (GB)</label>
        <div className="flex items-center">
            <input
                type="range"
                name="memoryGB"
                min="1"
                max="512"
                value={formData.memoryGB}
                onChange={handleInputChange}
                className="w-full h-2 bg-gray-200 rounded-lg appearance-none
cursor-pointer"
            />
            <span className="ml-3 text-gray-700 font-medium min-w-[40px]
text-center">
                {formData.memoryGB}
            </span>
        </div>
        <p className="mt-1 text-xs text-gray-500">Range: 1-512 GB</p>
    </div>

    <div>
        <label className="block text-sm font-medium text-gray-700 mb-1">Storage (GB)</label>
        <div className="flex items-center">
            <input
                type="range"
                name="storageGB"
                min="10"
                max="4096"
                value={formData.storageGB}
                onChange={handleInputChange}
                className="w-full h-2 bg-gray-200 rounded-lg appearance-none
cursor-pointer"
            />
            <span className="ml-3 text-gray-700 font-medium min-w-[40px]
text-center">
                {formData.storageGB}
            </span>
        </div>
    </div>

```

```

        <p className="mt-1 text-xs text-gray-500">Range: 10-4096 GB</p>
      </div>
    </div>

    { /* Resource allocation visualization */ }
    <div className="mt-8 p-4 bg-gray-50 rounded-lg">
      <h3 className="text-sm font-medium text-gray-700 mb-3">Resource
Allocation</h3>
      <div className="grid grid-cols-3 gap-4">
        <div>
          <div className="flex justify-between mb-1">
            <span className="text-xs text-gray-500">CPU</span>
            <span className="text-xs text-gray-
500">{Math.round(cpuPercentage)}%</span>
          </div>
          <div className="w-full bg-gray-200 rounded-full h-2">
            <div className="bg-blue-500 h-2 rounded-full" style={{ width:
`${cpuPercentage}%` }}></div>
          </div>
        </div>

        <div>
          <div className="flex justify-between mb-1">
            <span className="text-xs text-gray-500">Memory</span>
            <span className="text-xs text-gray-
500">{Math.round(memoryPercentage)}%</span>
          </div>
          <div className="w-full bg-gray-200 rounded-full h-2">
            <div className="bg-green-500 h-2 rounded-full" style={{
width: `${memoryPercentage}%` }}></div>
          </div>
        </div>

        <div>
          <div className="flex justify-between mb-1">
            <span className="text-xs text-gray-500">Storage</span>
            <span className="text-xs text-gray-
500">{Math.round(storagePercentage)}%</span>
          </div>
          <div className="w-full bg-gray-200 rounded-full h-2">
            <div className="bg-amber-500 h-2 rounded-full" style={{
width: `${storagePercentage}%` }}></div>
          </div>
        </div>
      </div>
    </div>

```

```

        </div>
    </div>
</div>

{/* Network Configuration */}
<div className={` ${activeTab} === 'network' ? 'block' : 'hidden'}`>
    <div className="bg-white p-6 rounded-lg shadow-sm">
        <div className="flex justify-between items-center mb-6">
            <h2 className="text-xl font-semibold text-gray-800 flex items-center">
                <Network className="mr-2 h-5 w-5 text-blue-500" />
                Network Configuration
            </h2>
            <button
                type="button"
                onClick={addVNIC}
                className="flex items-center px-3 py-2 bg-blue-500 text-white text-sm rounded-lg hover:bg-blue-600 transition-colors"
            >
                <Plus className="h-4 w-4 mr-1" /> Add vNIC
            </button>
        </div>

        <div className="mb-6">
            <div className="overflow-hidden shadow ring-1 ring-black ring-opacity-5 rounded-lg">
                <table className="min-w-full divide-y divide-gray-200">
                    <thead className="bg-gray-50">
                        <tr>
                            <th scope="col" className="px-6 py-3 text-left text-xs font-medium text-gray-500 uppercase tracking-wider">Name</th>
                            <th scope="col" className="px-6 py-3 text-left text-xs font-medium text-gray-500 uppercase tracking-wider">IP Address</th>
                            <th scope="col" className="px-6 py-3 text-left text-xs font-medium text-gray-500 uppercase tracking-wider">Subnet Mask</th>
                            <th scope="col" className="px-6 py-3 text-left text-xs font-medium text-gray-500 uppercase tracking-wider">VLAN ID</th>
                            <th scope="col" className="px-6 py-3 text-left text-xs font-medium text-gray-500 uppercase tracking-wider">Action</th>
                        </tr>
                    </thead>
                    <tbody className="bg-white divide-y divide-gray-200">
                        {formData.vnics.map(vnic => (
                            <tr key={vnic.id}>
                                <td className="px-6 py-4 whitespace-nowrap">

```

```

        <input
            value={vnic.name}
            onChange={(e) => handleVNICChange(vnic.id, 'name',
e.target.value)}
            className="bg-gray-50 border border-gray-300 text-
gray-900 text-sm rounded-lg focus:ring-blue-500 focus:border-blue-500 block w-
full p-2"
        />
    </td>
    <td className="px-6 py-4 whitespace-nowrap">
        <input
            value={vnic.ipAddress}
            onChange={(e) => handleVNICChange(vnic.id,
'ipAddress', e.target.value)}
            className="bg-gray-50 border border-gray-300 text-
gray-900 text-sm rounded-lg focus:ring-blue-500 focus:border-blue-500 block w-
full p-2"
            placeholder="192.168.1.1"
        />
    </td>
    <td className="px-6 py-4 whitespace-nowrap">
        <input
            value={vnic.subnetMask}
            onChange={(e) => handleVNICChange(vnic.id,
'subnetMask', e.target.value)}
            className="bg-gray-50 border border-gray-300 text-
gray-900 text-sm rounded-lg focus:ring-blue-500 focus:border-blue-500 block w-
full p-2"
        />
    </td>
    <td className="px-6 py-4 whitespace-nowrap">
        <input
            type="number"
            min="1"
            max="4095"
            value={vnic.vlanId}
            onChange={(e) => handleVNICChange(vnic.id, 'vlanId',
e.target.value)}
            className="bg-gray-50 border border-gray-300 text-
gray-900 text-sm rounded-lg focus:ring-blue-500 focus:border-blue-500 block w-
full p-2"
        />
    </td>
    <td className="px-6 py-4 whitespace-nowrap">
        <button

```

```

                                type="button"
                                onClick={() => removeVNIC(vnic.id)}
                                className="inline-flex items-center px-2 py-1 border
border-transparent text-xs font-medium rounded text-red-700 bg-red-100 hover:bg-
red-200"

                                disabled={formData.vnics.length <= 1}
                            >
                                <Trash2 className="h-4 w-4 mr-1" /> Remove
                            </button>
                        </td>
                    </tr>
                </tbody>
            </table>
        </div>
    </div>

    <div>
        <label className="block text-sm font-medium text-gray-700 mb-
1">Bandwidth (Mbps)</label>
        <div className="flex items-center">
            <input
                type="range"
                name="bandwidthMbps"
                min="1"
                max="10000"
                value={formData.bandwidthMbps}
                onChange={handleInputChange}
                className="w-full h-2 bg-gray-200 rounded-lg appearance-none
cursor-pointer"
            />
            <span className="ml-3 text-gray-700 font-medium min-w-[60px]
text-center">
                {formData.bandwidthMbps}
            </span>
        </div>
        <p className="mt-1 text-xs text-gray-500">Range: 1-10000 Mbps</p>
    </div>
</div>

    { /* NFV Features */ }
    <div className={` ${activeTab === 'features' ? 'block' : 'hidden'} `}>
        <div className="bg-white p-6 rounded-lg shadow-sm">

```

```

    <h2 className="text-xl font-semibold mb-6 text-gray-800 flex items-
center">
    <Settings className="mr-2 h-5 w-5 text-blue-500" />
    NFV Features
  </h2>

  <div className="grid grid-cols-1 md:grid-cols-2 gap-6">
    <div className="p-4 border border-gray-200 rounded-lg">
      <label className="flex items-center mb-4 cursor-pointer">
        <div className="mr-4 flex-shrink-0">
          <div className={`w-12 h-6 ${formData.highAvailability ? 'bg-
blue-500' : 'bg-gray-200'} rounded-full p-1 transition-colors duration-300 ease-
in-out`}>
            <div className={`bg-white w-4 h-4 rounded-full shadow-md
transform transition-transform duration-300 ease-in-out
${formData.highAvailability ? 'translate-x-6' : ''}`}></div>
          </div>
        </div>
        <div>
          <input
            type="checkbox"
            name="highAvailability"
            checked={formData.highAvailability}
            onChange={handleInputChange}
            className="sr-only"
          />
          <span className="text-sm font-medium text-gray-900">High
Availability</span>
          <p className="text-xs text-gray-500 mt-1">
            Enables automatic failover and redundancy for mission-
critical workloads
          </p>
        </div>
      </label>
    </div>

    <div className="p-4 border border-gray-200 rounded-lg">
      <label className="flex items-center mb-4 cursor-pointer">
        <div className="mr-4 flex-shrink-0">
          <div className={`w-12 h-6 ${formData.autoScaling ? 'bg-blue-
500' : 'bg-gray-200'} rounded-full p-1 transition-colors duration-300 ease-in-
out`}>
            <div className={`bg-white w-4 h-4 rounded-full shadow-md
transform transition-transform duration-300 ease-in-out ${formData.autoScaling ?
'translate-x-6' : ''}`}></div>

```

```

        </div>
      </div>
      <div>
        <input
          type="checkbox"
          name="autoScaling"
          checked={formData.autoScaling}
          onChange={handleInputChange}
          className="sr-only"
        />
        <span className="text-sm font-medium text-gray-900">Auto-
Scaling</span>

        <p className="text-xs text-gray-500 mt-1">
          Automatically adjusts resources based on workload demands
        </p>
      </div>
    </label>

    {formData.autoScaling && (
      <div className="pl-16 grid grid-cols-2 gap-4 mt-4 pt-4 border-t
border-gray-100">
        <div>
          <label className="block text-xs font-medium text-gray-700
mb-1">Min Instances</label>
          <input
            type="number"
            name="autoScalingMin"
            min="1"
            value={formData.autoScalingMin}
            onChange={handleInputChange}
            className="bg-gray-50 border border-gray-300 text-gray-
900 text-sm rounded-lg focus:ring-blue-500 focus:border-blue-500 block w-full p-
2"
          />
        </div>
        <div>
          <label className="block text-xs font-medium text-gray-700
mb-1">Max Instances</label>
          <input
            type="number"
            name="autoScalingMax"
            min="1"
            value={formData.autoScalingMax}
            onChange={handleInputChange}

```

```

        className="bg-gray-50 border border-gray-300 text-gray-900 text-sm rounded-lg focus:ring-blue-500 focus:border-blue-500 block w-full p-2"

        />
    </div>
</div>
    })
</div>
</div>

<div className="mt-8 p-4 bg-blue-50 rounded-lg border border-blue-100">
    <h3 className="text-sm font-medium text-blue-800 mb-2">Configuration Summary</h3>
    <div className="grid grid-cols-1 md:grid-cols-2 gap-4">
        <div className="flex items-center">
            <Server className="h-4 w-4 text-blue-500 mr-2" />
            <span className="text-xs text-gray-700">Server Type: </span>
            <span className="text-xs font-medium text-gray-900 ml-1">{formData.networkFunctionType}</span>
        </div>
        <div className="flex items-center">
            <Cpu className="h-4 w-4 text-blue-500 mr-2" />
            <span className="text-xs text-gray-700">Resources: </span>
            <span className="text-xs font-medium text-gray-900 ml-1">{formData.vcpuCores} vCPU, {formData.memoryGB} GB RAM, {formData.storageGB} GB Storage</span>
        </div>
        <div className="flex items-center">
            <Network className="h-4 w-4 text-blue-500 mr-2" />
            <span className="text-xs text-gray-700">Network: </span>
            <span className="text-xs font-medium text-gray-900 ml-1">{formData.vnics.length} vNICs, {formData.bandwidthMbps} Mbps</span>
        </div>
        <div className="flex items-center">
            <Shield className="h-4 w-4 text-blue-500 mr-2" />
            <span className="text-xs text-gray-700">Features: </span>
            <span className="text-xs font-medium text-gray-900 ml-1">
                {formData.highAvailability ? 'HA, ' : ''}
                {formData.autoScaling ? `Auto-scaling (${formData.autoScalingMin}-${formData.autoScalingMax})` : 'No Auto-scaling'}
            </span>
        </div>
    </div>
</div>

```



```
    </div>
  </div>
  { /* End of NFV Features */}
  <div className="flex justify-end mt-8">
    <button
      type="submit"
      className={`flex items-center px-6 py-3 bg-blue-600 text-white
rounded-lg font-semibold shadow hover:bg-blue-700 transition-colors
${isSubmitting ? 'opacity-50 cursor-not-allowed' : ''}`}
      disabled={isSubmitting}
    >
      <Save className="h-5 w-5 mr-2" />
      {isSubmitting ? 'Submitting...' : 'Create Server'}
    </button>
  </div>
</form>
</div>
);
}
```