

# Лабораторная работа № 15

## Настройка сетевого журналирования

Митрофанов Тимур Александрович

2025-12-13

# Содержание I

1. Информация

2. Вводная часть

3. Выполнение заданий

4. Выводы

## Раздел 1

### 1. Информация

## 1.1 Докладчик

► Митрофанов Тимур Александрович

## 1.1 Докладчик

- ▶ Митрофанов Тимур Александрович
- ▶ Российский университет дружбы народов им. П. Лумумбы

## Раздел 2

### 2. Вводная часть

## 2.1 Цели и задачи

Цель - получение навыков по работе с журналами системных событий.

1. Настройте сервер сетевого журналирования событий.

## 2.1 Цели и задачи

Цель - получение навыков по работе с журналами системных событий.

1. Настройте сервер сетевого журналирования событий.
2. Настройте клиент для передачи системных сообщений в сетевой журнал на сервере.



## 2.1 Цели и задачи

Цель - получение навыков по работе с журналами системных событий.

1. Настройте сервер сетевого журналирования событий.
2. Настройте клиент для передачи системных сообщений в сетевой журнал на сервере.
3. Просмотрите журналы системных событий с помощью нескольких программ. При наличии сообщений о некорректной работе сервисов исправьте ошибки в настройках соответствующих служб.

## 2.1 Цели и задачи

Цель - получение навыков по работе с журналами системных событий.

1. Настройте сервер сетевого журналирования событий.
2. Настройте клиент для передачи системных сообщений в сетевой журнал на сервере.
3. Просмотрите журналы системных событий с помощью нескольких программ. При наличии сообщений о некорректной работе сервисов исправьте ошибки в настройках соответствующих служб.
4. Напишите скрипты для Vagrant, фиксирующие действия по установке и настройке сетевого сервера журналирования.

## Раздел 3

### 3. Выполнение заданий

## 3.1 Настройка сервера сетевого журнала

```

root@server:/etc/rsyslog.d - sudo -i

[tamtrofanov@server.tamtrofanov.net ~]$ sudo -i
[sudo] password for tamtrofanov:
[root@server.tamtrofanov.net ~]#
[root@server.tamtrofanov.net ~]#
[root@server.tamtrofanov.net ~]# cd /etc/rsyslog.d
touch netlog-server.conf
[root@server.tamtrofanov.net rsyslog.d]# nano /etc/rsyslog.d/netlog-server.conf
[root@server.tamtrofanov.net rsyslog.d]# cat /etc/rsyslog.d/netlog-server.conf
$ModLoad imtcp
$InputTCPServerRun 514
[root@server.tamtrofanov.net rsyslog.d]#
[root@server.tamtrofanov.net rsyslog.d]# systemctl restart rsyslog
[root@server.tamtrofanov.net rsyslog.d]#
[root@server.tamtrofanov.net rsyslog.d]# lsof | grep TCP
lsof: WARNING: can't stat() fuse.gvfsd-fuse file system /run/user/1001/gvfs
Output information may be incomplete.
lsof: WARNING: can't stat() fuse.portal file system /run/user/1001/doc
Output information may be incomplete.
systemd      1          root    42u    IPv4        4967      0t0      TCP *:sunrpc (LISTEN)
systemd      1          root    44u    IPv6        4983      0t0      TCP *:sunrpc (LISTEN)
systemd      1          root    91u    IPv6        8944      0t0      TCP *:websock (LISTEN)
rpcbind      873        rpc      5u     IPv4        4967      0t0      TCP *:sunrpc (LISTEN)
rpcbind      873        rpc      7u     IPv6        4983      0t0      TCP *:sunrpc (LISTEN)
cupsd        1278       root     7u     IPv6        11731     0t0      TCP localhost:ipp (LISTEN)
cupsd        1278       root     8u     IPv4        11732     0t0      TCP localhost:ipp (LISTEN)
sshd         1287       root     7u     IPv4        11669     0t0      TCP *:down (LISTEN)
sshd         1287       root     8u     IPv6        11671     0t0      TCP *:down (LISTEN)
sshd         1287       root     9u     IPv4        11673     0t0      TCP *:ssh (LISTEN)
sshd         1287       root    10u     IPv6        11675     0t0      TCP *:ssh (LISTEN)
named        1353      named    27u    IPv4        11800     0t0      TCP localhost:domain (LISTEN)
named        1353      named    29u    IPv4        11801     0t0      TCP localhost:domain (LISTEN)
named        1353      named    33u    IPv6        11804     0t0      TCP localhost:domain (LISTEN)
named        1353      named    34u    IPv6        11805     0t0      TCP localhost:domain (LISTEN)
named        1353      named    35u    IPv4        10917     0t0      TCP localhost:rndc (LISTEN)
named        1353      named    36u    IPv4        10918     0t0      TCP localhost:rndc (LISTEN)
named        1353      named    37u    IPv6        10924     0t0      TCP localhost:rndc (LISTEN)

```

## 3.2 Настройка межсетевого экрана

```
[root@server.tamitrofanov.net rsyslog.d]# firewall-cmd --add-port=514/tcp  
firewall-cmd --add-port=514/tcp --permanent  
success  
success  
[root@server.tamitrofanov.net rsyslog.d]# █
```

Рисунок 2: Настройка межсетевого экрана

## 3.3 настройка клиента



root@client:/etc/rsyslog.d – sudo -i

```
[tamitrofanov@client.tamitrofanov.net ~]$ sudo -i
[sudo] password for tamitrofanov:
[root@client.tamitrofanov.net ~]#
[root@client.tamitrofanov.net ~]#
[root@client.tamitrofanov.net ~]#
[root@client.tamitrofanov.net ~]# cd /etc/rsyslog.d
touch netlog-client.conf
[root@client.tamitrofanov.net rsyslog.d]#
[root@client.tamitrofanov.net rsyslog.d]# nano /etc/rsyslog.d/netlog-client.conf
[root@client.tamitrofanov.net rsyslog.d]#
[root@client.tamitrofanov.net rsyslog.d]# cat /etc/rsyslog.d/netlog-client.conf
*. * @@server.user.net:514
[root@client.tamitrofanov.net rsyslog.d]# systemctl restart rsyslog
[root@client.tamitrofanov.net rsyslog.d]#
[root@client.tamitrofanov.net rsyslog.d]# nano /etc/rsyslog.d/netlog-client.conf
[root@client.tamitrofanov.net rsyslog.d]# cat /etc/rsyslog.d/netlog-client.conf
*. * @@server.tamitrofanov.net:514
[root@client.tamitrofanov.net rsyslog.d]# systemctl restart rsyslog
[root@client.tamitrofanov.net rsyslog.d]#
```

## 3.4 Просмотр журнала

```
root@server:/etc/rsyslog.d – sudo -i

[root@server.tamirofanov.net rsyslog.d]# tail -f /var/log/messages
Dec 13 18:19:13 client systemd[1]: Starting fwupd-refresh.service - Refresh fwupd metadata and update motd...
Dec 13 18:19:13 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 18:19:13 client systemd[1]: fwupd-refresh.service: Deactivated successfully.
Dec 13 18:19:13 client systemd[1]: Finished fwupd-refresh.service - Refresh fwupd metadata and update motd.
Dec 13 18:19:13 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 27.
Dec 13 18:19:13 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 18:19:08 server NetworkManager[1257]: <info> [1765639148.8991] agent-manager: agent[ecf1d71edce40a65, :1.85/or
g.gnome.Shell.NetworkAgent/1001]: agent registered
Dec 13 18:19:23 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 18:19:23 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 28.
Dec 13 18:19:23 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 18:19:33 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 18:19:34 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 29.
Dec 13 18:19:34 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 18:19:44 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 18:19:44 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 30.
Dec 13 18:19:44 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 18:19:54 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 18:19:54 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 31.
Dec 13 18:19:54 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
```


## 3.5 Графическое окружение

[tamitrofanov@server.tamitrofanov.net ~]\$ gnome-system-monitor

Process Name	User	% CPU	ID	Memory	Disk read total	Disk write
gdm-wayland-session	tamitrofanov	0.00	2899	393.2 kB	4.1 kB	
gjs	tamitrofanov	0.00	3072	4.9 MB	N/A	
gjs	tamitrofanov	0.00	3300	5.7 MB	N/A	
gnome-keyring-daemon	tamitrofanov	0.00	2887	978.9 kB	426.0 kB	4.1 kB
gnome-session-binary	tamitrofanov	0.00	2908	1.7 MB	565.2 kB	
gnome-session-binary	tamitrofanov	0.00	2957	2.5 MB	1.8 MB	4.1 kB
gnome-session-ctl	tamitrofanov	0.00	2955	393.2 kB	24.6 kB	
gnome-shell	tamitrofanov	3.47	2986	309.9 MB	14.8 MB	307.1 kB
gnome-shell-calendar-server	tamitrofanov	0.00	3041	3.4 MB	3.3 MB	
gnome-software	tamitrofanov	0.00	3149	65.4 MB	10.5 MB	
gnome-system-monitor	tamitrofanov	0.35	4366	151.5 MB	8.5 MB	118.1 kB
goa-daemon	tamitrofanov	0.00	3262	3.3 MB	569.3 kB	
goa-identity-service	tamitrofanov	0.00	3331	1.4 MB	143.4 kB	
gsd-ally-settings	tamitrofanov	0.00	3080	524.3 kB	N/A	
gsd-color	tamitrofanov	0.00	3081	3.8 MB	N/A	
gsd-datetime	tamitrofanov	0.00	3085	1.4 MB	N/A	
gsd-disk-utility-notify	tamitrofanov	0.00	3124	917.5 kB	69.6 kB	



## 3.6 Inav



```
LOG - sudo -i
2025-12-13T21:26:16 MSK
Press F2 to enable mouse support
LOG : 2025-12-13T21:26:16.000 : syslog.log : messages[10459] : systemd[1] :
Dec 13 21:24:33 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 1105.
Dec 13 21:24:33 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 21:24:43 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 21:24:43 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 1106.
Dec 13 21:24:43 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 21:24:47 server gnome-shell[3006]: Cursor update failed: drmModeAtomicCommit: Invalid argument
Dec 13 21:24:53 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 21:24:54 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 1107.
Dec 13 21:24:54 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 21:25:04 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 21:25:04 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 1108.
Dec 13 21:25:04 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 21:25:14 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 21:25:14 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 1109.
Dec 13 21:25:14 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 21:25:24 server gnome-shell[3006]: Cursor update failed: drmModeAtomicCommit: Invalid argument
Dec 13 21:25:24 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 21:25:25 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 1110.
Dec 13 21:25:25 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 21:25:35 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 21:25:35 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 1111.
Dec 13 21:25:35 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 21:25:45 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 21:25:45 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 1112.
Dec 13 21:25:45 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 21:25:54 server NetworkManager[1256]: <info> [1765650354.4106] agent-manager: agent[228f291d5cfd97f4, :1.87/
Dec 13 21:25:55 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 21:25:55 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 1113.
Dec 13 21:25:55 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 21:26:06 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 21:26:06 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 1114.
Dec 13 21:26:06 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
Dec 13 21:26:16 client systemd[1]: serial-getty@ttyS0.service: Deactivated successfully.
Dec 13 21:26:16 client systemd[1]: serial-getty@ttyS0.service: Scheduled restart job, restart counter is at 1115.
Dec 13 21:26:16 client systemd[1]: Started serial-getty@ttyS0.service - Serial Getty on ttyS0.
```

## 3.7 Настройка запуска службы на сервере

```
[root@server.tamitrofanov.net lnav-0.13.2]# cd /vagrant/provision/server
mkdir -p /vagrant/provision/server/netlog/etc/rsyslog.d
cp -R /etc/rsyslog.d/netlog-server.conf /vagrant/provision/server/netlog/etc/rsyslog.d
[root@server.tamitrofanov.net server]# cd /vagrant/provision/server
touch netlog.sh
chmod +x netlog.sh
[root@server.tamitrofanov.net server]# nano netlog.sh
[root@server.tamitrofanov.net server]# cat netlog.sh
#!/bin/bash

echo "Provisioning script $0"

echo "Copy configuration files"
cp -R /vagrant/provision/server/netlog/etc/* /etc
restorecon -vR /etc

echo "Configure firewall"
firewall-cmd --add-port=514/tcp
firewall-cmd --add-port=514/tcp --permanent

echo "Start rsyslog service"
```

## 3.8 Настройка запуска службы на клиенте



root@client:/vagrant/provision/client – sudo -i

```
[root@client.tamitrofanov.net rsyslog.d]# cd /vagrant/provision/client
mkdir -p /vagrant/provision/client/netlog/etc/rsyslog.d
cp -R /etc/rsyslog.d/netlog-client.conf /vagrant/provision/client/netlog/etc/rsyslog.d/
[root@client.tamitrofanov.net client]# cd /vagrant/provision/client
touch netlog.sh
chmod +x netlog.sh
[root@client.tamitrofanov.net client]# nano netlog.sh
[root@client.tamitrofanov.net client]# cat netlog.sh
#!/bin/bash

echo "Provisioning script $0"

echo "Install needed packages"
dnf -y install lnav

echo "Copy configuration files"
cp -R /vagrant/provision/client/netlog/etc/* /etc
restorecon -vR /etc

echo "Start rsyslog service"
```

## 3.9 Вагрант для сервера

```
132 server.vm.provision "server netlog",  
133   type: "shell",  
134   preserve_order: true,  
135   path: "provision/server/netlog.sh"  
136
```

Рисунок 9: Вагрант для сервера

## 3.10 Вагрант для клиента

```
client.vm.provision "client netlog",  
  type: "shell",  
  preserve_order: true,  
  path: "provision/client/netlog.sh"
```

Рисунок 10: Вагрант для клиента

## Раздел 4

### 4. Выводы

## 4.1 слайд 1

Сегодня я получил навыки по работе с журналами системных событий.